





ISO/IEC17025 Accredited Lab.

Report No: FCC1006438 File reference No: 2010-08-12

Applicant: Guangzhou Chiyuan Electronic Co.,Ltd.

Product: 2CH/4CH/6CH Radio Control

Model No: CY200/ CY400/ CY600

Brand Name: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C,

Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: Aug 12, 2010

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1006438 Page 2 of 46

Date: 2010-08-12



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Page 3 of 46

Report No: 1006438 Date: 2010-08-12



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	4
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment.	5
3.0	Technical Details	6
3.1	Summary of Test Results	6
3.2	Test Standards	6
4.0	EUT Modification.	6
5.0	Power Line Conducted Emission Test.	7
5.1	Schematics of the Test.	7
5.2	Test Method and Test Procedure.	7
5.3	Configuration of the EUT	7
5.4	EUT Operating Condition.	8
5.5	Conducted Emission Limit.	8
5.6	Test Result.	8
6.0	Radiated Emission test.	10
6.1	Test Method and Test Procedure.	10
6.2	Configuration of the EUT	11
6.3	EUT Operation Condition.	11
6.4	Radiated Emission Limit.	12
6.5	Test Result.	14
7.0	Band Edge	23
7.1	Test Method and Test Procedure.	23
7.2	Radiated Test Setup.	23
7.3	Configuration of the EUT.	23
7.4	EUT Operating Condition.	23
7.5	Band Edge Limit.	23
7.6	Band Edge Test Result.	24
8.0	Antenna Requirement	26
9.0	20dB bandwidth measurement	27
10.0	FCC ID Label	30
11.0	Photo of Test Setup and EUT View	31

Report No: 1006438 Page 4 of 46

Date: 2010-08-12



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Guangzhou Chiyuan Electronic Co.,Ltd.

Address: 2/F.,No.1Bldg.,Boyi Industrial Garden,4th Gongye Rd.Zhicun Dashi Street,Panyu

Dis., Guangzhou, China

Telephone: +86-20-34796226/34797226

Fax: +86-20-34796116

1.3 Description of EUT

Product: 2CH/4CH/6CH Radio Control

Manufacturer: Guangzhou Chiyuan Electronic Co.,Ltd.

Brand Name: N/A

Model Number: CY200/ CY400/ CY600

Additional Model Name N-2, N-4, N-6

Additional Trade Name N/A

Rating: DC 9.6V (8pcs AA batteries)

Modulation Type: GFSK

Operation Frequency 2402-2478MHz

Antenna Designation Dipole antenna and the maximum gain is 2.5dBi.

1.4 Submitted Sample

1 Sample

1.5 Test Duration

2010-06-30 to 2010-08-12

The report refers only to the sample tested and does not apply to the bulk.

Page 5 of 46

Report No: 1006438 Date: 2010-08-12



1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

2.0		Test Equipm	ents		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2009-12-05	2010-12-04
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2009-12-05	2010-12-04
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2009-12-05	2010-12-04
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2009-12-05	2010-12-04
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2010-03-29	2011-03-28
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2010-02-17	2011-02-16
System Controller	CT	SC100	-	2010-02-17	2011-02-16
Field probe	Holaday	HI-6005	105152	2010-02-17	2011-02-16
Bilog Antenna	Chase	CBL6111C	2576	2010-02-17	2011-02-16
Loop Antenna	EMCO	6502	00042960	2010-02-17	2011-02-16
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2010-02-17	2011-02-16
3m OATS			N/A	2010-02-17	2011-02-16
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2010-08-14	2011-08-13
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2010-07-03	2011-07-02
Power meter	Anritsu	ML2487A	6K00003613	2010-02-17	2011-02-16
Power sensor	Anritsu	MA2491A	32263	2010-02-17	2011-02-16
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2010-05-14	2011-05-13
LISN	AFJ	LS16C	10010947251	2010-5-14	2011-05-13
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2010-5-14	2011-05-13
9*6*6 Anechoic			N/A	2010-5-14	2011-05-13

Page 6 of 46

Report No: 1006438 Date: 2010-08-12



3.0 Technical Details

3.1 Summary of test results

Standard	Test Type	Result	Notes
ECC David 15 David and 15 207	Conducted	NT/A	Not
FCC Part 15, Paragraph 15.207	Emission Test	N/A	Complies
ECC D. 4 15 C. L 4 C. D	Field Strength		
FCC Part 15 Subpart C Paragraph 15.249(a)	of	PASS	Complies
& 15.249(b) Limit	Fundamental		
FCC Part 15, Paragraph 15.209	Radiated Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(d)	Band Edge	DA GG	G 11
Limit	Test	PASS	Complies

3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249

4.0 EUT Modification


No modification by Shenzhen Timeway Technology Consulting Co.,Ltd

Report No: 1006438 Date: 2010-08-12



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

One channels are provided to the EUT

A. EUT

Device	Manufacturer	Model	FCC ID
2CH/4CH/6CH	Guangzhou Chiyuan Electronic Co.,Ltd.	CY200/ CY400/	V6KCY246
Radio Control		CY600	

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 8 of 46

Date: 2010-08-12

Report No: 1006438



C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Eraguangy(MHz)	Class A Lir	nits (dB µ V)	Class B Limits (dB µ V)		
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2010-08-12

A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Normal operation mode

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual

Frequency	Line	Reading(dBμV)	Limit(dBμV)
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average

B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Normal operation mode

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual

Frequency	luency Line Reading(dBμV)		Limit(dBµV)		
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average

Note: Due to DC Operation, this test item not applicable

Report No: 1006438 Page 10 of 46


Date: 2010-08-12



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup




Page 11 of 46

Report No: 1006438 Date: 2010-08-12



Block diagram of Test setup for frequency below 30MHz



Configuration of The EUT Same as section 5.3 of this report

EUT Operating Condition
Same as section 5.4 of this report.

Page 12 of 46

Report No: 1006438 Date: 2010-08-12



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

	Fundamental Frequency	Field Strength of Fundamental (3m)			Field S	trength of Harmo	onics (3m)
	(MHz)	mV/m	dBuV/m		uV/m	dBu	V/m
Ī	2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note:

- 1. RF Field Strength $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
0.009-0.490	3	20log 2400/F (kHz) + 80
0.490-1.705	3	20log 24000/F (kHz) + 40
1.705-30	3	20log 30 + 40
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK and AV detector.
- 6. If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula Ld1 = Ld2 * (d2/d1)

Report No: 1006438 Page 13 of 46

Date: 2010-08-12



6.5 Test result

Fundamental & Harmonics Radiated Emission Data \mathbf{A}

Product:	2CH/4CH/6CH Radio Control	Test Mode:	Low Channel (CY600)
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	9.6VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2402	104.52 (PK)/86.52(AV)	V	114/94	-9.48/-7.48
2402	99.91 (PK)/83.26(AV)	Н	114/94	-14.09/-10.74
4804	62.39(PK)/47.38(AV)	V	74/54	-11.61/-6.62
4804	49.25(PK)	Н	74/54	-4.48
7206	58.76(PK)/43.10(AV)	V	74/54	-15.24/-10.90
7206	40.13(PK)	Н	74/54	-13.87
9608		H/V	74/54	
12010		H/V	74/54	
14412		H/V	74/54	
16814		H/V	74/54	
19216		H/V	74/54	
21618		H/V	74/54	
24020		H/V	74/54	

Report No: 1006438 Page 14 of 46

Date: 2010-08-12

Product:	2CH/4CH/6CH Radio Control	Test Mode:	Middle Channel (CY600)
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	9.6VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2440	105.57 (PK)/87.52(AV)	V	114/94	-8.43/-6.48
2440	101.91 (PK)/84.86(AV)	Н	114/94	-12.09/-9.14
4880	57.20(PK)/42.55(AV)	V	74/54	-16.80/-11.45
4880		Н	74/54	
7320	56.12(PK)/42.76(AV)	V	74/54	-17.88/-11.24
7320	45.46(PK)	Н	74/54	-8.54
9760		H/V	74/54	
12200		H/V	74/54	
14640		H/V	74/54	
17080		H/V	74/54	
19520		H/V	74/54	
21960		H/V	74/54	
24400		H/V	74/54	

Page 15 of 46

Report No: 1006438 Date: 2010-08-12

Product:	2CH/4CH/6CH Radio Control	Test Mode:	High Channel (CY600)		
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃		
Test Voltage:	9.6VDC	Humidity:	56%		
Test Result:	Pass				

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2478	101.55(PK)/84.42(AV)	V	114/94	-12.45/9.58
2478	95.31 (PK)/80.81(AV)	Н	114/94	-18.69/-13.19
4956	54.65(PK)/39.38(AV)	V	74/54	-19.35/-14.62
4956	47.19(PK)	Н	74/54	-6.81
7434		H/V	74/54	
9912		H/V	74/54	
12390		H/V	74/54	
14868		H/V	74/54	
17346		H/V	74/54	
19824		H/V	74/54	
22302		H/V	74/54	
24780		H/V	74/54	

Note: (1) PK= Peak, AV= Average

- (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
- (3)Margin=Emission-Limits
- (4)According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) As the RF modular and antenna is the same, Model CY600 to conducted radiated emissions above 1GHz

Report No: 1006438 Date: 2010-08-12



B. General Radiated Emission Data


Radiated Emission In Horizontal (30MHz----1000MHz)

Model: CY200

EUT set Condition: Keep transmitting Mode: Normal work

Results: Pass

Please refer to following diagram for individual



Date: 17.AUG.2010 08:06:10

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
		Н	

Report No: 1006438 Page 17 of 46

Date: 2010-08-12




Radiated Emission In Vertical (30MHz---1000MHz

Model: CY200

EUT set Condition: Keep transmitting Mode: Normal work

Results: Pass

Please refer to following diagram for individual



Date: 14.OCT.2010 08:33:34

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
		V	

Report No: 1006438 Page 18 of 46

Date: 2010-08-12



Radiated Emission In Vertical (30MHz---1000MHz


ssion in vertical (50MHz

Model: CY400

EUT set Condition: Keep transmitting Mode: Normal work

Results: Pass

Please refer to following diagram for individual



Date: 17.AUG.2010 08:09:07

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
		V	

Report No: 1006438 Page 19 of 46

Date: 2010-08-12




Radiated Emission In Vertical (30MHz---1000MHz

Model: CY400

EUT set Condition: Keep transmitting Mode: Normal work

Results: Pass

Please refer to following diagram for individual



Date: 17.AUG.2010 08:06:49

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
		V	

Report No: 1006438 Page 20 of 46

Date: 2010-08-12




Radiated Emission In Vertical (30MHz---1000MHz

Model: CY600

EUT set Condition: Keep transmitting Mode: Normal work

Results: Pass

Please refer to following diagram for individual



Date: 17.AUG.2010 08:08:20

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
		V	

Report No: 1006438 Page 21 of 46

Date: 2010-08-12




Radiated Emission In Vertical (30MHz---1000MHz

Model: CY600

EUT set Condition: Keep transmitting Mode: Normal work

Results: Pass

Please refer to following diagram for individual




Date: 17.AUG.2010 08:07:50

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
		V	

Report No: 1006438 Page 22 of 46


Date: 2010-08-12



EUT set Condition: Keep transmitting
Mode: Low Channel (CY600)

Results: Pass

Please refer to following diagram for individual



Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \) V/m)

Page 23 of 46

Report No: 1006438 Date: 2010-08-12




7. Band Edge

7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) Set Spectrum as RBW=VBW=1MHz and Peak detector used
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

7.3 Configuration of The EUT

Same as section 5.3 of this report

7.4 EUT Operating Condition

Same as section 5.4 of this report.

7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Page 24 of 46

Report No: 1006438 Date: 2010-08-12



7.6 Test Result

Product:		2CH/4CH/6CH Radio Control				Test	Test Mode:		Low Channel			
Mode		Keeping Transmitting				Test	Test Voltage		DC9.6V			
Temperature		24 deg. C				Hu	Humidity		56% RH			
Tes	Test Result:		Pass				Detector		PK			
22	2390MHz		$\frac{PK (dB\mu V/m)}{AV (dB\mu V/m)}$		37.6		Limit		$74(dB\mu V/m)$			
23									54(dBµV/m)			
	Ref Lvl 107 dBμV		Marker 3		3 [T1] 41.04 dBμV .39000000 GHz		1 MI 1 MI 5 ms	Hz	- Att	10 dB dBμV		
107 100							▼ 3	[T1]	41.	.04 dBμV	Α	
90							∇1	[T1]	98. 2.40214	.01 dB/uV 1429 GHz		
							∇2	[T1]	73. 2.40000	1 1		
80	1MAX									2	1MA	
70 60												
50												
40									3 m			
30		when \		manhan		Lundon	lyn, wh.					
20												
10												
7	Start 2.31 GHz 9.5 MHz/ Stop 2.405 GHz											
Date: 01.JUL.2010 10:14:35												

Note: 1. Field Strength in restrict band measured in conventional manner

2. Emission Level = Reading Level + Probe Factor + Cable Loss.

Page 25 of 46

Report No: 1006438 Date: 2010-08-12

Product:	20	CH/4CH/6C		Control	Test	Mode:		High Channel		
Mode	Keeping Transmitting					Test Voltage		DC9.6V		
Temperature	24 deg. C					Humidity		56% RH		
Test Result:	Pass				Detector		PK			
2200741	PK (dBμV/m) 40.3		_			$74(dB\mu V/m)$				
2390MHz	AV(dBμV/m)				Limit		54(dBμV/m)			
	Marker 2		2 [T1]		RBW	RBW 1 MHz		Hz RFAtt 10 dB		
Ref Lvl			44.0	7 dB μ V	VBW	1 M	Hz			
107 dBμV		2	.483500	00 GHz	SWT	5 m	s U	In i t	dB μ V	
107						▼ 2	[T1]	44	.07 dBμV	
100								2.48350	9 <mark>888 GHz</mark>	Α
						∇_1	[T1]	1	.56 dBμV	
90 /	$\overline{}$							2.47795	5591 GHz	
	\									
80 /										
	\									
1MAX										1MA
70		\								
60 /										
50		\	2							
		1	Lithren	Manyka						
40				- William		hammy t	~hmp~rw	Murshaly,	Mulyly	
30										
20										
10										
7	75 611			0 -	MII				0 5 511	l
Start 2.475 GHz 2.5 MHz/ Stop 2.5 GHz										
Date: 01.JUL.2010 10:40:34										

Note: 1. Field Strength in restrict band measured in conventional manner

2. Emission Level = Reading Level + Probe Factor + Cable Loss.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: 1006438 Page 26 of 46

Date: 2010-08-12



8.0 Antenna Requirement

Applicable Standard


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The maximum Gain of the antennas is 2.5dBi.

Test Result: Pass


Page 27 of 46

Report No: 1006438 Date: 2010-08-12




Page 28 of 46

Report No: 1006438 Date: 2010-08-12



Page 29 of 46

Report No: 1006438 Date: 2010-08-12



Page 30 of 46

Report No: 1006438 Date: 2010-08-12




10.0 FCC ID Label

FCC ID: V6KCY246

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 31 of 46

Report No: 1006438 Date: 2010-08-12



11.0 Photo of testing

11.1 Conducted test View--

N/A

11.2 Radiated emission test view



Report No: 1006438 Date: 2010-08-12



11.3 Photo for the EUT



Outside View of the CY200



Outside View of the CY200

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to


Page 33 of 46

Report No: 1006438 Date: 2010-08-12



Inside View of the CY200

270 280 290 300 310 320 330 340 350 360 370



Inside View of the CY200

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to


Page 34 of 46

Report No: 1006438 Date: 2010-08-12





Inside View of the CY200



Inside View of the CY200

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to


Page 35 of 46

Report No: 1006438 Date: 2010-08-12





Inside View of the CY200



Inside View of the CY200

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 36 of 46

Report No: 1006438 Date: 2010-08-12



Inside View of the CY200



Outside View of the CY400

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 37 of 46

Report No: 1006438 Date: 2010-08-12



Outside View of the CY400



Inside View of the CY400


The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 38 of 46

Report No: 1006438 Date: 2010-08-12



Inside View of the CY400



Inside View of the CY400

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion


of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 39 of 46

Report No: 1006438 Date: 2010-08-12





Inside View of the CY400



Inside View of the CY400

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to


Page 40 of 46

Report No: 1006438 Date: 2010-08-12





Inside View of the CY400



Inside View of the CY400

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 41 of 46

Report No: 1006438 Date: 2010-08-12



Inside View of the CY400



Outside View of the CY600

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 42 of 46

Report No: 1006438 Date: 2010-08-12





Outside View of the CY600



Inside View of the CY600

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to


Page 43 of 46

Report No: 1006438 Date: 2010-08-12





Inside View of the CY600



Inside View of the CY600

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 44 of 46

Report No: 1006438 Date: 2010-08-12





Inside View of the CY600



Inside View of the CY600

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 45 of 46

Report No: 1006438 Date: 2010-08-12





Outside View of the N-2



Outside View of the N-4

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 46 of 46

Date: 2010-08-12

Report No: 1006438





Outside View of the N-6

--End of the report--