

FCC RF EXPOSURE REPORT

FCC ID: V7TSP3V1

Project No. : 1906C015
Equipment : Smart Wi-Fi Plug Mini
Model Name : SP3
Series Model : N/A
Applicant : SHENZHEN TENDA TECHNOLOGY CO.,LTD
Address : 6-8 Floor, Tower E3, No. 1001,
Zhongshanyuan Road, Nanshan District,
Shenzhen, China. 518052

According : FCC Guidelines for Human Exposure IEEE
C95.1 & FCC Part 2.1091

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Certificate #5123.02

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Jun. 24, 2019

1. GENERAL SUMMARY

Equipment : Smart Wi-Fi Plug Mini
 Brand Name : Tenda
 Test Model : SP3
 Series Model : N/A
 Applicant : SHENZHEN TENDA TECHNOLOGY CO.,LTD
 Manufacturer : SHENZHEN TENDA TECHNOLOGY CO.,LTD
 Address : 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District,
 Shenzhen, China. 518052
 Date of Test : Jun. 10, 2019 ~ Jun. 20, 2019
 Test Sample : Engineering Sample No.: DG19060550
 Standards : FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1906C015) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of A2LA according to the ISO/IEC 17025 quality assessment standard and technical standard(s).

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	1

3. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1	1.2589	28.04	636.7955	0.15957	1	Complies

Note: The calculated distance is 20 cm.

End of Test Report