

FCC PART 15.247

TEST REPORT

For

SHENZHEN TENDA TECHNOLOGY CO., LTD.

Tenda Industrial Park, No 34-1, Shilong Rd., Shiyan Town, Bao'an District, Shenzhen, China

FCC ID: V7TD151

Report Type: Original Report	Product Type: ADSL Router
Test Engineer:	Leon Chen
Report Number:	R2DG130813005-00B
Report Date:	2013-09-29
Reviewed By:	Ivan Cao RF Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §1.1310& §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST EQUIPMENT LIST AND DETAILS.....	29
TEST DATA	29

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	38
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST EQUIPMENT LIST AND DETAILS.....	51
TEST DATA	51
FCC §15.247(e) - POWER SPECTRAL DENSITY	56
APPLICABLE STANDARD	56
TEST PROCEDURE	56
TEST EQUIPMENT LIST AND DETAILS.....	56
TEST DATA	56

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *SHENZHEN TENDA TECHNOLOGY CO.,LTD.*'s product, model number: *D151 (FCC ID: V7TD151)* (the "EUT") in this report was a *ADSL Router*, which was measured approximately: 17.3 cm (L) x 14.5 cm (W) x 18.5 cm (H), rated input voltage: DC 9V from adapter.

Adapter Information: HEWEISHUN
MODEL: TEA09U-09100
INPUT: AC 100-240V, 50/60Hz, 0.3A
OUTPUT: DC 9V, 1.0A

** All measurement and test data in this report was gathered from production sample serial number: 130813005 (Assigned by BACL, Dongguan). The EUT was received on 2013-08-15.*

Objective

This report is prepared on behalf of *SHENZHEN TENDA TECHNOLOGY CO.,LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: *V7TD151*.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at <http://ts.nist.gov/standards/scopes/5000690.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4G band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n20 modes were tested with Channel 1, 6 and 11.
For 802.11n40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

EUT Exercise Software

The software “MTool 2.0.0.3” was used for testing, which was provided by manufacturer.

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
HP	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	0293
DELL (1#)	PC	GX620	/
DELL (2#)	PC	GX620	/
DELL (3#)	PC	GX620	/
Huawei	DSLAM Swith	MA5615	98MA6444773-001

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Parallel Cable	yes	no	1.2	Laptop	Printer
Serial Cable	yes	no	1.2	Laptop	Modem
RJ45 Cable	no	no	1.0	EUT	Laptop
RJ45 Cable*3	no	no	10.0	EUT	PC
RJ11 Cable	no	no	10.0	EUT	DSLAM Swicth
Keyboard Cable	yes	no	2.0	Laptop	Keyboard
Adapter DC Line	No	No	1.8	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1310, §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) , §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2462	5	3.16	10.62	11.53	20	0.007	1.0
802.11g	2462	5	3.16	12.62	18.28	20	0.011	1.0
802.11n20	2437	5	3.16	12.56	18.03	20	0.011	1.0
802.11n40	2422	5	3.16	12.25	16.79	20	0.011	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT have one dipole antenna, which use a unique type of connector to attach to the EUT, and the maximum gain is 5.0 dBi, please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCS 30	830245/006	2012-11-29	2013-11-28
R&S	L.I.S.N	ESH3-Z5	843331/015	2013-9-17	2014-9-16
R&S	L.I.S.N	ESH3-Z5	100113	2012-11-29	2013-11-28
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

4.09dB at 0.400 MHz in the **Line** conducted mode


Test Data**Environmental Conditions**

Temperature:	26.9°C
Relative Humidity:	63 %
ATM Pressure:	99.1 kPa


The testing was performed by Leon Chen on 2013-09-19.

Test Mode: Transmitting

120 V, 60 Hz, Line:



Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.400	50.09	0.32	57.85	7.76	QP
0.400	43.76	0.32	47.85	4.09	AV
0.600	47.13	0.31	56.00	8.87	QP
0.600	38.32	0.31	46.00	7.68	AV
0.770	47.03	0.32	56.00	8.97	QP
0.770	38.32	0.32	46.00	7.68	AV
1.080	48.17	0.32	56.00	7.83	QP
1.080	39.00	0.32	46.00	7.00	AV
2.250	46.46	0.37	56.00	9.54	QP
2.240	38.07	0.37	46.00	7.93	AV
5.810	50.75	0.54	60.00	9.25	QP
5.830	42.67	0.54	50.00	7.33	AV

120 V, 60 Hz, Neutral:

Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.550	46.15	0.21	56.00	9.85	QP
0.550	35.05	0.21	46.00	10.95	AV
0.830	46.48	0.22	56.00	9.52	QP
0.830	32.69	0.22	46.00	13.31	AV
1.440	46.38	0.25	56.00	9.62	QP
1.440	33.64	0.25	46.00	12.36	AV
1.810	45.86	0.26	56.00	10.14	QP
1.810	35.45	0.26	46.00	10.55	AV
2.230	45.88	0.28	56.00	10.12	QP
2.220	33.45	0.28	46.00	12.55	AV
5.320	49.15	0.42	60.00	10.85	QP
5.310	41.82	0.41	50.00	8.18	AV

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 2 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

For the radiated emissions test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	JB3	A060611-1	2011-9-6	2014-9-5
HP	HP AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM 30	849016/001	2012-12-7	2013-12-6
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
DUCMMUN Technologies	horn antenna	ARN-4223-02	1007726-01	2013-6-17	2014-6-16
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	N/A	N/A
QUINSTAR	Amplifier	QLW-18405536-J0	15964001001	N/A	N/A
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

2.01 dB at 2483.5 MHz in the Vertical polarization for 802.11g Mode

Test Data

Environmental Conditions

Temperature:	26.2°C
Relative Humidity:	59 %
ATM Pressure:	100.3kPa

The testing was performed by Leon Chen on 2013-09-17.

Mode: Transmitting
802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2412 MHz									
2412	61.71	PK	H	25.67	3.93	0.00	91.31	N/A	N/A
2412	55.67	AV	H	25.67	3.93	0.00	85.27	N/A	N/A
2412	72.38	PK	V	25.67	3.93	0.00	101.98	N/A	N/A
2412	66.57	AV	V	25.67	3.93	0.00	96.17	N/A	N/A
2390	27.45	PK	V	25.61	3.84	0.00	56.90	74.00	17.10
2390	15.69	AV	V	25.61	3.84	0.00	45.14	54.00	8.86
4824	47.12	PK	V	30.64	4.73	27.26	55.23	74.00	18.77
4824	43.86	AV	V	30.64	4.73	27.26	51.97	54.00	2.03 *
7236	38.62	PK	V	34.17	6.56	26.36	52.99	74.00	21.01
7236	29.12	AV	V	34.17	6.56	26.36	43.49	54.00	10.51
9648	34.26	PK	V	36.06	8.70	26.06	52.96	74.00	21.04
9648	20.12	AV	V	36.06	8.70	26.06	38.82	54.00	15.18
3216	40.36	PK	V	27.89	4.96	27.48	45.73	74.00	28.27
3216	36.58	AV	V	27.89	4.96	27.48	41.95	54.00	12.05
250.23	47.5	QP	V	12.17	1.92	21.49	40.10	46.00	5.90*
Middle Channel: 2437 MHz									
2437	61.45	PK	H	25.74	3.98	0.00	91.17	N/A	N/A
2437	55.43	AV	H	25.74	3.98	0.00	85.15	N/A	N/A
2437	72.41	PK	V	25.74	3.98	0.00	102.13	N/A	N/A
2437	66.63	AV	V	25.74	3.98	0.00	96.35	N/A	N/A
4874	47.23	PK	V	30.77	4.76	27.26	55.50	74.00	18.50
4874	43.32	AV	V	30.77	4.76	27.26	51.59	54.00	2.41 *
7311	36.35	PK	V	34.35	6.70	26.51	50.89	74.00	23.11
7311	27.54	AV	V	34.35	6.70	26.51	42.08	54.00	11.92
9748	33.32	PK	V	36.30	8.60	25.68	52.54	74.00	21.46
9748	20.12	AV	V	36.30	8.60	25.68	39.34	54.00	14.66
2213	34.25	PK	V	25.15	3.51	27.25	35.66	74.00	38.34
2213	21.43	AV	V	25.15	3.51	27.25	22.84	54.00	31.16
3216	41.26	PK	V	27.89	4.96	27.48	46.63	74.00	27.37
3216	37.68	AV	V	27.89	4.96	27.48	43.05	54.00	10.95
250.25	47.5	QP	V	12.17	1.92	21.49	40.10	46.00	5.90*
High Channel: 2462 MHz									
2462	61.46	PK	H	25.80	3.93	0.00	91.19	N/A	N/A
2462	55.52	AV	H	25.80	3.93	0.00	85.25	N/A	N/A
2462	72.56	PK	V	25.80	3.93	0.00	102.29	N/A	N/A
2462	66.81	AV	V	25.80	3.93	0.00	96.54	N/A	N/A
2483.5	31.26	PK	V	25.86	3.80	0.00	60.92	74.00	13.08
2483.5	18.52	AV	V	25.86	3.80	0.00	48.18	54.00	5.82
4924	45.82	PK	V	30.90	4.70	27.27	54.15	74.00	19.85
4924	41.62	AV	V	30.90	4.70	27.27	49.95	54.00	4.05 *
7386	33.25	PK	V	34.53	6.84	26.66	47.96	74.00	26.04
7386	19.57	AV	V	34.53	6.84	26.66	34.28	54.00	19.72
9848	32.73	PK	V	36.54	8.49	25.49	52.27	74.00	21.73
9848	18.89	AV	V	36.54	8.49	25.49	38.43	54.00	15.57
3216	42.36	PK	V	27.89	4.96	27.48	47.73	74.00	26.27
3216	38.52	AV	V	27.89	4.96	27.48	43.89	54.00	10.11
250.06	47.3	QP	V	12.18	1.92	21.49	39.91	46.00	6.09 *

*Within measurement uncertainty!

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2412 MHz									
2412	65.83	PK	H	25.67	3.93	0.00	95.43	N/A	N/A
2412	53.33	AV	H	25.67	3.93	0.00	82.93	N/A	N/A
2412	76.96	PK	V	25.67	3.93	0.00	106.56	N/A	N/A
2412	63.64	AV	V	25.67	3.93	0.00	93.24	N/A	N/A
2390	39.12	PK	V	25.61	3.84	0.00	68.57	74.00	5.43
2390	20.89	AV	V	25.61	3.84	0.00	50.34	54.00	3.66 *
4824	58.36	PK	V	30.64	4.73	27.26	66.47	74.00	7.53
4824	43.36	AV	V	30.64	4.73	27.26	51.47	54.00	2.53 *
7236	46.36	PK	V	34.17	6.56	26.36	60.73	74.00	13.27
7236	31.05	AV	V	34.17	6.56	26.36	45.42	54.00	8.58
9648	35.62	PK	V	36.06	8.70	26.06	54.32	74.00	19.68
9648	20.57	AV	V	36.06	8.70	26.06	39.27	54.00	14.73
3216	38.69	PK	V	27.89	4.96	27.48	44.06	74.00	29.94
3216	25.47	AV	V	27.89	4.96	27.48	30.84	54.00	23.16
250.05	47.5	QP	V	12.18	1.92	21.49	40.11	46.00	5.89 *
Middle Channel: 2437 MHz									
2437	66.36	PK	H	25.74	3.98	0.00	96.08	N/A	N/A
2437	54.26	AV	H	25.74	3.98	0.00	83.98	N/A	N/A
2437	77.12	PK	V	25.74	3.98	0.00	106.84	N/A	N/A
2437	63.68	AV	V	25.74	3.98	0.00	93.40	N/A	N/A
4874	57.36	PK	V	30.77	4.76	27.26	65.63	74.00	8.37
4874	42.68	AV	V	30.77	4.76	27.26	50.95	54.00	3.05 *
7311	43.25	PK	V	34.35	6.70	26.51	57.79	74.00	16.21
7311	28.69	AV	V	34.35	6.70	26.51	43.23	54.00	10.77
9748	35.62	PK	V	36.30	8.60	25.68	54.84	74.00	19.16
9748	20.57	AV	V	36.30	8.60	25.68	39.79	54.00	14.21
3215	37.62	PK	V	27.89	4.95	27.48	42.98	74.00	31.02
3215	24.56	AV	V	27.89	4.95	27.48	29.92	54.00	24.08
3615	40.36	PK	V	29.05	5.03	27.43	47.01	74.00	26.99
3615	27.58	AV	V	29.05	5.03	27.43	34.23	54.00	19.77
250.11	46.6	QP	V	12.18	1.92	21.49	39.21	46.00	6.79
High Channel: 2462 MHz									
2462	68.45	PK	H	25.80	3.93	0.00	98.18	N/A	N/A
2462	54.45	AV	H	25.80	3.93	0.00	84.18	N/A	N/A
2462	77.93	PK	V	25.80	3.93	0.00	107.66	N/A	N/A
2462	64.37	AV	V	25.80	3.93	0.00	94.10	N/A	N/A
2483.5	38.52	PK	V	25.86	3.80	0.00	68.18	74.00	5.82
2483.5	22.33	AV	V	25.86	3.80	0.00	51.99	54.00	2.01 *
4924	58.69	PK	V	30.90	4.70	27.27	67.02	74.00	6.98
4924	43.52	AV	V	30.90	4.70	27.27	51.85	54.00	2.15 *
7386	45.63	PK	V	34.53	6.84	26.66	60.34	74.00	13.66
7386	30.81	AV	V	34.53	6.84	26.66	45.52	54.00	8.48
9848	36.52	PK	V	36.54	8.49	25.49	56.06	74.00	17.94
9848	21.65	AV	V	36.54	8.49	25.49	41.19	54.00	12.81
3216	36.95	PK	V	27.89	4.96	27.48	42.32	74.00	31.68
3216	23.58	AV	V	27.89	4.96	27.48	28.95	54.00	25.05
250.25	47.5	QP	V	12.17	1.92	21.49	40.10	46.00	5.90 *

*Within measurement uncertainty!

802.11 n20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2412 MHz									
2412	65.44	PK	H	25.67	3.93	0.00	95.04	N/A	N/A
2412	52.38	AV	H	25.67	3.93	0.00	81.98	N/A	N/A
2412	75.87	PK	V	25.67	3.93	0.00	105.47	N/A	N/A
2412	62.17	AV	V	25.67	3.93	0.00	91.77	N/A	N/A
2390	41.16	PK	V	25.61	3.84	0.00	70.61	74.00	3.39 *
2390	21.48	AV	V	25.61	3.84	0.00	50.93	54.00	3.07 *
4824	48.74	PK	V	30.64	4.73	27.26	56.85	74.00	17.15
4824	31.44	AV	V	30.64	4.73	27.26	39.55	54.00	14.45
7236	36.32	PK	V	34.17	6.56	26.36	50.69	74.00	23.31
7236	20.38	AV	V	34.17	6.56	26.36	34.75	54.00	19.25
9648	33.32	PK	V	36.06	8.70	26.06	52.02	74.00	21.98
9648	19.32	AV	V	36.06	8.70	26.06	38.02	54.00	15.98
2213	36.25	PK	V	25.15	3.51	27.25	37.66	74.00	36.34
2213	23.47	AV	V	25.15	3.51	27.25	24.88	54.00	29.12
250.08	46.5	QP	V	12.18	1.92	21.49	39.11	46.00	6.89
Middle Channel: 2437 MHz									
2437	66.82	PK	H	25.74	3.98	0.00	96.54	N/A	N/A
2437	53.61	AV	H	25.74	3.98	0.00	83.33	N/A	N/A
2437	76.97	PK	V	25.74	3.98	0.00	106.69	N/A	N/A
2437	63.82	AV	V	25.74	3.98	0.00	93.54	N/A	N/A
4874	47.69	PK	V	30.77	4.76	27.26	55.96	74.00	18.04
4874	30.42	AV	V	30.77	4.76	27.26	38.69	54.00	15.31
7311	35.62	PK	V	34.35	6.70	26.51	50.16	74.00	23.84
7311	19.86	AV	V	34.35	6.70	26.51	34.40	54.00	19.60
9748	33.68	PK	V	36.30	8.60	25.68	52.90	74.00	21.10
9748	19.13	AV	V	36.30	8.60	25.68	38.35	54.00	15.65
3215	35.62	PK	V	27.89	4.95	27.48	40.98	74.00	33.02
3215	22.57	AV	V	27.89	4.95	27.48	27.93	54.00	26.07
3615	34.21	PK	V	29.05	5.03	27.43	40.86	74.00	33.14
3615	20.68	AV	V	29.05	5.03	27.43	27.33	54.00	26.67
250.36	46.5	QP	V	12.17	1.92	21.49	39.10	46.00	6.90
High Channel: 2462 MHz									
2462	66.63	PK	H	25.80	3.93	0.00	96.36	N/A	N/A
2462	53.48	AV	H	25.80	3.93	0.00	83.21	N/A	N/A
2462	76.74	PK	V	25.80	3.93	0.00	106.47	N/A	N/A
2462	63.71	AV	V	25.80	3.93	0.00	93.44	N/A	N/A
2483.5	38.84	PK	V	25.86	3.80	0.00	68.50	74.00	5.50
2483.5	22.03	AV	V	25.86	3.80	0.00	51.69	54.00	2.31 *
4924	48.52	PK	V	30.90	4.70	27.27	56.85	74.00	17.15
4924	30.63	AV	V	30.90	4.70	27.27	38.96	54.00	15.04
7386	36.78	PK	V	34.53	6.84	26.66	51.49	74.00	22.51
7386	20.57	AV	V	34.53	6.84	26.66	35.28	54.00	18.72
9848	34.26	PK	V	36.54	8.49	25.49	53.80	74.00	20.20
9848	20.12	AV	V	36.54	8.49	25.49	39.66	54.00	14.34
2213	35.69	PK	V	25.15	3.51	27.25	37.10	74.00	36.90
2213	22.85	AV	V	25.15	3.51	27.25	24.26	54.00	29.74
250.03	46.7	QP	V	12.18	1.92	21.49	39.31	46.00	6.69

*Within measurement uncertainty!


802.11 n40 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2422 MHz									
2422	62.91	PK	H	25.70	3.95	0.00	92.56	N/A	N/A
2422	48.73	AV	H	25.70	3.95	0.00	78.38	N/A	N/A
2422	73.43	PK	V	25.70	3.95	0.00	103.08	N/A	N/A
2422	57.87	AV	V	25.70	3.95	0.00	87.52	N/A	N/A
2390	42.53	PK	V	25.61	3.84	0.00	71.98	74.00	2.02 *
2390	22.43	AV	V	25.61	3.84	0.00	51.88	54.00	2.12 *
4844	42.92	PK	V	30.69	4.78	27.26	51.13	74.00	22.87
4844	27.86	AV	V	30.69	4.78	27.26	36.07	54.00	17.93
7266	35.32	PK	V	34.24	6.62	26.42	49.76	74.00	24.24
7266	19.68	AV	V	34.24	6.62	26.42	34.12	54.00	19.88
9688	33.28	PK	V	36.15	8.66	25.91	52.18	74.00	21.82
9688	17.68	AV	V	36.15	8.66	25.91	36.58	54.00	17.42
2213	36.32	PK	V	25.15	3.51	27.25	37.73	74.00	36.27
2213	22.75	AV	V	25.15	3.51	27.25	24.16	54.00	29.84
250.13	47.1	QP	V	12.18	1.92	21.49	39.71	46.00	6.29
Middle Channel: 2437 MHz									
2437	62.91	PK	H	25.74	3.98	0.00	92.63	N/A	N/A
2437	48.73	AV	H	25.74	3.98	0.00	78.45	N/A	N/A
2437	73.43	PK	V	25.74	3.98	0.00	103.15	N/A	N/A
2437	57.87	AV	V	25.74	3.98	0.00	87.59	N/A	N/A
4874	42.52	PK	V	30.77	4.76	27.26	50.79	74.00	23.21
4874	27.35	AV	V	30.77	4.76	27.26	35.62	54.00	18.38
7311	34.26	PK	V	34.35	6.70	26.51	48.80	74.00	25.20
7311	19.12	AV	V	34.35	6.70	26.51	33.66	54.00	20.34
9748	33.65	PK	V	36.30	8.60	25.68	52.87	74.00	21.13
9748	17.46	AV	V	36.30	8.60	25.68	36.68	54.00	17.32
3215	36.52	PK	V	27.89	4.95	27.48	41.88	74.00	32.12
3215	21.86	AV	V	27.89	4.95	27.48	27.22	54.00	26.78
3615	34.26	PK	V	29.05	5.03	27.43	40.91	74.00	33.09
3615	20.47	AV	V	29.05	5.03	27.43	27.12	54.00	26.88
250.12	47.2	QP	V	12.18	1.92	21.49	39.81	46.00	6.19 *
High Channel: 2452 MHz									
2452	63.11	PK	H	25.78	4.00	0.00	92.88	N/A	N/A
2452	48.56	AV	H	25.78	4.00	0.00	78.33	N/A	N/A
2452	73.52	PK	V	25.78	4.00	0.00	103.29	N/A	N/A
2452	57.21	AV	V	25.78	4.00	0.00	86.98	N/A	N/A
2483.5	38.66	PK	V	25.86	3.80	0.00	68.32	74.00	5.68
2483.5	21.14	AV	V	25.86	3.80	0.00	50.80	54.00	3.20 *
4904	43.38	PK	V	30.85	4.72	27.27	51.68	74.00	22.32
4904	26.81	AV	V	30.85	4.72	27.27	35.11	54.00	18.89
7356	34.63	PK	V	34.45	6.79	26.60	49.27	74.00	24.73
7356	19.35	AV	V	34.45	6.79	26.60	33.99	54.00	20.01
9808	34.66	PK	V	36.44	8.53	25.48	54.15	74.00	19.85
9808	17.81	AV	V	36.44	8.53	25.48	37.30	54.00	16.70
2213	36.56	PK	V	25.15	3.51	27.25	37.97	74.00	36.03
2213	22.14	AV	V	25.15	3.51	27.25	23.55	54.00	30.45
250.03	47.4	QP	V	12.18	1.92	21.49	40.01	46.00	5.99 *

*Within measurement uncertainty!


Conducted Spurious Emissions at Antenna Port

802.11b Low Channel




Date: 17.SEP.2013 09:45:01

802.11b Middle Channel




Date: 17.SEP.2013 09:47:44

802.11b High Channel




Date: 17.SEP.2013 09:52:27

802.11g Low Channel




Date: 17.SEP.2013 09:56:09

802.11g Middle Channel




Date: 17.SEP.2013 09:58:00

802.11g High Channel




Date: 17.SEP.2013 09:59:41

802.11n20 Low Channel




Date: 17.SEP.2013 10:02:08

802.11n20 Middle Channel




Date: 17.SEP.2013 10:04:21

802.11n20 High Channel




Date: 17.SEP.2013 10:06:11

802.11n40 Low Channel




Date: 17.SEP.2013 10:11:31

802.11n40 Middle Channel



Date: 17.SEP.2013 10:13:23

802.11n40 High Channel



Date: 17.SEP.2013 10:15:13


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.2° C
Relative Humidity:	59 %
ATM Pressure:	100.3kPa

The testing was performed by Leon Chen on 2013-09-17.


Test Mode: Transmitting

Test Result: Pass.

Please refer to the following tables and plots.


Channel	Frequency	6 dB Bandwidth	Limit
	(MHz)	(MHz)	(kHz)
802.11b mode			
Low	2412	8.11	>500
Middle	2437	8.15	>500
High	2462	8.11	>500
802.11g mode			
Low	2412	14.75	>500
Middle	2437	15.02	>500
High	2462	15.10	>500
802.11n20 mode			
Low	2412	15.14	>500
Middle	2437	14.39	>500
High	2462	15.06	>500
802.11n40 mode			
Low	2422	34.13	>500
Middle	2437	34.13	>500
High	2452	35.32	>500

802.11b Low Channel




Date: 17.SEP.2013 09:43:40

802.11b Middle Channel




Date: 17.SEP.2013 09:46:43

802.11b High Channel




Date: 17.SEP.2013 09:51:46

802.11g Low Channel




Date: 17.SEP.2013 09:55:15

802.11g Middle Channel




Date: 17.SEP.2013 09:56:52

802.11g High Channel




Date: 17.SEP.2013 09:58:47

802.11n20 Low Channel




Date: 17.SEP.2013 10:00:55

802.11n20 Middle Channel




Date: 17.SEP.2013 10:03:07

802.11n20 High Channel




Date: 17.SEP.2013 10:05:07

802.11n40 Low Channel




Date: 17.SEP.2013 10:10:29

802.11n40 Middle Channel



Date: 17.SEP.2013 10:12:18

802.11n40 High Channel




Date: 17.SEP.2013 10:14:10

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER**Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. According to KDB 558074 D01 DTS Meas Guidance v03r01, place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.2~27.5° C
Relative Humidity:	56~65 %
ATM Pressure:	99~100.6kPa

The testing was performed by Leon Chen from 2013-09-17 to 2013-09-29.

Test Mode: Transmitting

Channel	Frequency	Conducted Output Power	Limit	Result
	(MHz)	(dBm)	(dBm)	
802.11b mode				
Low	2412 MHz	10.33	30	PASS
Middle	2437 MHz	10.62	30	PASS
High	2462 MHz	10.51	30	PASS
802.11g mode				
Low	2412 MHz	12.28	30	PASS
Middle	2437 MHz	12.33	30	PASS
High	2462 MHz	12.62	30	PASS
802.11n20 mode				
Low	2412 MHz	12.52	30	PASS
Middle	2437 MHz	12.56	30	PASS
High	2462 MHz	12.08	30	PASS
802.11n40 mode				
Low	2422 MHz	12.14	30	PASS
Middle	2437 MHz	12.13	30	PASS
High	2452 MHz	12.25	30	PASS

Please refer to the following plots

Ref 20 dBm * Att 30 dB * RBW 100 kHz * VBW 300 kHz SWT 5 ms Marker 1 [T1] 2.80 dBm 2.413960000 GHz

20 Offset 1 dB

1 PK
MAXH

OBW 10.080000000 MHz
Temp 1 [T1 OBW] -7.85 dBm A

2.406960000 GHz
Temp 2 [T1 OBW] -7.85 dBm LVL

2.417040000 GHz

3DB

Center 2.412 GHz 4 MHz/ Span 40 MHz

Date: 17.SEP.2013 09:43:47

MARKER 1

- *RBW 300 kHz
- *VBW 1 MHz
- SWT 2.5 ms

Marker 1 [T1]

-0.54 dBm

2.41248384 GHz

Offset 1 dB

1 RM MAXH

B

LVL

3DB

Center 2.412 GHz

1.512 MHz/

Span 15.12 MHz


Tx Channel

Bandwidth 10.08 MHz

Power 10.33 dBm


Date: 29.SEP.2013 18:43:54

802.11b RF OBW, Middle Channel




Date: 17.SEP.2013 09:46:50

802.11b RF Output Power, Middle Channel




Date: 29.SEP.2013 18:45:34

802.11b RF OBW, High Channel




Date: 17.SEP.2013 09:51:53

802.11b RF Output Power, High Channel




Date: 29.SEP.2013 18:46:27

802.11g RF OBW, Low Channel




Date: 17.SEP.2013 09:55:22

802.11g RF Output Power, Low Channel




Date: 29.SEP.2013 18:48:42

802.11g RF OBW, Middle Channel




Date: 17.SEP.2013 09:56:59

802.11g RF Output Power, Middle Channel




Date: 29.SEP.2013 18:49:13

802.11g RF OBW, High Channel




Date: 17.SEP.2013 09:58:54

802.11g RF Output Power, High Channel




Date: 29.SEP.2013 18:49:28

802.11n20 RF OBW, Low Channel




Date: 17.SEP.2013 10:01:02

802.11n20 RF Output Power, Low Channel




Date: 29.SEP.2013 19:33:01

802.11n20 RF OBW, Middle Channel




Date: 17.SEP.2013 10:03:13

802.11n20 RF Output Power, Middle Channel




Date: 29.SEP.2013 19:24:25

802.11n20 RF OBW, High Channel




Date: 17.SEP.2013 10:05:14

802.11n20 RF Output Power, High Channel




Date: 29.SEP.2013 19:24:54

802.11n40 RF OBW, Low Channel




Date: 17.SEP.2013 10:10:36

802.11n40 RF Output Power, Low Channel




Date: 29.SEP.2013 19:27:10

802.11n40 RF OBW, Middle Channel




Date: 17.SEP.2013 10:12:25

802.11n40 RF Output Power, Middle Channel




Date: 29.SEP.2013 19:28:02

802.11n40 RF OBW, High Channel



Date: 17.SEP.2013 10:14:17

802.11n40 RF Output Power, High Channel



Date: 29.SEP.2013 19:28:33

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	26.2 °C
Relative Humidity:	59%
ATM Pressure:	100.3 kPa

The testing was performed by Leon Chen on 2013-09-17.

Test Result: Compliance


Please refer to following table and plots.

802.11b: Band Edge, Left Side



Date: 17.SEP.2013 09:45:13

802.11b: Band Edge, Right Side




Date: 17.SEP.2013 09:52:39

*RBW 100 kHz Marker 4 [T1] -33.08 dBm
 *VBW 300 kHz
 Ref 20 dBm *Att 30 dB SWT 5 ms 2.399426573 GHz

20 Offset 1 dB
 1 PK MAXH
 Marker 1 [T1] -0.11 dBm
 2.405704000 GHz
 Marker 2 [T1] -43.15 dBm
 2.390000000 GHz
 Marker 3 [T1] -38.03 dBm
 2.400000000 GHz
 LVL
 3dB
 F1 F2
 Start 2.38 GHz 4.2 MHz/ Stop 2.422 GHz


802.11g: Band Edge, Right Side



Page 53 of 63

[illegible]

802.11n20 Band Edge, Right Side



Page 54 of 63

1 PK MAXH

Ref 20 dBm * Att 30 dB

* RBW 100 kHz * VBW 300 kHz * SWT 10 ms

Marker 4 [T1] -34.97 dBm 2.399696304 GHz

20 Offset 1 dB

Marker 1 [T1] -1.85 dBm 2.424516000 GHz

Marker 2 [T1] -40.46 dBm 2.390000000 GHz


Marker 3 [T1] -34.97 dBm 2.400000000 GHz

D1 -21.847 dBm

F1 F2

Start 2.38 GHz 6.2 MHz/ Stop 2.442 GHz

802.11n40 Band Edge, Right Side



Page 55 of 63

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. According to KDB 558074 D01 DTS Meas Guidance v03r01, set the RBW = 3 kHz, VBW = 30 kHz, Set the span to 1.5 times the DTS channel bandwidth.
4. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.1° C
Relative Humidity:	62 %
ATM Pressure:	100.5kPa


The testing was performed by Leon Chen on 2013-09-17.

*Test Mode: Transmitting***Test Result:** Pass

Channel	PSD	Limit	Result
	(dBm/3kHz)	(dBm/3kHz)	
802.11b mode			
Low	-11.75	8	PASS
Middle	-12.79	8	PASS
High	-11.83	8	PASS
802.11g mode			
Low	-13.52	8	PASS
Middle	-13.08	8	PASS
High	-13.26	8	PASS
802.11n20 mode			
Low	-13.39	8	PASS
Middle	-13.30	8	PASS
High	-13.31	8	PASS
802.11n40 mode			
Low	-15.92	8	PASS
Middle	-16.61	8	PASS
High	-15.92	8	PASS


Please refer to the following plots

Power Spectral Density, 802.11b Low Channel




Date: 17.SEP.2013 09:44:49

Power Spectral Density, 802.11b Middle Channel




Date: 17.SEP.2013 09:47:31

Power Spectral Density, 802.11b High Channel




Date: 17.SEP.2013 09:52:15

Power Spectral Density, 802.11g Low Channel




Date: 17.SEP.2013 09:55:56

Power Spectral Density, 802.11g Middle Channel




Date: 17.SEP.2013 09:57:47

Power Spectral Density, 802.11g High Channel




Date: 17.SEP.2013 09:59:29

Power Spectral Density, 802.11n20 Low Channel




Date: 17.SEP.2013 10:01:56


Power Spectral Density, 802.11n20 Middle Channel



Date: 17.SEP.2013 10:04:08


Power Spectral Density, 802.11n20 High Channel

Date: 17.SEP.2013 10:05:59

Power Spectral Density, 802.11n40 Low Channel


Date: 17.SEP.2013 10:11:18

Power Spectral Density, 802.11n40 Middle Channel



Date: 17.SEP.2013 10:13:10

Power Spectral Density, 802.11n40 High Channel



Date: 17.SEP.2013 10:15:00

***** END OF REPORT *****