



**Neutron Engineering Inc.**

# FCC Radio Test Report

## FCC ID: V7TW312A

This report concerns (check one): ☒ Original Grant ☐ Class II Change

**Issued Date** : Apr. 02, 2014  
**Project No.** : 1403C031  
**Equipment** : Wireless N300 Wall Plate Access Point  
**Model Name** : W312A  
**Applicant** : SHENZHEN TENDA TECHNOLOGY CO.,LTD  
**Address** : 6-8 Floor, Tower E3, No. 1001,  
Zhongshanyuan Road, Nanshan District,  
Shenzhen, China. 518052

**Tested by:** Neutron Engineering Inc. EMC Laboratory  
**Date of Receipt:** Mar. 06, 2014  
**Date of Test:** Mar. 06, 2014 ~ Mar. 31, 2014

**Testing Engineer** :

*David Mao*

(David Mao)

**Technical Manager** :

*Leo Hung*

(Leo Hung)

**Authorized Signatory** :

*Steven Lu*

(Steven Lu)

### Neutron Engineering Inc.

No.3,Jinshagang 1st Road, ShiXia,  
Dalang Town, Dong Guan, China.

TEL: 0769-8318-3000

FAX: 0769-8319-6000



### **Declaration**

**Neutron** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

**Neutron's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

**Neutron's** reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

**Neutron's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



| <b>Table of Contents</b>                                     | <b>Page</b> |
|--|-------------|
| <b>1 . CERTIFICATION</b>                                     | <b>6</b>    |
| <b>2 . SUMMARY OF TEST RESULTS</b>                           | <b>7</b>    |
| 2.1 TEST FACILITY  | 8           |
| 2.2 MEASUREMENT UNCERTAINTY                                  | 8           |
| <b>3 . GENERAL INFORMATION</b>                               | <b>9</b>    |
| 3.1 GENERAL DESCRIPTION OF EUT                               | 9           |
| 3.2 DESCRIPTION OF TEST MODES                                | 11          |
| 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING             | 12          |
| 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 13          |
| 3.5 DESCRIPTION OF SUPPORT UNITS                             | 14          |
| <b>4 . EMC EMISSION TEST</b>                                 | <b>15</b>   |
| 4.1 CONDUCTED EMISSION MEASUREMENT                           | 15          |
| 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS                   | 15          |
| 4.1.2 TEST PROCEDURE   | 15          |
| 4.1.3 DEVIATION FROM TEST STANDARD                           | 15          |
| 4.1.4 TEST SETUP   | 16          |
| 4.1.5 EUT OPERATING CONDITIONS                               | 16          |
| 4.1.6 EUT TEST CONDITIONS                                    | 16          |
| 4.1.7 TEST RESULTS   | 16          |
| 4.2 RADIATED EMISSION MEASUREMENT                            | 19          |
| 4.2.1 RADIATED EMISSION LIMITS                               | 19          |
| 4.2.2 TEST PROCEDURE   | 20          |
| 4.2.3 DEVIATION FROM TEST STANDARD                           | 20          |
| 4.2.4 TEST SETUP   | 21          |
| 4.2.5 EUT OPERATING CONDITIONS                               | 22          |
| 4.2.6 EUT TEST CONDITIONS                                    | 22          |
| 4.2.7 TEST RESULTS (9K~ 30MHZ)                               | 23          |
| 4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHZ)                   | 24          |
| 4.2.9 TEST RESULTS (ABOVE 1000 MHZ)                          | 31          |
| <b>5 . BANDWIDTH TEST</b>                                    | <b>60</b>   |
| 5.1 APPLIED PROCEDURES                                       | 60          |
| 5.1.1 TEST PROCEDURE   | 60          |
| 5.1.2 DEVIATION FROM STANDARD                                | 60          |
| 5.1.3 TEST SETUP   | 60          |
| 5.1.4 EUT OPERATION CONDITIONS                               | 60          |
| 5.1.5 EUT TEST CONDITIONS                                    | 60          |
| 5.1.6 TEST RESULTS   | 61          |



| <b>Table of Contents</b>                       | <b>Page</b> |
|--|-------------|
| <b>6 . MAXIMUM OUTPUT POWER TEST</b>           | <b>73</b>   |
| 6.1 APPLIED PROCEDURES / LIMIT                 | 73          |
| 6.1.1 TEST PROCEDURE                           | 73          |
| 6.1.2 DEVIATION FROM STANDARD                  | 73          |
| 6.1.3 TEST SETUP                               | 73          |
| 6.1.4 EUT OPERATION CONDITIONS                 | 73          |
| 6.1.5 EUT TEST CONDITIONS                      | 73          |
| 6.1.6 TEST RESULTS                             | 74          |
| <b>7 . ANTENNA CONDUCTED SPURIOUS EMISSION</b> | <b>77</b>   |
| 7.1 APPLIED PROCEDURES / LIMIT                 | 77          |
| 7.1.1 TEST PROCEDURE                           | 77          |
| 7.1.2 DEVIATION FROM STANDARD                  | 77          |
| 7.1.3 TEST SETUP                               | 77          |
| 7.1.4 EUT OPERATION CONDITIONS                 | 77          |
| 7.1.5 EUT TEST CONDITIONS                      | 77          |
| 7.1.6 TEST RESULTS                             | 78          |
| <b>8 . POWER SPECTRAL DENSITY TEST</b>         | <b>108</b>  |
| 8.1 APPLIED PROCEDURES / LIMIT                 | 108         |
| 8.1.1 TEST PROCEDURE                           | 108         |
| 8.1.2 DEVIATION FROM STANDARD                  | 108         |
| 8.1.3 TEST SETUP                               | 108         |
| 8.1.4 EUT OPERATION CONDITIONS                 | 108         |
| 8.1.5 EUT TEST CONDITIONS                      | 108         |
| 8.1.6 TEST RESULTS                             | 109         |
| <b>9 . MEASUREMENT INSTRUMENTS LIST</b>        | <b>123</b>  |
| <b>10 . EUT TEST PHOTO</b>                     | <b>125</b>  |



**REPORT ISSUED HISTORY**

| Issued No.          | Description     | Issued Date   |
|---------------------|-----------------|---------------|
| NEI-FCCP-1-1403C031 | Original Issue. | Apr. 02, 2014 |



## **1. CERTIFICATION**

Equipment : Wireless N300 Wall Plate Access Point  
Brand Name : Tenda  
Model Name : W312A  
Applicant : SHENZHEN TENDA TECHNOLOGY CO.,LTD  
Date of Test : Mar. 06, 2014 ~ Mar. 31, 2014  
Test Item : ENGINEERING SAMPLE  
Standard(s) : FCC Part15, Subpart C(15.247) / ANSI C63.4-2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1403C031) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

| Applied Standard(s): FCC Part15 (15.247) , Subpart C |         |                                     |          |        |
|--|---------|-------------------------------------|----------|--------|
| Standard(s)  | Section | Test Item                           | Judgment | Remark |
| FCC  |         |                                     |          |        |
| 15.207   |         | Conducted Emission                  | PASS     |        |
| 15.247(d)  |         | Antenna conducted Spurious Emission | PASS     |        |
| 15.247(a)(2)   |         | 6dB Bandwidth                       | PASS     |        |
| 15.247(b)(3)   |         | Peak Output Power                   | PASS     |        |
| 15.247(e)  |         | Power Spectral Density              | PASS     |        |
| 15.203   |         | Antenna Requirement                 | PASS     |        |
| 15.209/15.205  |         | Transmitter Radiated Emissions      | PASS     |        |

### NOTE:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r01 (Measurement Guidelines of DTS)



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792  
Neutron's test firm number for FCC: 319330

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

### A. Conducted Measurement :

| Test Site | Method | Measurement Frequency Range | U , (dB) | NOTE |
|-----------|--------|-----------------------------|----------|------|
| DG-C02    | CISPR  | 150 KHz ~ 30MHz             | 1.94     |      |

### B. Radiated Measurement :

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U , (dB) | NOTE |
|-----------|--------|-----------------------------|------------|----------|------|
| DG-CB03   | CISPR  | 9KHz~30MHz                  | V          | 3.79     |      |
|           |        | 9KHz~30MHz                  | H          | 3.57     |      |
|           |        | 30MHz ~ 200MHz              | V          | 3.82     |      |
|           |        | 30MHz ~ 200MHz              | H          | 3.60     |      |
|           |        | 200MHz ~ 1,000MHz           | V          | 3.86     |      |
|           |        | 200MHz ~ 1,000MHz           | H          | 3.94     |      |
|           |        | 1GHz~18GHz                  | V          | 3.12     |      |
|           |        | 1GHz~18GHz                  | H          | 3.68     |      |
|           |        | 18GHz~40GHz                 | V          | 4.15     |      |
|           |        | 18GHz~40GHz                 | H          | 4.14     |      |





### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                        |                                       |  |
|------------------------|---------------------------------------|--|
| Equipment              | Wireless N300 Wall Plate Access Point |  |
| Brand Name             | Tenda                                 |  |
| Model Name             | W312A                                 |  |
| Model Difference       | N/A                                   |  |
| Product Description    | Operation Frequency                   | 2412~2462 MHz  |
|                        | Modulation Technology                 | 802.11b:DSSS<br>802.11g:OFDM<br>802.11n:OFDM   |
|                        | Bit Rate of Transmitter               | 802.11b: 11/5.5/2/1 Mbps<br>802.11g:<br>54/48/36/24/18/12/9/6 Mbps<br>802.11n up to 300 Mbps       |
|                        | Output Power (Max.)-Peak              | 802.11b: 20.26 dBm<br>802.11g: 20.32 dBm<br>802.11n(20MHz): 23.30 dBm<br>802.11n(40MHz): 21.59 dBm |
| Power Source           | Supplied from PoE.                    |  |
| Power Rating           | DC 48V 320mA                          |  |
| Connecting I/O Port(s) | Please refer to the User's Manual     |  |

**Note:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2. Channel List:

| CH 01 – CH 11 for 802.11b, 802.11g, 802.11n(20MHz)<br>CH 03 – CH 09 for 802.11n(40MHz) |                 |         |                 |         |                 |         |                 |
|--|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel  | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 01   | 2412            | 04      | 2427            | 07      | 2442            | 10      | 2457            |
| 02   | 2417            | 05      | 2432            | 08      | 2447            | 11      | 2462            |
| 03   | 2422            | 06      | 2437            | 09      | 2452            |         |                 |

3. Table for Filed Antenna:

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | Length |
|------|-------|------------|--------------|-----------|------------|--------|
| 1    | Tenda | Q5106      | Internal     | N/A       | 3.81       | 90mm   |
| 2    | Tenda | Q5101      | Internal     | N/A       | 3.81       | 70mm   |

Note:

(1) The EUT incorporates a MIMO function. Physically, the EUT provides two completed two transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, **Direction gain =  $G_{ANT}$** , that is Directional gain=3.81.

4.

| Operating Mode<br>TX Mode | 1TX                | 2TX               |
|---------------------------|--------------------|-------------------|
|                           |                    |                   |
| 802.11b                   | V (ANT 1 or ANT 2) | -                 |
| 802.11g                   | V (ANT 1 or ANT 2) | -                 |
| 802.11n(20MHz)            | -                  | V (ANT 1 + ANT 2) |
| 802.11n(40MHz)            | -                  | V (ANT 1 + ANT 2) |



### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description                      |
|--------------|----------------------------------|
| Mode 1       | TX B MODE CHANNEL 01/06/11       |
| Mode 2       | TX G MODE CHANNEL 01/06/11       |
| Mode 3       | TX N-20MHZ MODE CHANNEL 01/06/11 |
| Mode 4       | TX N-40MHZ MODE CHANNEL 03/06/09 |
| Mode 5       | TX MODE                          |

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

| For Conducted Test |             |
|--------------------|-------------|
| Final Test Mode    | Description |
| Mode 5             | TX MODE     |

| For Radiated Test |                                  |
|-------------------|----------------------------------|
| Final Test Mode   | Description                      |
| Mode 1            | TX B MODE CHANNEL 01/06/11       |
| Mode 2            | TX G MODE CHANNEL 01/06/11       |
| Mode 3            | TX N-20MHZ MODE CHANNEL 01/06/11 |
| Mode 4            | TX N-40MHZ MODE CHANNEL 03/06/09 |

Note:

- (1) The measurements are performed at the high, middle, low available channels.
- (2) 802.11b mode: DBPSK (1Mbps)  
 802.11g mode: OFDM (6Mbps)  
 802.11n HT20 mode : BPSK (13Mbps)  
 802.11n HT40 mode : BPSK (27Mbps)  
 For radiated emission tests, the highest output powers were set for final test.
- (3) For radiated below 1G test, the 802.11b is found to be the worst case and recorded.



### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

|                        |                 |                 |                 |
|------------------------|-----------------|-----------------|-----------------|
| Test software version  | MP.2.0.0.3      |                 |                 |
| <b>Frequency</b>       | <b>2412 MHz</b> | <b>2437 MHz</b> | <b>2462 MHz</b> |
| IEEE 802.11b DSSS      | 70              | 71              | 71              |
| IEEE 802.11g OFDM      | 62              | 63              | 64              |
| IEEE 802.11n (20MHz)   | 47              | 47              | 48              |
| <b>Frequency (MHz)</b> | <b>2422 MHz</b> | <b>2437 MHz</b> | <b>2452 MHz</b> |
| IEEE 802.11n (40MHz)   | 43              | 45              | 47              |




### 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

#### Conducted TX Mode:




#### Control Room

C-1: RJ11 Cable  
C-2: RJ45 Cable  
C-3: USB Cable  
C-4: RJ11 Cable



#### Radiated TX Mode:



**3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment      | Mfr/Brand | Model/Type No. | FCC ID | Series No.  | Note |
|------|----------------|-----------|----------------|--------|-------------|------|
| E-1  | iPod nano (2G) | Apple     | A1199          | DOC    | YM7214GEVQ5 |      |
| E-2  | Notebook       | Lenovo    | E46L           | DOC    | EB22953770  |      |
| E-3  | Phone          | N/A       | N/A            | N/A    | N/A         |      |
| E-4  | Gateway        | Huawei    | EspaceU1911    | N/A    | N/A         |      |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| C-1  | NO            | NO           | 10m    |      |
| C-2  | NO            | NO           | 10m    |      |
| C-3  | YES           | NO           | 1.2m   |      |
| C-4  | NO            | NO           | 10m    |      |



## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| Frequency (MHz) | Class A (dBuV) |         | Class B (dBuV) |           | Standard |
|-----------------|----------------|---------|----------------|-----------|----------|
|                 | Quasi-peak     | Average | Quasi-peak     | Average   |          |
| 0.15 -0.5       | 79.00          | 66.00   | 66 - 56 *      | 56 - 46 * | CISPR    |
| 0.50 -5.0       | 73.00          | 60.00   | 56.00          | 46.00     | CISPR    |
| 5.0 -30.0       | 73.00          | 60.00   | 60.00          | 50.00     | CISPR    |
|                 |                |         |                |           |          |
| 0.15 -0.5       | 79.00          | 66.00   | 66 - 56 *      | 56 - 46 * | FCC      |
| 0.50 -5.0       | 73.00          | 60.00   | 56.00          | 46.00     | FCC      |
| 5.0 -30.0       | 73.00          | 60.00   | 60.00          | 50.00     | FCC      |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 KHz    |


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



**Note:** 1.Support units were connected to second LISN .  
 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80  
 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 18°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Remark:


- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note 』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform.In this case, a “ \* ” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.





Test Mode : TX MODE

**Line**




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   | *   | 0.3335       | 39.86                    | 9.54                    | 49.40                    | 59.36         | -9.96      | peak     |         |
| 2   |     | 0.3335       | 26.70                    | 9.54                    | 36.24                    | 49.36         | -13.12     | AVG      |         |
| 3   |     | 0.5835       | 33.92                    | 9.60                    | 43.52                    | 56.00         | -12.48     | peak     |         |
| 4   |     | 1.2670       | 33.16                    | 9.66                    | 42.82                    | 56.00         | -13.18     | peak     |         |
| 5   |     | 16.2265      | 37.52                    | 10.34                   | 47.86                    | 60.00         | -12.14     | peak     |         |
| 6   |     | 23.1290      | 36.60                    | 10.47                   | 47.07                    | 60.00         | -12.93     | peak     |         |
| 7   |     | 26.6093      | 35.68                    | 10.58                   | 46.26                    | 60.00         | -13.74     | peak     |         |



Test Mode : TX MODE

**Neutral**



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   | *   | 0.3335       | 39.26                    | 9.53                    | 48.79                    | 59.36         | -10.57     | peak     |         |
| 2   |     | 0.3335       | 26.50                    | 9.53                    | 36.03                    | 49.36         | -13.33     | AVG      |         |
| 3   |     | 0.5990       | 35.66                    | 9.59                    | 45.25                    | 56.00         | -10.75     | peak     |         |
| 4   |     | 0.5990       | 23.70                    | 9.59                    | 33.29                    | 46.00         | -12.71     | AVG      |         |
| 5   |     | 0.9937       | 34.04                    | 9.63                    | 43.67                    | 56.00         | -12.33     | peak     |         |
| 6   |     | 16.2265      | 35.64                    | 10.51                   | 46.15                    | 60.00         | -13.85     | peak     |         |
| 7   |     | 23.1290      | 34.88                    | 10.72                   | 45.60                    | 60.00         | -14.40     | peak     |         |
| 8   |     | 26.6093      | 34.74                    | 10.87                   | 45.61                    | 60.00         | -14.39     | peak     |         |



## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz-1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009~0.490     | 2400/F(KHz)                       | 300                           |
| 0.490~1.705     | 24000/F(KHz)                      | 30                            |
| 1.705~30.0      | 30                                | 30                            |
| 30~88           | 100                               | 3                             |
| 88~216          | 150                               | 3                             |
| 216~960         | 200                               | 3                             |
| 960~1000        | 500                               | 3                             |

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| Frequency (MHz) | (dBuV/m) (at 3 meters) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                         | Setting  |
|--|--|
| Attenuation                                | Auto   |
| Start Frequency                            | 1000 MHz                                       |
| Stop Frequency                             | 10th carrier harmonic                          |
| RBW / VBW<br>(Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter     | Setting                           |
|------------------------|-----------------------------------|
| Attenuation            | Auto                              |
| Start ~ Stop Frequency | 9KHz~90KHz for PK/AVG detector    |
| Start ~ Stop Frequency | 90KHz~110KHz for QP detector      |
| Start ~ Stop Frequency | 110KHz~490KHz for PK/AVG detector |
| Start ~ Stop Frequency | 490KHz~30MHz for QP detector      |
| Start ~ Stop Frequency | 30MHz~1000MHz for QP detector     |



#### **4.2.2 TEST PROCEDURE**


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### **4.2.3 DEVIATION FROM TEST STANDARD**


No deviation

#### 4.2.4 TEST SETUP

##### (A) Radiated Emission Test Set-Up Frequency Below 1 GHz




##### (B) Radiated Emission Test Set-Up Frequency Above 1 GHz



Note: The antenna can be moved between 1 to 4 meters above the ground.

(C) For radiated emissions below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 21°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz



#### 4.2.7 TEST RESULTS (9K~ 30MHZ)

Test Mode : TX Mode 2412MHz

| Freq.<br>(MHz) | Ant.<br>0°/90° | Reading(RA)<br>(dBuV) | Corr.Factor(CF)<br>(dB) | Measured(FS)<br>(dBuV/m) | Limits(QP)<br>(dBuV/m) | Margin<br>(dB) | Note |
|----------------|----------------|-----------------------|-------------------------|--------------------------|------------------------|----------------|------|
| 0.0094         | 0°             | 68.35                 | 24.30                   | 92.65                    | 128.12                 | -35.47         | AV   |
| 0.0094         | 0°             | 72.35                 | 24.30                   | 96.65                    | 148.12                 | -51.47         | PK   |
| 0.0135         | 0°             | 70.35                 | 24.30                   | 94.65                    | 125.00                 | -30.35         | AV   |
| 0.0137         | 0°             | 79.35                 | 24.30                   | 103.65                   | 145.00                 | -41.35         | PK   |
| 0.0245         | 0°             | 56.36                 | 24.02                   | 80.38                    | 119.82                 | -39.45         | AV   |
| 0.0246         | 0°             | 60.12                 | 24.02                   | 84.14                    | 139.82                 | -55.69         | PK   |
| 0.0326         | 0°             | 61.36                 | 23.50                   | 84.86                    | 117.34                 | -32.48         | AV   |
| 0.0328         | 0°             | 65.38                 | 23.50                   | 88.88                    | 137.34                 | -48.46         | PK   |
| 0.5670         | 0°             | 18.72                 | 20.01                   | 38.73                    | 72.53                  | -33.80         | QP   |
| 1.7536         | 0°             | 18.95                 | 19.52                   | 38.47                    | 69.54                  | -31.07         | QP   |

| Freq.<br>(MHz) | Ant.<br>0°/90° | Reading(RA)<br>(dBuV) | Corr.Factor(CF)<br>(dB) | Measured(FS)<br>(dBuV/m) | Limits(QP)<br>(dBuV/m) | Margin<br>(dB) | Note |
|----------------|----------------|-----------------------|-------------------------|--------------------------|------------------------|----------------|------|
| 0.0094         | 90°            | 76.35                 | 24.30                   | 100.65                   | 128.19                 | -27.54         | AVG  |
| 0.0094         | 90°            | 82.36                 | 24.30                   | 106.66                   | 148.19                 | -41.53         | PK   |
| 0.0236         | 90°            | 56.38                 | 24.07                   | 80.45                    | 120.15                 | -39.69         | AVG  |
| 0.0237         | 90°            | 59.35                 | 24.07                   | 83.42                    | 140.15                 | -56.72         | PK   |
| 0.0316         | 90°            | 57.35                 | 23.57                   | 80.92                    | 117.61                 | -36.70         | AVG  |
| 0.0318         | 90°            | 58.35                 | 23.57                   | 81.92                    | 137.61                 | -55.70         | PK   |
| 0.0427         | 90°            | 59.35                 | 22.86                   | 82.21                    | 115.00                 | -32.78         | AVG  |
| 0.0429         | 90°            | 63.35                 | 22.86                   | 86.21                    | 135.00                 | -48.78         | PK   |
| 0.4912         | 90°            | 17.45                 | 19.82                   | 37.27                    | 73.78                  | -36.51         | QP   |
| 1.7156         | 90°            | 18.63                 | 19.53                   | 38.16                    | 69.54                  | -31.38         | QP   |

#### Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.



#### **4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHZ)**

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.





|            |                      |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 01 |
|------------|----------------------|


**Vertical**



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 37.7600      | 51.74                    | -21.70                  | 30.04                      | 40.00           | -9.96      | peak     |         |
| 2   | *   | 250.1900     | 53.13                    | -16.95                  | 36.18                      | 46.00           | -9.82      | peak     |         |
| 3   |     | 321.0000     | 53.16                    | -17.83                  | 35.33                      | 46.00           | -10.67     | peak     |         |
| 4   |     | 450.0100     | 49.06                    | -15.74                  | 33.32                      | 46.00           | -12.68     | peak     |         |
| 5   |     | 500.4500     | 48.31                    | -15.33                  | 32.98                      | 46.00           | -13.02     | peak     |         |
| 6   |     | 749.7400     | 38.88                    | -7.16                   | 31.72                      | 46.00           | -14.28     | peak     |         |



|            |                      |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 01 |
|------------|----------------------|




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 250.1900     | 53.17                    | -22.49                  | 30.68                      | 46.00           | -15.32     | peak     |         |
| 2   | *   | 321.0000     | 57.01                    | -17.39                  | 39.62                      | 46.00           | -6.38      | peak     |         |
| 3   |     | 399.5700     | 44.33                    | -12.87                  | 31.46                      | 46.00           | -14.54     | peak     |         |
| 4   |     | 450.0100     | 51.53                    | -13.28                  | 38.25                      | 46.00           | -7.75      | peak     |         |
| 5   |     | 500.4500     | 50.57                    | -13.96                  | 36.61                      | 46.00           | -9.39      | peak     |         |
| 6   |     | 749.7400     | 44.47                    | -8.32                   | 36.15                      | 46.00           | -9.85      | peak     |         |



|            |                      |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 06 |
|------------|----------------------|


**Vertical**



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   | *   | 321.0000     | 58.51                    | -17.39                  | 41.12                      | 46.00           | -4.88      | peak     |         |
| 2   |     | 399.5700     | 44.33                    | -12.87                  | 31.46                      | 46.00           | -14.54     | peak     |         |
| 3   |     | 450.0100     | 51.53                    | -13.28                  | 38.25                      | 46.00           | -7.75      | peak     |         |
| 4   |     | 500.4500     | 49.57                    | -13.96                  | 35.61                      | 46.00           | -10.39     | peak     |         |
| 5   |     | 749.7400     | 44.97                    | -8.32                   | 36.65                      | 46.00           | -9.35      | peak     |         |
| 6   |     | 874.8700     | 39.24                    | -9.50                   | 29.74                      | 46.00           | -16.26     | peak     |         |



|            |                      |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 06 |
|------------|----------------------|




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   | *   | 37.7600      | 52.74                    | -21.70                  | 31.04                      | 40.00           | -8.96      | peak     |         |
| 2   |     | 250.1900     | 53.13                    | -16.95                  | 36.18                      | 46.00           | -9.82      | peak     |         |
| 3   |     | 321.0000     | 53.66                    | -17.83                  | 35.83                      | 46.00           | -10.17     | peak     |         |
| 4   |     | 450.0100     | 50.56                    | -15.74                  | 34.82                      | 46.00           | -11.18     | peak     |         |
| 5   |     | 500.4500     | 50.31                    | -15.33                  | 34.98                      | 46.00           | -11.02     | peak     |         |
| 6   |     | 749.7400     | 41.88                    | -7.16                   | 34.72                      | 46.00           | -11.28     | peak     |         |



|            |                      |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 11 |
|------------|----------------------|


**Vertical**



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   | *   | 321.0000     | 57.51                    | -17.39                  | 40.12                      | 46.00           | -5.88      | peak     |         |
| 2   |     | 399.5700     | 44.33                    | -12.87                  | 31.46                      | 46.00           | -14.54     | peak     |         |
| 3   |     | 450.0100     | 50.03                    | -13.28                  | 36.75                      | 46.00           | -9.25      | peak     |         |
| 4   |     | 500.4500     | 49.07                    | -13.96                  | 35.11                      | 46.00           | -10.89     | peak     |         |
| 5   |     | 749.7400     | 46.47                    | -8.32                   | 38.15                      | 46.00           | -7.85      | peak     |         |
| 6   |     | 900.0900     | 36.72                    | -6.88                   | 29.84                      | 46.00           | -16.16     | peak     |         |



|            |                      |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 11 |
|------------|----------------------|



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 250.1900     | 52.67                    | -22.49                  | 30.18                      | 46.00           | -15.82     | peak     |         |
| 2   | *   | 321.0000     | 56.51                    | -17.39                  | 39.12                      | 46.00           | -6.88      | peak     |         |
| 3   |     | 399.5700     | 43.83                    | -12.87                  | 30.96                      | 46.00           | -15.04     | peak     |         |
| 4   |     | 450.0100     | 51.53                    | -13.28                  | 38.25                      | 46.00           | -7.75      | peak     |         |
| 5   |     | 500.4500     | 49.57                    | -13.96                  | 35.61                      | 46.00           | -10.39     | peak     |         |
| 6   |     | 749.7400     | 44.47                    | -8.32                   | 36.15                      | 46.00           | -9.85      | peak     |         |



#### **4.2.9 TEST RESULTS (ABOVE 1000 MHZ)**

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency;"H" denotes spurious frequency;"E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



Test Mode : TX B MODE 2412MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |               | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|---------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV            | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)      | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | V        | 26.49        | 18.86        | 34.09        | 60.58         | 52.95         | 74.00    | 54.00    | X/E        |
| <b>2412.90</b> | <b>V</b> | <b>70.79</b> | <b>68.46</b> | <b>34.16</b> | <b>104.95</b> | <b>102.62</b> |          |          | <b>X/F</b> |
| 4823.87        | V        | 48.07        | 44.58        | 6.43         | 54.50         | 51.01         | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |               | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|---------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV            | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)      | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | H        | 25.33        | 17.64        | 34.09        | 59.42         | 51.73         | 74.00    | 54.00    | X/E        |
| <b>2412.90</b> | <b>H</b> | <b>70.49</b> | <b>68.14</b> | <b>34.16</b> | <b>104.65</b> | <b>102.30</b> |          |          | <b>X/F</b> |
| 4823.98        | H        | 48.06        | 44.51        | 6.43         | 54.49         | 50.94         | 74.00    | 54.00    | X/H        |

Test Mode : TX B MODE 2437MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |               | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|---------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV            | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)      | (dBuV/m) | (dBuV/m) |            |
| <b>2436.10</b> | <b>V</b> | <b>71.22</b> | <b>68.96</b> | <b>34.23</b> | <b>105.45</b> | <b>103.19</b> |          |          | <b>X/F</b> |
| 4874.19        | V        | 46.92        | 43.43        | 6.58         | 53.50         | 50.01         | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |               | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|---------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV            | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)      | (dBuV/m) | (dBuV/m) |            |
| <b>2436.10</b> | <b>H</b> | <b>72.42</b> | <b>70.12</b> | <b>34.23</b> | <b>106.65</b> | <b>104.35</b> |          |          | <b>X/F</b> |
| 4873.86        | H        | 46.11        | 43.36        | 6.58         | 52.69         | 49.94         | 74.00    | 54.00    | X/H        |

Test Mode : TX B MODE 2462MHz



| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |               | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|---------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV            | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)      | (dBuV/m) | (dBuV/m) |            |
| <b>2461.20</b> | <b>V</b> | <b>73.46</b> | <b>71.26</b> | <b>34.31</b> | <b>107.77</b> | <b>105.57</b> |          |          | <b>X/F</b> |
| 2483.50        | V        | 26.22        | 17.40        | 34.37        | 60.59         | 51.77         | 74.00    | 54.00    | X/E        |
| 4923.75        | V        | 46.38        | 43.19        | 6.72         | 53.10         | 49.91         | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |               | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|---------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV            | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)      | (dBuV/m) | (dBuV/m) |            |
| <b>2461.10</b> | <b>H</b> | <b>76.16</b> | <b>73.88</b> | <b>34.31</b> | <b>110.47</b> | <b>108.19</b> |          |          | <b>X/F</b> |
| 2483.50        | H        | 26.40        | 18.46        | 34.37        | 60.77         | 52.83         | 74.00    | 54.00    | X/E        |
| 4924.18        | H        | 45.17        | 43.02        | 6.72         | 51.89         | 49.74         | 74.00    | 54.00    | X/H        |







TX CH01 (Above 1000 MHz, Vertical)







TX CH01 (Above 1000 MHz, Horizontal)







TX CH06 (Above 1000 MHz, Vertical)







TX CH06 (Above 1000 MHz, Horizontal)







TX CH11 (Above 1000 MHz, Vertical)





TX CH11 (Above 1000 MHz, Horizontal)





Test Mode : TX G MODE 2412MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | V        | 34.58        | 18.23        | 34.09        | 68.67         | 52.32        | 74.00    | 54.00    | X/E        |
| <b>2413.20</b> | <b>V</b> | <b>71.98</b> | <b>61.69</b> | <b>34.16</b> | <b>106.14</b> | <b>95.85</b> |          |          | <b>X/F</b> |
| 4823.99        | V        | 43.17        | 41.18        | 6.43         | 49.60         | 47.61        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | H        | 32.48        | 18.99        | 34.09        | 66.57         | 53.08        | 74.00    | 54.00    | X/E        |
| <b>2413.20</b> | <b>H</b> | <b>70.00</b> | <b>60.92</b> | <b>34.16</b> | <b>104.16</b> | <b>95.08</b> |          |          | <b>X/F</b> |
| 4823.87        | H        | 43.06        | 40.51        | 6.43         | 49.49         | 46.94        | 74.00    | 54.00    | X/H        |

Test Mode : TX G MODE 2437MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2436.80</b> | <b>V</b> | <b>72.12</b> | <b>63.97</b> | <b>34.23</b> | <b>106.35</b> | <b>98.20</b> |          |          | <b>X/F</b> |
| 4873.97        | V        | 44.82        | 42.63        | 6.58         | 51.40         | 49.21        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2436.00</b> | <b>H</b> | <b>69.61</b> | <b>61.88</b> | <b>34.23</b> | <b>103.84</b> | <b>96.11</b> |          |          | <b>X/F</b> |
| 4873.79        | H        | 43.91        | 41.37        | 6.58         | 50.49         | 47.95        | 74.00    | 54.00    | X/H        |



Test Mode : TX G MODE 2462MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2462.20</b> | <b>V</b> | <b>73.75</b> | <b>65.08</b> | <b>34.31</b> | <b>108.06</b> | <b>99.39</b> |          |          | <b>X/F</b> |
| 2483.50        | V        | 30.55        | 18.17        | 34.37        | 64.92         | 52.54        | 74.00    | 54.00    | X/E        |
| 4924.17        | V        | 42.69        | 45.78        | 6.72         | 49.41         | 52.50        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2456.10</b> | <b>H</b> | <b>70.63</b> | <b>62.14</b> | <b>34.29</b> | <b>104.92</b> | <b>96.43</b> |          |          | <b>X/F</b> |
| 2483.50        | H        | 26.11        | 16.17        | 34.37        | 60.48         | 50.54        | 74.00    | 54.00    | X/E        |
| 4924.11        | H        | 43.71        | 41.12        | 6.72         | 50.43         | 47.84        | 74.00    | 54.00    | X/H        |





TX CH01 (Above 1000 MHz, Vertical)









TX CH01 (Above 1000 MHz, Horizontal)







TX CH06 (Above 1000 MHz, Vertical)







TX CH06 (Above 1000 MHz, Horizontal)







TX CH11 (Above 1000 MHz, Vertical)





TX CH11 (Above 1000 MHz, Horizontal)





Test Mode : TX N-20M MODE 2412MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | V        | 31.80        | 18.74        | 34.09        | 65.89         | 52.83        | 74.00    | 54.00    | X/E        |
| <b>2413.40</b> | <b>V</b> | <b>74.69</b> | <b>63.03</b> | <b>34.16</b> | <b>108.85</b> | <b>97.19</b> |          |          | <b>X/F</b> |
| 4824.14        | V        | 43.07        | 41.58        | 6.43         | 49.50         | 48.01        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | H        | 33.55        | 18.76        | 34.09        | 67.64         | 52.85        | 74.00    | 54.00    | X/E        |
| <b>2412.70</b> | <b>H</b> | <b>73.00</b> | <b>62.06</b> | <b>34.16</b> | <b>107.16</b> | <b>96.22</b> |          |          | <b>X/F</b> |
| 4824.14        | H        | 42.06        | 40.53        | 6.43         | 48.49         | 46.96        | 74.00    | 54.00    | X/H        |

Test Mode : TX N-20M MODE 2437MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2464.00</b> | <b>V</b> | <b>74.67</b> | <b>64.99</b> | <b>34.31</b> | <b>108.98</b> | <b>99.30</b> |          |          | <b>X/F</b> |
| 4874.17        | V        | 43.21        | 41.32        | 6.58         | 49.79         | 47.90        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2461.60</b> | <b>H</b> | <b>75.11</b> | <b>64.85</b> | <b>34.31</b> | <b>109.42</b> | <b>99.16</b> |          |          | <b>X/F</b> |
| 4874.01        | H        | 42.16        | 42.10        | 6.58         | 48.74         | 48.68        | 74.00    | 54.00    | X/H        |



Test Mode : TX N-20M MODE 2462MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.         |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|--------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak         | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)     | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2469.20</b> | <b>V</b> | <b>63.29</b> | <b>53.63</b> | <b>34.51</b> | <b>97.80</b> | <b>88.14</b> |          |          | <b>X/F</b> |
| 2483.50        | V        | 23.34        | 13.71        | 34.56        | 57.90        | 48.27        | 74.00    | 54.00    | X/E        |
| 4923.95        | V        | 42.29        | 42.14        | 6.72         | 49.01        | 48.86        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2464.00</b> | <b>H</b> | <b>74.67</b> | <b>64.99</b> | <b>34.31</b> | <b>108.98</b> | <b>99.30</b> |          |          | <b>X/F</b> |
| 2483.50        | H        | 31.63        | 18.64        | 34.37        | 66.00         | 53.01        | 74.00    | 54.00    | X/E        |
| 4924.14        | H        | 41.37        | 41.22        | 6.72         | 48.09         | 47.94        | 74.00    | 54.00    | X/H        |





TX CH01 (Above 1000 MHz, Vertical)







TX CH01 (Above 1000 MHz, Horizontal)









TX CH06 (Above 1000 MHz, Vertical)







TX CH06 (Above 1000 MHz, Horizontal)







TX CH11 (Above 1000 MHz, Vertical)





TX CH11 (Above 1000 MHz, Horizontal)





Test Mode : TX N-40M MODE 2422MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | V        | 29.76        | 19.19        | 34.09        | 63.85         | 53.28        | 74.00    | 54.00    | X/E        |
| <b>2410.80</b> | <b>V</b> | <b>67.87</b> | <b>56.02</b> | <b>34.16</b> | <b>102.03</b> | <b>90.18</b> |          |          | <b>X/F</b> |
| 4843.78        | V        | 41.91        | 39.14        | 6.50         | 48.41         | 45.64        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| 2390.00        | H        | 30.49        | 19.07        | 34.09        | 64.58         | 53.16        | 74.00    | 54.00    | X/E        |
| <b>2420.00</b> | <b>H</b> | <b>67.38</b> | <b>55.93</b> | <b>34.18</b> | <b>101.56</b> | <b>90.11</b> |          |          | <b>X/F</b> |
| 4843.90        | H        | 41.01        | 38.34        | 6.50         | 47.51         | 44.84        | 74.00    | 54.00    | X/H        |

Test Mode : TX N-40M MODE 2437MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2438.00</b> | <b>V</b> | <b>67.13</b> | <b>57.19</b> | <b>34.23</b> | <b>101.36</b> | <b>91.42</b> |          |          | <b>X/F</b> |
| 4874.03        | V        | 41.93        | 39.16        | 6.58         | 48.51         | 45.74        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2438.40</b> | <b>H</b> | <b>68.19</b> | <b>57.24</b> | <b>34.23</b> | <b>102.42</b> | <b>91.47</b> |          |          | <b>X/F</b> |
| 4874.02        | H        | 41.22        | 38.43        | 6.58         | 47.80         | 45.01        | 74.00    | 54.00    | X/H        |



Test Mode : TX N-40M MODE 2452MHz

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2445.20</b> | <b>V</b> | <b>68.46</b> | <b>57.04</b> | <b>34.25</b> | <b>102.71</b> | <b>91.29</b> |          |          | <b>X/F</b> |
| 2483.50        | V        | 27.78        | 17.96        | 34.37        | 62.15         | 52.33        | 74.00    | 54.00    | X/E        |
| 2487.00        | V        | 28.31        | 18.49        | 34.38        | 62.69         | 52.87        | 74.00    | 54.00    | X/E        |
| 4903.76        | V        | 40.82        | 39.27        | 6.67         | 47.49         | 45.94        | 74.00    | 54.00    | X/H        |

| Freq.          | Ant.Pol. | Reading      |              | Ant./CF      | Act.          |              | Limit    |          | Note       |
|----------------|----------|--------------|--------------|--------------|---------------|--------------|----------|----------|------------|
|                |          | Peak         | AV           |              | Peak          | AV           | Peak     | AV       |            |
| (MHz)          | H/V      | (dBuV)       | (dBuV)       | CF(dB)       | (dBuV/m)      | (dBuV/m)     | (dBuV/m) | (dBuV/m) |            |
| <b>2460.00</b> | <b>H</b> | <b>68.16</b> | <b>56.88</b> | <b>34.30</b> | <b>102.46</b> | <b>91.18</b> |          |          | <b>X/F</b> |
| 2483.50        | H        | 27.14        | 17.87        | 34.37        | 61.51         | 52.24        | 74.00    | 54.00    | X/E        |
| 2488.20        | H        | 27.83        | 18.44        | 34.38        | 62.21         | 52.82        | 74.00    | 54.00    | X/E        |
| 4904.25        | H        | 41.82        | 38.74        | 6.67         | 48.49         | 45.41        | 74.00    | 54.00    | X/H        |





TX CH03 (Above 1000 MHz, Vertical)







TX CH03 (Above 1000 MHz, Horizontal)







TX CH06 (Above 1000 MHz, Vertical)









TX CH06 (Above 1000 MHz, Horizontal)







TX CH09 (Above 1000 MHz, Vertical)





TX CH09 (Above 1000 MHz, Horizontal)





## 5. BANDWIDTH TEST

### 5.1 Applied procedures

| FCC Part15 (15.247) , Subpart C |           |                       |        |
|---------------------------------|-----------|-----------------------|--------|
| Section                         | Test Item | Frequency Range (MHz) | Result |
| 15.247(a)(2)                    | Bandwidth | 2400-2483.5           | PASS   |


#### 5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


#### 5.1.5 EUT TEST CONDITIONS



Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz



### 5.1.6 TEST RESULTS


Test Mode : TX B Mode\_CH01/06/11









Test Mode: TX G Mode\_CH01/06/11













Test Mode : TX N-20MHz Mode\_CH01/06/11\_ANT 1










Test Mode : TX N-20MHz Mode\_CH01/06/11\_ANT 2








## TX CH 03



\*REW 100 kHz    Delta 1 [T1]     
 \*VSW 300 kHz                       -1.52 dB  
 Ref 20 dBm       \*Att 30 dB        SWT 10 ms       36.260000000 MHz



20 Offset 1 dB  
 OBW 36.300000000 MHz  
 Marker 1 [T1]  
 -4.60 dBm  
 2.403740000 GHz  
 Temp 1 [T1 OBW]  
 F2 -3.82 dBm  
 2.3850000 GHz  
 Temp 2 [T1 OBW]  
 -4.56 dBm  
 2.440150000 GHz



D1 0.13 dBm  
 D2 0.17 dBm

F1  
 F2

1 PK  
 MAXH


B  
 LVL  
 3dB



Center 2.422 GHz    5.5 MHz/    Span 55 MHz





Test Mode : TX N-40MHz Mode\_CH03/06/09\_ANT 2









## 6. MAXIMUM OUTPUT POWER TEST

### 6.1 Applied procedures / limit

| FCC Part15 (15.247) , Subpart C |                      |                 |                       |        |
|---------------------------------|----------------------|-----------------|-----------------------|--------|
| Section                         | Test Item            | Limit           | Frequency Range (MHz) | Result |
| 15.247(b)(3)                    | Maximum Output Power | 1 Watt or 30dBm | 2400-2483.5           | PASS   |

#### 6.1.1 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- The maximum peak conducted output power was performed in accordance with method 9.1.3 of FCC KDB 558074 D01 DTS Meas Guidance v03r01.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Transmit output power was measured while the host equipment supply voltage was varied from 85 % to 115 % of the nominal rated supply voltage. No change in transmit output power was observed.

#### 6.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz



**6.1.6 TEST RESULTS**

| Test Mode : TX B Mode |                 |                         |             |              |
|-----------------------|-----------------|-------------------------|-------------|--------------|
| Test Channel          | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
| CH01                  | 2412            | 20.26                   | 30          | 1            |
| CH06                  | 2437            | 20.23                   | 30          | 1            |
| CH11                  | 2462            | 20.17                   | 30          | 1            |

| Test Mode : TX G Mode |                 |                         |             |              |
|-----------------------|-----------------|-------------------------|-------------|--------------|
| Test Channel          | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
| CH01                  | 2412            | 20.11                   | 30          | 1            |
| CH06                  | 2437            | 20.17                   | 30          | 1            |
| CH11                  | 2462            | 20.32                   | 30          | 1            |



**Test Mode : TX N-20M Mode\_ANT 1**

| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
|--------------|-----------------|-------------------------|-------------|--------------|
| CH01         | 2412            | 20.13                   | 30          | 1            |
| CH06         | 2437            | 20.21                   | 30          | 1            |
| CH11         | 2462            | 20.32                   | 30          | 1            |

**Test Mode : TX N-20M Mode\_ANT 2**

| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
|--------------|-----------------|-------------------------|-------------|--------------|
| CH01         | 2412            | 20.21                   | 30          | 1            |
| CH06         | 2437            | 20.27                   | 30          | 1            |
| CH11         | 2462            | 20.25                   | 30          | 1            |

**Test Mode : TX N-20M Mode\_Total**

| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
|--------------|-----------------|-------------------------|-------------|--------------|
| CH01         | 2412            | 23.18                   | 30          | 1            |
| CH06         | 2437            | 23.25                   | 30          | 1            |
| CH11         | 2462            | 23.30                   | 30          | 1            |



**Test Mode : TX N-40M Mode\_ANT 1**

| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
|--------------|-----------------|-------------------------|-------------|--------------|
| CH03         | 2422            | 18.19                   | 30          | 1            |
| CH06         | 2437            | 18.65                   | 30          | 1            |
| CH09         | 2452            | 18.73                   | 30          | 1            |

**Test Mode : TX N-40M Mode\_ANT 2**

| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
|--------------|-----------------|-------------------------|-------------|--------------|
| CH03         | 2422            | 18.25                   | 30          | 1            |
| CH06         | 2437            | 18.38                   | 30          | 1            |
| CH09         | 2452            | 18.43                   | 30          | 1            |

**Test Mode : TX N-40M Mode\_Total**

| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) | Limit (Watt) |
|--------------|-----------------|-------------------------|-------------|--------------|
| CH03         | 2422            | 21.23                   | 30          | 1            |
| CH06         | 2437            | 21.53                   | 30          | 1            |
| CH09         | 2452            | 21.59                   | 30          | 1            |



## **7. ANTENNA CONDUCTED SPURIOUS EMISSION**

### **7.1 Applied procedures / limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

#### **7.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

#### **7.1.2 DEVIATION FROM STANDARD**

No deviation.

#### **7.1.3 TEST SETUP**



#### **7.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

#### **7.1.5 EUT TEST CONDITIONS**

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz




**7.1.6 TEST RESULTS**

|             |           |
|-------------|-----------|
| Test Mode : | TX B Mode |
|-------------|-----------|




### TX B mode CH01





Date: 23.MAR.2014 15:05:12

### TX B mode CH11




Date: 23.MAR.2014 15:07:47








### TX B mode CH06 (30M~1000MHz)



Date: 23.MAR.2014 15:12:29


### TX B mode CH06 (1000MHz~10<sup>th</sup> Harmonic)



Date: 23.MAR.2014 15:12:51




### TX B mode CH11 (30M~1000MHz)



Date: 23.MAR.2014 15:08:02

### TX B mode CH11 (1000MHz~10<sup>th</sup> Harmonic)




Date: 23.MAR.2014 15:08:25



|                    |                  |
|--------------------|------------------|
| <b>Test Mode :</b> | <b>TX G Mode</b> |
|--------------------|------------------|




### TX G mode CH01







Date: 23.MAR.2014 15:17:54



### TX G mode CH11



Date: 23.MAR.2014 15:23:39












|                    |                            |
|--------------------|----------------------------|
| <b>Test Mode :</b> | <b>TX N-20M Mode_ANT 1</b> |
|--------------------|----------------------------|








### TX HT20 mode CH01 (30M~1000MHz)



Date: 23.MAR.2014 15:38:33


### TX HT20 mode CH01 (1000MHz~10<sup>th</sup> Harmonic)




Date: 23.MAR.2014 15:38:50



### TX HT20 mode CH06 (30M~1000MHz)




### TX HT20 mode CH06 (1000MHz~10<sup>th</sup> Harmonic)






### TX HT20 mode CH11 (30M~1000MHz)



Date: 23.MAR.2014 15:44:48



### TX HT20 mode CH11 (1000MHz~10<sup>th</sup> Harmonic)



Date: 23.MAR.2014 15:45:04




|                    |                            |
|--------------------|----------------------------|
| <b>Test Mode :</b> | <b>TX N-20M Mode_ANT 2</b> |
|--------------------|----------------------------|






### TX HT20 mode CH01 (30M~1000MHz)




### TX HT20 mode CH01 (1000MHz~10<sup>th</sup> Harmonic)






### TX HT20 mode CH06 (30M~1000MHz)



Date: 23.MAR.2014 15:49:43

### TX HT20 mode CH06 (1000MHz~10<sup>th</sup> Harmonic)




Date: 23.MAR.2014 15:50:13






### TX HT20 mode CH11 (30M~1000MHz)




### TX HT20 mode CH11 (1000MHz~10<sup>th</sup> Harmonic)






|                    |                            |
|--------------------|----------------------------|
| <b>Test Mode :</b> | <b>TX N-40M Mode_ANT 1</b> |
|--------------------|----------------------------|






### TX HT40 mode CH03 (30M~1000MHz)



Date: 23.MAR.2014 15:59:37


### TX HT40 mode CH03 (1000MHz~10<sup>th</sup> Harmonic)



Date: 23.MAR.2014 15:59:50




### TX HT40 mode CH06 (30M~1000MHz)





Date: 23.MAR.2014 16:12:02

### TX HT40 mode CH06 (1000MHz~10<sup>th</sup> Harmonic)





Date: 23.MAR.2014 16:12:17











|                    |                            |
|--------------------|----------------------------|
| <b>Test Mode :</b> | <b>TX N-40M Mode_ANT 2</b> |
|--------------------|----------------------------|













## 8. POWER SPECTRAL DENSITY TEST

### 8.1 Applied procedures / limit

| FCC Part15 (15.247) , Subpart C |                        |                        |                       |        |
|---------------------------------|------------------------|------------------------|-----------------------|--------|
| Section                         | Test Item              | Limit                  | Frequency Range (MHz) | Result |
| 15.247(e)                       | Power Spectral Density | 8 dBm<br>(in any 3KHz) | 2400-2483.5           | PASS   |


#### 8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=3KHz, VBW=10KHz, Sweep time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


#### 8.1.5 EUT TEST CONDITIONS



Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz



## 8.1.6 TEST RESULTS


Test Mode :TX B Mode\_CH01/06/11









Test Mode :TX G Mode\_CH01/06/11













Test Mode : TX N-20M Mode\_CH01/06/11\_ANT 1









Test Mode : TX N-20M Mode\_CH01/06/11\_ANT 2










| Test Mode : TX N-20M Mode_CH01/06/11_Total |                    |                        |                |
|--|--------------------|------------------------|----------------|
| Test Channel                               | Frequency<br>(MHz) | Power Density<br>(dBm) | Limit<br>(dBm) |
| CH01                                       | 2412               | -8.63                  | 8              |
| CH06                                       | 2437               | -8.15                  | 8              |
| CH11                                       | 2462               | -8.77                  | 8              |




Test Mode : TX N-40M Mode\_CH03/06/09\_ANT 1









Test Mode : TX N-40M Mode\_CH03/06/09\_ANT 2









| Test Mode : TX N-40M Mode_CH03/06/09_Total |                    |                        |                |
|--|--------------------|------------------------|----------------|
| Test Channel                               | Frequency<br>(MHz) | Power Density<br>(dBm) | Limit<br>(dBm) |
| CH03                                       | 2422               | -12.54                 | 8              |
| CH06                                       | 2437               | -10.76                 | 8              |
| CH09                                       | 2452               | -12.00                 | 8              |



## 9. MEASUREMENT INSTRUMENTS LIST

| Conducted Emission Measurement |                   |              |          |            |                  |
|--------------------------------|-------------------|--------------|----------|------------|------------------|
| Item                           | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                              | LISN              | EMCO         | 3816/2   | 00052765   | Apr. 25, 2014    |
| 2                              | LISN              | R&S          | ENV216   | 100087     | Nov. 09, 2014    |
| 3                              | Test Cable        | N/A          | C_17     | N/A        | Mar.14, 2015     |
| 4                              | EMI TEST RECEIVER | R&S          | ESCS30   | 826547/022 | Apr. 25, 2014    |
| 5                              | 50Ω Terminator    | SHX          | TF2-3G-A | 08122902   | Apr. 25, 2014    |

| Radiated Emission Measurement |                         |              |           |            |                  |
|-------------------------------|-------------------------|--------------|-----------|------------|------------------|
| Item                          | Kind of Equipment       | Manufacturer | Type No.  | Serial No. | Calibrated until |
| 1                             | Antenna                 | Schwarbeck   | VULB9160  | 9160-3232  | Apr. 25, 2014    |
| 2                             | Amplifier               | HP           | 8447D     | 2944A09673 | Apr. 25, 2014    |
| 3                             | Test Receiver           | R&S          | ESCI      | 100382     | Apr. 25, 2014    |
| 4                             | Test Cable              | N/A          | C-01_CB03 | N/A        | Jul. 02, 2014    |
| 5                             | Antenna                 | ETS          | 3115      | 00075789   | Apr. 25, 2014    |
| 6                             | Amplifier               | Agilent      | 8449B     | 3008A02274 | Apr. 25, 2014    |
| 7                             | Spectrum                | Agilent      | E4408B    | US39240143 | Nov. 09, 2014    |
| 8                             | Test Cable              | HUBER+SUHNER | C-45      | N/A        | Apr. 30, 2014    |
| 9                             | Controller              | CT           | SC100     | N/A        | N/A              |
| 10                            | Horn Antenna            | EMCO         | 3115      | 9605-4803  | Apr. 25, 2014    |
| 11                            | Active Loop Antenna     | R&S          | HFH2-Z2   | 830749/020 | Apr. 25, 2014    |
| 12                            | Broad-Band Horn Antenna | Schwarzbeck  | BBHA 9170 | 9170319    | Oct. 22, 2014    |

| 6dB Bandwidth Measurement |                   |              |          |            |                  |
|---------------------------|-------------------|--------------|----------|------------|------------------|
| Item                      | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                         | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 09, 2014    |

| Peak Output Power Measurement |                       |              |          |            |                  |
|-------------------------------|-----------------------|--------------|----------|------------|------------------|
| Item                          | Kind of Equipment     | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                             | P-series Power meter  | Agilent      | N1911A   | MY45100473 | Apr. 25, 2014    |
| 2                             | Wireband Power sensor | Agilent      | N1921A   | MY51100041 | Apr. 25, 2014    |



**Antenna Conducted Spurious Emission Measurement**

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 09, 2014    |

**Power Spectral Density Measurement**

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 09, 2014    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
All calibration period of equipment list is one year.




**10. EUT TEST PHOTO**

**Conducted Measurement Photos**



**Radiated Measurement Photos  
9K~30MHz**





**Radiated Measurement Photos  
30~1000MHz**





**Radiated Measurement Photos  
Above 1000MHz**

