



## Quick Installation Guide

Ceiling AP Series


### Package contents

- Wireless ceiling AP x 1
- Power adapter x 1
- Accessories (Screws, plastic nuts, and plastic anchors)
- Quick Installation Guide

If items are missing or damaged, please keep the original package and contact the local reseller or distributor immediately.

This Quick Installation Guide is for installation in a residential only. For more practice on function details, please go to [www.tenda.com](#).

## 1. Getting to know your AP



## 2. Installing your AP

⚠️ Note: You may need a rabbit hammer, a marker, a hammer drill, a screwdriver, and a ladder for the installation. Please prepare them yourself.

### Ceiling installation

- Position the bracket on the ceiling and mark screw holes on the ceiling with the marker.




- Drill holes in the marked positions using a hammer drill.




⚠️ Tip: Plastic anchors are more general for holding up wall strength such as plasterboard. Please choose Option A.

- Option A: Align the plastic anchors into the holes using the included screws. Align the holes in the bracket with the holes in the ceiling, and then use the included screws to fix the bracket.



- Option B: Align the plastic nuts with the holes in the ceiling. Then use the included screws to fix the bracket.



- Connect a CAT5 or better cable to the LAN port of the AP. Connect the PWR jack to the PWR port, or a power adapter to the PWR jack to supply power for the AP.



- Insert the pins of the AP into the hooks of the bracket, and push the AP to one side until you hear a click.




### Wall mounting


- Position the bracket on the wall, and mark screw holes on the wall with the marker.



- Drill holes in the marked positions using a hammer drill.



- Insert the plastic anchors into the holes using the included screws. Align the holes in the bracket with the holes in the wall, and then use the included screws to fix the bracket.



- Connect a CAT5 or better cable to the LAN port of the AP. Connect the PWR jack to the PWR port, or a power adapter to the PWR jack to supply power for the AP.



- Insert the pins of the AP into the hooks of the bracket, and push the AP to one side until you hear a click.



## 3. Connecting and Configuring your APs

### Scenario 1: Deploying your network without a management device for Tenda AP

⚠️ Connect and configure your APs one by one. That is to say, connect one AP to your PC, then configure it. After finished, connect the second AP and repeat ① and ② on them.

#### ① Connect devices

- Connect your AP to a PoE port on the PoE switch using an Ethernet cable. Refer to the figure for detailed connection. After connecting, it indicates that the pattern is broken.

After starting, it indicates that the AP's LED indicator blinks and the lower-right Internet icon on your computer is displayed.

The AP is powered on via the LED indicator has been turned off, indicating the AP is online.

⚠️ Caution:

The port specification may vary. Before connecting one, check if the power source equipment you use complies with your AP.



#### ② Configure the IP address of your AP (Example: Win10)

Right-click the network icon on the lower-right corner of your computer. Click Network and Sharing Center > Change adapter settings. Right-click the Ethernet, then Properties. Select Internet Protocol Version 4 (TCP/IPv4) and click Properties.

Configure the IP address of your AP (Example: 192.168.0.x or 2 to 253).

Before powering on, check if the power sourcing equipment is connected correctly with your AP.



#### ③ Log in to the web UI of the AP

- Start a web browser on your computer and access 192.168.0.254. Right-click the network icon on the lower-right corner of your computer. Click Network and Sharing Center > Change adapter settings. Right-click the Ethernet, then Properties. Select Internet Protocol Version 4 (TCP/IPv4) and click Properties.

Choose Quick Setup. The 2.4GHz configuration page appears.

Configure the IP address of the AP (192.168.0.201), Security Mode (WPA2-PSK is recommended), and click Save.

Then select 5GHz from the Radio Band drop-down list and repeat this step.



#### ④ Modifying the IP address of the AP

- Choose Internet Settings > LAN Setup. Modify the IP address of the AP to 192.168.0.201 or 2 to 253, and ensure that the new IP address has not been used in this network. Click Save.

Example: You change the new IP address of the first AP to 192.168.0.201, and the new IP address of the second AP to 192.168.0.202.




### Scenario 2: Deploying your network with an Tenda access controller (AC)

#### ① Connect devices

Use Ethernet cables to connect APs to the ports of the switch. Refer to the following figure for detailed connection.

#### ② Configure APs


Start a web browser on your computer and log in to the web UI of the AC. Refer to your AC user guide for detailed instructions.



### Scenario 3: Deploying your network with an Tenda router that includes the AC functionality

#### ① Connect devices

Use Ethernet cables to connect APs to the PoE port of the switch. Refer to the following figure for detailed connection.



## FAQ

Q1: I cannot access the web UI of the AP after entering 192.168.0.254.

What should I do?

Check if the network is stable.

Check if your Ethernet cables are connected properly. If yes, then the corresponding LED indicator lights.

Ensure that the IP address of your computer has been set to 192.168.0.x (x 2 to 253), and the IP address is used only by other devices in the network.

Check if the AP is powered on.

Disable the firewall of your computer, or replace the computer if you consider your should not have a firewall installed. If the problem still exists, then repeat the procedure for the other APs.

If two or more APs are connected to the network without an AC, you should disable the wireless function of the APs. Then repeat the procedure for the other APs. Then repeat this procedure to change the IP addresses of the other APs.

Meanwhile, ensure that the IP addresses of the APs are the same network segment.

Reboot the APs and then log in to the AP's web UI using their new IP addresses.

The AP must be rebooted to change its IP address. If the IP address is not changed, then repeat the steps above to change the IP address of the AP.

After rebooting, log in to the AP's web UI using the new IP address.

If the problem persists, reset the AP.

Q2: My wireless AC cannot find the AP. What should I do?

What should I do?

If you use the Tenda AC, the AP can only be managed by Tenda AC.

Ensure that all the devices in the network are connected properly and the AP has internet access.

If WLAN has been defined in your network, verify that the corresponding WLAN has been added to your AC.

Otherwise, ensure that the wireless version of your AP and AC are the same with the latest firmware versions available on [http://www.tenda.com](#).

Reboot your AP.

#### Q3: How to upgrade my AP?

##### A3: Perform as follows:

- Obtain the latest version, download it from our official website <http://www.tenda.com>.

2. Unzip the file you downloaded.

3. Log in to the web UI of the AP (choose Tools > Maintenance, just navigate to the Firmware Upgrade section, Click Upgrade, select and upload the file ending .bin from the file folder you unzipped, and click Upgrade).

4. After successful upgrade, restart your AP to apply your settings.

#### Q4: How to reset my AP?

##### A4: Reset using the RESET button

Log in to the web UI of the AP (choose Tools > Maintenance, and navigate to the Reset section, then follow the on-screen instruction to reset it.

Note: Resetting clears all configurations of your AP.

#### CE

##### CE Mark Warning

This is a Class B product. In a domestic environment, this product may cause radio interference. If this occurs, the user may be required to take adequate measures to reduce the interference.

Operations in the 5.15-5.25 GHz band are restricted to indoor use only. This equipment should be installed and operated with minimum distance 20cm from the human body.

This equipment is a class B product. It generates, uses and radiates radio frequency energy and if not installed and used in accordance with the instructions, may cause interference to radio communications. However, there is no guarantee that interference will not occur in some situations. If this equipment does cause interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio/television technician for help.

The device is a Class B product only.

Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

##### Declaration of Conformity

Hereby, SHENZHEN TENDA TECHNOLOGY CO., LTD. declares that the radio equipment type is in compliance with Directive 2014/53/EU.

This equipment complies with the essential requirements and other relevant harmonized standards listed in the following internet address: <http://www.tenda.com/service/download-data/101.html>

Operating Frequency: 2.4GHz - 2.472GHz, 5GHz - 5.25GHz, 5.725 - 5.825GHz

Power Output: 20dBm, 19.9dBm, 50dBm, 22.8dBm

Software Version: V1.0.0.2

#### FC

##### FC Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in some situations. If this equipment does cause interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio/television technician for help.

The device is a Class B product only.

Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any change or modification not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This equipment must not be co-located or operating in conjunction with any other antenna or transmitter.

Operating Frequency: 2.4GHz - 2.483GHz, 5.15 - 5.25GHz, 5.725 - 5.825GHz

Power Output: 20dBm, 19.9dBm, 50dBm, 22.8dBm

Software Version: V1.0.0.2

##### Technical Support

Shenzhen Tenda Technology Co., Ltd. is located at No. 100, Shangyuan Road, Nanshan District, Shenzhen, China. 518062

401# Building, 18th Floor, Shangyuan Building, Shenzhen, China

&lt;p