


The sticker must be placed centered on top cover of the radio and readable from front side like on sketch



The sticker shall not peel off from the surface (metallic) on a temperature from -40 to +85°c

Teil muss der Bosch-Norm N 2580-1 entsprechen Part has to correspond with the Bosch standard N 2580-1.1



S	Shrinkage:								SAP:											
Р	rojekt-Library:	BP.	_Labels	;																
N	Measures without indication of tolerance acc. to								ISO 2768-g								D ID-CorelDraw			
3				6				9				12				Replace	es:			
2				5				8				11								
1				4				7				10				Replace	ed by:			
Ind.	Mod.Nr.	Date	Name	Ind.	Mod.Nr.	Date	Name	Ind.	Mod.Nr.	Date	Name	Ind.	Mod.Nr.	Date	Name					
								Dwn. 06-11-2009 - P. Barreiro					Part name/Part title							
									Ckd. M. Monteiro					Radio Label						
Pint.							Ntc.					Radio Labei								
	Material: First Use							Dpt. BrgP/END												
В	Background: white;							(A) DOCOLL					Dr	awing-Nr./Re		Scale				
Printing: Black;							⋓ BOSCH					X XXX XXX XXX 1:1								
	Backside adhesive Rubber coated;						Car Multimedia Portugal Lda.						\\\\ \\\\			""				
Sticker supplied in Roll format;							odi malamodia i ortugui Eddi					No. of she	ets	01	S	neet no.	01			
С	Chromo Paper 90g/m2							Weight:					This includes:							