

# SPECIFICATION FOR APPROVAL

MESSRS:

MODEL:



No.	Customer P/N	Kwang Sung P/N	Descriptions	ERP Code
1		KMA93A2450X-M01	Multi-layer Chip Antenna 1. Center frequency : 2450MHz 2. Gain : 2dBi max. 3. VSWR : 2:1 max. 4. Polarization : Linear 5. Azimuth Beam Pattern: Omni-directional 6. Impedance : 50 Ω	

DATE: 2007. 01. 10



**KWANG SUNG**

KWANG SUNG ELECTRONICS CO., LIMITED  
 108, 4-GA, WONHYO-RO, YONGSAN-GU, SEOUL, KOREA  
 TEL: +822-711-2001/5 FAX: +822-716-8283  
[http:// www.kse.com.hk](http://www.kse.com.hk)

承認 (APPROVAL)		
作成	検討	承認
年	月	日

관리번호:KS03QR0010-A

A4 (210x297)mm

<b>SPECIFICATION</b>	DATE	2007. 01. 10
	REV	0
	PAGE	1/10
<b>MULTILAYER CHIP ANTENNA</b>		

<b>PART NO</b>	<b>KMA93A2450X-M01</b>
<b>ERP CODE</b>	

<b>APPROVED</b>	<b>DRAWN</b>	<b>DESIGNED</b>	<b>CHECKED</b>	<b>APPROVED</b>
	<i><b>I.K. LEE</b></i>	<i><b>S.H.NOH</b></i>		<i><b>J.S. JEON</b></i>
	Jan. / 10	Jan. / 10		Jan. / 10

<b>SPECIFICATION</b>	DATE	2007. 01. 10
<b>MULTILAYER CHIP ANTENNA</b>	REV	0
	PAGE	2/10

## CONTENTS.

1. SCOPE	P3
2. PART NUMBERING	P3
3. COMPOSITION AND MATERIAL	P4
4. ELECTRIC CHARACTERISTICS	P4
5. ENVIRONMENTAL CHARACTERISTICS	P5
6. DIMENSIONS AND MECHANICAL SPECIFICATIONS	P6
7. RECOMMENDED LAND PATTERN	P7
8. REFLOW SOLDERING STANDARD CONDITION	P7
9. PACKAGE SPECIFITION	P8
10. FREQUENCY CHARACTERISTICS	P9
11. RADIATION CHARACTERISTICS	P10

<b>SPECIFICATION</b>	DATE	2007. 01. 10
<b>MULTILAYER CHIP ANTENNA</b>	REV	0
	PAGE	3/10

## 1. Scope

This specification covers the characteristics of the multi-layer chip antenna for the cordless phone, Wireless-LAN and Bluetooth.

## 2. Part Numbering

KMA	93	A	2450	X	M01
①	②	③	④	⑤	⑥

### 1) Product ID.

Product ID	Full Name
KMA	Kwang-Sung Multi-layer Chip Antenna

### 2) Dimension. (L x W)

Code	Dimension (L x W)
93	9.0 mm x 3.0 mm
62	6.0 mm x 2.0 mm

### 3) Type.

Code	Type
A	A-type
B	B-type

### 4) Nominal Center Frequency.

Code	Center Frequency
2450	2450MHz

### 5) Material.

Code	Material
X	X200-W

### 6) Serial no.

Code	Symbol name
M01	Series number

<b>SPECIFICATION</b>	DATE	2007. 01. 10
<b>MULTILAYER CHIP ANTENNA</b>	REV	0
	PAGE	4/10

### 3. Materials

3-1. Materials : Dielectric Ceramic.

3-2. Internal Electrode : Silver(Ag)

3-3. External Electrode : Ag/Ni/Au or Ag/Ni/Sn.

### 4. Electric Characteristics

Characteristics	Specification
Nominal Center Frequency (fo)	2450MHz
Band Width	200 MHz min.
Gain	2dBi max. (at 25℃)
Polarization	Linear
V.S.W.R	2 : 1 max
Azimuth Beam Pattern	Omni-directional
Input / output impedance	50Ω
Measuring conditions	Equipment used : HP 8719ES
	Jigs used : Kwang-sung Standard Jig

※ test condition : Temperature 25±2℃ Humidity 45～75%R

<b>SPECIFICATION</b>  <b>MULTILAYER CHIP ANTENNA</b>	DATE	2007. 01. 10
	REV	0
	PAGE	5/10


## 5. Environmental Characteristics

The device should satisfy the electrical characteristics specified in paragraph 4 after the following tests.

Measurements should be done after putting in the typical condition (20~30℃/ 55~75%RH) for 2hours minimum.

※**Test condition** : Temperature 25±2℃


Humidity 45~75%RH

Sub clause number and Test item		Condition of test	Performance requirements
5-1	Tensile strength	 <p>Wire: 0.6~0.8 tined Cu wire</p>	No visual damage and strength(F) > 4kgf
5-2	Heat Proof	Temperature 85±2℃ for 96±2 hours Measure condition : left for 24hrs min. at room temp. (used KSE standard board)	No visual damage and $\Delta f < 1.5\%$ $(\Delta f =  f_i - f_c  / f_i)$ $f_i$ : center frequency of initial condition (room temp.) $f_c$ : center frequency after being cycled.
5-3	Cold Proof	Temperature -30±2℃ for 96±2 hours Measure condition : left for 24hrs min. at room temp. (used KSE standard board)	No visual damage and $\Delta f < 1.5\%$ $(\Delta f =  f_i - f_c  / f_i)$ $f_i$ : center frequency of initial condition (room temp.) $f_c$ : center frequency after being cycled.
5-4	Moisture Proof	Temperature 40±2℃ Humidity 95%RH for 96 hours Measure condition : left for 24hrs min. at room temp. (used KSE standard board)	No visual damage and $\Delta f < 1.5\%$ $(\Delta f =  f_i - f_c  / f_i)$ $f_i$ : center frequency of initial condition (room temp.) $f_c$ : center frequency after being cycled.
5-5	Adhesive Strength of Termination	Applied force on SMD chip till detached point from PCB.	No mechanical damage and strength(F) > 7kgf
5-7	Solder Heat Proof	Re-flowed at 250±5℃ for 10±1seconds	More than 40% of the terminal electrode shall be covered with new solder.

<b>SPECIFICATION</b>	DATE	2007. 01. 10
	REV	0
	PAGE	6/10
<b>MULTILAYER CHIP ANTENNA</b>		

## 6. Dimensions and Mechanical Specifications.

### 6-1. Dimensions



**L=9.0, W=3.0, t=1.0**


### 6-2. Mechanical Specifications.

Items	Specification
Dimensions(L x W x H)	9.0 x 3.0 x 1.0 mm
Operating Temp.	-35 ~ +85 °C
Internal Electrode	Ag
External Electrode	Ag/Ni/Au or Ag/Ni/Sn


<b>SPECIFICATION</b>	DATE	2007. 01. 10
	REV	0
	PAGE	7/10
<b>MULTILAYER CHIP ANTENNA</b>		

### 7. Recommended Land Pattern


7-1. Land pattern. (Top View)



### 8. Reflow Soldering Standard Conditions.



a) non Pb-free




b) Pb free




<b>SPECIFICATION</b>	DATE	2007. 01. 10
	REV	0
	PAGE	8/10
<b>CHIP MULTILAYER LC FILTER</b>		

9. Package specifications

9-1. Dimensions of Carrier Tape (unit: mm)




9-2. style of Reel




<b>SPECIFICATION</b>	DATE	2007. 01. 10
	REV	0
	PAGE	9/10
<b>MULTILAYER CHIP ANTENNA</b>		

# 10. Frequency Characteristic.

## 10-1. S11 (return loss and Smith chart)




## 10-2. Bluetooth matching on the reference board




<div> <div>SPECIFICATION</div> <div>MULTILAYER CHIP ANTENNA</div> </div>	DATE	2007. 01. 10
	REV	0
	PAGE	10/10

11. Radiation Characteristic.



a) Azimuth



b) Elevation