

Center for Quality Engineering

Test Report No.: E01P0001

FCC ID: VBNFRBB-01

Order No.: E01P **Pages:** 182 **Munich,** Mar 08, 2011

Client: Nokia Siemens Networks Oy

Equipment Under Test: Flexi Multiradio BTS RF module 760MHz

Radio Access Technology: E-UTRA

Manufacturer: Nokia Siemens Networks Oy

Task: Conformance test according to the test specifications mentioned

below

Test Specification(s): FCC 47 CFR Part 2, 27 and 90

Result: The EUT complies with the requirements of the specifications.

The results relate only to the items tested as described in this test report.

approved by: Date Signature

Neuhäusler

Lab Manager Technical Services Mar 08, 2011

Bauer

Lab Manager EMC Mar 08, 2011

This document was signed electronically.



CONTENTS

1	Summary	4
2	References	5
	2.1 Specifications	5
	2.2 Glossary of Terms	5
3	General Information	6
	3.1 Identification of Client	6
	3.2 Test Laboratory	6
	3.3 Time Schedule	6
	3.4 Participants	6
4	Equipment Under Test	7
	4.1 Description of EUT	7
	4.2 Configuration of EUT	7
	4.3 Operating Conditions	8
	4.4 Compliance Criteria	8
5	General Description of Tests	9
	5.1 Tested Carrier Frequencies	9
	5.2 Modulation Characteristics	9
	5.3 Test Configuration	10
	5.4 Calibration of the Test Equipment	10
6	Test Results	11
	6.1 Test No. 1: RF power output (§ 2.1046, § 27.50, § 90.205, § 90.542)	11
	6.1.1 Purpose	11
	6.1.2 Limits	11
	6.1.3 EUT Operating Condition	11
	6.1.4 Test Configuration	11
	6.1.5 Test Procedure and Results	11
	6.2 Test No. 2: Modulation Characteristics (§ 2.1047, § 2.201)	
	6.3 Test No. 3: Occupied Bandwidth (§ 2.1049)	
	6.3.1 Purpose	
	6.3.2 Limits	
	6.3.3 EUT Operating Condition	
	6.3.4 Test Configuration	
	6.3.5 Test Procedure and Results	
	6.4 Test No. 4: Spurious Emissions at Antenna Terminals (8.2.1051, 8.2.1057, 8.27.53)	17







6.4.1 Purpose	17
6.4.2 Limits	17
6.4.3 EUT Operating Condition	17
6.4.4 Test Configuration	17
6.4.5 Test Procedure and Results	18
6.5 Test No. 5: Field Strength of Spurious Radiation (§ 2.1053, § 2.1057, § 27.53)	26
6.5.1 Purpose	26
6.5.2 Limits	26
6.5.3 EUT Operating Condition	26
6.5.4 Test Configuration	27
6.5.5 Test Procedure and Results	27
6.6 Test No. 6: Frequency Stability (§ 2.1055, § 27.54)	29
6.6.1 Purpose	29
6.6.2 Limits	29
6.6.3 EUT Operating Condition	29
6.6.4 Test Configuration	29
6.6.5 Test Procedure and Results	30
7 Test Data and Screenshots	36
7.1 Part List of the RF Measurement Test Equipment	36
7.2 Spectral Plots	37
7.2.1 Test No. 1: RF Power Output	37
7.2.2 Test No. 2: Modulation Characteristics	52
7.2.3 Test No. 3: Occupied Bandwidth	53
7.2.4 Test No. 4: Spurious Emissions at the Antenna Terminals	67
7.2.5 Test No. 5: Field Strength of Spurious Radiation	177



1 Summary

The measurements described in this report were conducted pursuant to 47 CFR § 2.947 and § 2.1041. All applicable paragraphs of the 47 CFR parts 2, 27 and 90 of the most current version of the rules were considered.

The following tests were performed according to the FCC rules in order to verify the compliance of the EUT with the FCC requirements:

Test No.	Measurement	FCC Rule	Page Number of this Report	Result
1	RF Power Output	§ 2.1046, § 27.50, § 90.205, § 90.542	11	compliant
2	Modulation Characteristics	§ 2.1047, § 2.201	14	compliant
3	Occupied Bandwidth	§ 2.1049	15	compliant
4	Spurious Emissions at Antenna Terminals	§ 2.1051, § 2.1057, § 27.53, § 90.543	17	compliant
5	Field Strength of Spurious Radiation	§ 2.1053, § 2.1057, § 27.53, § 90.543	26	compliant
6	Frequency Stability	§ 2.1055, § 27.54	29	compliant

Table 1-1: Results – Summary

In accordance with the FCC Rule §15.3 (z) the equipment was tested with the limits that are valid for an *unintentional radiator*.



2 References

2.1 Specifications

No	Standard	Title	Date
[1]	FCC 47 CFR	Code of Federal Regulations,	2010-10
	Part 2, 27 and 90	Title 47: Telecommunication	
		Part 2: Frequency Allocations and Radio Treaty Matters;	
		General Rules and Regulations	
		Part 27: Miscelleanous Wireless Communications Services	
		Part 90: Private Land Mobile Radio Services	

Quadrature Phase Shift Keying -Modulation

2.2 Glossary of Terms

QPSK

16QAM	16 Quadrature Amplitude Modulation
64QAM	64 Quadrature Amplitude Modulation
AC	Alternating Current
BTS	Base Transceiver System
BW	Bandwidth
chk	checked against a calibrated reference
cnn	calibration not necessary
DC	Direct Current
EIRP	Equivalent Isotropic Radiated Power
EUT	Equipment Under Test
FCC	Federal Communications Commission
LTE	Long Term Evolution
P	Power
Prat	Rated Output Power
RF	Radio Frequency



3 General Information

3.1 Identification of Client

Nokia Siemens Networks Oy P.O. Box 319, Kaapelitie 4, FI-90651, Oulu, Finland Jaakko Sirvio

3.2 Test Laboratory

Nokia Siemens Networks Oy P.O. Box 319, Kaapelitie 4, FI-90651, Oulu, Finland Jaakko Sirvio

3.3 Time Schedule

Test No.:	1, 2, 3, 4	5	6
Start of Test:	Feb 03, 2011	Jan 15, 2011	Feb 09, 2011
End of Test:	Feb 08, 2011	Feb 02, 2011	Feb 09, 2011

3.4 Participants

Name	Function
Hannu Eskola (NSN)	Testing, Setup of EUT
Jari Veijola (NSN)	Testing, Setup of EUT
Sami Riuttanen (NSN)	Testing, Setup of EUT
Stephane Nakpane (SGS CQE)	Editor



4 Equipment Under Test

The tested equipment is representative for serial production.

4.1 Description of EUT

The BTS performs the full RAN function of a LTE system (evolved UTRA). This is sometimes refered to as collapsed RAN, where equivalent functions of former 3G BTS and 3G RNC are all integrated into BTS. BTS is connected directly to the core network via S1 interface, and to mobile stations via Air interface (Uu). In addition BTSs are optionally connected directly to each others via X2 interface for handover purposes.

4.2 Configuration of EUT

The used different EUT configurations are shown by the following tables.

Module Type	Flexi Multiradio BTS RF module 760MHz (E-UTRA Band 14)		
Radio Access Technology	E-UTRA		
Frequency Bands	Uplink Downlink		
Block D:	788 - 793 758 - 763		
Public Safety Broadband:	793 - 798	763 - 768	
	Single Carrier		
Rated Output Power (Prat)	40 W		
Channel Bandwidth	5MHz (Config. A),	10 MHz (Config. B)	
	RX TX		
Number of Antenna Ports	12 (RX1 to RX12)	6 (TX1 to TX6)	
МІМО	Yes	Yes	

Table 4-1: Overview of EUT Configuration

The tests were performed with one EUT at the antenna ports TX1 and/or TX2.

The used different EUT configurations are shown by the following table.

Module Name	Serial-No.	Module Type	Config.
FRBB	L9105200422	RF module	A, B
FRBB	L9105200426	RF module	A, B
Other Medules	Module Type		Confin
Other Modules	wodule Type		Config.
FSME	System module		A, B

Table 4-2: Configuration of EUT

For a functional description of the modules, please refer to the appropriate related parts and exhibit sections of this certification application.



4.3 Operating Conditions

If not stated otherwise, the following standard setup procedure for the EUT was used:

The transmitter was set up according to 3GPP TS 36.141 E-UTRA Test Models (TM) for all tests:

- E-TM 1.1: QPSK modulation,
- E-TM 3.1: 64QAM modulation,
- E-TM 3.2: 16QAM modulation

The Flexi Multiradio BTS was supplied with 48 V DC.

During the measurements, one carrier channel was tested at a time. The carrier was set to the maximum power level to ensure the maximum emission amplitudes during all measurements.

During the tests, the Flexi Multiradio BTS is transmitting a pseudo random bit pattern on the data channels. This ensures that the measurements of the emission characteristics of the transmitter are pursuant to § 2.1049.

4.4 Compliance Criteria

The EUT must fulfil the requirements (described in the specifications mentioned in chapter 2.1, Specifications) for the selected test cases.



5 General Description of Tests

5.1 Tested Carrier Frequencies

The measurements were done on several carrier frequencies, according to the following table:

Config A:

Channel Bandwith: 5MHz		
Frequency [MHz] Remark		
760.5	lowest possible carrier frequency	
763.0	frequency at the middle of the band	
765.5	highest possible carrier frequency	

Table 5-1: Carrier Frequencies for 5MHz channel bandwidth

Config B:

Channel Bandwith: 10MHz		
Frequency [MHz] Remark		
763.0	only possible carrier frequency	

Table 5-2: Carrier Frequencies for 10MHz channel bandwidth

5.2 Modulation Characteristics

The EUT supports QPSK, 16QAM and 64QAM modulation.



5.3 Test Configuration

If not stated otherwise, the following measurement configuration was used to perform all measurements (see figure below).




Figure 5-1: Test Configuration (single output)




Figure 5-2: Test Configuration (combined output)

The RF output of the transceiver (cell) under test is connected to a signal analyzer via a high power attenuator to protect the input of the signal analyzer from high RF power levels. A description of the analyzer settings is given in each of the sections describing the measurements. The other transceivers are terminated.

A complete list of the measurement equipment is included on page 36 of this measurement report.

5.4 Calibration of the Test Equipment

All relevant test equipment has a valid calibration from an external calibration laboratory. Additionally the signal analyzer has a built-in self-calibration procedure. This calibration procedure was activated prior to the measurements so that the analyzer is deemed accurate. High quality cables were used to connect the measurement equipment to the EUT. The actual loss of the attenuator and the cables was measured with a high precision network analyzer and taken into account for all measurements.



6 Test Results

6.1 Test No. 1: RF power output (§ 2.1046, § 27.50, § 90.205, § 90.542)

6.1.1 Purpose

The RF power output measurements were performed pursuant to § 2.1046 in order to determine the base station maximum RF output power.

6.1.2 Limits

According to § 27.50 (755-763 MHz) and § 90.542 (763-768 MHz), base stations with an emission bandwidth greater than 1 MHz must not exceed an ERP of 1000 watts/MHz with an antenna height up to 305 meters HAAT.

6.1.3 EUT Operating Condition

The standard setup procedure as described in section 4.3 of this report was used.

6.1.4 Test Configuration

The test configuration used is described in section 5.3 of this report.

6.1.5 Test Procedure and Results

Detachable Antenna:

The maximum output power at the antenna terminals was measured using a signal analyzer.

The RF power was measured with a frequency sweep across the carrier (see screenshots). The carrier power was calculated from the signal analyzer by integration over the result. The base station maximum output power is the sum of the measured carrier power and the external attenuation (cable loss of the test set up).

The following table shows the measured output powers at the antenna connector. Screenshots of the measurements are included on page 37 onwards of this report.



Config A:

Carrier Frequency	RF Power Output		Result
[MHz]	[dBm]	[W]	
QPSK-Modulation TX	K 1	, = =	
760.5	45.83	38.28	compliant
763.0	45.72	37.33	compliant
765.5	45.66	36.81	compliant
QPSK-Modulation TX	K 2		
760.5	45.91	38.99	compliant
763.0	45.67	36.90	compliant
765.5	45.73	37.41	compliant
QPSK-Modulation TX	(1+TX2		<u>.</u>
760.5	48.88	77.27	compliant
763.0	48.71	74.23	compliant
765.5	48.71	74.22	compliant
16QAM-Modulation	ΓX1		<u>.</u>
760.5	45.88	38.73	compliant
763.0	45.73	37.41	compliant
765.5	45.65	36.73	compliant
16QAM-Modulation	ΓX2	·	<u>.</u>
760.5	45.93	39.17	compliant
763.0	45.70	37.15	compliant
765.5	45.75	37.58	compliant
16QAM-Modulation	TX1+TX2		·
760.5	48.92	77.90	compliant
763.0	48.73	74.56	compliant
765.5	48.71	74.31	compliant
64QAM-Modulation	ΓX1		·
760.5	45.86	38.55	compliant
763.0	45.73	37.41	compliant
765.5	45.63	36.56	compliant
64QAM-Modulation	ГХ2		
760.5	45.91	38.99	compliant
763.0	45.75	37.58	compliant
765.5	45.71	37.24	compliant
64QAM-Modulation	ΓX1+TX2		
760.5	48.90	77.54	compliant
763.0	48.75	74.99	compliant
765.5	48.68	73.80	compliant
Measurement Uncer	tainty:	±0.4dB	

Table 6-1: Results – RF Power Output (5 MHz Channel BW)



Config B:

Carrier Frequency	RF Power Output	Result			
[MHz]	[dBm]	[W]			
QPSK-Modulation TX	(1				
763.0	45.70	37.15	compliant		
QPSK-Modulation TX	(2				
763.0	45.76	37.67	compliant		
QPSK-Modulation TX	(1+TX2				
763.0	48.74	74.82	compliant		
16QAM-Modulation T	X1				
763.0	45.75	37.58	compliant		
16QAM-Modulation T	X2				
763.0	45.77	37.76	compliant		
16QAM-Modulation T	X1+TX2				
763.0	48.77	75.34	compliant		
64QAM-Modulation T	X1				
763.0	45.75	37.58	compliant		
64QAM-Modulation T	64QAM-Modulation TX2				
763.0	45.80	38.02	compliant		
64QAM-Modulation T	64QAM-Modulation TX1+TX2				
763.0	48.79	75.60	compliant		
Measurement Uncert	ainty:	±0.4dB	_		

Table 6-2: Results – RF Power Output (10 MHz Channel BW)

The base station maximum output power was found to be compliant with the manufacturer's specifications and with all requirements of the FCC rules.



6.2 Test No. 2: Modulation Characteristics (§ 2.1047, § 2.201)

The occupied bandwidth was measured to be 5 MHz (Config. A) and 10MHz (Config. B), which represents the 99% power bandwidth (see the following section and screenshots on pages 53 onwords. Therefore, the modulation characteristic of the base stations transceiver is **5M00F9W** or **10M00F9W**.

No further testing is required under this section of the FCC rules. No measurements other than the occupied bandwidth are required.

The modulation characteristics were found to be compliant with the manufacturer's specifications and with all requirements of the FCC rules.



6.3 Test No. 3: Occupied Bandwidth (§ 2.1049)

6.3.1 Purpose

The measurements are performed to determine the occupied bandwidth of the EUT pursuant to § 2.1049.

6.3.2 Limits

According to § 2.1049 the 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to 0.5% of the emitted power.

6.3.3 EUT Operating Condition

The standard setup procedure as described in section 4.3 of this report was used.

6.3.4 Test Configuration

The test configuration used is described in section 5.3 of this report.

6.3.5 Test Procedure and Results

The 99% occupied bandwidth of the carrier emission is measured using a signal analyzer with Resolution Bandwidth set to 30 kHz (less than 1% of bandwidth; see screenshots on pages 53 onwords for details). The following table summarizes the results:

Config A:

Carrier Frequency [MHz]	Occupied Bandwidth [MHz]	Result			
QPSK-Modulation TX1					
760.5	4.4788	compliant			
763.0	4.4788	compliant			
765.5	4.4788	compliant			
QPSK-Modulation TX2					
760.5	4.4788	compliant			
763.0	4.4788	compliant			
765.5	4.4788	compliant			
16QAM-Modulation TX1					
760.5	4.4707	compliant			
763.0	4.4707	compliant			
765.5	4.4625	compliant			
16QAM-Modulation TX2					
760.5	4.4707	compliant			
763.0	4.4707	compliant			
765.5	4.4707	compliant			



Carrier Frequency [MHz]	Occupied Bandwidth [MHz]	Result
64QAM-Modulation TX1		
760.5	4.4788	compliant
763.0	4.4788	compliant
765.5	4.4788	compliant
64QAM-Modulation TX2		
760.5	4.4788	compliant
763.0	4.4788	compliant
765.5	4.4788	compliant
Measurement Uncertainty:		±48kHz

Table 6-3: Results – Occupied Bandwidth (5 MHz Channel BW)

Config B:

Carrier Frequency [MHz]	Occupied Bandwidth [MHz]	Result
QPSK-Modulation TX1		
763.0	8.9346	compliant
QPSK-Modulation TX2		
763.0	8.9346	compliant
16QAM-Modulation TX1		
763.0	8.9346	compliant
16QAM-Modulation TX2		
763.0	8.9346	compliant
64QAM-Modulation TX1		
763.0	8.9346	compliant
64QAM-Modulation TX2		
763.0	8.9346	compliant
Measurement Uncertainty:		±48kHz

Table 6-4: Results – Occupied Bandwidth (10 MHz Channel BW)

The occupied bandwidth was found to be compliant with the manufacturer's specifications and with all requirements of the FCC rules.



6.4 Test No. 4: Spurious Emissions at Antenna Terminals (§ 2.1051, § 2.1057, § 27.53)

6.4.1 Purpose

The measurements of the spurious emissions at the equipment output terminals were performed pursuant to § 2.1051 in order to verify that all emissions are below the specified limits.

6.4.2 Limits

Compliance with § 27.53 and § 90.543 requires that any emission will be sufficiently attenuated. Following requirements have to be fulfilled:

- According to § 27.53(d) for operations in the 758-763 MHz band, the power of any emission outside the licensee's frequency bands of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, in accordance with the following:
 - On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log₁₀ P dB (P = transmitter power in Watts) in a 6.25 kHz band segment.
 - On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log_{10} P$ dB (P = transmitter power in Watts).
- 2. According to § 90.543(e) For operations in the 763-768 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, in accordance with the following:

On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $76 + 10 \log_{10} P$ dB (P = transmitter power in Watts) in a 6.25 kHz band segment.

The compliance limits were calculated in the following way:

Maximum transmitter output power [W]: P

Maximum transmitter output power [dBm]: 30 + 10 log₁₀ P (conversion from W to dBm)

Attenuation required by FCC:

769-775 MHz and 799-805 MHz: $76 + 10 \log_{10} P$ Below 758 MHz, Above 805 MHz: $43 + 10 \log_{10} P$ Between 775-799 MHz: $43 + 10 \log_{10} P$

Compliance limit = Maximum transmitter output power- Required attenuation

769-775 MHz and 799-805 MHz: $= 30 + 10 \log_{10} P - (76 + 10 \log_{10} P) = \underline{-46 \text{ dBm}}$ Below 758 MHz, Above 805 MHz: $= 30 + 10 \log_{10} P - (43 + 10 \log_{10} P) = \underline{-13 \text{ dBm}}$ Between 775-799 MHz: $= 30 + 10 \log_{10} P - (43 + 10 \log_{10} P) = \underline{-13 \text{ dBm}}$

3. According to § 90.543(f) all emissions including harmonics in the band 1559-1610 MHz shall be limited to -40 dBm/MHz EIRP for wideband signals, and -50 dBm EIRP for discrete emissions of less than 700 Hz bandwidth.

6.4.3 EUT Operating Condition

The standard setup procedure as described in section 4.3 of this report was used.

6.4.4 Test Configuration

The test configuration used is described in section 5.3 of this report.



6.4.5 Test Procedure and Results

Signal analyzer settings:

The tests were carried out in accordance with § 27.53 and § 90.543. For the frequency ranges 769-775 MHz and 799-805 MHz a resolution bandwith of 3 kHz was used instead of the required 6.25 kHz. Therefore the limit applicable for these frequency ranges was tightened by 3.2 dB.

For the frequency ranges immediately outside and adjacent to the carrier frequency block the resolution bandwidth was lowered to a minimum of 30 kHz.

For the frequency range 30-758 MHz a resolution bandwith of 100 kHz was used instead of 1 MHz. Therefore the applicable limit was tightened by 10 dB.

For all other frequency ranges a 1 MHz resolution bandwidth was used for the measurements.

According to § 2.1057, all emissions including the fundamental frequency from the lowest radio frequency generated in the equipment, without going below 9 kHz, up to the 10th harmonic were investigated.

The following tables summarize the worst case detected emission levels (see screenshots on pages 67 onwords for details). The external attenuation (cable loss of the set up) is already added in the results. It can be seen separately as the 'Offset' value in the screenshots.

Config A Lower band edge:

Carrier Frequency: 760.5 MHz			
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result
QPSK-Modulation TX	(1		
-	758.0	-16.65	compliant
QPSK-Modulation TX	(2		
-	758.0	-17.38	compliant
QPSK-Modulation TX	(1+TX2		
-	758.0	-14.23	compliant
16QAM-Modulation T	X1		
-	758.0	-18.88	compliant
16QAM-Modulation T	X2		
-	758.0	-18.19	compliant
16QAM-Modulation T	X1+TX2		
-	758.0	-16.92	compliant
64QAM-Modulation T	X1		
-	758.0	-17.23	compliant
64QAM-Modulation T	X2		
-	758.0	-17.43	compliant
64QAM-Modulation TX1+TX2			
-	758.0	-14.29	compliant
Measurement Uncert	ainty:		f < 1.0GHz: ±1.1dB 1.0GHz ≤ f <3.6GHz: ±1.2dB 3.6GHz ≤ f <8.0GHz: ±1.6dB

Table 6-5: Results - Spurious Emissions (Lower band edge) (5 MHz Channel BW)



Config A Upper band edge:

Carrier Frequency: 765.5 MHz			
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result
QPSK-Modulation TX	1		
-	768.0	-17.78	compliant
QPSK-Modulation TX	2		
-	768.0	-17.36	compliant
QPSK-Modulation TX	1+TX2		
-	768.0	-13.72	compliant
16QAM-Modulation T	X1		
-	768.0	-17.77	compliant
16QAM-Modulation T	X2		
-	768.0	-17.76	compliant
16QAM-Modulation T	X1+TX2		
-	768.0	-13.29	compliant
64QAM-Modulation T	X1		
-	768.0	-18.83	compliant
64QAM-Modulation T	X2		
-	768.0	-18.18	compliant
64QAM-Modulation TX1+TX2			
-	768.0	-13.86	compliant
Measurement Uncerta	ainty:		f < 1.0GHz: ±1.1dB 1.0GHz ≤ f <3.6GHz: ±1.2dB 3.6GHz ≤ f <8.0GHz: ±1.6dB

Table 6-6: Results - Spurious Emissions (Upper band edge) (5 MHz Channel BW)



Config A Spurious emissions:

	Carrier Frequency: 763.0 MHz			
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result	
QPSK-Modulation TX	K 1			
0.009 - 758	758.000	-30.89	compliant	
769 - 775	773.279	-53.93	compliant	
775 - 799	791.308	-34.76	compliant	
799 - 805	802.106	-61.93	compliant	
805 - 1559	1546.917	-40.41	compliant	
1559 -1610	1599.375	-50.23	compliant	
1610 - 7700	3527.244	-42.52	compliant	
QPSK-Modulation TX	X2	•		
0.009 - 758	758.000	-32.48	compliant	
769 - 775	769.663	-49.44	compliant	
775 - 799	775.035	-34.70	compliant	
799 - 805	799.038	-62.63	compliant	
805 - 1559	1542.083	-40.45	compliant	
1559 -1610	1587.688	-50.22	compliant	
1610 - 7700	3542.308	-42.52	compliant	
QPSK-Modulation TX	X1+TX2			
0.009 - 758	758.000	-27.12	compliant	
769 - 775	769.731	-55.54	compliant	
775 - 799	775.115	-35.48	compliant	
799 - 805	804.740	-62.32	compliant	
805 - 1559	1526.375	-36.95	compliant	
1559 -1610	1590.221	-56.82	compliant	
1610 - 7700	3534.776	-50.45	compliant	
16QAM-Modulation	ΓX1	'		
0.009 - 758	758.000	-31.55	compliant	
769 - 775	773.365	-51.65	compliant	
775 - 799	797.846	-34.76	compliant	
799 - 805	799.308	-62.57	compliant	
805 - 1559	1482.875	-40.42	compliant	
1559 -1610	1596.024	-50.24	compliant	
1610 - 7700	3542.308	-42.47	compliant	
16QAM-Modulation TX2				
0.009 - 758	758.000	-32.67	compliant	
769 - 775	769.221	-49.53	compliant	
775 - 799	797.500	-34.77	compliant	
799 - 805	801.500	-62.19	compliant	
805 - 1559	1548.125	-40.43	compliant	
1559 -1610	1599.947	-50.23	compliant	
1610 - 7700	3512.179	-42.47	compliant	



	Carrier Frequency: 763.0 MHz			
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result	
16QAM-Modulation T	TX1+TX2			
0.009 - 758	758.000	-29.15	compliant	
769 - 775	769.933	-51.03	compliant	
775 - 799	791.231	-40.54	compliant	
799 - 805	801.337	-63.39	compliant	
805 - 1559	1526.375	-33.16	compliant	
1559 -1610	1593.736	-56.87	compliant	
1610 - 7700	2289.407	-50.37	compliant	
64QAM-Modulation T	TX1			
0.009 - 758	756.833	-30.79	compliant	
769 - 775	773.337	-50.85	compliant	
775 - 799	778.731	-34.81	compliant	
799 - 805	803.375	-62.40	compliant	
805 - 1559	1472.000	-40.41	compliant	
1559 -1610	1596.024	-50.24	compliant	
1610 - 7700	3527.244	-42.54	compliant	
64QAM-Modulation T	X2			
0.009 - 758	758.000	-32.21	compliant	
769 - 775	769.798	-49.55	compliant	
775 - 799	775.000	-34.77	compliant	
799 - 805	804.981	-62.01	compliant	
805 - 1559	1550.542	-40.46	compliant	
1559 -1610	1595.779	-50.23	compliant	
1610 - 7700	3519.711	-42.52	compliant	
64QAM-Modulation T	X1+TX2	•		
0.009 - 758	758.000	-35.88	compliant	
769 - 775	769.404	-54.78	compliant	
775 - 799	775.346	-40.49	compliant	
799 - 805	803.837	-63.35	compliant	
805 - 1559	1526.375	-33.61	compliant	
1559 -1610	1599.130	-56.78	compliant	
1610 - 7700	2289.407	-48.60	compliant	
Measurement Uncertainty:		f < 1.0GHz: ±1.1dB 1.0GHz ≤ f <3.6GHz: ±1.2dB 3.6GHz ≤ f <8.0GHz: ±1.6dB		

Table 6-7: Results - Spurious Emissions (5 MHz Channel BW)



Config B Lower band edge:

Carrier Frequency: 763.0 MHz			
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result
QPSK-Modulation TX	1		
-	758.0	-19.16	compliant
QPSK-Modulation TX	2		
-	758.0	-19.76	compliant
QPSK-Modulation TX	1+TX2		
-	758.0	-14.11	compliant
16QAM-Modulation T	X1	•	
-	758.0	-20.45	compliant
16QAM-Modulation T	X2		
-	758.0	-20.14	compliant
16QAM-Modulation T	X1+TX2	•	
-	758.0	-15.15	compliant
64QAM-Modulation T	X1		
-	758.0	-19.31	compliant
64QAM-Modulation T	X2		
-	758.0	-20.14	compliant
64QAM-Modulation TX1+TX2			
-	758.0	-14.46	compliant
Measurement Uncerta	ainty:		f < 1.0GHz: ±1.1dB 1.0GHz ≤ f <3.6GHz: ±1.2dB 3.6GHz ≤ f <8.0GHz: ±1.6dB

Table 6-8: Results - Spurious Emissions (Lower band edge) (10 MHz Channel BW)



Config B Upper band edge:

Carrier Frequency: 763.0 MHz			
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result
QPSK-Modulation TX	(1		
-	768.0	-19.90	compliant
QPSK-Modulation TX	[2		
-	768.0	-19.80	compliant
QPSK-Modulation TX	(1+TX2		
-	768.0	-15.00	compliant
16QAM-Modulation T	X1	•	
-	768.0	-21.00	compliant
16QAM-Modulation T	X2		
-	768.0	-19.87	compliant
16QAM-Modulation T	X1+TX2		
-	768.0	-15.06	compliant
64QAM-Modulation T	X1	'	
-	768.0	-20.34	compliant
64QAM-Modulation T	X2	<u>. </u>	
-	768.0	-19.63	compliant
64QAM-Modulation TX1+TX2			
-	768.0	-15.41	compliant
Measurement Uncerta	ainty:		f < 1.0GHz: ±1.1dB 1.0GHz ≤ f <3.6GHz: ±1.2dB 3.6GHz ≤ f <8.0GHz: ±1.6dB

Table 6-9: Results - Spurious Emissions (Upper band edge) (10 MHz Channel BW)



Config B Spurious emissions:

Frequency Range [MHz] Emission Frequency [MHz] Maximum Emission Level [dBm] Result QPSK-Modulation TX1 0.009 - 758 758.000 -28.58 compliant 769 - 775 769.798 -49.79 compliant 775 - 799 775.038 -34.72 compliant 799 - 805 799.346 -61.76 compliant 805 - 1559 1555.375 -40.49 compliant 1559 -1610 1599.865 -50.24 compliant 1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 0.009 - 758 758.000 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 - 1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07				
0.009 - 758 758.000 -28.58 compliant 769 - 775 769.798 -49.79 compliant 775 - 799 775.038 -34.72 compliant 799 - 805 799.346 -61.76 compliant 805 - 1559 1555.375 -40.49 compliant 1559 - 1610 1599.865 -50.24 compliant 1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 -30.07 compliant 0.009 - 758 758.000 -30.07 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
769 - 775 769.798 -49.79 compliant 775 - 799 775.038 -34.72 compliant 799 - 805 799.346 -61.76 compliant 805 - 1559 1555.375 -40.49 compliant 1559 -1610 1599.865 -50.24 compliant 1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
775 - 799 775.038 -34.72 compliant 799 - 805 799.346 -61.76 compliant 805 - 1559 1555.375 -40.49 compliant 1559 - 1610 1599.865 -50.24 compliant 1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
799 - 805 799.346 -61.76 compliant 805 - 1559 1555.375 -40.49 compliant 1559 -1610 1599.865 -50.24 compliant 1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 0.009 - 758 758.000 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
805 - 1559 1555.375 -40.49 compliant 1559 -1610 1599.865 -50.24 compliant 1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 0.009 - 758 758.000 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
1559 -1610 1599.865 -50.24 compliant 1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 0.009 - 758 758.000 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
1610 - 7700 3527.244 -42.55 compliant QPSK-Modulation TX2 0.009 - 758 758.000 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
QPSK-Modulation TX2 0.009 - 758 758.000 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
0.009 - 758 758.000 -30.07 compliant 769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
769 - 775 769.596 -50.82 compliant 775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
775 - 799 775.077 -34.65 compliant 799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 0.009 - 758 758.000 -26.07 compliant				
799 - 805 803.904 -62.00 compliant 805 - 1559 1551.750 -40.46 compliant 1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 -26.07 compliant				
805 - 1559 1551.750 -40.46 compliant 1559 - 1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 0.009 - 758 758.000 -26.07 compliant				
1559 -1610 1595.125 -50.26 compliant 1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 0.009 - 758 758.000 -26.07 compliant				
1610 - 7700 3527.244 -42.50 compliant QPSK-Modulation TX1+TX2 0.009 - 758 758.000 -26.07 compliant				
QPSK-Modulation TX1+TX2 758.000 -26.07 compliant				
0.009 - 758 758.000 -26.07 compliant				
· ·				
769 - 775 769.826 -49.40 compliant				
775 - 799 775.308 -35.52 compliant				
799 - 805 801.279 -62.42 compliant				
805 - 1559 1526.375 -41.36 compliant				
1559 -1610 1609.183 -56.91 compliant				
1610 - 7700 2291.635 -46.26 compliant				
16QAM-Modulation TX1				
0.009 - 758 758.000 -29.23 compliant				
769 - 775 769.558 -49.73 compliant				
775 - 799 775.231 -34.70 compliant				
799 - 805 803.413 -62.52 compliant				
805 - 1559 1544.500 -40.43 compliant				
1559 -1610 1606.731 -50.20 compliant				
1610 - 7700 3527.244 -42.54 compliant				
16QAM-Modulation TX2				
0.009 - 758 758.000 -29.94 compliant				
769 - 775 769.779 -50.57 compliant				
775 - 799 775.000 -34.71 compliant				
799 - 805 800.462 -62.59 compliant				
805 - 1559 1552.958 -40.35 compliant				
1559 -1610 1588.913 -50.28 compliant				
1610 - 7700 3497.115 -42.52 compliant				



Carrier Frequency: 763.0 MHz			
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result
16QAM-Modulation T	X1+TX2		
0.009 - 758	758.000	-26.35	compliant
769 - 775	770.125	-49.39	compliant
775 - 799	775.000	-31.53	compliant
799 - 805	801.462	-62.89	compliant
805 - 1559	1526.375	-39.24	compliant
1559 -1610	1600.438	-56.87	compliant
1610 - 7700	3512.179	-50.46	compliant
64QAM-Modulation T	X1		
0.009 - 758	758.000	-28.23	compliant
769 - 775	769.827	-49.58	compliant
775 - 799	775.077	-34.70	compliant
799 - 805	802.615	-62.41	compliant
805 - 1559	1470.792	-40.47	compliant
1559 -1610	1600.438	-50.22	compliant
1610 - 7700	3519.712	-42.55	compliant
64QAM-Modulation T	X2		
0.009 - 758	758.000	-30.34	compliant
769 - 775	769.625	-49.54	compliant
775 - 799	775.000	-34.74	compliant
799 - 805	799.769	-62.74	compliant
805 - 1559	1559.000	-40.46	compliant
1559 -1610	1598.558	-50.27	compliant
1610 - 7700	3512.179	-42.49	compliant
64QAM-Modulation T	X1+TX2		
0.009 - 758	758.000	-26.01	compliant
769 - 775	769.019	-49.46	compliant
775 - 799	775.000	-32.07	compliant
799 - 805	800.683	-63.68	compliant
805 - 1559	1526.375	-39.06	compliant
1559 -1610	1593.817	-56.91	compliant
1610 - 7700	2291.634	-49.37	compliant
Measurement Uncertainty:			f < 1.0GHz: ±1.1dB 1.0GHz ≤ f <3.6GHz: ±1.2dB 3.6GHz ≤ f <8.0GHz: ±1.6dB

Table 6-10: Results - Spurious Emissions (10 MHz Channel BW)

The measured conducted emission levels were found to be compliant with the manufacturer's specifications and with all requirements of the FCC rules.



6.5 Test No. 5: Field Strength of Spurious Radiation (§ 2.1053, § 2.1057, § 27.53)

6.5.1 Purpose

The measurement of spurious radiated emissions was performed pursuant to § 2.1053 and § 2.1057 to verify that the field strength of any spurious emissions radiated directly from the cabinet, control circuits, power leads or intermediate circuit elements are attenuated below the specified limits.

6.5.2 Limits

Compliance with § 27.53 and § 90.543 requires that any emission will be sufficiently attenuated. Following requirements have to be fulfilled:

- According to § 27.53(d) for operations in the 758-763 MHz band, the power of any emission outside the licensee's frequency bands of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, in accordance with the following:
 - On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log₁₀ P dB (P = transmitter power in Watts) in a 6.25 kHz band segment.
 - On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log_{10} P$ dB (P = transmitter power in Watts).
- 2. According to § 90.543(e) For operations in the 763-768 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, in accordance with the following:

On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $76 + 10 \log_{10} P$ dB (P = transmitter power in Watts) in a 6.25 kHz band segment.

The compliance limits were calculated in the following way:

Maximum transmitter output power [W]: P

Maximum transmitter output power [dBm]: 30 + 10 log₁₀ P (conversion from W to dBm)

Attenuation required by FCC:

769-775 MHz and 799-805 MHz: $76 + 10 \log_{10} P$ Below 758 MHz, Above 805 MHz: $43 + 10 \log_{10} P$ Between 775-799 MHz: $43 + 10 \log_{10} P$

Compliance limit = Maximum transmitter output power- Required attenuation

769-775 MHz and 799-805 MHz: = $30 + 10 \log_{10} P - (76 + 10 \log_{10} P) = \frac{-46 \text{ dBm}}{10 \log_{10} P} = \frac{-13 \text{ dBm}}{10 \log_{10$

3. According to § 90.543(f) all emissions including harmonics in the band 1559-1610 MHz shall be limited to -40 dBm/MHz EIRP for wideband signals, and -50 dBm EIRP for discrete emissions of less than 700 Hz bandwidth.

6.5.3 EUT Operating Condition

The standard setup procedure as described in section 4.3 of this report was used.



6.5.4 Test Configuration

The measurements were performed in an anechoic chamber. The radiated test site complies with the site attenuation requirements listed in ANSI C63.4 2003 and is listed with the FCC.




Figure 6-1: Test Configuration

Photographs of the EUT in the anechoic chamber are shown on page 177 of this test report.

6.5.5 Test Procedure and Results

TIA/EIA-603-C-2004, Section 2.2.12

The test was performed in a semi-anechoic shielded room. The EUT was placed on a non-conductive 0.8 m high table standing on the turntable. During the test in the frequency range 30 - 8000 MHz the distance from the EUT to the measuring antenna was 3 m. In order to find the maximum levels of the disturbance radiation the angle of the turntable, the height of the measuring antenna were varied during the tests. The test was performed with the measuring antenna being both in horizontal and vertical polarizations.

Vertical and horizontal polarizations in the frequency range 30 - 8000 MHz was first measured by using the peak detector. During the peak detector scan the turntable was rotated from 0° to 360° with 30° step with the antenna heights 1.0 m and 2.5 m.

The limit of -13 dBm has been calculated to correspond 84.4 dB (μ V/m). The limit of -46 dBm has been calculated to correspond 51.4 dB (μ V/m). Spurious emissions closer than 20 dB to the limits were measured with average detector.

According to § 2.1057, all emissions from the lowest radio frequency generated in the equipment, without going below 9 kHz, up to the 10th harmonic were investigated.



The antenna substitution method was used to determine the equivalent radiated power at spurious frequencies. The EUT was replaced with a reference substitution antenna with a known gain referenced to an isotropic radiator $G_{Antenna[dBi]}$. This antenna was fed with a signal at the spurious frequency $P_{Gen[dBm]}$. The level of the signal was adjusted to repeat the previously measured level. The resulting EIRP is the signal level fed to the reference antenna corrected for gain referenced to an isotropic radiator.

The formula below was used to calculate the EIRP of the EUT.

 $P_{EIRP[dbm]} = P_{Gen[dBm]} - L_{Cable[dB]} + G_{Antenna[dBi]}$

Worst case detected emission levels are reported in the following table (refer to spectral plots included on Annex 5 for details). The antenna factor and cable loss is according to the manufacturer's specification.

Config A:

Carrier Frequency: 763.0 MHz						
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result			
30 - 8000	More than 20dB belo	ow limits -13/-46 dBm	compliant			
Measurement Uncert	ainty:	±5.4dB				

Table 6-11: Results – Field Strength of Spurious Radiation (5 MHz Channel BW)

Config B:

Carrier Frequency: 763.0 MHz						
Frequency Range [MHz]	Emission Frequency [MHz]	Maximum Emission Level [dBm]	Result			
30 - 7700	More than 20dB belo	ow limits -13/-46 dBm	compliant			
Measurement Uncert	tainty:	±5.4dB				

Table 6-12: Results – Field Strength of Spurious Radiation (10 MHz Channel BW)

The measured emission levels were found to be compliant with the manufacturer's specifications and with all requirements of the FCC rules.



6.6 Test No. 6: Frequency Stability (§ 2.1055, § 27.54)

6.6.1 Purpose

Frequency stability measurements were performed to verify that the frequency deviation of the emission stays within the licensee's frequency block under extreme temperature (-30°C to +50 °C) and supply voltage conditions according to § 2.1055.

6.6.2 Limits

According to § 27.54, the frequency of the fundamental emission is required to stay within the authorized frequency block.

6.6.3 EUT Operating Condition

The standard setup procedure as described in section 4.3 of this report was used.

6.6.4 Test Configuration




Figure 6-2: Test Configuration for frequency stability with voltage variation




Figure 6-3: Test Configuration for frequency stability with temperature variation

A complete list of the measurement equipment is included on page 36 of this measurement report.



6.6.5 Test Procedure and Results

Frequency Stability with Temperature Variation:

The supply voltage of the EUT was set to the nominal value and the temperature of the environmental chamber was varied in 10 degree steps from -30 degrees celsius to +50 degrees celsius. The EUT was allowed to stabilize at each temperature and the frequency error was measured.

Config A:

	Carrier Frequency: 763.0 MHz								
Supply Voltage (DC)	Ambient Temperature		uency on [ppm]		cturer's	Result			
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]				
QPSK Modulation	TX1								
-48.0	-30	-0.98	-0.0013	38	0.05	compliant			
-48.0	-20	-1.16	-0.0015	38	0.05	compliant			
-48.0	-10	-0.91	-0.0012	38	0.05	compliant			
-48.0	0	-0.50	-0.0007	38	0.05	compliant			
-48.0	+10	0.61	0.0008	38	0.05	compliant			
-48.0	+30	0.67	0.0009	38	0.05	compliant			
-48.0	+40	0.37	0.0005	38	0.05	compliant			
-48.0	+50	0.54	0.0007	38	0.05	compliant			
QPSK Modulation	TX2								
-48.0	-30	-0.89	-0.0012	38	0.05	compliant			
-48.0	-20	-1.03	-0.0013	38	0.05	compliant			
-48.0	-10	-0.76	-0.0010	38	0.05	compliant			
-48.0	0	-0.47	-0.0006	38	0.05	compliant			
-48.0	+10	0.41	0.0005	38	0.05	compliant			
-48.0	+30	0.79	0.0010	38	0.05	compliant			
-48.0	+40	0.76	0.0010	38	0.05	compliant			
-48.0	+50	0.37	0.0005	38	0.05	compliant			
16QAM Modulation	on TX1								
-48.0	-30	-0.69	-0.0009	38	0.05	compliant			
-48.0	-20	-0.66	-0.0009	38	0.05	compliant			
-48.0	-10	0.40	0.0005	38	0.05	compliant			
-48.0	0	0.36	0.0005	38	0.05	compliant			
-48.0	+10	0.61	0.0008	38	0.05	compliant			
-48.0	+30	0.99	0.0013	38	0.05	compliant			
-48.0	+40	1.10	0.0014	38	0.05	compliant			
-48.0	+50	0.99	0.0013	38	0.05	compliant			
16QAM Modulation	n TX2								
-48.0	-30	-0.70	-0.0009	38	0.05	compliant			
-48.0	-20	-0.73	-0.0010	38	0.05	compliant			
-48.0	-10	-0.40	-0.0005	38	0.05	compliant			
-48.0	0	0.44	0.0006	38	0.05	compliant			
-48.0	+10	0.81	0.0011	38	0.05	compliant			
-48.0	+30	1.07	0.0014	38	0.05	compliant			
-48.0	+40	0.85	0.0011	38	0.05	compliant			
-48.0	+50	0.95	0.0012	38	0.05	compliant			



Carrier Frequency: 763.0 MHz								
Supply Voltage (DC)	Ambient Temperature		uency on [ppm]		cturer's ication	Result		
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]			
64QAM Modulation	on TX1							
-48.0	-30	1.47	0.0019	38	0.05	compliant		
-48.0	-20	1.67	0.0022	38	0.05	compliant		
-48.0	-10	2.12	0.0028	38	0.05	compliant		
-48.0	0	2.73	0.0036	38	0.05	compliant		
-48.0	+10	2.83	0.0037	38	0.05	compliant		
-48.0	+30	2.95	0.0039	38	0.05	compliant		
-48.0	+40	2.86	0.0037	38	0.05	compliant		
-48.0	+50	2.75	0.0036	38	0.05	compliant		
64QAM Modulation	on TX2							
-48.0	-30	1.57	0.0021	38	0.05	compliant		
-48.0	-20	1.63	0.0021	38	0.05	compliant		
-48.0	-10	2.30	0.0030	38	0.05	compliant		
-48.0	0	2.83	0.0037	38	0.05	compliant		
-48.0	+10	2.99	0.0039	38	0.05	compliant		
-48.0	+30	2.63	0.0034	38	0.05	compliant		
-48.0	+40	2.83	0.0037	38	0.05	compliant		
-48.0	+50	2.85	0.0037	38	0.05	compliant		
Measurement Un	certainty:				±1.0 Hz			

Table 6-13: Results – Frequency stability with temp. var. (5 MHz Channel BW)



Config B:

		Carrier Fre	equency: 763	3.0 MHz		
Supply Voltage (DC)	Ambient Temperature		uency on [ppm]		acturer's fication	Result
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation	n TX1					
-48.0	-30	-0.59	-0.0008	38	0.05	compliant
-48.0	-20	0.57	0.0007	38	0.05	compliant
-48.0	-10	1.10	0.0014	38	0.05	compliant
-48.0	0	1.03	0.0013	38	0.05	compliant
-48.0	+10	1.69	0.0022	38	0.05	compliant
-48.0	+30	1.40	0.0018	38	0.05	compliant
-48.0	+40	1.36	0.0018	38	0.05	compliant
-48.0	+50	1.56	0.0020	38	0.05	compliant
QPSK Modulation	TX2					
-48.0	-30	-0.41	-0.0005	38	0.05	compliant
-48.0	-20	1.14	0.0015	38	0.05	compliant
-48.0	-10	0.81	0.0011	38	0.05	compliant
-48.0	0	1.22	0.0016	38	0.05	compliant
-48.0	+10	1.56	0.0020	38	0.05	compliant
-48.0	+30	1.99	0.0026	38	0.05	compliant
-48.0	+40	1.44	0.0019	38	0.05	compliant
-48.0	+50	1.19	0.0016	38	0.05	compliant
16QAM Modulation	on TX1					
-48.0	-30	0.49	0.0006	38	0.05	compliant
-48.0	-20	0.70	0.0009	38	0.05	compliant
-48.0	-10	1.33	0.0017	38	0.05	compliant
-48.0	0	1.16	0.0015	38	0.05	compliant
-48.0	+10	1.94	0.0025	38	0.05	compliant
-48.0	+30	1.65	0.0022	38	0.05	compliant
-48.0	+40	1.94	0.0025	38	0.05	compliant
-48.0	+50	1.70	0.0022	38	0.05	compliant
16QAM Modulation	on TX2					
-48.0	-30	-0.24	-0.0003	38	0.05	compliant
-48.0	-20	0.93	0.0012	38	0.05	compliant
-48.0	-10	0.96	0.0013	38	0.05	compliant
-48.0	0	1.17	0.0015	38	0.05	compliant
-48.0	+10	2.10	0.0028	38	0.05	compliant
-48.0	+30	1.83	0.0024	38	0.05	compliant
-48.0	+40	2.10	0.0028	38	0.05	compliant
-48.0	+50	1.67	0.0022	38	0.05	compliant



	Carrier Frequency: 763.0 MHz								
Supply Voltage (DC)	Ambient Temperature	Frequency Deviation [ppm]		Manufacturer's Specification		Result			
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]				
64QAM Modulation	on TX1								
-48.0	-30	-0.74	-0.0010	38	0.05	compliant			
-48.0	-20	0.45	0.0006	38	0.05	compliant			
-48.0	-10	1.18	0.0015	38	0.05	compliant			
-48.0	0	1.30	0.0017	38	0.05	compliant			
-48.0	+10	1.65	0.0022	38	0.05	compliant			
-48.0	+30	1.72	0.0023	38	0.05	compliant			
-48.0	+40	1.51	0.0020	38	0.05	compliant			
-48.0	+50	1.64	0.0021	38	0.05	compliant			
64QAM Modulation	on TX2								
-48.0	-30	-0.29	-0.0004	38	0.05	compliant			
-48.0	-20	0.73	0.0010	38	0.05	compliant			
-48.0	-10	0.82	0.0011	38	0.05	compliant			
-48.0	0	1.21	0.0016	38	0.05	compliant			
-48.0	+10	1.47	0.0019	38	0.05	compliant			
-48.0	+30	1.77	0.0023	38	0.05	compliant			
-48.0	+40	1.37	0.0018	38	0.05	compliant			
-48.0	+50	1.56	0.0020	38	0.05	compliant			
Measurement Un	certainty:				±1.0 Hz				

Table 6-14: Results – Frequency stability with temp. var. (10 MHz Channel BW)



Frequency Stability with Supply Voltage Variation:

The EUT was placed in a climatic chamber and allowed to stabilize at +20 degrees celsius for at least 30 minutes. With the supply voltage of the EUT set to 85% of the nominal value, the frequency error was measure. This procedure was repeated at 100% and 115% of the nominal supply voltage value.

Config A:

Carrier Frequency: 763.0 MHz							
Supply Voltage (DC)	Ambient Temperature	Temperature Deviation [ppm] Specifica			Result		
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]		
QPSK Modulation	TX1					•	
-40.8	+20	0.46	0.0006	38	0.05	compliant	
-48.0	+20	0.20	0.0003	38	0.05	compliant	
-55.2	+20	0.54	0.0007	38	0.05	compliant	
QPSK Modulation	TX2					•	
-40.8	+20	0.62	0.0008	38	0.05	compliant	
-48.0	+20	0.38	0.0005	38	0.05	compliant	
-55.2	+20	0.68	0.0009	38	0.05	compliant	
16QAM Modulatio	n TX1					•	
-40.8	+20	1.00	0.0013	38	0.05	compliant	
-48.0	+20	0.88	0.0012	38	0.05	compliant	
-55.2	+20	0.93	0.0012	38	0.05	compliant	
16QAM Modulatio	n TX2						
-40.8	+20	0.76	0.0010	38	0.05	compliant	
-48.0	+20	0.75	0.0010	38	0.05	compliant	
-55.2	+20	0.59	0.0008	38	0.05	compliant	
64QAM Modulatio	n TX1		•			•	
-40.8	+20	2.87	0.0038	38	0.05	compliant	
-48.0	+20	2.77	0.0036	38	0.05	compliant	
-55.2	+20	2.73	0.0036	38	0.05	compliant	
64QAM Modulatio	n TX2		•				
-40.8	+20	2.76	0.0036	38	0.05	compliant	
-48.0	+20	2.73	0.0036	38	0.05	compliant	
-55.2	+20	2.76	0.0036	38	0.05	compliant	
Measurement Unc	ertainty:		•		±1.0 Hz	•	

Table 6-15: Results – Frequency stability with voltage var. (5 MHz Channel BW)



Config B:

Carrier Frequency: 763.0 MHz							
Supply Voltage (DC)	Ambient Temperature	mperature Deviation [ppm] Specific			Result		
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]		
QPSK Modulation	TX1					·	
-40.8	+20	1.32	0.0017	38	0.05	compliant	
-48.0	+20	1.72	0.0023	38	0.05	compliant	
-55.2	+20	1.72	0.0023	38	0.05	compliant	
QPSK Modulation	TX2						
-40.8	+20	1.51	0.0020	38	0.05	compliant	
-48.0	+20	1.83	0.0024	38	0.05	compliant	
-55.2	+20	1.62	0.0021	38	0.05	compliant	
16QAM Modulatio	n TX1						
-40.8	+20	1.54	0.0020	38	0.05	compliant	
-48.0	+20	1.80	0.0024	38	0.05	compliant	
-55.2	+20	1.42	0.0019	38	0.05	compliant	
16QAM Modulatio	n TX2						
-40.8	+20	1.79	0.0023	38	0.05	compliant	
-48.0	+20	1.87	0.0025	38	0.05	compliant	
-55.2	+20	1.57	0.0021	38	0.05	compliant	
64QAM Modulatio	n TX1						
-40.8	+20	1.97	0.0026	38	0.05	compliant	
-48.0	+20	1.51	0.0020	38	0.05	compliant	
-55.2	+20	1.42	0.0019	38	0.05	compliant	
64QAM Modulatio	n TX2						
-40.8	+20	1.44	0.0019	38	0.05	compliant	
-48.0	+20	1.68	0.00222	38	0.05	compliant	
-55.2	+20	1.57	0.0021	38	0.05	compliant	
Measurement Und	certainty:				±1.0 Hz		

Table 6-16: Results – Frequency stability with voltage var. (10 MHz Channel BW)

The measured frequency stability was found to be compliant with the manufacturer's specifications and with all requirements of the FCC rules.



7 Test Data and Screenshots

7.1 Part List of the RF Measurement Test Equipment

No.	Test Equipment	Type (Manufacturer)	Serial Number	Calibration date	Calibration due	Test No.
1	Network Analyzer	Hewlett-Packard: HP8753E	US38431868	06/2010	06/2011	1, 2, 3, 4, 6
2	Network Analyzer	Hewlett-Packard: HP8720ES	US39172107	06/2010	06/2011	1, 2, 3, 4, 6
3	Calibration kit	Hewlett-Packard: HP85032B	2919A04843	06/2010	06/2011	1, 2, 3, 4, 6
4	DC power	Sörensen: DHP series	9950C0085	cnn	-	1, 2, 3, 4, 6
5	Signal Analyzer	Rohde & Schwarz: FSQ 26	100206	02/2010	02/2011	1, 2, 3, 4, 6
6	Frequency Standard	Datum 8040	0041005473	01/2010	01/2011	6
7	Temperature/ humidity meter	VAISALA: HMI 31	P3730008	12/2010	12/2011	1, 2, 3, 4, 5, 6
8	Enviromental chamber	Weiss technik	59226012320 010	06/2010	06/2011	6
9	Attenuator	Spinner: BN 74 53 58	35016	cnn	-	1, 2, 3, 4, 6
10	Attenuator	Spinner: BN 74 53 58	25823	cnn	-	1, 2, 3, 4, 6
11	Attenuator	Spinner: BN 52 77 36	86962	cnn	-	1, 2, 3, 4, 6
12	Attenuator	Spinner: BN 53 12 51	32803	cnn	-	1, 2, 3, 4, 6
13	Attenuator	Weinschel: 66-20-34	BM6886	cnn	-	4
14	Attenuator	Weinschel: 66-20-33	BV3346	cnn	-	4
15	High pass filter	Mini-Circuits: SHP-1000	15542	cnn	-	4
16	Combiner	Weinschel: 1870A	6275	cnn	-	4
17	Semianechoic chamber	Siemens Matsushita 9m × 5m × 6m (room 0039)	Product No S&M B83317- C6019-T232	08/2008	08/2011	5
18	EMI Test Receiver	R&S ESIB 26	100335	07/2010	07/2011	5
19	Horn Antenna	Emco 3115	00075697	07/2010	07/2011	5
20	Bilog Antenna	Chase CBL6112B	2694	07/2010	07/2011	5
21	Amplifier	Miteq AFSX4	791117	cnn	-	5
22	Antenna Mast	Deisel HD240	2401323194	cnn	-	5
23	Mast Controller	Deisel HD100	1001331	cnn	-	5
24	Amplifier	HP 83017A	3123A00444	cnn	-	5

Table 7-1: Part List of the RF Measurement Test Equipment




7.2 Spectral Plots

7.2.1 Test No. 1: RF Power Output

The value 'Power' is the carrier power (RF Power Output) at the antenna terminals measured by the signal analyzer. 'Offset' is the external attenuation (cable loss of the test set up). The external attenuation is frequency dependant. Thus the various 'Offset' values in the screenshots may differ.


Config A TX1:



Date: 7.FEB.2011 08:35:41

Figure 7-1: RF Power Output – QPSK (760.5 MHz) (5MHz Channel BW)






Date: 7.FEB.2011 14:14:14


Figure 7-2: RF Power Output – QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:12:38


Figure 7-3: RF Power Output – QPSK (765.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 08:41:32


Figure 7-4: RF Power Output – 16QAM (760.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 14:15:21


Figure 7-5: RF Power Output – 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:14:36


Figure 7-6: RF Power Output – 16QAM (765.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 08:39:54


Figure 7-7: RF Power Output – 64QAM (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 14:16:17

Figure 7-8: RF Power Output – 64QAM (763.0 MHz) (5MHz Channel BW)






Date: 7.FEB.2011 11:16:25

Figure 7-9: RF Power Output – 64QAM (765.5 MHz) (5MHz Channel BW)




Config A TX2:



Date: 7.FEB.2011 08:45:01


Figure 7-10: RF Power Output – QPSK (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 13:56:41


Figure 7-11: RF Power Output – QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:27:39


Figure 7-12: RF Power Output – QPSK (765.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 08:48:20


Figure 7-13: RF Power Output – 16QAM (760.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 13:58:59


Figure 7-14: RF Power Output – 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:29:48


Figure 7-15: RF Power Output – 16QAM (765.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 08:46:55


Figure 7-16: RF Power Output – 64QAM (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 14:01:37

Figure 7-17: RF Power Output – 64QAM (763.0 MHz) (5MHz Channel BW)






Date: 7.FEB.2011 11:31:35

Figure 7-18: RF Power Output – 64QAM (765.5 MHz) (5MHz Channel BW)




Config B TX1:



Date: 7.FEB.2011 14:25:58


Figure 7-19: RF Power Output – QPSK (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 14:27:35

Figure 7-20: RF Power Output – 16QAM (763.0 MHz) (10MHz Channel BW)






Date: 7.FEB.2011 14:29:37

Figure 7-21: RF Power Output – 64QAM (763.0 MHz) (10MHz Channel BW)




Config B TX2:



Date: 7.FEB.2011 14:32:25


Figure 7-22: RF Power Output – QPSK (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 14:34:09

Figure 7-23: RF Power Output – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 7.FEB.2011 14:35:41

Figure 7-24: RF Power Output – 64QAM (763.0 MHz) (10MHz Channel BW)



7.2.2 Test No. 2: Modulation Characteristics


No additional measurements are required for the modulation characteristics. Please refer to test no. 3, occupied bandwidth on Annex 2.



7.2.3 Test No. 3: Occupied Bandwidth


The value 'OBW' is the measured occupied bandwidth.

Config A TX1:



Date: 7.FEB.2011 08:36:55


Figure 7-25: Occupied Bandwidth – QPSK (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 14:09:40


Figure 7-26: Occupied Bandwidth – QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:13:38


Figure 7-27: Occupied Bandwidth - QPSK (765.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 08:42:16

Figure 7-28: Occupied Bandwidth – 16QAM (760.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 14:10:32

Date: 7.FEB.2011 11:15:22

Figure 7-29: Occupied Bandwidth - 16QAM (763.0 MHz) (5MHz Channel BW)





Figure 7-30: Occupied Bandwidth – 16QAM (765.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 08:40:47

Date: 7.FEB.2011 14:11:26

Figure 7-31: Occupied Bandwidth - 64QAM (760.5 MHz) (5MHz Channel BW)





Figure 7-32: Occupied Bandwidth – 64QAM (763.0 MHz) (5MHz Channel BW)






Date: 7.FEB.2011 11:17:27

Figure 7-33: Occupied Bandwidth – 64QAM (765.5 MHz) (5MHz Channel BW)




Config A TX2:



Date: 7.FEB.2011 08:46:07


Figure 7-34: Occupied Bandwidth – QPSK (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 13:58:00


Figure 7-35: Occupied Bandwidth - QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:28:24


Figure 7-36: Occupied Bandwidth - QPSK (765.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 08:49:10


Figure 7-37: Occupied Bandwidth – 16QAM (760.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 14:00:16


Figure 7-38: Occupied Bandwidth - 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:30:34


Figure 7-39: Occupied Bandwidth – 16QAM (765.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 08:47:39


Figure 7-40: Occupied Bandwidth - 64QAM (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 14:03:48

Figure 7-41: Occupied Bandwidth – 64QAM (763.0 MHz) (5MHz Channel BW)






Date: 7.FEB.2011 11:32:36

Figure 7-42: Occupied Bandwidth – 64QAM (765.5 MHz) (5MHz Channel BW)




Config B TX1:



Date: 7.FEB.2011 14:26:35


Figure 7-43: Occupied Bandwidth – QPSK (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 14:28:31

Figure 7-44: Occupied Bandwidth – 16QAM (763.0 MHz) (10MHz Channel BW)






Date: 7.FEB.2011 14:30:34

Figure 7-45: Occupied Bandwidth – 64QAM (763.0 MHz) (10MHz Channel BW)




Config B TX2:



Date: 7.FEB.2011 14:33:18


Figure 7-46: Occupied Bandwidth – QPSK (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 14:34:53

Figure 7-47: Occupied Bandwidth – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 7.FEB.2011 14:36:27

Figure 7-48: Occupied Bandwidth – 64QAM (763.0 MHz) (10MHz Channel BW)



7.2.4 Test No. 4: Spurious Emissions at the Antenna Terminals

The external attenuation (cable loss of the setup) can be seen as the 'Offset' value in the screenshots. The external attenuation is frequency dependant. Thus the various 'Offset' values in the screenshots may differ. The maximum Spurious Emission levels are given on Annex 3 and Annex 4.

Config A TX1:





Figure 7-49: Spurious Emissions (Lower band edge)
– QPSK (760.5 MHz) (5MHz Channel BW)


Date: 7.FEB.2011 09:09:43





Date: 7.FEB.2011 11:05:24


Figure 7-50: Spurious Emissions (Upper band edge)
- QPSK (765.5 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 09:26:32


Figure 7-51: Spurious Emissions (9kHz – 150kHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 09:47:27


Figure 7-52: Spurious Emissions (150kHz – 30MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 8.FEB.2011 15:06:52


Figure 7-53: Spurious Emissions (30MHz – 758MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 12:58:12


Figure 7-54: Spurious Emissions (769MHz – 775MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:43:58


Figure 7-55: Spurious Emissions (775MHz – 799MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 13:36:38


Figure 7-56: Spurious Emissions (799MHz – 805MHz) – QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:15:49


Figure 7-57: Spurious Emissions (805MHz – 1559MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:21:05


Figure 7-58: Spurious Emissions (1559MHz – 1610MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 15:00:06


Figure 7-59: Spurious Emissions (1610MHz – 3GHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:54:32


Figure 7-60: Spurious Emissions (3GHz – 7.7GHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 09:10:36


Figure 7-61: Spurious Emissions (Lower band edge)
- 16QAM (760.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:06:32


Figure 7-62: Spurious Emissions (Upper band edge)
- 16QAM (765.5 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 09:26:58


Figure 7-63: Spurious Emissions (9kHz – 150kHz) – 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 09:47:55


Figure 7-64: Spurious Emissions (150kHz – 30MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 8.FEB.2011 15:08:09


Figure 7-65: Spurious Emissions (30MHz – 758MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 12:59:01


Figure 7-66: Spurious Emissions (769MHz – 775MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:44:46


Figure 7-67: Spurious Emissions (775MHz – 799MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 13:35:30


Figure 7-68: Spurious Emissions (799MHz – 805MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:16:15


Figure 7-69: Spurious Emissions (805MHz – 1559MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:21:39


Figure 7-70: Spurious Emissions (1559MHz – 1610MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:59:31


Figure 7-71: Spurious Emissions (1610MHz – 3GHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:56:10


Figure 7-72: Spurious Emissions (3GHz – 7.7GHz) – 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 09:11:33


Figure 7-73: Spurious Emissions (Lower band edge)
- 64QAM (760.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:07:25


Figure 7-74: Spurious Emissions (Upper band edge)
- 64QAM (765.5 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 09:27:38


Figure 7-75: Spurious Emissions (9kHz – 150kHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 09:48:22


Figure 7-76: Spurious Emissions (150kHz – 30MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 8.FEB.2011 15:09:29


Figure 7-77: Spurious Emissions (30MHz – 758MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 13:00:05


Figure 7-78: Spurious Emissions (769MHz – 775MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:45:16


Figure 7-79: Spurious Emissions (775MHz – 799MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 13:36:03


Figure 7-80: Spurious Emissions (799MHz – 805MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:16:46


Figure 7-81: Spurious Emissions (805MHz – 1559MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:22:10


Figure 7-82: Spurious Emissions (1559MHz – 1610MHz)
– 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:58:46

Figure 7-83: Spurious Emissions (1610MHz – 3GHz) – 64QAM (763.0 MHz) (5MHz Channel BW)






Date: 4.FEB.2011 14:57:06

Figure 7-84: Spurious Emissions (3GHz – 7.7GHz) – 64QAM (763.0 MHz) (5MHz Channel BW)




Config A TX2:



Date: 7.FEB.2011 08:55:58


Figure 7-85: Spurious Emissions (Lower band edge)
- QPSK (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:00:55


Figure 7-86: Spurious Emissions (Upper band edge)
- QPSK (765.5 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 09:23:01


Figure 7-87: Spurious Emissions (9kHz – 150kHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 09:46:07


Figure 7-88: Spurious Emissions (150kHz – 30MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 8.FEB.2011 15:11:14


Figure 7-89: Spurious Emissions (30MHz – 758MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:04:13


Figure 7-90: Spurious Emissions (769MHz – 775MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 13:41:46


Figure 7-91: Spurious Emissions (775MHz – 799MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:38:33


Figure 7-92: Spurious Emissions (799MHz – 805MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:11:06


Figure 7-93: Spurious Emissions (805MHz – 1559MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:24:11


Figure 7-94: Spurious Emissions (1559MHz – 1610MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 15:02:38


Figure 7-95: Spurious Emissions (1610MHz – 3GHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:48:17


Figure 7-96: Spurious Emissions (3GHz – 7.7GHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 08:58:26


Figure 7-97: Spurious Emissions (Lower band edge)
- 16QAM (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:02:11


Figure 7-98: Spurious Emissions (Upper band edge)
- 16QAM (765.5 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 09:23:58


Figure 7-99: Spurious Emissions (9kHz – 150kHz) – 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 09:45:36


Figure 7-100: Spurious Emissions (150kHz – 30MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 8.FEB.2011 15:12:22


Figure 7-101: Spurious Emissions (30MHz – 758MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:05:42


Figure 7-102: Spurious Emissions (769MHz – 775MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 13:42:20


Figure 7-103: Spurious Emissions (775MHz – 799MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:38:05


Figure 7-104: Spurious Emissions (799MHz – 805MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:11:53


Figure 7-105: Spurious Emissions (805MHz – 1559MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:24:39


Figure 7-106: Spurious Emissions (1559MHz – 1610MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 15:02:05


Figure 7-107: Spurious Emissions (1610MHz – 3GHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:49:34


Figure 7-108: Spurious Emissions (3GHz – 7.7GHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 08:59:29


Figure 7-109: Spurious Emissions (Lower band edge)
- 64QAM (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:03:07


Figure 7-110: Spurious Emissions (Upper band edge)
- 64QAM (765.5 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 09:24:32


Figure 7-111: Spurious Emissions (9kHz – 150kHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 09:45:04


Figure 7-112: Spurious Emissions (150kHz – 30MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 8.FEB.2011 15:13:27


Figure 7-113: Spurious Emissions (30MHz – 758MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:06:31


Figure 7-114: Spurious Emissions (769MHz – 775MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 13:42:51


Figure 7-115: Spurious Emissions (775MHz – 799MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 13:37:43


Figure 7-116: Spurious Emissions (799MHz – 805MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 14:12:32


Figure 7-117: Spurious Emissions (805MHz – 1559MHz)
– 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 4.FEB.2011 14:25:10


Figure 7-118: Spurious Emissions (1559MHz – 1610MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 4.FEB.2011 15:01:31

Figure 7-119: Spurious Emissions (1610MHz – 3GHz) – 64QAM (763.0 MHz) (5MHz Channel BW)




Date: 4.FEB.2011 14:51:06

Figure 7-120: Spurious Emissions (3GHz – 7.7GHz)
– 64QAM (763.0 MHz) (5MHz Channel BW)




Config A TX1+TX2:



Date: 7.FEB.2011 09:16:42


Figure 7-121: Spurious Emissions (Lower band edge)
- QPSK (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 10:53:21


Figure 7-122: Spurious Emissions (Upper band edge)
- QPSK (765.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:49:04


Figure 7-123: Spurious Emissions (9kHz – 150kHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:53:50


Figure 7-124: Spurious Emissions (150kHz – 30MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 8.FEB.2011 15:15:52


Figure 7-125: Spurious Emissions (30MHz – 758MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 12:44:22


Figure 7-126: Spurious Emissions (769MHz – 775MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 12:59:25


Figure 7-127: Spurious Emissions (775MHz – 799MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 12:53:24


Figure 7-128: Spurious Emissions (799MHz – 805MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 13:40:38


Figure 7-129: Spurious Emissions (805MHz – 1559MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 13:11:05


Figure 7-130: Spurious Emissions (1559MHz – 1610MHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 13:44:15


Figure 7-131: Spurious Emissions (1610MHz – 3GHz)
– QPSK (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 13:49:18


Figure 7-132: Spurious Emissions (3GHz – 7.7GHz)
– QPSK (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 09:18:09


Figure 7-133: Spurious Emissions (Lower band edge)
- 16QAM (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 10:55:35


Figure 7-134: Spurious Emissions (Upper band edge)
- 16QAM (765.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:49:44


Figure 7-135: Spurious Emissions (9kHz – 150kHz) – 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:53:19


Figure 7-136: Spurious Emissions (150kHz – 30MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 8.FEB.2011 15:16:55


Figure 7-137: Spurious Emissions (30MHz – 758MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 12:46:30


Figure 7-138: Spurious Emissions (769MHz – 775MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 12:56:37


Figure 7-139: Spurious Emissions (775MHz – 799MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 12:53:55


Figure 7-140: Spurious Emissions (799MHz – 805MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 13:41:20


Figure 7-141: Spurious Emissions (805MHz – 1559MHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 13:10:19


Figure 7-142: Spurious Emissions (1559MHz – 1610MHz) – 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 13:44:49


Figure 7-143: Spurious Emissions (1610MHz – 3GHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 13:48:39


Figure 7-144: Spurious Emissions (3GHz – 7.7GHz)
– 16QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 09:19:20


Figure 7-145: Spurious Emissions (Lower band edge)
- 64QAM (760.5 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 10:56:35


Figure 7-146: Spurious Emissions (Upper band edge)
- 64QAM (765.5 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 11:50:23


Figure 7-147: Spurious Emissions (9kHz – 150kHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 11:52:45


Figure 7-148: Spurious Emissions (150kHz – 30MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 8.FEB.2011 15:17:57


Figure 7-149: Spurious Emissions (30MHz – 758MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 12:45:28


Figure 7-150: Spurious Emissions (769MHz – 775MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 12:57:12


Figure 7-151: Spurious Emissions (775MHz – 799MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 12:54:21


Figure 7-152: Spurious Emissions (799MHz – 805MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 13:41:54


Figure 7-153: Spurious Emissions (805MHz – 1559MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)



Date: 7.FEB.2011 13:09:37


Figure 7-154: Spurious Emissions (1559MHz – 1610MHz) – 64QAM (763.0 MHz) (5MHz Channel BW)





Date: 7.FEB.2011 13:45:38

Figure 7-155: Spurious Emissions (1610MHz – 3GHz) – 64QAM (763.0 MHz) (5MHz Channel BW)




Date: 7.FEB.2011 13:48:04

Figure 7-156: Spurious Emissions (3GHz – 7.7GHz)
– 64QAM (763.0 MHz) (5MHz Channel BW)




Config B TX1:



Date: 8.FEB.2011 14:43:30


Figure 7-157: Spurious Emissions (Lower band edge)
- QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:46:10


Figure 7-158: Spurious Emissions (Upper band edge)
- QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:26:39


Figure 7-159: Spurious Emissions (9kHz – 150kHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:33:12


Figure 7-160: Spurious Emissions (150kHz – 30MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 09:52:06


Figure 7-161: Spurious Emissions (30MHz – 758MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:56:11


Figure 7-162: Spurious Emissions (769MHz – 775MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 12:54:42


Figure 7-163: Spurious Emissions (775MHz – 799MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 12:59:01


Figure 7-164: Spurious Emissions (799MHz – 805MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:33:58


Figure 7-165: Spurious Emissions (805MHz – 1559MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:36:40


Figure 7-166: Spurious Emissions (1559MHz – 1610MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:05:33


Figure 7-167: Spurious Emissions (1610MHz – 3GHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:07:59


Figure 7-168: Spurious Emissions (3GHz – 7.7GHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:42:42


Figure 7-169: Spurious Emissions (Lower band edge)
- 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:47:12


Figure 7-170: Spurious Emissions (Upper band edge)
- 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:27:10


Figure 7-171: Spurious Emissions (9kHz – 150kHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:34:01


Figure 7-172: Spurious Emissions (150kHz – 30MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 09:50:14


Figure 7-173: Spurious Emissions (30MHz – 758MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:58:13


Figure 7-174: Spurious Emissions (769MHz – 775MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 12:53:30


Figure 7-175: Spurious Emissions (775MHz – 799MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:00:22


Figure 7-176: Spurious Emissions (799MHz – 805MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:33:03


Figure 7-177: Spurious Emissions (805MHz – 1559MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:37:39


Figure 7-178: Spurious Emissions (1559MHz – 1610MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:04:29


Figure 7-179: Spurious Emissions (1610MHz – 3GHz)
– 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:09:04


Figure 7-180: Spurious Emissions (3GHz – 7.7GHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:41:48


Figure 7-181: Spurious Emissions (Lower band edge)
- 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:48:16


Figure 7-182: Spurious Emissions (Upper band edge)
- 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:27:44


Figure 7-183: Spurious Emissions (9kHz – 150kHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:34:39


Figure 7-184: Spurious Emissions (150kHz – 30MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 09:48:41


Figure 7-185: Spurious Emissions (30MHz – 758MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 10:01:05


Figure 7-186: Spurious Emissions (769MHz – 775MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 12:52:20


Figure 7-187: Spurious Emissions (775MHz – 799MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:02:08


Figure 7-188: Spurious Emissions (799MHz – 805MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:32:01


Figure 7-189: Spurious Emissions (805MHz – 1559MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:38:43


Figure 7-190: Spurious Emissions (1559MHz – 1610MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:03:33

Figure 7-191: Spurious Emissions (1610MHz – 3GHz) – 64QAM (763.0 MHz) (10MHz Channel BW)






Date: 8.FEB.2011 14:10:12

Figure 7-192: Spurious Emissions (3GHz – 7.7GHz) – 64QAM (763.0 MHz) (10MHz Channel BW)




Config B TX2:



Date: 8.FEB.2011 14:40:12


Figure 7-193: Spurious Emissions (Lower band edge)
- QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:50:18


Figure 7-194: Spurious Emissions (Upper band edge)
- QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:22:44


Figure 7-195: Spurious Emissions (9kHz – 150kHz) – QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:35:51


Figure 7-196: Spurious Emissions (150kHz – 30MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:46:36


Figure 7-197: Spurious Emissions (30MHz – 758MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 10:04:29


Figure 7-198: Spurious Emissions (769MHz – 775MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 10:45:18


Figure 7-199: Spurious Emissions (775MHz – 799MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:03:42


Figure 7-200: Spurious Emissions (799MHz – 805MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:30:23


Figure 7-201: Spurious Emissions (805MHz – 1559MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:43:44


Figure 7-202: Spurious Emissions (1559MHz – 1610MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:01:53


Figure 7-203: Spurious Emissions (1610MHz – 3GHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:18:42


Figure 7-204: Spurious Emissions (3GHz – 7.7GHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:39:07


Figure 7-205: Spurious Emissions (Lower band edge)
- 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:51:15


Figure 7-206: Spurious Emissions (Upper band edge)
- 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:23:28


Figure 7-207: Spurious Emissions (9kHz – 150kHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:36:22


Figure 7-208: Spurious Emissions (150kHz – 30MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:44:37


Figure 7-209: Spurious Emissions (30MHz - 758MHz) - 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 10:06:35


Figure 7-210: Spurious Emissions (769MHz – 775MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 10:44:20


Figure 7-211: Spurious Emissions (775MHz – 799MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:06:54


Figure 7-212: Spurious Emissions (799MHz – 805MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:29:18


Figure 7-213: Spurious Emissions (805MHz – 1559MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:44:46


Figure 7-214: Spurious Emissions (1559MHz – 1610MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:00:55


Figure 7-215: Spurious Emissions (1610MHz – 3GHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:19:59


Figure 7-216: Spurious Emissions (3GHz – 7.7GHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 14:37:31


Figure 7-217: Spurious Emissions (Lower band edge)
- 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:52:16


Figure 7-218: Spurious Emissions (Upper band edge)
- 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:24:04


Figure 7-219: Spurious Emissions (9kHz – 150kHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:37:03


Figure 7-220: Spurious Emissions (150kHz – 30MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:41:59


Figure 7-221: Spurious Emissions (30MHz - 758MHz) - 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 10:08:30


Figure 7-222: Spurious Emissions (769MHz – 775MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 10:43:14


Figure 7-223: Spurious Emissions (775MHz – 799MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:08:00


Figure 7-224: Spurious Emissions (799MHz – 805MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:28:13


Figure 7-225: Spurious Emissions (805MHz – 1559MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:45:55


Figure 7-226: Spurious Emissions (1559MHz – 1610MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:59:48

Figure 7-227: Spurious Emissions (1610MHz – 3GHz) – 64QAM (763.0 MHz) (10MHz Channel BW)




Date: 8.FEB.2011 14:21:11

Figure 7-228: Spurious Emissions (3GHz – 7.7GHz) – 64QAM (763.0 MHz) (10MHz Channel BW)




Config A TX1+TX2:



Date: 7.FEB.2011 15:07:53


Figure 7-229: Spurious Emissions (Lower band edge)
- QPSK (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 15:16:07


Figure 7-230: Spurious Emissions (Upper band edge)
- QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:12:06


Figure 7-231: Spurious Emissions (9kHz – 150kHz) – QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:40:04


Figure 7-232: Spurious Emissions (150kHz – 30MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:36:53


Figure 7-233: Spurious Emissions (30MHz – 758MHz) – QPSK (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 15:21:12


Figure 7-234: Spurious Emissions (769MHz – 775MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 10:25:59


Figure 7-235: Spurious Emissions (775MHz – 799MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:13:12


Figure 7-236: Spurious Emissions (799MHz – 805MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:23:54


Figure 7-237: Spurious Emissions (805MHz – 1559MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:49:14


Figure 7-238: Spurious Emissions (1559MHz – 1610MHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:56:50


Figure 7-239: Spurious Emissions (1610MHz – 3GHz)
– QPSK (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:24:07


Figure 7-240: Spurious Emissions (3GHz – 7.7GHz)
– QPSK (763.0 MHz) (10MHz Channel BW)





Date: 7.FEB.2011 15:10:55


Figure 7-241: Spurious Emissions (Lower band edge)
- 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 15:15:03


Figure 7-242: Spurious Emissions (Upper band edge)
- 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:12:56


Figure 7-243: Spurious Emissions (9kHz – 150kHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:40:47


Figure 7-244: Spurious Emissions (150kHz – 30MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:35:30


Figure 7-245: Spurious Emissions (30MHz – 758MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 15:24:34


Figure 7-246: Spurious Emissions (769MHz – 775MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 10:29:25


Figure 7-247: Spurious Emissions (775MHz – 799MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:15:00


Figure 7-248: Spurious Emissions (799MHz – 805MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:22:39


Figure 7-249: Spurious Emissions (805MHz – 1559MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:50:09


Figure 7-250: Spurious Emissions (1559MHz – 1610MHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:55:49


Figure 7-251: Spurious Emissions (1610MHz – 3GHz) – 16QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:25:41


Figure 7-252: Spurious Emissions (3GHz – 7.7GHz) – 16QAM (763.0 MHz) (10MHz Channel BW)





Date: 7.FEB.2011 15:10:04


Figure 7-253: Spurious Emissions (Lower band edge)
- 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 15:14:18


Figure 7-254: Spurious Emissions (Upper band edge)
- 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 07:13:59


Figure 7-255: Spurious Emissions (9kHz – 150kHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 07:41:25


Figure 7-256: Spurious Emissions (150kHz – 30MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 09:33:51


Figure 7-257: Spurious Emissions (30MHz – 758MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 7.FEB.2011 15:27:20


Figure 7-258: Spurious Emissions (769MHz – 775MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 10:27:44


Figure 7-259: Spurious Emissions (775MHz – 799MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:17:22


Figure 7-260: Spurious Emissions (799MHz – 805MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:21:29


Figure 7-261: Spurious Emissions (805MHz – 1559MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 13:51:32


Figure 7-262: Spurious Emissions (1559MHz – 1610MHz) – 64QAM (763.0 MHz) (10MHz Channel BW)





Date: 8.FEB.2011 13:54:35

Figure 7-263: Spurious Emissions (1610MHz – 3GHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



Date: 8.FEB.2011 14:28:20

Figure 7-264: Spurious Emissions (3GHz – 7.7GHz) – 64QAM (763.0 MHz) (10MHz Channel BW)



7.2.5 Test No. 5: Field Strength of Spurious Radiation

Worst case detected emission levels are reported in the following spectral plots. The antenna factor and cable loss is according to the manufacturer's specification.




Figure 7-265: Photograph of the anechoic chamber with the EUT



Config A (QPSK, 64QAM, 16QAM):




Figure 7-266: Radiated Emission (30MHz – 1GHz) (5MHz Channel BW)




Figure 7-267: Radiated Emission (1GHz - 3GHz) (5MHz Channel BW)






Figure 7-268: Radiated Emission (3GHz – 8GHz) (5MHz Channel BW)




Figure 7-269: Radiated Emission (769MHz – 775MHz) (5MHz Channel BW)






Figure 7-270: Radiated Emission (799MHz – 805MHz) (5MHz Channel BW)



Config B (QPSK, 64QAM, 16QAM):




Figure 7-271: Radiated Emission (30MHz – 1GHz) (10MHz Channel BW)




Figure 7-272: Radiated Emission (1GHz – 8GHz) (10MHz Channel BW)






Figure 7-273: Radiated Emission (769MHz – 775MHz) (10MHz Channel BW)




Figure 7-274: Radiated Emission (799MHz – 805MHz) (10MHz Channel BW)