

RF Exposure Report

Report No.: SA181221C07

FCC ID: VBNAHFB-01

Test Model: AHFB

Received Date: Dec. 21, 2018

Test Date: Dec. 26, 2018 ~ Jan. 26, 2019

Aug. 01 ~ Aug. 12, 2019

Issued Date: Aug. 14, 2019

Applicant: Nokia Solutions and Networks

Address: 6000 Connection Drive, Irving, TX 75039

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA181221C07 Page No. 1 / 7 Report Format Version: 6.1.1



Table of Contents

Relea	se Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
	1 ,	5 5
3	Calculation Result of Maximum Tune up Power	6
4	Brief Summary of results	7



Release Control Record

Issue No.	Description	Date Issued
SA181221C07	Original release	Aug. 14, 2019



1 Certificate of Conformity

Product: AirScale Base Station RRH 1.9GHz

Brand: Nokia

Test Model: AHFB

Sample Status: Production Unit

Applicant: Nokia Solutions and Networks

Test Date: Dec. 26, 2018 ~ Jan. 26, 2019

Aug. 01 ~ Aug. 12, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Pettie Chen / Senior Specialist

Approved by: , **Date:** Aug. 14, 2019

Bruce Chen / Senior Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Average Time (minutes)				
(A)Limits For Occupational / Control Exposures								
300-1500			F/300	6				
1500-100,000	1500-100,000		5	6				
	(B)Limits For General Population / Uncontrolled Exposure							
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

For General Population

The antenna of this product, under normal use condition, is at least 278cm away from the body of the user. So, this device is classified as **fixed device**.

For Occupational Population

The antenna of this product, under normal use condition, is at least 124cm away from the body of the user. So, this device is classified as **fixed device**.

2.4 Antenna Gain

Antenna Spec.	Direction Panel antenna with 16.4dBi gain
Antenna Model	NA
Antenna Gain	16.4dBi



Calculation Result of Maximum Tune up Power

For General Population

Single Carrier: Module Model: WNCEL-30905

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)
WCDMA Band 25	1932.4~1992.6	59.55	278	0.928	1

Single Carrier: Module Model: WNCEL-30906

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WCDMA Band 25	1932.4~1992.6	59.47	278	0.911	1

Multi Carrier:

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WCDMA Band 25	1932.4~1992.6	55.62	278	0.376	1

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA+ LTE Band 25	1932.4~1992.6	59.84	278	0.992	1

For Occupational Population Single Carrier: Module Model: WNCEL-30905

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WCDMA Band 25	1932.4~1992.6	59.55	124	4.666	5

Single Carrier: Module Model: WNCEL-30906

Cirigio Carrior. Modale Modeli Tri CEE 00000							
Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)		
WCDMA Band 25	1932.4~1992.6	59.47	124	4.581	5		

Multi Carrier:

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 25	1932.4~1992.6	55.62	124	1.888	5

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WCDMA+ LTE Band 25	1932.4~1992.6	59.84	124	4.988	5



4 Brief Summary of results

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(cm)	
Configuration	Occupational	General Population
WCDMA only	124	278
WCDMA Band 25 / WCDMA+ LTE Band 25	124	278