


## LABEL MATERIAL:

1. MATERIAL: Flexcon ThermFilm Select 21940-2 mil gloss topcoat white polyester with permanent acrylic adhesive on 50# bleached Kraft liner (or philips approved equivalent).
2. LABEL MATERIAL TO BE UL RECOGNIZED UNDER UL969-UL FILE NO. PG JI2.MH257.MH25732, RLPJO-120.
3. PRINTING MUST BE IN BLACK COLOR.
4. DELIVERY: IN ROLLS ON A STD. 3" DIA. CORE.
5. PART MUST BE ROHS COMPLIANT PER DIRECTIVE 2002/95/EC.

**THIS PART MUST COMPLY WITH ALL APPLICABLE UL REQUIREMENTS OUTLINED IN DOCUMENT 4435 604 00001**

D	ECO1050190 – CHANGE ICC TO IC				08.01.12		10275 West Higgins Road Rosemont, Illinois 60018-5603 Form: 13HM1482
C	ECO1050018 – CHANGE MAX AMP RATING				7.10.12		
B	ECO1049860 – CHANGE MAX AMP RATING				06.27.12		
REV.	(ECR/ECO NO.) DESCRIPTION OF CHANGE				DATE		
UNLESS OTHERWISE SPECIFIED UNITS ARE IN:	TOLERANCES	ORIG. DRAWN BY:	ALEX CRUZ	DATE:	06.14.12	TITLE: PRODUCT LABEL STARSENSE HV OLC (LLC7315)	
	FRACTIONS:	REVISED BY:	B.CARDENAS	DATE:	08.01.12		
		APPROVED BY:	MING LI	DATE:	08.01.12		
MM	DECIMALS: X.X = ±0.3 X.XX = ±0.13	APPROVED BY:		DATE:		DRAWING NO.: 4435 290 30501	
SIZE LTR	ANGLES: ±1°	RESP. FACILITY FOR PRODT. DWG. MAINTENANCE ROSEMONT.			SCALE NTS	SHEET 1 OF 1	

This document and data disclosed herein or herewith is not to be reproduced, used or disclosed in whole or in part to anyone without the express written consent/permission of Philips Lighting Electronics N.A.