

RF EXPOSURE REPORT

MODEL NO.: SA970306L02 **MODEL NO.:** Kurve Adapter

ACCORDING: FCC Guidelines for Human Exposure

IEEE C95.1

APPLICANT: iFoundry Systems Singapore Pte Ltd

ADDRESS: 67 Ayer Rajah Crescent Unit 03-20/22 Singapore

139950

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang

244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBn	Pout (mW)	
Conducted Power	0.800	1.202
EIRP Power	-0.840	0.824

^{*}Note: The antenna is printed antenna with -1.64dBi gain.

Threshold for no SAR evaluation is 24.58mW Transmitter power is 0.824mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold