Test Report of FCC CFR 47 Part 15 Subpart C

On Behalf of

Hannspree Inc.

FCC ID:	VD2-HSG1255	
Product Description:	Tablet PC	
Model No.:	HSG1255	
Supplementary Model:	HSG1254	
Prepared for:	Hannspree Inc.	
	4F., No. 48, Wucyuan Rd., Wugu Indus	strial Zone, New Taipei City
	248,Taiwan	
Prepared by:	Bontek Compliance Testing Labo	ratory Ltd
	1/F, Block East H-3, OCT Eastern Ind.	Zone, Qiaocheng East
	Road, Nanshan, Shenzhen, China	
	Tel: 86-755-86337020	
	Fax: 86-755-86337028	
Report No.:	BCT12FR201E	
Issue Date:	July 23, 2012	
Test Date:	June20~ July 23, 2012	
Test by:	Reviewed E	Зу:
	Vincent jiang	kevin chi
	Vincent Jiang	Kevin Chi

TABLE OF CONTENTS

1.	GENERAL INFORMATION	
	1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
	1.2 RELATED SUBMITTAL(S) / GRANT (S) AND TEST METHODOLOGY	
_		
2.	SYSTEM TEST CONFIGURATION	
	2.1 EUT CONFIGURATION	
	2.3 GENERAL TEST PROCEDURES	5
	2.4 MEASUREMENT UNCERTAINTY	5
	2.5TEST EQUIPMENT LIST AND DETAILS	
3.	SUMMARY OF TEST RESULTS	8
	TEST OF AC POWER LINE CONDUCTED EMISSION	
	4.1 APPLICABLE STANDARD	
	4.2 TEST SETUP DIAGRAM	
	TEST OF MAXIMUM PEAK OUTPUT POWER	
Ͽ.	5.1 APPLICABLE STANDARD	
	5.2 EUT SETUP	18
	5.3 TEST EQUIPMENT LIST AND DETAILS	18
	5.4 TEST PROCEDURE	
_		
6.	TEST OF PEAK POWER SPECTRAL DENSITY	
	6.1 APPLICABLE STANDARD	
	6.3 TEST EQUIPMENT LIST AND DETAILS	2 <i>e</i>
	6.4 TEST PROCEDURE	
	6.5 TEST RESULT	
7.	TEST OF 6DB BANDWIDTH	
	7.1 APPLICABLE STANDARD	
	7.3 TEST EQUIPMENT LIST AND DETAILS	
	7.4 TEST PROCEDURE	34
	7.5 TEST RESULT	
8.	TEST OF CONDUCTED SPURIOUS EMISSION	
	8.1 APPLICABLE STANDARD	
	8.2 EUT SETUP	
	8.4 TEST PROCEDURE	
	8.5 TEST RESULT	42
9.	TEST OF RADIATED SPURIOUS EMISSION	46
	9.1 RADIATED SPURIOUS EMISSION	
	9.1.1 LIMITS	
	9.1.2 EUT SETUP	
	9.1.4 Test Result	48
	9.2 RESTRICTED BAND EDGES	
	TEST RESULT	
10). ANTENNA REQUIREMENT	
	10.1 STANDARD APPLICABLE	
	TU.Z ANTENNA CONNECTED CONSTRUCTION	00

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Hannspree Inc.

Address of applicant: 4F., No. 48, Wucyuan Rd., Wugu Industrial Zone, New Taipei City

248, Taiwan

Manufacturer: HuiKe Electronics(shenzhen) Co.,Ltd

Address of manufacturer: Building 1,2,3,Huike Industrial Park,Mingying Industrial Zone,

ShuiTian, ShiYan, Baoan, Shenzhen, China

General Description of E.U.T

Items	Description
EUT Description:	Tablet PC
Trade Name:	I-INC HANNspree
Model No.:	HSG1255
Supplementary Model:	HSG1254
	Supplementary models have same circuit and appearance, Just use different display screen.
Frequency Band:	IEEE 802.11b/g,
	IEEE 802.11n HT20
	(DTS Band) : 2.412 GHz ~ 2.4835 GHz (2.4 GHz ISM Band),
Channel Spacing:	IEEE 802.11b/g, 802.11n HT20: 5MHz
Number of Channels:	IEEE 802.11b/g, 802.11n HT20:11 Channels
Transmit Data Rate:	IEEE802.11b: 11, 5.5, 2, 1 Mbps
	IEEE802.11g : 54 , 48 , 36 , 24 ,18 , 12 , 9 , 6 Mbps
	IEEE802.11n HT20: 130, 117, 104, 78, 52, 39, 26, 13 Mbps
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)
	IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Type:	Built-in Antenna
Rated Voltage:	Intput: 5VDC 2.0A from AC/DC adapter
Adapter description:	Model: YHXH015-050200
	Input:100-240V~, 50/60Hz, ~0.4A
	Output: 5VDC 2.0A
	Model: DSA-12PFA-05 FEU 050200
	Input:100-240V~, 50/60Hz, ~0.5A
	Output: 5VDC 2.0A

Remark: * The test data gathered are from the production sample provided by the manufacturer.

1.2 Related Submittal(s) / Grant (s) and Test Methodology

The tests were performed based on the Electromagnetic Interference (EMI) tests performed on the EUT. Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 - 2003 Radiated testing was performed at an antenna to EUT distance 3 meters.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.207, 15.209 and 15.247 rules and the FCC publication KDB558074 of Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247).

1.3 Test Facility

All measurement required was performed at laboratory of Bontek Compliance Testing Laboratory Ltd at 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China.

The test facility is recognized, certified, or accredited by the following organizations:

FCC - Registration No.: 338263

BONTEK COMPLIANCE TESTING LABORATORY LTD. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March 03, 2011.

IC Registration No.: 7631A

The 3m alternate test site of BONTEK COMPLIANCE TESTING LABORATORY LTD. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on January 25, 2011.

CNAS - Registration No.: L3923

BONTEK COMPLIANCE TESTING LABORATORY LTD. to ISO/IEC 17025:25 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. The acceptance letter from the CNAS is maintained in our files: Registration: L3923,March 22,2012.

TUV - Registration No.: UA 50203122-0001

BONTEK COMPLIANCE TESTING LABORATORY LTD. An assessment of the laboratory was conducted according to the "Procedures and Conditions for EMC Test Laboratories" with reference to EN ISO/IEC 17025 by a TUV Rheinland auditor. Audit Report NO. 17010783-002.

Report No.: BCT12FR-201E Page 4 of 66 FCC ID: VD2-HSG1255

2. SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

2.3 General Test Procedures

Conducted Emissions: The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2003 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

Radiated Emissions: The EUT is a placed on as turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Power Line Conducted Emission	+/- 2.3 dB
Radiated Emission	+/- 3.4 dB

Uncertainty figures are valid to a confidence level of 95%.

Report No.: BCT12FR-201E Page 5 of 66 FCC ID: VD2-HSG1255

2.5Test Equipment List and Details

Test equipments list of Shenzhen Bontek Compliance Testing Laboratory Co., Ltd .

No.	Equipment	Manufacturer	Model No.	S/N	Calculator date	Calculator due date
1	EMI Test Receiver	R&S	ESCI	100687	2012-4-6	2013-4-5
2	EMI Test Receiver	R&S	ESPI	100097	2011-7-25	2012-7-24
3	Amplifier	HP	8447D	1937A02492	2012-4-6	2013-4-5
4	Horn Antenna	R/S	CH14-H052	1091698	2012-4-6	2013-4-5
5	Horn Antenna	SCHWARZBECK	BBHA9120A	0499	2011-11-28	2012-11-27
6	Single Power Conductor Module	FCC	FCC-LISN-5- 50-1-01- CISPR25	07101	2012-4-6	2013-4-5
7	Single Power Conductor Module	FCC	FCC-LISN-5- 50-1-01- CISPR25	07102	2012-4-6	2013-4-5
8	Power Clamp	SCHWARZBECK	MDS-21	3812	2012-4-6	2013-4-5
9	Positioning Controller	C&C	CC-C-1F	MF7802113	N/A	N/A
10	`Electrostatic Discharge Simulator	TESEQ	NSG437	125	2011-4-11	2012-4-10
11	Fast Transient Burst Generator	SCHAFFNER	MODULA615 0	34572	2012-4-6	2013-4-5
12	Fast Transient Noise Simulator	Noiseken	FNS-105AX	10501	2011-6-16	2012-6-15
14	Color TV Pattern Genenator	PHILIPS	PM5418	TM209947	N/A	N/A
15	Power Frequency Magnetic Field Generator	EVERFINE	EMS61000- 8K	608002	2012-4-6	2013-4-5
16	Capacitive Coupling Clamp	TESEQ	CDN8014	25096	2012-4-6	2013-4-5
17	High Field Biconical Antenna	ELECTRO- METRICS	EM-6913	166	2011-11-28	2012-11-27
18	Log Periodic Antenna	ELECTRO- METRICS	EM-6950	811	2011-11-28	2012-11-27
19	Remote Active Vertical Antenna	ELECTRO- METRICS	EM-6892	304	2011-11-28	2012-11-27
20	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	N/A	N/A
21	Teo Line Single Phase Module	SCHWARZBECK	NSLK8128	8128247	2011-10-24	2012-10-23
22	Triple-Loop Antenna	EVERFINE	LLA-2	711002	2012-4-6	2013-4-5
23	Electric bridge	Jhai	JK2812C	803024	N/A	N/A
24	RF POWER AMPLIFIER	FRANKONIA	FLL-75	1020A1109	2012-4-6	2013-4-5
25	CDN	FRANKONIA	CDN M2+M3	A3027019	2012-4-6	2013-4-5
26	6DB Attenuator	FRANKONIA	N/A	1001698	2012-4-6	2013-4-5
27	EM Injection clamp	FCC	F-203I-23mm	091536	2012-4-6	2013-4-5

28	9kHz-2.4GHz signal generator 2024	MARCONI	10S/6625-99- 457-8730	112260/042	2012-4-6	2013-4-5
29	10dB attenuator	ELECTRO- METRICS	EM-7600	836	2012-4-6	2013-4-5
30	ISN	TESEQ	ISN-T800	30301	2011-6-23	2012-6-22
31	10KV surge generator	SANKI	SKS-0510M	048110003E 321	2011-11-14	2012-11-13
32	HRMONICS&FLICK RE ANALYSER	VOLTECH	PM6000	200006700433	2011-6-27	2012-6-26
33	Spectrum Analyzer	R&S	FSP	100397	2011-11-2	2012-11-1
34	Broadband preamplifier	SCH WARZBECK	BBV9718	9718-182	2012-4-6	2013-4-5
35	Temperature & Humidity Chamber	TOPSTAT	TOS-831A	3438A05208	2012-4-6	2013-4-5

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207	AC Power Line Conducted Emission	Pass
FCC §15.247(b)	Maximum Peak Output Power	Pass
FCC §15.247(e)	Power Spectral Density	Pass
FCC §15.247(a)	6dB Bandwidth	Pass
FCC §15.247 (d)	Conducted Spurious Emission	Pass
FCC §15.205 and §15.209 &	Radiated Spurious Emission	Pass
FCC §15.203/15.247(b)/(c)	Antenna Requirement	Pass

4. TEST OF AC POWER LINE CONDUCTED EMISSION


4.1 Applicable Standard

Refer to FCC §15.207.

For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency Range (MHz)	Limits (dBuV)			
Trequency Range (MHz)	Quasi-Peak	Average		
0.150~0.500	66∼56	56∼46		
0.500~5.000	56	46		
5.000~30.00	60	50		

4.2 Test Setup Diagram



Remark: The EUT was connected to a 120VAC/ 60Hz power source.

4.3 Test Result

Temperature (°C) : 23~25	EUT: Tablet PC
Humidity (%RH): 45~58	M/N: HSG1255
Barometric Pressure (mbar): 950~1000	Operation Condition: HD Playing/Connect to PC/SD Card Playing

Report No.: BCT12FR-201E Page 9 of 66 FCC ID: VD2-HSG1255

EUT: Tablet PC
M/N: HSG1255
Operating Condition: HD Playing
Test Site: Shielded Room


Operator: Yang

Test Specification: AC 120V/60Hz for adapter (Model: YHXH015-050200)

Comment: L Line

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR-201E05_fin"

7/1	7/12/2012 9:31PM								
	Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE	
	0.190500	46.70	10.9	64	17.3	QP	L1	GND	
	3.106500	33.10	10.3	56	22.9	QP	L1	GND	
	3.174000	32.90	10.3	56	23.1	QP	L1	GND	
	3.264000	33.90	10.3	56	22.1	QP	L1	GND	
	3.394500	34.50	10.3	56	21.5	QP	L1	GND	
	3.489000	33.50	10.3	56	22.5	QP	L1	GND	

MEASUREMENT RESULT: "12FR-201E05_fin2"

7/12/2012 9: Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.442500	27.10	10.3	47	19.9	AV	L1	GND
1.302000	23.80	10.2	46	22.2	AV	L1	GND
1.491000	23.90	10.2	46	22.1	AV	L1	GND
1.873500	22.90	10.2	46	23.1	AV	L1	GND
3.142500	23.90	10.3	46	22.1	AV	L1	GND
3.331500	24.20	10.3	46	21.8	AV	L1	GND


EUT: Tablet PC HSG1255 M/N: **HD** Playing **Operating Condition:** Test Site: Shielded Room

Operator: Yang

Test Specification: AC 120V/60Hz for adapter (Model: YHXH015-050200)

Comment: N Line

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR-201E06_fin"

7/12/2012 9:34PM								
Freque	ncy I MHz	dBµV		.mit Ma lBµV	rgin 1 dB	Detector	Line	PE
0.190	500 4	16.80	10.9	64	17.2	QP	N	GND
0.442	500 3	35.80	10.3	57	21.2 (QP	N	GND
2.094	000	32.80	10.2	56	23.2 (QP	N	GND
3.138	000 3	33.80	10.3	56	22.2 (QP	N	GND
3.273	000 3	30.80	10.3	56	25.2 (QP	N	GND
3.457	500 3	34.00	10.3	56	22.0 (QP .	N	GND

MEASUREMENT RESULT: "12FR-201E06_fin2"

7/12/2012 9: Frequency MHz	34PM Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	34.30	10.9	54	19.7	AV	N	GND
0.442500	28.00	10.3	47	19.0	AV	N	GND
0.505500	26.60	10.2	46	19.4	AV	N	GND
1.045500	24.50	10.3	46	21.5	AV	N	GND
1.396500	24.40	10.2	46	21.6	AV	N	GND
3.205500	24.70	10.3	46	21.3	AV	N	GND

EUT: Tablet PC
M/N: HSG1255
Operating Condition: Connect to PC
Test Site: Shielded Room


Operator: Yang

Test Specification: AC 120V/60Hz for adapter (Model: YHXH015-050200)

Comment: L Line

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR-201E01 fin"

7/12/2012	9:19PM						
Frequen M	cy Leve Hz dBµ'			Margin dB	Detector	Line	PE
0.1905	00 46.9	0 10.9	64	17.1	QP	L1	GND
2.3820	00 31.7	0 10.2	56	24.3	QP	L1	GND
3.1425	00 33.4	0 10.3	56	22.6	QP	L1	GND
3.2055	00 34.2	0 10.3	56	21.8	QP	L1	GND
3.3000	00 34.0	0 10.3	56	22.0	QP	L1	GND
3.4260	00 33.8	0 10.3	56	22.2	QP	L1	GND

MEASUREMENT RESULT: "12FR-201E01_fin2"

7.	/12/2012 9:1 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
	0.190500	33.90	10.9	54	20.1	ΔV	L1	GND
	0.442500	26.70	10.3	47		AV	L1	GND
	0.699000	24.20	10.2	46	21.8	AV	L1	GND
	2.854500	23.40	10.2	46	22.6	AV	L1	GND
	3.205500	24.20	10.3	46	21.8	AV	L1	GND
	3.300000	24.20	10.3	46	21.8	AV	L1	GND


EUT: Tablet PC HSG1255 M/N: **Operating Condition:** Connect to PC Test Site: Shielded Room

Operator: Yang

Test Specification: AC 120V/60Hz for adapter (Model: YHXH015-050200)

Comment: N Line

SCAN TABLE: "Voltage (9K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR-201E02_fin"

7,	/12/2012 9:2	23PM						
	Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
	0.190500	47.00	10.9	64	17.0	QP	N	GND
	0.253500	40.40	10.7	62	21.2	QP	N	GND
	0.442500	35.80	10.3	57	21.2	QP	N	GND
	3.016500	32.20	10.2	56	23.8	QP	N	GND
	3.106500	33.80	10.3	56	22.2	QP	N	GND
	3.367500	31.10	10.3	56	24.9	QP	N	GND

MEASUREMENT RESULT: "12FR-201E02 fin2"

7/12/2012 9:2 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	34.70	10.9	54	19.3	AV	N	GND
0.442500	28.00	10.3	47	19.0	AV	N	GND
0.505500	26.60	10.2	46	19.4	AV	N	GND
0.699000	25.60	10.2	46	20.4	AV	N	GND
1.014000	24.00	10.3	46	22.0	AV	N	GND
3.363000	24.50	10.3	46	21.5	AV	N	GND

EUT: Tablet PC M/N: HSG1255


Operating Condition: SD Card Playing Test Site: Shielded Room

Operator: Yang

Test Specification: AC 120V/60Hz for adapter (Model: YHXH015-050200)

Comment: L Line

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR-201E04_fin"

7/12/2012 9	:29PM						
Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	46.70	10.9	64	17.3	QP	L1	GND
1.968000	33.10	10.2	56	22.9	QP	L1	GND
3.268500	34.20	10.3	56	21.8	QP	L1	GND
3.336000	31.30	10.3	56	24.7	QP	L1	GND
3.426000	33.80	10.3	56	22.2	QP	L1	GND
3.552000	33.30	10.3	56	22.7	QP	L1	GND

MEASUREMENT RESULT: "12FR-201E04_fin2"

7/12/2012	9:29PM						
Frequen M	cy Leve: Hz dBµ'		Limit dBµV	Margin dB	Detector	Line	PE
0.1905	00 33.8	0 10.9	54	20.2	AV	L1	GND
0.4425	00 26.9	0 10.3	47	20.1	AV	L1	GND
0.5100	00 25.1	0 10.2	46	20.9	AV	L1	GND
1.5540	00 24.1	0 10.2	46	21.9	AV	L1	GND
1.9995	00 23.1	0 10.2	46	22.9	AV	L1	GND
3.2685	00 24.6	0 10.3	46	21.4	AV	L1	GND

EUT: Tablet PC M/N: HSG1255


Operating Condition: SD Card Playing Test Site: Shielded Room

Operator: Yang

Test Specification: AC 120V/60Hz for adapter (Model: YHXH015-050200)

N Line Comment:

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR-201E03_fin"

7/12/2012 9:2 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	46.90	10.9	64	17.1	QP	N	GND
0.442500	35.70	10.3	57	21.3	QP	N	GND
3.075000	33.40	10.3	56	22.6	QP	N	GND
3.138000	33.40	10.3	56	22.6	QP	N	GND
3.205500	34.50	10.3	56	21.5	QP	N	GND
3.426000	33.60	10.3	56	22.4	QP	N	GND

MEASUREMENT RESULT: "12FR-201E03_fin2"

7/12/2012 Frequen	ncy Le	vel Transo BµV di		Margin dB	Detector	Line	PE
0.3795 0.4470 0.5100 0.6990 2.2245 3.2730	000 27 000 26 000 25 500 21	.50 10.4 .40 10.3 .30 10.4 .60 10.4 .60 10.3	3 47 2 46 2 46 2 46	20.8 19.5 19.7 20.4 24.4 23.4		N N N N N	GND GND GND GND GND GND

EUT: Tablet PC M/N: HSG1255

Operating Condition: SD Card Playing Test Site: Shielded Room


Operator: Yang

Test Specification: AC 120V/60Hz for adapter

(Model: DSA-12PFA-05 FEU 050200)

Comment: L Line

SCAN TABLE: "Voltage (9K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR201E07 fin"

7/12/2012	9:15PM						
Frequenc MH	-	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.45150	0 33.30	10.3	57	23.5	QP	L1	GND
4.37100	0 25.00	10.3	56	31.0	QP	L1	GND
6.40950	0 29.60	10.4	60	30.4	QP	L1	GND
6.66150	0 27.90	10.4	60	32.1	QP	L1	GND
8.43900	0 20.30	10.5	60	39.7	QP	L1	GND
9.67650	0 28.70	10.5	60	31.3	QP	L1	GND

MEASUREMENT RESULT: "12FR-0922E07_fin2"

7/12/2012 9:1	5PM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dΒμV	dB	dΒμV	dB			
28.027500	33.50	11.0	50	16.5	AV	L1	GND
28.779000	35.80	11.1	50	14.2	AV	L1	GND
29.283000	36.30	11.1	50	13.7	AV	L1	GND
29.535000	36.00	11.1	50	14.0	AV	L1	GND

EUT: Tablet PC M/N: HSG1255

Operating Condition: SD Card Playing Test Site: Shielded Room

Operator: Yang


Test Specification: AC 120V/60Hz for adapter

(Model: DSA-12PFA-05 FEU 050200)

Comment: N Line

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "12FR201E08 fin"

7/12/2012 9	:20PM						
Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.456000	34.10	10.3	57	22.7	QP	N	GND
4.398000	27.60	10.3	56	28.4	QP	N	GND
5.631000	19.20	10.4	60	40.8	QP	N	GND
8.709000	28.50	10.5	60	31.5	QP	N	GND
14.397000	14.60	10.5	60	45.4	QP	N	GND
14.856000	27.70	10.5	60	32.3	QP	N	GND

MEASUREMENT RESULT: "12FR-0922E08_fin2"


,	7/12/2012 9:2	0 PM						
	Frequency MHz	Level dBµV		Limit dBµV	Margin dB	Detector	Line	PE
	28.779000	35.40	11.1	50	14.6	AV	N	GND
	29.031000	35.70	11.1	50	14.3	AV	N	GND
	29.283000	35.60	11.1	50	14.4	AV	N	GND
	29.535000	36.30	11.1	50	13.7	AV	N	GND

5. Test of Maximum Peak Output Power

5.1 Applicable Standard

Refer to FCC §15.247 (b)

5.2 EUT Setup



5.3 Test Equipment List and Details

See section 2.5.

5.4 Test Procedure

Connect the EUT to spectrum analyzer, set the center frequency of the spectrum analyzer to the channel center frequency. Set the RBW to 1MHz and VBW to 3MHz.

Measurement of Digital Transmission Systems Operating under Section 15.247

5.5 Test Result

Temperature (°C) : 22~23	EUT: Tablet PC
Humidity (%RH): 50~54	M/N: HSG1255
Barometric Pressure (mbar): 950~1000	Operation Condition: Tx Mode

Report No.: BCT12FR-201E Page 18 of 66 FCC ID: VD2-HSG1255

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	Peak Power Chain C (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2412	14.77	30	PASS
Middle	2437	14.50	30	PASS
High	2462	14.47	30	PASS

NOTE: 1. At finial test to get the worst-case emission at 11Mbps.

IEEE 802.11g mode

Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2412	14.01	30	PASS
Middle	2437	13.95	30	PASS
High	2462	13.55	30	PASS


NOTE: 1. At finial test to get the worst-case emission at 6Mbps.

IEEE 802.11n HT20 mode


Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2412	13.84	30	PASS
Middle	2437	13.85	30	PASS
High	2462	13.82	30	PASS

NOTE: 1. At finial test to get the worst-case emission at 13Mbps.


MAXIMUM PEAK OUTPUT POWER (802.11b MODE CH Low)




MAXIMUM PEAK OUTPUT POWER (802.11b MODE CH Mid)




MAXIMUM PEAK OUTPUT POWER (802.11b MODE CH High)




MAXIMUM PEAK OUTPUT POWER (802.11g MODE CH Low)




MAXIMUM PEAK OUTPUT POWER (802.11g MODE CH Mid)




MAXIMUM PEAK OUTPUT POWER (802.11g MODE CH High)




MAXIMUM PEAK OUTPUT POWER (802.11n HT20 MODE CH Low)



MAXIMUM PEAK OUTPUT POWER (802.11n HT20 MODE CH Mid)



MAXIMUM PEAK OUTPUT POWER (802.11n HT20 MODE CH High)




6. Test of Peak Power Spectral Density

6.1 Applicable Standard

Refer to FCC §15.247 (e).

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.2 EUT Setup



Spectrum Analyzer

6.3 Test Equipment List and Details

See section 2.5.

6.4 Test Procedure

The transmitter output was connected to the spectrum analyzer, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW=3KHz and VBW ≧ RBW, set sweep time=span / 3KHz.

The power spectral density was measured and recorded. The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

NOTE: Total peak power calculation formula:

10 log (10[^] (Chain A Power / 10) + 10[^] (Chain C Power / 10)).

6.5 Test Result

Temperature (°C) : 22~23	EUT: Tablet PC
Humidity (%RH): 50~54	M/N: HSG1255
Barometric Pressure (mbar): 950~1000	Operation Condition: Tx Mode

Report No.: BCT12FR-201E Page 26 of 66 FCC ID: VD2-HSG1255

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
Low	2412	-11.18	8	PASS
Middle	2437	-11.26	8	PASS
High	2462	-11.80	8	PASS

NOTE: 1. At finial test to get the worst-case emission at 11Mbps.

IEEE 802.11g mode

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
Low	2412	-12.33	8	PASS
Middle	2437	-14.16	8	PASS
High	2462	-13.56	8	PASS


NOTE: 1. At finial test to get the worst-case emission at 6Mbps.

IEEE 802.11n HT20 mode


Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz (dBm)	Maximum Limit (dBm)	Pass / Fail
Low	2412	-14.46	8	PASS
Middle	2437	-15.88	8	PASS
High	2462	-16.61	8	PASS

NOTE: 1. At finial test to get the worst-case emission at 13Mbps.


POWER SPECTRAL DENSITY (802.11b MODE CH Low)




POWER SPECTRAL DENSITY (802.11b MODE CH Mid)




POWER SPECTRAL DENSITY (802.11b MODE CH High)




POWER SPECTRAL DENSITY (802.11g MODE CH Low)




POWER SPECTRAL DENSITY (802.11g MODE CH Mid)




POWER SPECTRAL DENSITY (802.11g MODE CH High)




POWER SPECTRAL DENSITY (802.11n HT20 MODE CH Low)



POWER SPECTRAL DENSITY (802.11n HT20 MODE CH Mid)



POWER SPECTRAL DENSITY (802.11n HT20 MODE CH High)




7. Test of 6dB Bandwidth

7.1 Applicable Standard

Refer to FCC §15.247 (a) (2).

The minimum 6 dB bandwidth shall be at least 500 kHz.

7.2 EUT Setup



7.3 Test Equipment List and Details

See section 2.5.

7.4 Test Procedure

The transmitter output was connected to a spectrum analyzer. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

7.5 Test Result

Temperature ($^{\circ}$ C) : 22~23	EUT: Tablet PC
Humidity (%RH): 50~54	M/N: HSG1255
Barometric Pressure (mbar): 950~1000	Operation Condition: Tx Mode

Report No.: BCT12FR-201E Page 34 of 66 FCC ID: VD2-HSG1255

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	7500	500	PASS
Middle	2437	7400	500	PASS
High	2462	7225	500	PASS

NOTE: 1. At finial test to get the worst-case emission at 11Mbps.

IEEE 802.11g mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	13700	500	PASS
Middle	2437	13700	500	PASS
High	2462	13300	500	PASS


NOTE: 1. At finial test to get the worst-case emission at 6Mbps.

IEEE 802.11n HT20 mode


Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	14200	500	PASS
Middle	2437	14100	500	PASS
High	2462	14000	500	PASS

NOTE: 1. At finial test to get the worst-case emission at 13Mbps.


6dB BANDWIDTH (802.11b MODE CH Low)




6dB BANDWIDTH (802.11b MODE CH Mid)




6dB BANDWIDTH (802.11b MODE CH High)




6dB BANDWIDTH (802.11g MODE CH Low)




6dB BANDWIDTH (802.11g MODE CH Mid)




6dB BANDWIDTH (802.11g MODE CH High)




6dB BANDWIDTH (802.11n HT20 MODE CH Low)



6dB BANDWIDTH (802.11n HT20 MODE CH Mid)



6dB BANDWIDTH (802.11n HT20 MODE CH High)




8. Test of Conducted Spurious Emission

8.1 Applicable Standard

Refer to FCC §15.247 (d).

Output power was measured based on the use of RMS averaging over a time interval, therefore the required attenuation is 30 dB.

8.2 EUT Setup



8.3 Test Equipment List and Details

See section 2.5.

8.4 Test Procedure

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

8.5 Test Result

Temperature (°C) : 22~23	EUT: Tablet PC
Humidity (%RH): 50~54	M/N: HSG1255
Barometric Pressure (mbar): 950~1000	Operation Condition: TX Mode

Report No.: BCT12FR-201E Page 42 of 66 FCC ID: VD2-HSG1255

IEEE 802.11b mode

CH Low

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2412.6535	97.49	109.19	N/A	N/A	
1197.014	40.58	52.28	89.19	-36.91	PASS
4910.2404	42.91	54.61	89.19	-34.58	PASS
6979.038	46.45	58.15	89.19	-31.04	PASS

CH Mid

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2437.1524	98.78	110.48	N/A	N/A	
1462.2444	41.28	52.98	90.48	-37.50	PASS
4857.1943	44.06	55.76	90.48	-34.72	PASS
6819.8998	45.76	57.46	90.48	-33.02	PASS

CH High

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2462.5352	97.74	109.44	N/A	N/A	
1303.1062	40.93	52.63	89.44	-36.81	PASS
5493.7474	44.02	55.72	89.44	-33.72	PASS
6766.8537	45.39	57.09	89.44	-32.35	PASS

IEEE 802.11g mode

CH Low

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2412.6352	93.04	104.74	N/A	N/A	
1409.7984	40.47	52.17	84.74	-32.57	PASS
5865.0701	44.22	55.92	84.74	-28.82	PASS
6713.8076	45.37	57.07	84.74	-27.67	PASS

CH Mid

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2436.9525	93.81	105.51	N/A	N/A	
1674.4288	41.44	53.14	85.51	-32.37	PASS
5546.7935	43.12	54.82	85.51	-30.69	PASS
6766.8537	45.53	57.23	85.51	-28.28	PASS

CH High

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2461.5352	92.89	104.59	N/A	N/A	
1780.521	41.29	52.99	84.59	-31.60	PASS
6501.6232	45.57	57.27	84.59	-27.32	PASS
6979.038	45.45	57.15	84.59	-27.44	PASS

IEEE 802.11n HT20 mode

CH Low

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2411.8565	89.64	101.34	N/A	N/A	
1462.2444	42.12	53.82	81.34	-27.52	PASS
5440.7014	43.81	55.51	81.34	-25.83	PASS
6925.9919	46.22	57.92	81.34	-23.42	PASS

CH Mid

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2437.5246	89.92	101.62	N/A	N/A	
1674.4288	41.33	53.03	81.62	-28.59	PASS
5546.7935	42.93	54.63	81.62	-26.99	PASS
6713.8076	45.86	57.56	81.62	-24.06	PASS

CH High

Frequency (MHz)	Reading (dBµV)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Pass/Fail
2462.5385	89.32	101.02	N/A	N/A	
1886.6132	40.59	52.29	81.02	-28.73	PASS
5546.7935	43.14	54.84	81.02	-26.18	PASS
6925.9919	46.11	57.81	81.02	-23.21	PASS

9. Test of Radiated Spurious Emission

9.1 Radiated Spurious Emission

9.1.1 Limits

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 -1710	10.6 -12.7
6.26775 - 6.26825	108 -121.94	1718.8 - 1722.2	13.25 -13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 – 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 -16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 -335.4	3600 - 4400	(²)
13.36 - 13.41			

15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Report No.: BCT12FR-201E Page 46 of 66 FCC ID: VD2-HSG1255

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88 88 - 216	100 ** 150 **	3
216 - 960 Above 960	200 ** 500	3 3

^{**} Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz, However, operation within these frequency bands is permitted under other sections of this Part, e-g, Sections 15.231 and 15.241.

15.209 (b) In the emission table above, the tighter limit applies at the band edges.

9.1.2 EUT Setup




Figure 1: Frequencies measured below 1 GHz configuration




Figure 2: Frequencies measured above 1 GHz configuration

Report No.: BCT12FR-201E Page 47 of 66 FCC ID: VD2-HSG1255

9.1.3 Test Procedure

- a). The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b). White measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. White measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
- c). The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d). For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e). The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f). If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.

NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

9.1.4 Test Result

Temperature (°C): 22~23	EUT: Tablet PC
Humidity (%RH): 50~54	M/N: HSG1255
Barometric Pressure (mbar): 950~1000	Operation Condition: ON & TX Mode

Note: In this testing, the EUT was respectively tested in three different orientations. That is:

- (1) EUT was lie vertically, and then its Antenna oriented upward
- (2) EUT was lie vertically, and then its Antenna oriented downward
- (3) EUT was lie flatwise, and then its Antenna oriented to the receiving antenna

The worst test data see following pages When the EUT was lie flatwise, and its Antenna oriented to the receiving antenna, the worst test data was got as following table.

Report No.: BCT12FR-201E Page 48 of 66 FCC ID: VD2-HSG1255

WORST-CASE RADIATED EMISSION BELOW 1 GHz

Normal operating Mode:

Horizontal

Frequency	Meter Reading	Antenna Factor	Cable Loss	Emission Levels	Limits	Margin	Detector Mode
(MHz)	(dBµV)	(dB/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	PK/QP
84.32	26.40	7.97	1.18	36.56	40.00	-3.44	QP
160.01	16.50	12.60	1.59	30.69	43.50	-12.81	QP
402.48	14.50	14.44	2.72	36.66	46.00	-9.34	QP
652.74	14.50	18.00	3.05	35.55	46.00	-10.45	QP
726.46	9.60	20.84	3.84	34.28	46.00	-11.72	QP
823.46	10.30	21.80	4.14	36.24	46.00	-9.76	QP
N/A							

Vertical

Frequency	Meter Reading	Antenna Factor	Cable Loss	Emission Levels	Limits	Margin	Detector Mode
(MHz)	(dBµV)	(dB/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	PK/QP
142.52	21.40	7.89	1.01	30.30	40.00	-9.70	QP
191.02	16.10	12.60	1.59	30.29	43.50	-13.21	QP
216.24	25.70	12.20	2.02	39.92	46.00	-6.08	QP
239.52	22.80	14.44	2.72	39.96	46.00	-6.04	QP
503.36	16.50	18.00	3.05	37.55	46.00	-8.45	QP
749.74	13.20	21.80	4.14	39.14	46.00	-6.86	QP
N/A							

REMARK: Emission level (dB μ V/m) =Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dB μ V).

WORST-CASE RADIATED EMISSION BELOW 30 MHz

Frequency	Meter Reading	Antenna Factor	Cable Loss	Emission Levels	Limits	Margin	Detector Mode
(MHz)	(dBµV)	(dB/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	PK/QP
0.510	19.10	7.89	1.02	28.01	67.0	-38.99	QP
15.40	19.50	8.75	1.21	29.46	49.5	-20.04	QP
19.30	16.20	8.73	1.05	25.98	49.5	-23.52	QP
23.20	21.20	7.33	1.68	30.21	49.5	-19.29	QP

TRANSMITTER RADIATED EMISSION ABOVE 1 GHz

IEEE 802.11b TX (CH Low)

Horizontal

TX / IEEE	802.11b m	ode / CH	Low	Me	asurem	ent Distanc	e at 3m Hor	izontal pol	arity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4824.15	51.24	32.81	3.71	41.34	0.69	47.12	74.00	-26.88	Р
4824.15	39.25	32.81	3.71	41.34	0.69	35.13	54.00	-18.87	Α
7236.35	49.85	38.83	4.93	41.42	1.44	53.62	74.00	-20.38	Р
7236.35	37.49	38.83	4.93	41.42	1.44	41.26	54.00	-12.74	Α
9645.85	48.75	38.75	5.74	38.43	0.61	55.42	74.00	-18.58	Р
9645.85	37.69	38.75	5.74	38.43	0.61	44.36	54.00	-9.64	Α
N/A									Р
N/A									Α

Vertical

TX / IEEE	802.11b m	ode / CH	Low	M	easuren	nent Distand	ce at 3m Ve	ertical pol	arity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4823.85	53.62	32.81	3.70	41.34	0.69	49.49	74.00	-24.51	Р
4823.85	42.00	32.81	3.70	41.34	0.69	37.87	54.00	-16.13	Α
7236.18	51.42	38.83	4.93	41.42	1.44	55.19	74.00	-18.81	Р
7236.18	39.85	38.83	4.93	41.42	1.44	43.62	54.00	-10.38	Α
9647.94	50.24	38.75	5.74	38.43	0.61	56.92	74.00	-17.08	Р
9647.94	39.68	38.75	5.74	38.43	0.61	46.36	54.00	-7.64	Α
N/A									Р
N/A									Α

REMARK:

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3. The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

Report No.: BCT12FR-201E Page 50 of 66 FCC ID: VD2-HSG1255

IEEE 802.11b TX (CH Middle)

Horizontal

				Mea	asureme	ent Distance	at 3m H	orizontal po	larity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV /m)	(dB)	(P/Q/A)
4876.53	51.28	32.93	3.73	41.41	0.71	47.24	74.00	-26.76	Р
4876.53	41.96	32.93	3.73	41.41	0.71	37.92	54.00	-16.08	Α
7309.41	50.24	38.93	4.96	41.32	1.59	54.40	74.00	-19.60	Р
7309.41	39.42	38.93	4.96	41.32	1.59	43.58	54.00	-10.42	Α
9747.83	49.85	38.85	5.75	38.24	0.55	56.76	74.00	-17.24	Р
9747.83	38.65	38.85	5.75	38.24	0.55	45.56	54.00	-8.44	Α
N/A									Р
N/A									Α

Vertical

TX / IEEE	802.11b m	ode / CH	Middle	М	easurer	nent Distan	ce at 3m	Vertical pol	arity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV /m)	(dB)	(P/Q/A)
4876.92	53.64	32.93	3.73	41.42	0.71	49.60	74.00	-24.40	Р
4876.92	43.84	32.93	3.73	41.42	0.71	39.80	54.00	-14.20	Α
7309.25	51.51	38.93	4.96	41.32	1.59	55.67	74.00	-18.33	Р
7309.25	40.93	38.93	4.96	41.32	1.59	45.09	54.00	-8.91	Α
9748.35	52.14	38.85	5.75	38.24	0.55	59.05	74.00	-14.95	Р
9748.35	40.57	38.85	5.75	38.24	0.55	47.48	54.00	-6.52	Α
N/A									Р
N/A									Α

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3.The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

IEEE 802.11b TX (CH High)

Horizontal

TX / IEEE	802.11b m	ode / CH	High	Ме	asurem	ent Distanc	e at 3m Hor	izontal po	larity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4923.85	52.46	33.03	3.76	41.49	0.73	48.50	74.00	-25.50	Р
4923.85	42.11	33.03	3.76	41.49	0.73	38.15	54.00	-15.85	Α
7385.69	51.24	39.04	4.99	41.21	1.76	55.82	74.00	-18.18	Р
7385.69	39.51	39.04	4.99	41.21	1.76	44.09	54.00	-9.91	Α
9848.15	50.24	38.95	5.76	38.06	0.49	57.39	74.00	-16.61	Р
9848.15	38.96	38.95	5.76	38.06	0.49	46.10	54.00	-7.90	Α
N/A									Р
N/A									Α

Vertical

TX / IEEE	802.11b m	ode / CH	High	N	leasure	ment Distan	ce at 3m Ve	rtical pola	rity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4924.03	53.84	33.03	3.76	41.49	0.73	49.88	74.00	-24.12	Р
4924.03	43.45	33.03	3.76	41.49	0.73	39.49	54.00	-14.51	Α
7386.08	52.41	39.04	4.99	41.21	1.76	56.99	74.00	-17.01	Р
7386.08	40.57	39.04	4.99	41.21	1.76	45.15	54.00	-8.85	Α
9847.35	52.11	38.95	5.76	38.06	0.49	59.10	74.00	-14.90	Р
9847.35	41.35	38.95	5.76	38.06	0.49	48.49	54.00	-5.51	Α
N/A									Р
N/A									Α

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3. The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

IEEE 802.11g TX (CH Low)

Horizontal

TX / IEE	E 802.11g ı	mode / Cl	H Low	N	leasure	ment Distan	ce at 3m Ho	rizontal po	olarity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4824.23	52.12	32.81	3.71	41.34	0.69	48.00	74.00	-26.00	Р
4824.23	42.11	32.81	3.71	41.34	0.69	37.99	54.00	-16.01	Α
7236.00	51.24	38.83	4.93	41.42	1.44	55.01	74.00	-18.99	Р
7236.00	40.35	38.83	4.93	41.42	1.44	44.12	54.00	-9.88	Α
9642.15	50.22	38.74	5.74	38.44	0.61	56.88	74.00	-17.12	Р
9642.15	38.95	38.74	5.74	38.44	0.61	45.61	54.00	-8.39	Α
N/A									Р
N/A									Α

Vertical

TX / IEE	E 802.11 g	mode / C	H Low	ı	Measure	ment Distar	ice at 3m V	ertical pola	arity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4824.00	54.24	32.81	3.70	41.34	0.69	50.11	74.00	-23.89	Р
4824.00	43.97	32.81	3.70	41.34	0.69	39.84	54.00	-14.16	Α
7236.39	51.62	38.83	4.93	41.42	1.44	54.39	74.00	-19.61	Р
7236.39	41.52	38.83	4.93	41.42	1.44	45.29	54.00	-8.71	Α
9641.57	52.21	38.74	5.74	38.44	0.62	57.87	74.00	-16.13	Р
9641.57	41.25	38.74	5.74	38.44	0.62	47.91	54.00	-6.09	Α
N/A									Р
N/A									Α

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3.The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

IEEE 802.11g TX (CH Middle)

Horizontal

TX / IEEE	802.11g m	node / CH	Middle	М	easuren	nent Distand	e at 3m Hoi	izontal pola	rity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4871.16	50.24	32.92	3.73	41.41	0.71	46.19	74.00	-27.81	Р
4871.16	41.35	32.92	3.73	41.41	0.71	37.30	54.00	-16.70	Α
7318.25	49.85	38.95	4.96	41.31	1.61	54.06	74.00	-19.94	Р
7318.25	40.22	38.95	4.96	41.31	1.61	45.43	54.00	-8.57	Α
9748.35	50.24	38.85	5.75	38.24	0.55	57.15	74.00	-16.85	Р
9748.35	39.58	38.85	5.75	38.24	0.55	46.49	54.00	-7.51	Α
N/A									Р
N/A									Α

Vertical

TX / IEE	E 802.11g ı	node / Cł	H Middle	Measurement Distance at 3m Vertical polarity						
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)	
4871.56	53.62	32.92	3.73	41.41	0.71	49.57	74.00	-24.43	Р	
4871.56	44.17	32.92	3.73	41.41	0.71	40.12	54.00	-13.88	Α	
7317.24	51.24	38.94	4.96	41.31	1.61	55.45	74.00	-18.55	Р	
7317.24	42.33	38.94	4.96	41.31	1.61	45.54	54.00	-8.46	Α	
9747.26	52.34	38.85	5.75	38.25	0.55	59.25	74.00	-14.75	Р	
9747.26	41.52	38.85	5.75	38.25	0.55	48.43	54.00	-5.57	Α	
N/A									Р	
N/A									Α	

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3. The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

IEEE 802.11g TX (CH High)

Horizontal

TX / IEE	E 802.11g ı	mode / Cl	H High	N	leasure	ment Distan	ce at 3m Horiz	ontal pola	rity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4924.35	51.24	33.03	3.76	41.49	0.73	47.28	74.00	-26.72	Р
4924.35	40.26	33.03	3.76	41.49	0.73	36.30	54.00	-17.70	Α
7384.86	49.87	39.04	4.99	41.21	1.75	54.44	74.00	-19.56	Р
7384.86	38.65	39.04	4.99	41.21	1.75	43.22	54.00	-10.78	Α
9847.56	50.14	38.95	5.76	38.06	0.49	57.28	74.00	-16.72	Р
9847.56	39.85	38.95	5.76	38.06	0.49	46.99	54.00	-7.01	Α
N/A									Р
N/A									Α

Vertical

TX / IEE	E 802.11g	mode / Cl	H High		Measur	ement Dista	nce at 3m Ver	tical polari	ity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4923.85	53.22	33.03	3.76	41.49	0.73	49.26	74.00	-24.74	Р
4923.85	42.61	33.03	3.76	41.49	0.73	38.65	54.00	-15.35	Α
7385.94	51.33	39.04	4.99	41.21	1.76	55.91	74.00	-18.09	Р
7385.94	40.25	39.04	4.99	41.21	1.76	45.83	54.00	-8.17	А
9847.59	52.64	38.95	5.76	38.06	0.49	59.78	74.00	-14.22	Р
9847.59	41.24	38.95	5.76	38.06	0.49	48.38	54.00	-5.62	Α
N/A									Р
N/A									Α

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3. The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

IEEE 802.11n HT20 TX (CH Low)

Horizontal

TX / IEEE	E 802.11n F	IT20 mod	e / CH Low	Measurement Distance at 3m Horizontal polarity						
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)	
4824.35	50.24	32.81	3.71	41.34	0.69	46.12	74.00	-27.88	Р	
4824.35	38.95	32.81	3.71	41.34	0.69	34.83	54.00	-19.17	Α	
7235.86	51.22	38.83	4.93	41.43	1.43	54.99	74.00	-19.01	Р	
7235.86	38.97	38.83	4.93	41.43	1.43	42.74	54.00	-11.26	Α	
9648.35	50.22	38.75	5.74	38.43	0.61	55.90	74.00	-18.10	Р	
9648.35	38.64	38.75	5.74	38.43	0.61	45.32	54.00	-8.68	Α	
N/A									Р	
N/A									Α	

Vertical

TX / IEEE	E 802.11n H	IT20 mod	e / CH Low	Measurement Distance at 3m Vertical polarity						
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)	
4823.59	52.64	32.81	3.70	41.34	0.69	48.51	74.00	-25.49	Р	
4823.59	41.25	32.81	3.70	41.34	0.69	37.12	54.00	-16.88	Α	
7236.24	53.26	38.83	4.93	41.42	1.44	57.03	74.00	-16.97	Р	
7236.24	41.25	38.83	4.93	41.42	1.44	44.02	54.00	-9.98	Α	
9647.15	52.14	38.75	5.74	38.43	0.61	58.81	74.00	-15.19	Р	
9647.15	40.36	38.75	5.74	38.43	0.61	47.03	54.00	-6.97	Α	
N/A									Р	
N/A									Α	

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3. The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

IEEE 802.11n HT20 TX (CH Middle)

Horizontal

TX / IEEE	802.11n F	IT20 mod	e / CH Middle	М	easuren	nent Distand	ce at 3m Hor	rizontal pola	arity
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)
4872.69	50.24	32.92	3.73	41.41	0.71	46.19	74.00	-27.81	Р
4872.69	40.36	32.92	3.73	41.41	0.71	36.31	54.00	-17.69	Α
7311.54	49.87	38.94	4.96	41.32	1.60	54.05	74.00	-19.95	Р
7311.54	38.65	38.94	4.96	41.32	1.60	42.83	54.00	-11.17	Α
9748.27	50.24	38.85	5.75	38.24	0.55	57.15	74.00	-16.85	Р
9748.27	39.85	38.85	5.75	38.24	0.55	46.76	54.00	-7.24	Α
N/A									Р
N/A									Α

Vertical

TX / IEEE	TX / IEEE 802.11n HT20 mode / CH Middle					Measurement Distance at 3m Vertical polarity						
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark			
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)			
4873.26	52.14	32.92	3.73	41.41	0.71	49.09	74.00	-24.91	Р			
4873.26	42.33	32.92	3.73	41.41	0.71	38.28	54.00	-15.72	Α			
7312.25	51.84	38.94	4.96	41.32	1.60	56.02	74.00	-17.98	Р			
7312.25	40.25	38.94	4.96	41.32	1.60	44.43	54.00	-9.57	Α			
9748.65	51.68	38.85	5.75	38.24	0.55	58.59	74.00	-15.41	Р			
9748.65	41.25	38.85	5.75	38.24	0.55	48.16	54.00	-5.84	Α			
N/A									Р			
N/A									Α			

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3.The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

IEEE 802.11n HT20 TX (CH High)

Horizontal

TX / IEEE	802.11n H	IT20 mod	e / CH High	Measurement Distance at 3m Horizontal polarity						
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)	
4923.85	51.14	33.03	3.76	41.49	0.73	48.18	74.00	-25.82	Р	
4923.85	40.35	33.03	3.76	41.49	0.73	36.39	54.00	-17.61	Α	
7386.54	50.28	39.04	4.99	41.21	1.76	54.86	74.00	-19.14	Р	
7386.54	39.48	39.04	4.99	41.21	1.76	44.06	54.00	-9.94	Α	
9849.33	49.87	38.95	5.76	38.06	0.49	57.02	74.00	-16.98	Р	
9849.33	39.65	38.95	5.76	38.06	0.49	46.80	54.00	-7.20	Α	
N/A									Р	
N/A									Α	

Vertical

TX / IEEE	802.11n H	IT20 mod	e / CH High	Measurement Distance at 3m Vertical polarity						
Freq.	Reading	AF	Cable Loss	Pre- amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	(P/Q/A)	
4923.16	53.26	33.03	3.76	41.48	0.73	48.30	74.00	-25.70	Р	
4923.16	42.17	33.03	3.76	41.48	0.73	38.21	54.00	-15.79	Α	
7385.46	52.86	39.04	4.99	41.21	1.75	57.43	74.00	-16.57	Р	
7385.46	41.33	39.04	4.99	41.21	1.75	45.90	54.00	-8.10	А	
9849.17	52.34	38.95	5.76	38.06	0.49	59.49	74.00	-14.51	Р	
9849.17	42.65	38.95	5.76	38.06	0.49	49.80	54.00	-4.20	Α	
N/A									Р	
N/A									Α	

- 1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- 2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- 3. The result basic equation calculation is as follow: Level = Reading + AF + Cable Preamp + Filter Dist, Margin = Level-Limit
- 4. The other emission levels were 20dB below the limit
- 5. The test limit distance is 3M limit.

9.2 RESTRICTED BAND EDGES

TEST RESULT

IEEE 802.11b mode

Channel	Freq.(MHz)	Level(dBuV)	Limit(dBuV)	Margin(dB)	Detector
	2390	54.25	74	-19.75	Peak
LOW	2390	51.45	54	-2.55	Average
	2483.5	52.05	74	-21.95	Peak
HIGH	2483.5	48.77	54	-5.23	Average


IEEE 802.11g mode

Channel	Freq.(MHz)	Level(dBuV)	Limit(dBuV)	Margin(dB)	Detector
	2390	57.26	74	-16.74	Peak
LOW	2390	49.55	54	-4.45	Average
	2483.5	51.96	74	-22.04	Peak
HIGH	2483.5	50.12	54	-3.38	Average


IEEE 802.11n HT20 mode

Channel	Freq.(MHz)	Level(dBuV)	Limit(dBuV)	Margin(dB)	Detector
	2390	59.21	74	-14.79	Peak
LOW	2390	49.87	54	-4.13	Average
	2483.5	52.59	74	-21.41	Peak
HIGH	2483.5	49.05	54	-4.95	Average


CH Low (802.11b MODE-Peak)




CH Low (802.11b MODE-Average)




CH High (802.11b MODE-Peak)




CH High (802.11b MODE-Average)




CH Low (802.11g MODE-Peak)









CH High (802.11g MODE-Peak)




CH High (802.11g MODE-Average)




CH Low (802.11n HT20 MODE-Peak)




CH Low (802.11n HT20 MODE-Average)



CH High (802.11n HT20 MODE-Peak)



CH High (802.11n HT20 MODE-Average)



10. ANTENNA REQUIREMENT

10.1 Standard Applicable

Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Section 15.247(b)/(c):

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

If the intentional radiator is used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

10.2 Antenna Connected Construction

The antenna connector is designed with permanent attachment and no consideration of replacement.

Report No.: BCT12FR-201E Page 66 of 66 FCC ID: VD2-HSG1255