

No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Telephone: +86 (0) 20 8215 5555 Fax: +86 (0) 20 8207 5059

Email: sgs\_internet\_operations@sgs.com

FEDERAL COMMUNICATIONS COMMISSION

Registration number: 556682

Report No.: SZEMO080501734ETF

: 1 of 11 Page

FCC ID : VDB-GC598935

# TEST REPORT

Application No. : SZEMO080501734ETF(SGS SZ NO.: SZTYR080501582 /EL)

: CHENGHAI HAILIANG PLASTIC TOYS FACTORY **Applicant** 

**FCC ID** : VDB-GC598935 Fundamental Frequency: 49.860MHz

**Equipment under Test (EUT):** 

: R/ C CONSTRUCTION CAR ( TOY-R/C BULLDOZER , TOY-R/C CEMENT **EUT Name** 

TRUCK、 TOY-R/C DUMP TRUCK、 TOY-R/C EXCAVATOR)

: 3058、3068、3078、3098、3358、3368、3378、3398、1616707、1616709、 Item No.

1616705

Please refer to section 2 of this report which indicates which item was actually

tested and which were electrically identical.

: FCC PART 15, SUBPART C: 2007 **Standards** 

**Section 15.235** 

**Date of Receipt** : 08 May 2008

**Date of Test** : 08 to 14 May 2008

: 16 May 2008 Date of Issue

Test Result: PASS \*

Authorized Signature:

Robinson Lo

Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at http://www.sqs.com/terms\_and\_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, may be prosecuted to the fullest extens without prior approval of the Company.

Member of the SGS Group (SGS SA)



Report No.: SZEMO080501734ETF

Page : 2 of 9

\* In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEMO080501734ETF

Page 3 of 9

#### 2 **Test Summary**

Test	Test Requirement	Stanadard Paragraph	Result	
Radiated Emission (30MHz to 1000MHz)	FCC PART 15 :2007	Section 15.235	PASS	
Occupied Bandwidth	FCC PART 15 :2007	Section 15.235	PASS	

Tx: In this whole report Tx (or tx) means Transmitter. Rx: In this whole report Rx (or rx) means Receiver. RF: In this whole report RF means Radiated Frequency.

Remark:

Labelled Age Grading: 8 up Country of Origin: China

New batteries were installed in the EUT during all tests.

Item No.:

3058、3068、3078、3098、3358、3368、3378、3398、1616707、1616709、1616705

Only the item in the picture 5.3 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the items 301839, 301862, 301863, 301517, 301535, 301536, 301539, with only difference being the packaging.



Report No.: SZEMO080501734ETF

Page : 4 of 9

# **Contents**

			Page
1	COV	/ER PAGE	1
2	TES	T SUMMARY	3
3	CON	ITENTS	4
4	GEN	IERAL INFORMATION	5
	4 1	CLIENT INFORMATION	5
	4.1	DETAILS OF E.U.T.	5
	4.3	DESCRIPTION OF SUPPORT UNITS	5
	4.4	TEST LOCATION	5
	4.5	OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5	TES	T RESULTS	6
	5.1	TEST INSTRUMENTS	6
	5.2	E.U.T. OPERATION	
	5.3	TEST PROCEDURE & MEASUREMENT DATA	6
	5.3.1		6-7
	5.3.2	2 Occupied Bandwidth	



Report No.: SZEMO080501734ETF

Page : 5 of 9

#### 4 General Information

#### 4.1 **Client Information**

Applicant: CHENGHAI HAILIANG PLASTIC TOYS FACTORY

Address of Applicant: QIANXI INDUSTRIAL AREA, EAST AN CHENG ROAD LIANXIA, CHENGHAI

### 4.2 Details of E.U.T.

Power Supply: 9.0V DC (1\*9.0V "6F22" Size Battery) for Tx;

4.8V DC (Rechargeable Battery) for Rx.

Power Cord: N/A-

### 4.3 Description of Support Units

The EUT was tested as an independent unit: a 49MHz radio transmitter.

### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Tel: +86 20 8215 5555 Fax: +86 20 8207 5059

# 4.5 Other Information Requested by the Customer

None.



Report No.: SZEMO080501734ETF

Page 6 of 9

#### **Test Results** 5

### Test Instruments

R8	R&TTE RE in Chamber									
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)				
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2007	15-06-2008				
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2007	11-12-2008				
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A				
4	Coaxial cable	SGS	N/A	SEL0028	01-06-2007	31-05-2008				
5	Coaxial cable	SGS	N/A	SEL0027	20-10-2007	19-10-2008				
6	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	12-08-2007	11-08-2008				
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	27-06-2007	26-06-2008				
8	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	15-06-2007	14-06-2008				

# 5.2 E.U.T. Operation

Input voltage: 9.0V DC (1\*9.0V "6F22" Size Battery) for the transmitter.

Operating Environment:

Temperature: 23.0 °C Humidity: 52 % RH Atmospheric Pressure: 1015 mbar

**EUT Operation:** 

Test the EUT in transmitting mode.

#### 5.3 **Test Procedure & Measurement Data**

#### 5.3.1 **Radiated Emissions**

Test Requirement: FCC Part15 C Section 15.235

Test Method: **ANSI C63.4** 

Measurement Distance: 3m (Semi-Anechoic Chamber)

Requirements: Carrier frequency will not exceed 80dBuV/m AT 3m.

> Out of band emissions shall not exceed:  $40.0 \text{ dB}\mu\text{V/m}$  between 30MHz & 88MHz43.5 dBµV/m between 88MHz & 216MHz  $46.0 \text{ dB}\mu\text{V/m}$  between 216MHz & 960MHz

54.0 dBµV/m above 960MHz

Detector: Peak Scan (120kHz resolution bandwidth)

#### FCC ID.: VDB-GC598935



Report No.: SZEMO080501734ETF

Page 7 of 9

#### Test Procedure:

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7 The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

The following measurements were performed on the modified modified EUT on 10 April 2007: Test the EUT in transmitting mode.

#### Intentional emission

Test Frequency	Peak (dBμV/m)		Limits	Margin (dB)	
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
49.860	68.88	53.18	100.0	31.12	46.82

Test Frequency	Average (dBμV/m)		Limits	Margin (dB)		
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal	
49.860	64.52	49.07	80.0	15.48	30.93	



Report No.: SZEMO080501734ETF

Page : 8 of 9

#### Other emissions

#### Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
97.90	1.18	9.02	27.89	46.31	28.62	43.50	-14.88
198.78	1.40	10.19	27.16	38.50	22.93	43.50	-20.57
249.22	1.67	12.27	26.92	38.88	25.90	46.00	-20.10
296.75	1.89	13.76	26.73	39.74	28.66	46.00	-17.34
497.54	2.59	17.80	27.70	36.00	28.69	46.00	-17.31

#### Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
97.90	1.18	9.02	27.89	32.39	14.70	43.50	-28.80
249.22	1.67	12.27	26.92	32.32	19.34	46.00	-26.66
297.72	1.89	13.81	26.73	31.58	20.55	46.00	-25.45
432.55	2.34	16.56	27.52	31.00	22.38	46.00	-23.62
670.20	2.85	21.32	27.37	30.71	27.51	46.00	-18.49

#### Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a imit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

Test Results: The unit does meet the FCC Part 15 C Section 15.235 requirements.



Report No.: SZEMO080501734ETF

Page 9 of 9

#### 5.3.2 **Occupied Bandwidth**

Test Requirement: FCC Part15 C Section 15.235

Test Method: **ANSI C63.4** 

Operation within the band 49.82 - 49.90 MHz

Modulation Signal: AM

Requirements: The field strength of any emissions appearing between the band edges

> and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits in Section 15.209, whichever permits the higher emission levels. The field strength of any emissions removed by more than 10 kHz from the band edges shall not exceed the general radiated emission limits in


Section 15.209.

Method of measurement: The useful radiated emission from the EUT was detected by the spectrum

> analyer with peak detector. The vertical Scale is set to −10dB per division. The horizontal scale is set to 8KHz per division. The EUT tested under

modulation signal.

The graph as below, represents the emissions take for this device.



Date: 6.MAY.2008 17:23:56

The results: The unit does meet the FCC Part 15 C Section 15.235 requirements.

FCC ID.: VDB-GC598935