

## FCC Test Report

**Report No.:** RF181213E04

**FCC ID:** VECAP11

**Test Model:** AP11

**Series Model:** AP11-S

**Received Date:** Dec. 13, 2018

**Test Date:** Dec. 25, 2018 to Jan. 14, 2019

**Issued Date:** Mar. 05, 2019

**Applicant:** ST Electronics (Satcom & Sensor Systems) Pte Ltd

**Address:** 1 Ang Mo Kio Electronics Park Road #06-02 Singapore 567710

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**FCC Registration /  
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b>	<b>3</b>
<b>1 Certificate of Conformity</b>	<b>4</b>
<b>2 Summary of Test Results</b>	<b>5</b>
2.1 Measurement Uncertainty	5
2.2 Modification Record	5
<b>3 General Information</b>	<b>6</b>
3.1 General Description of EUT	6
3.2 Description of Test Modes	7
3.2.1 Test Mode Applicability and Tested Channel Detail	8
3.3 Duty Cycle of Test Signal	10
3.4 Description of Support Units	11
3.4.1 Configuration of System under Test	12
3.5 General Description of Applied Standards	13
<b>4 Test Types and Results</b>	<b>14</b>
4.1 Radiated Emission and Bandedge Measurement	14
4.1.1 Limits of Radiated Emission and Bandedge Measurement	14
4.1.2 Test Instruments	16
4.1.3 Test Procedures	18
4.1.4 Deviation from Test Standard	20
4.1.5 Test Setup	20
4.1.6 EUT Operating Conditions	21
4.1.7 Test Results	22
4.2 Conducted Emission Measurement	27
4.2.1 Limits of Conducted Emission Measurement	27
4.2.2 Test Instruments	27
4.2.3 Test Procedures	28
4.2.4 Deviation from Test Standard	28
4.2.5 Test Setup	28
4.2.6 EUT Operating Conditions	28
4.2.7 Test Results	29
4.3 20dB bandwidth Measurement	31
4.3.1 Limits of 20dB bandwidth Measurement	31
4.3.2 Test Instruments	31
4.3.3 Test Procedure	31
4.3.4 Test Setup	31
4.3.5 Deviation from Test Standard	31
4.3.6 EUT Operating Condition	31
4.3.7 Test Results	32
<b>5 Pictures of Test Arrangements</b>	<b>33</b>
<b>Appendix – Information of the Testing Laboratories</b>	<b>34</b>

### Release Control Record

Issue No.	Description	Date Issued
RF181213E04	Original release.	Mar. 05, 2019

## 1 Certificate of Conformity

**Product:** Miniature K-band Microwave Sensor

**Brand:** ST Engineering Electronics

**Test Model:** AP11

**Series Model:** AP11-S

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** ST Electronics (Satcom & Sensor Systems) Pte Ltd

**Test Date:** Dec. 25, 2018 to Jan. 14, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.245)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**

Mary Ko

, **Date:** Mar. 05, 2019

Mary Ko / Specialist

**Approved by :**

May Chen

, **Date:** Mar. 05, 2019

May Chen / Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.245)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -31.22dB at 19.52344MHz.
15.245	Radiated Emission Test	PASS	Meet the requirement of limit. Minimum passing margin is -3.4dB at 72.432MHz.
15.215 (c)	20dB Bandwidth	PASS	Meet the requirement of limit
15.203	Antenna Requirement	PASS	No antenna connector is used.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.53 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.08 dB
	6GHz ~ 18GHz	4.98 dB
	18GHz ~ 40GHz	5.19 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	Miniature K-band Microwave Sensor
Brand	ST Engineering Electronics
Test Model	AP11
Series Model	AP11-S
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	DC 3V
Modulation Type	CW
Operating Frequency	24.075~24.175GHz
Antenna Type	Patch antenna with 8dBi gain
Antenna Connector	NA
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. The EUT have two model names, which are identical to each other in all aspects except for the following table:

Brand	Model No.	Difference
ST Engineering Electronics	AP11	1. uses pin mount 2. Dimensions (15.2 x 24 x 11.8mm)
	AP11-S	1. uses SMT 2. Dimensions (15.2 x 21.5 x 3.5mm)

From the above models, model: **AP11** was selected as representative model for the test and its data was recorded in this report.

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

1 channel is provided in EUT for test:

Channel	Frequency
1	24.144GHz

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	BW	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz & Bandedge Measurement **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission **BW**: 20dB Bandwidth Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane (below 1GHz) & Z-plane (above 1GHz)**.

#### **Radiated Emission Test (Above 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TYPE
1	CW

#### **Radiated Emission Test (Below 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TYPE
1	CW

#### **Power Line Conducted Emission Test:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TYPE
1	CW

#### **20dB Bandwidth Measurement:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TYPE
1	CW




**Test Condition:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE $\geq$ 1G	22deg. C, 69%RH 22deg. C, 74%RH 25deg. C, 60%RH	120Vac, 60Hz	Andy Ho Weiwei Lo
RE<1G	24deg. C, 72%RH	120Vac, 60Hz	Andy Ho
PLC	23deg. C, 74%RH	120Vac, 60Hz	Andy Ho
BW	24deg. C, 66%RH	120Vac, 60Hz	Anderson Chen

### 3.3 Duty Cycle of Test Signal

Duty cycle of test signal is 100 %, duty factor is not required.



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	DC Power Supply	GOOD WILL INSTRUMENT CO., LTD.	GPC-3030D	7700087	NA	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	DC Cable	1	3	No	0	Provided by Lab

### **3.4.1 Configuration of System under Test**

**For conducted emission test:**

**For other test:**

### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.245)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

According to 15.245 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBuV/m)	
	Peak	Average
24075 ~ 24175	147.9	127.9
	Field Strength of Harmonics (dBuV/m)	
	107.9	87.9

Harmonic emissions in the restricted bands at and above 17.7 GHz shall not exceed the following field strength limits:

Application	Field Strength of Harmonics (dBuV/m)
Field disturbance sensors operating in the 24075-24175 MHz band and for Other field disturbance sensors designed for use only within a building or to open building doors.	87.9
All other field disturbance sensors	77.5

Note: Field disturbance sensors designed to be used in motor vehicles or aircraft must include features to prevent continuous operation unless their emissions in the restricted bands, other than the second and third harmonics from devices operating in the 24075-24175 MHz band, fully comply with the limits given in Section 15.209.

- (1) Field strength limits are specified at a distance of 3 meters.
- (2) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

##### Below 40GHz test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	July 12, 2018	July 11, 2019
Pre-Amplifier EMCI	EMC001340	980142	Feb. 09, 2018	Feb. 08, 2019
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019
RF Cable	NA	LOOPCAB-001	Jan. 15, 2018	Jan. 14, 2019
RF Cable	NA	LOOPCAB-002	Jan. 15, 2018	Jan. 14, 2019
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 05, 2018	May 04, 2019
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Nov. 22, 2018	Nov. 21, 2019
RF Cable	8D	966-3-1	Mar. 20, 2018	Mar. 19, 2019
RF Cable	8D	966-3-2	Mar. 20, 2018	Mar. 19, 2019
RF Cable	8D	966-3-3	Mar. 20, 2018	Mar. 19, 2019
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Sep. 27, 2018	Sep. 26, 2019
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Nov. 25, 2018	Nov. 24, 2019
Pre-Amplifier EMCI	EMC12630SE	980384	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-1200	160922	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-2000	150317	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-5000	150322	Jan. 29, 2018	Jan. 28, 2019
Spectrum Analyzer Keysight	N9030A	MY54490679	July 23, 2018	July 22, 2019
Pre-Amplifier EMCI	EMC184045SE	980386	Jan. 29, 2018	Jan. 28, 2019
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Nov. 25, 2018	Nov. 24, 2019
RF Cable	EMC102-KM-KM-1200	160924	Jan. 29, 2018	Jan. 28, 2019
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

##### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. The CANADA Site Registration No. is 20331-1
4. Loop antenna was used for all emissions below 30 MHz.
5. Tested Date: Jan. 12, 2019



**Above 40GHz test:**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250254	Nov. 14, 2018	Nov. 13, 2019
*Harmonic Mixer (33~55GHz) OML	M22HWD	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Horn Antenna (33~55GHz) OML	M22RH	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Harmonic Mixer (50~75GHz) OML	M15RH	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Horn Antenna (50~75GHz) OML	M15HWD	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Diplexer EMCI	DPL26	DPL26_01	Oct. 17, 2017	Oct. 16, 2019
*Diplexer EMCI	DPL26	DPL26_02	Oct. 17, 2017	Oct. 16, 2019
*Precision 30dB Attenuator Keysight	11708A	MY55260015	Oct. 17, 2017	Oct. 16, 2019
*Zero-Bias Detector (50~75GHz) Vdi	WR15ZBD	WR15R5 1-30	Oct. 17, 2017	Oct. 16, 2019
*WR15CH Conical Horn Keysight	WR15CH	WR15CH-01	Oct. 17, 2017	Oct. 16, 2019
*WR10CH Conical Horn Keysight	WR10CH	WR10CH-01	Oct. 17, 2017	Oct. 16, 2019
*Millimeter-Wave Signal Generator Frequency Extension Module (50~75 GHz) Keysight	E8257DV15	US54250106	Oct. 17, 2017	Oct. 16, 2019
PSG analog signal generator Keysight	E8257D	MY53401987	June 26, 2018	June 25, 2019
Antenna Tower & Turn Table CT	NA	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. \*The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3
4. The FCC Site Registration No. is 966073.
5. The VCCI Site Registration No. is G-137.
6. The CANADA Site Registration No. is IC 7450H-2.
7. Test Date: Jan. 04, 2019

#### 4.1.3 Test Procedures

##### **For Radiated emission: Below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### **For Radiated emission: 30MHz ~ 40GHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak and Average detection at frequency from 1GHz to 40GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

### For Radiated emission: Above 40GHz

External harmonic mixers are utilized.

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The distance at which limits are typically specified is 3 meter; however, closer measurement distances may be utilized.
- Begin handheld measurements with the test antenna (horn) at a distance of 1 meter from the EUT, in a horizontally polarized position. Slowly adjust its position, entirely covering the plane 1 meter from the EUT.
- Repeat (b) with the horn in a vertically polarized position.
- If the emission cannot be detected at 1 meter, reduce the RBW in order to increase system sensitivity. Note the value. If the emission still cannot be detected, move the horn closer to the EUT, noting the distance at which a measurement is made.
- Note the maximum level indicated on the Spectrum Analyzer.
- Based on the distance at which the measurement was made and the calculated distance to the edge of the far field, determine the appropriate distance attenuation factor. Apply this factor to the calculated field strength in order to determine the equivalent field strength at the distance at which the regulatory limit is specified. Compare to the appropriate limits
- Repeat (a) - (f) for every emission that must be measured, up through the required frequency range of investigation

### NOTE:

- The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak and Average detection at frequency above 40GHz.
- Shorter measurement distances may be used to improve the measurement system's noise floor. As ANSI C63.10 description is based on the measurement in distance of 3 meters, the data obtained at 1-meter distance was extrapolate results to the 3-m distance:

Test value at 3-meter distance (dBuV)

= Test value at 1 meter distance (dBuV) -20log(3/1)(dB)

= Test value at 1 meter distance (dBuV) -9.5(dB).

\* Measurements made at 1 meter distance. Test value converted to account for 3-meter measurement distance.

### FAR FIELD BOUNDARY CALCULATIONS

The far-field boundary is given as:

$$R \text{ far field} = (2 * L^2) / \lambda$$

where: L = Largest Antenna Dimension, including the reflector, in meters

$\lambda$  = wavelength in meters


FREQUENCY (GHz )	L (m)	Lambda (m)	R (Far Field) (m)
24.144	0.025	0.0124	0.1008

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz




##### For Radiated emission 30MHz to 1GHz



### For Radiated emission 1GHz to 40GHz



### For Radiated emission above 40GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

Set the EUT under transmission / receiver condition continuously at specific channel frequency.

#### 4.1.7 Test Results

##### Above 1GHz Data

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 18GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4060.00	37.8 PK	74.0	-36.2	1.50 H	213	37.5	0.3
2	4060.00	24.5 AV	54.0	-29.5	1.50 H	360	24.2	0.3
3	5114.00	39.9 PK	74.0	-34.1	1.64 H	135	36.9	3.0
4	5114.00	27.2 AV	54.0	-26.8	1.50 H	360	24.2	3.0
5	8004.00	45.2 PK	74.0	-28.8	1.35 H	219	35.9	9.3
6	8004.00	32.2 AV	54.0	-21.8	1.50 H	360	22.9	9.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3635.00	37.0 PK	74.0	-37.0	1.51 V	243	37.5	-0.5
2	3635.00	23.6 AV	54.0	-30.4	1.51 V	243	24.1	-0.5
3	6525.00	42.5 PK	74.0	-31.5	1.64 V	231	36.8	5.7
4	6525.00	29.4 AV	54.0	-24.6	1.64 V	231	23.7	5.7
5	7987.00	44.5 PK	74.0	-29.5	1.42 V	205	35.4	9.1
6	7987.00	32.0 AV	54.0	-22.0	1.42 V	205	22.9	9.1

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	18GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	24075.00	61.2 PK	74.0	-12.8	1.57 H	181	79.9	-18.7
2	24075.00	44.5 AV	54.0	-9.5	1.57 H	181	63.2	-18.7
3	*24144.00	105.0 PK	147.9	-42.9	1.57 H	181	123.6	-18.6
4	*24144.00	103.1 AV	127.9	-24.8	1.57 H	181	121.7	-18.6
5	24175.00	67.3 PK	74.0	-6.7	1.57 H	181	85.9	-18.6
6	24175.00	49.2 AV	54.0	-4.8	1.57 H	181	67.8	-18.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	24075.00	60.4 PK	74.0	-13.6	1.61 V	177	79.1	-18.7
2	24075.00	43.3 AV	54.0	-10.7	1.61 V	177	62.0	-18.7
3	*24144.00	91.2 PK	147.9	-56.7	1.61 V	177	109.8	-18.6
4	*24144.00	89.8 AV	127.9	-38.1	1.61 V	177	108.4	-18.6
5	24175.00	66.2 PK	74.0	-7.8	1.61 V	177	84.8	-18.6
6	24175.00	47.5 AV	54.0	-6.5	1.61 V	177	66.1	-18.6

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	40GHz ~ 100GHz		Average (AV)

ANTENNA POLARITY: HORIZONTAL							
NO.	FREQ. (GHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	EIRP Level (dBm)	Measured Power (dBm)	Receiver Antenna Gain (dBi)
1	48.288	76.5 PK	107.9	-31.4	-18.8	-60.6	24.3
2	48.288	63 AV	87.9	-24.9	-32.3	-74.1	24.3
3	72.432	79 PK	107.9	-28.9	-16.3	-61.8	24.1
4	72.432	64.4 AV	87.9	-23.5	-30.9	-76.4	24.1
ANTENNA POLARITY: VERTICAL							
NO.	FREQ. (GHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	EIRP Level (dBm)	Measured Power (dBm)	Receiver Antenna Gain (dBi)
1	48.288	78 PK	107.9	-29.9	-17.3	-59.1	24.3
2	48.288	64.1 AV	87.9	-23.8	-31.2	-73.0	24.3
3	72.432	79 PK	107.9	-28.9	-16.3	-61.8	24.1
4	72.432	64.5 AV	87.9	-23.4	-30.8	-76.3	24.1

#### REMARKS:

1. The measured power level is converted to EIRP using the equation:

$$\text{EIRP} = \text{PT} * \text{GT} = \text{Raw Value (dBm)} - \text{Receiver Antenna Gain (dBi)} + 20 \log (4 \pi D / \lambda)$$

where:

Raw Value (dBm) is the power of the receive measurement

Receiver Antenna Gain (dBi) is the gain of the receive measurement antenna

D is the measurement distance

$\lambda$  is the wavelength

2. Field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E * D)^2) / 30$$

Working in dB units, the above equation is equivalent to:

$$\text{EIRP [dBm]} = E [\text{dBuV/m}] + 20 \log (D [\text{meters}]) - 104.8$$

$$E = \text{EIRP} - 20 * \log (D) + 104.8$$

3. Shorter measurement distances may be used to improve the measurement system's noise floor. As ANSI C63.10 description is based on the measurement in distance of 3 meters, the data obtained at 1-meter distance was extrapolate results to the 3-m distance:

Test value at 3-meter distance (dBuV)

$$= \text{Test value at 1 meter distance (dBuV)} - 20 \log (3/1) (\text{dB})$$

$$= \text{Test value at 1 meter distance (dBuV)} - 9.5 (\text{dB}).$$

\*Measurements made at 1 meter distance. Test value converted to account for 3-meter measurement distance.

4. The far-field boundary is given in FCC KDB Publication 200443 as:

$$R \text{ far field} = (2 * L^2) / \lambda$$

L is the Largest Antenna Dimension, including the reflector

$\lambda$  is the wavelength

FREQUENCY (GHz )	L (m)	Lambda (m)	R (Far Field) (m)
24.144	0.025	0.0124	0.1008




# Below 1GHz Data

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.58	32.6 QP	40.0	-7.4	2.00 H	138	42.4	-9.8
2	49.08	28.2 QP	40.0	-11.8	2.00 H	241	37.1	-8.9
3	158.62	25.7 QP	43.5	-17.8	1.50 H	135	33.9	-8.2
4	367.44	25.8 QP	46.0	-20.2	1.50 H	224	31.2	-5.4
5	653.66	31.1 QP	46.0	-14.9	1.50 H	314	30.1	1.0
6	757.84	33.6 QP	46.0	-12.4	1.00 H	297	30.6	3.0

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.05	28.6 QP	40.0	-11.4	1.00 V	231	38.3	-9.7
2	48.89	27.4 QP	40.0	-12.6	1.00 V	162	36.3	-8.9
3	149.02	25.1 QP	43.5	-18.4	1.50 V	243	33.1	-8.0
4	312.59	24.8 QP	46.0	-21.2	1.50 V	224	31.4	-6.6
5	504.04	28.9 QP	46.0	-17.1	2.00 V	318	30.8	-1.9
6	644.37	31.9 QP	46.0	-14.1	1.50 V	172	30.9	1.0

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2018	Oct. 23, 2019
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 22, 2018	Oct. 21, 2019
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 04, 2018	June 03, 2019
50 ohms Terminator	N/A	3	Oct. 22, 2018	Oct. 21, 2019
RF Cable	5D-FB	COCCAB-001	Sep. 28, 2018	Sep. 27, 2019
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 16, 2018	Mar. 15, 2019
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3. Tested Date: Dec. 25, 2018

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.


#### 4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.02	2.23	-4.49	12.25	5.53	66.00	56.00	-53.75	-50.47
2	0.18906	10.04	10.90	1.55	20.94	11.59	64.08	54.08	-43.14	-42.49
3	0.35313	10.06	8.66	-13.40	18.72	-3.34	58.89	48.89	-40.17	-52.23
4	0.99766	10.11	3.65	-11.12	13.76	-1.01	56.00	46.00	-42.24	-47.01
5	3.78906	10.24	10.14	-13.83	20.38	-3.59	56.00	46.00	-35.62	-49.59
6	18.84766	11.01	11.92	5.87	22.93	16.88	60.00	50.00	-37.07	-33.12

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.93	2.58	-4.37	12.51	5.56	66.00	56.00	-53.49	-50.44
2	0.18906	9.94	10.92	1.61	20.86	11.55	64.08	54.08	-43.22	-42.53
3	0.49375	9.96	6.72	-13.44	16.68	-3.48	56.10	46.10	-39.42	-49.58
4	1.67969	10.02	10.06	-14.16	20.08	-4.14	56.00	46.00	-35.92	-50.14
5	4.66406	10.15	10.16	-13.83	20.31	-3.68	56.00	46.00	-35.69	-49.68
6	19.52344	10.85	12.81	7.93	23.66	18.78	60.00	50.00	-36.34	-31.22

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



### 4.3 20dB bandwidth Measurement

#### 4.3.1 Limits of 20dB bandwidth Measurement

According to 15.215(c), the requirement is to ensure the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified, is contained within the frequency band designated in the rule section under which the equipment is operated.

#### 4.3.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019

**Note:**


1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date: Jan. 14, 2019

#### 4.3.3 Test Procedure

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 300 kHz RBW and 1MHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Set both RBW and VBW of spectrum analyzer to 100 kHz and 300kHz with suitable frequency span from band edge. The bandedge was measured and recorded.

#### 4.3.4 Test Setup



#### 4.3.5 Deviation from Test Standard


No deviation.

#### 4.3.6 EUT Operating Condition


Set the EUT under transmission / receiver condition continuously.

#### 4.3.7 Test Results

##### For 20dB Bandwidth



##### For Bandedge





## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---