



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Portable Bluetooth 2.0 Speaker / FM Tuner

Model: M80

Trade Name: Artdio , kinyo

Prepared for

**KINYO CO., LTD.
NO.476 MING HU ROAD, HSIN CHU CITY, TAIWAN**

Prepared by

**COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.
(aka COMPLIANCE ENGINEERING SERVICE (CHINA))
NO. 5, JINAO INDUSTRIAL PARK, NO. 35 JUKENG ROAD,
DASHUIKENG VILLAGE, GUANLAN TOWN, BAOAN
DISTRICT, SHENZHEN, CHINA
TEL: 86-755-28055000
FAX: 86-755-28055221**



***Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document*



TABLE OF CONTENTS

| | |
|--|-----------|
| 1. TEST RESULT CERTIFICATION..... | 3 |
| 2. EUT DESCRIPTION | 4 |
| 3. TEST METHODOLOGY | 5 |
| 3.1 EUT CONFIGURATION | 5 |
| 3.2 EUT EXERCISE | 5 |
| 3.3 GENERAL TEST PROCEDURES | 5 |
| 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS | 6 |
| 3.5 DESCRIPTION OF TEST MODES | 6 |
| 4. INSTRUMENT CALIBRATION..... | 7 |
| 5. FACILITIES AND ACCREDITATIONS | 8 |
| 5.1 FACILITIES | 8 |
| 5.2 EQUIPMENT | 8 |
| 5.3 LABORATORY ACCREDITATIONS AND LISTING | 8 |
| 6. SETUP OF EQUIPMENT UNDER TEST | 9 |
| 6.1 SETUP CONFIGURATION OF EUT | 9 |
| 6.2 SUPPORT EQUIPMENT | 9 |
| 7. FCC PART 15.247 REQUIREMENTS..... | 10 |
| 7.1 PEAK POWER | 10 |
| 7.2 PEAK POWER SPECTRAL DENSITY | 11 |
| 7.3 BAND EDGES MEASUREMENT | 14 |
| 7.4 FREQUENCY SEPARATION | 19 |
| 7.5 NUMBER OF HOPPING FREQUENCY..... | 22 |
| 7.6 SPURIOUS EMISSIONS | 24 |
| 7.7 POWERLINE CONDUCTED EMISSIONS | 46 |
| APPENDIX 1 PHOTOGRPHS OF TEST SETUP..... | 48 |



1. TEST RESULT CERTIFICATION

Applicant: KINYO CO.,LTD.
No 476 Ming Hu Road Hsin Chu City Taiwan

Equipment Under Test: Portable Bluetooth 2.0 Speaker / FM Tuner

Trade Name: Artdio , kinyo

Model: M80

Date of Test: May 07-August 11,2008

| APPLICABLE STANDARDS | |
|------------------------------|-------------------------|
| STANDARD | TEST RESULT |
| FCC 47 CFR Part 15 Subpart C | No non-compliance noted |

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.207, 15.209 and 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Clinton Kao
Manager
Compliance Certification Service Inc.

Reviewed by:

Vincent Yao
Assistant manager
Compliance Certification Service Inc.



2. EUT DESCRIPTION

| | |
|------------------------------|--|
| Product | Portable Bluetooth 2.0 Speaker / FM Tuner |
| Trade Name | Artdio , kinyo |
| Model Number | M80 |
| Model Discrepancy | N/A |
| Power Supply | DC6V Powered by the battery Or DC6V Powered by the adapter Adapter Manufacturer / Model No.: S.T./ SW-060100A AC input:AC100-240V, 50/60Hz DC output: 6.0V/ 1000mA DC Output Cable: Un-shielded, 1.90m |
| Frequency Range | 2402 ~ 2480 MHz |
| Transmit Power | -3.31 dBm |
| Modulation Technique | FHSS(GFSK) |
| Number of Channels | 79 Channels |
| Antenna Specification | PCB Antenna Gain: 3 dBi (max) |
| Temperature Range | 0 ~ +55°C |

Note: This submittal(s) (test report) is intended for FCC ID: VF6ARM80 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2003. Radiated testing was performed at an antenna to EUT distance 3 meters.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003.

3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|----------------------------|---------------------|-----------------|------------------|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| ¹ 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.52525 | 2655 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 156.7 - 156.9 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 162.0125 - 167.17 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 167.72 - 173.2 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 240 - 285 | 3600 - 4400 | (²) |
| 13.36 - 13.41 | 322 - 335.4 | | |

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.5 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) are chosen for full testing.



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 5, Jinao industrial park, No.35 Jukeng Road, Dashuikeng Village, Guanlan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4: 2003 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTING

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

| | |
|---------------|------------|
| Taiwan | TAF |
|---------------|------------|

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

| | |
|---------------|------------------------|
| USA | FCC |
| Japan | VCCI |
| Canada | INDUSTRY CANADA |
| Taiwan | BSMI |

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsemc.com.tw>



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

| No. | Equipment | Model No. | Serial No. | FCC ID | Trade Name | Data Cable | Power Cord |
|-----|----------------|------------|--------------------------|-----------|----------------------|---------------------|----------------------|
| 1 | PC | M4600C | NS04619689NS1 6052619 | DoC | LENOVO | Unshielded 1.50m | Shielded 1.80m |
| 2 | KEYBOARD | SK-8815 | 02284283 | DoC | LENOVO | Shielded 1.80m | N/A |
| 3 | MOUSE | MO28U0L | 23-118901 | DoC | LENOVO | Shielded 1.80 | N/A |
| 4 | LCD MONITOR | T15E52 | N/A | DoC | GoLana Technology | Shielded 1.80 | Shielded 2.00m |
| 5 | MODEM | Modem-1414 | 9013593 | IFXDM1414 | ACEEX | Shielded, 1.50m | Unshielded, 2.00m |
| 6 | PRINTER | P310B | C41344000NK02 520275 | DoC | EPSON | Shielded, 1.50m | Unshielded, 1.80m |

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



7. FCC PART 15.247 REQUIREMENTS

7.1 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:


1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------------|--------------|---------|---------------|-----------------|
| RF Power Meter & Sensor | Anritsu | ML2487A | 6K00001491 | 02/23/2009 |
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted

Test Data

| Chanel | Frequency (MHz) | Reading Power (dBm) | Factor (dB) | Output Power (dBm) | Output Power (W) | Limit (W) | Result |
|--------|-----------------|---------------------|-------------|--------------------|------------------|-----------|--------|
| Low | 2402 | -4.87 | 1.0 | -3.87 | 0.00041 | 1 | PASS |
| Md | 2441 | -4.31 | 1.0 | -3.31 | 0.00047 | | PASS |
| High | 2480 | -4.45 | 1.0 | -3.45 | 0.00045 | | PASS |



7.2 PEAK POWER SPECTRAL DENSITY

LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted

Test Data

| Channel | Frequency | Reading (dBm) | Factor (dB) | PPSD (dBm) | Limit (dBm) | Result |
|---------|-----------|---------------|-------------|------------|-------------|--------|
| Low | 2402 | -16.74 | 2.00 | -14.74 | 8.00 | PASS |
| Mid | 2441 | -16.64 | 2.00 | -14.64 | | PASS |
| High | 2480 | -16.88 | 2.00 | -14.88 | | PASS |




Test Plot

PPSD (CH Low)

Agilent 20:12:51 Jun 27, 2008

R T

Mkr1 2.401 980 0 GHz
-14.74 dBm




PPSD (CH Mid)

Agilent 20:21:31 Jun 27, 2008

R T

Mkr1 2.440 980 0 GHz
-14.64 dBm






PPSD (CH High)

Agilent 20:27:43 Jun 27, 2008

R T

Mkr1 2.479 980 5 GHz

-14.88 dBm



7.3 BAND EDGES MEASUREMENT


LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

Refer to attach spectrum analyzer data chart.



Test Data


Band Edges (CH-Low)

Detector mode: Peak

Polarity: Vertical

Agilent 14:26:43 Jun 20, 2008

R T




Detector mode: Average

Polarity: Vertical

Agilent 14:30:33 Jun 20, 2008

R T






Detector mode: Peak

Polarity: Horizontal

Agilent 14:15:54 Jun 20, 2008

R T




Detector mode: Average

Polarity: Horizontal

Agilent 14:12:01 Jun 20, 2008

R T





Band Edges (CH-High)

Detector mode: Peak

Polarity: Vertical

2 Agilent 14:22:32 Jun 20, 2008

R T

Mkr1 2.483 50 GHz
54.47 dB μ V


Ref 110 dB μ V

Atten 20 dB

#Peak
Log
10
dB/

DI
74.0
dB μ V
LgAv

M1 S2
S3 FC
A
E(f):
FTun
Swp



Start 2.450 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

Stop 2.500 00 GHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Vertical

Agilent 14:24:13 Jun 20, 2008

R T

Mkr1 2.483 50 GHz
39.53 dB μ V


Ref 110 dB μ V

Atten 20 dB

#Avg
Log
10
dB/

DI
54.0
dB μ V
PAvg

M1 S2
S3 FC
A
E(f):
FTun
Swp



Start 2.450 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Stop 2.500 00 GHz

Sweep 12.33 s (601 pts)




Detector mode: Peak

Polarity: Horizontal

Agilent 14:18:43 Jun 20, 2008

R T

Mkr1 2.483 50 GHz
44.88 dB μ V




Detector mode: Average

Polarity: Horizontal

Agilent 14:21:25 Jun 20, 2008

R T

Mkr1 2.483 50 GHz
35.55 dB μ V





7.4 FREQUENCY SEPARATION

LIMIT


According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |
| Spectrum Analyzer | R&S | FSP30 | 1093.4495.30 | 07/22/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW, VBW=30kHz, Adjust Span to 3 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data

| Channel Separation (MHz) | Limit (kHz) | Result |
|--------------------------|-----------------------|--------|
| 1.0 | 841kHz (20dB BW, Max) | Pass |




Test Plot

Measurement of Channel Separation

Agilent 18:58:10 Jun 25, 2008

R T

Δ Mkr1 1.000 MHz
0.12 dB




Test Plot

20 dB bandwidth(CH Mid)

Agilent 15:19:19 Jun 20, 2008

R T

Δ Mkr1 833 kHz
-0.18 dB






20 dB bandwidth(CH Low)

Agilent 15:13:31 Jun 20, 2008

R T

▲ Mkr1 841 kHz

-0.18 dB



Center 2.402 000 GHz

Span 3 MHz

#Res BW 30 kHz

#VBW 30 kHz

Sweep 4.04 ms (601 pts)


20 dB bandwidth (CH High)

Agilent 15:15:44 Jun 20, 2008

R T

▲ Mkr1 840 kHz

0.18 dB



Center 2.480 000 GHz

Span 3 MHz

#Res BW 30 kHz

#VBW 30 kHz

Sweep 4.04 ms (601 pts)



7.5 NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = 1ms and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = 1ms.
4. Set the spectrum analyzer as RBW, VBW=510kHz,
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

Test Data

| Result (No. of CH) | Limit (No. of CH) | Result |
|--------------------|-------------------|--------|
| 79 | >15 | PASS |



Test Plot


Channel Number

2.4 GHz – 2.441 GHz

Agilent 17:52:25 Jun 27, 2008

R T

Mkr1 2.402 00 GHz
102.24 dB μ V




2.441 GHz – 2.4835 GHz

Agilent 17:56:56 Jun 27, 2008

R T

Mkr1 2.480 00 GHz
102.20 dB μ V





7.6 TIME OF OCCUPANCY (DWEELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

No non-compliance noted

Test Data

DH 1

CH Low: $0.42 * (1600/2)/79 * 31.6 = 134.4$ (ms)

CH Mid: $0.42 * (1600/2)/79 * 31.6 = 134.4$ (ms)

CH High: $0.43 * (1600/2)/79 * 31.6 = 137.6$ (ms)

| CH | Pulse Time (ms) | Total of Dwell (ms) | Period Time (s) | Limit (ms) | Result |
|------|--------------------|------------------------|--------------------|---------------|--------|
| Low | 0.42 | 134.4 | 31.60 | 400.00 | PASS |
| Mid | 0.42 | 134.4 | 31.60 | | PASS |
| High | 0.43 | 137.6 | 31.60 | | PASS |

DH 3

CH Low: $1.67 * (1600/4)/79 * 31.6 = 267.2$ (ms)

CH Mid: $1.68 * (1600/4)/79 * 31.6 = 268.8$ (ms)

CH High: $1.67 * (1600/4)/79 * 31.6 = 267.2$ (ms)

| CH | Pulse Time (ms) | Total of Dwell (ms) | Period Time (s) | Limit (ms) | Result |
|------|--------------------|------------------------|--------------------|---------------|--------|
| Low | 1.67 | 267.2 | 31.60 | 400.00 | PASS |
| Mid | 1.68 | 268.8 | 31.60 | | PASS |
| High | 1.67 | 267.2 | 31.60 | | PASS |

DH 5

CH Low: $2.93 * (1600/6)/79 * 31.6 = 312.5$ (ms)

CH Mid: $2.93 * (1600/6)/79 * 31.6 = 312.5$ (ms)

CH High: $2.92 * (1600/6)/79 * 31.6 = 311.5$ (ms)

| CH | Pulse Time (ms) | Total of Dwell (ms) | Period Time (s) | Limit (ms) | Result |
|------|--------------------|------------------------|--------------------|---------------|--------|
| Low | 2.93 | 312.5 | 31.60 | 400.00 | PASS |
| Mid | 2.93 | 312.5 | 31.60 | | PASS |
| High | 2.92 | 311.5 | 31.60 | | PASS |



Test Plot


DH 1

(CH Low)

Agilent 18:15:37 Jun 20, 2008

R T


Δ Mkr1 416.7 μs
-0.17 dB



Agilent 18:15:04 Jun 20, 2008

R T

Δ Mkr1 1.25 ms
-0.03 dB






(CH Mid)

Agilent 21:46:50 Jun 20, 2008

R T


Δ Mkr1 416.7 μs
0.01 dB



Agilent 21:46:06 Jun 20, 2008

R T

Δ Mkr1 1.25 ms
-0.01 dB






(CH High)

Agilent 21:50:19 Jun 20, 2008

R T


Δ Mkr1 425 μs
0.30 dB



Agilent 21:49:52 Jun 20, 2008

R T

Δ Mkr1 1.25 ms
0.00 dB






DH 3

(CH Low)

Agilent 16:40:06 Jun 20, 2008

R T


Δ Mkr1 1.667 ms
-0.04 dB



Agilent 16:40:51 Jun 20, 2008

R

Δ Mkr1 2.5 ms
-0.03 dB






(CH Mid)

Agilent 16:45:18 Jun 20, 2008

R T


▲ Mkr1 1.683 ms
-0.14 dB



Agilent 16:46:08 Jun 20, 2008

R

▲ Mkr1 2.5 ms
-0.01 dB






(CH High)

Agilent 16:50:26 Jun 20, 2008

R


▲ Mkr1 1.667 ms
-0.15 dB



Agilent 16:51:20 Jun 20, 2008

R

▲ Mkr1 2.5 ms
-0.01 dB






DH5

(CH Low)

Agilent 16:41:45 Jun 20, 2008

R T


Δ Mkr1 2.933 ms
-0.14 dB



Agilent 16:42:20 Jun 20, 2008

R T

Δ Mkr1 3.75 ms
-0.02 dB






(CH Mid)

Agilent 16:47:14 Jun 20, 2008

R T


▲ Mkr1 2.933 ms
0.07 dB



Agilent 16:46:08 Jun 20, 2008

R

▲ Mkr1 2.5 ms
-0.01 dB






(CH High)

Agilent 16:52:28 Jun 20, 2008

R T


Δ Mkr1 2.917 ms
-0.06 dB



Agilent 16:52:42 Jun 20, 2008

R

Δ Mkr1 3.75 ms
0.00 dB





SPURIOUS EMISSIONS

7.7 Conducted Measurement

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted




Test Plot

CH Low

30MHz – 2.9GHz

Agilent 16:29:29 Jun 20, 2008


R T



2.9GHz – 26.5GHz

Agilent 16:30:36 Jun 20, 2008

R T






CH Mid

30MHz – 2.9GHz

Agilent 16:31:46 Jun 20, 2008


R T



2.9GHz – 26.5GHz

Agilent 16:32:27 Jun 20, 2008

R T






CH High

30MHz – 2.9GHz

Agilent 16:34:35 Jun 20, 2008


R T



2.9GHz – 26.5GHz

Agilent 16:35:15 Jun 20, 2008

R T





7.7.2 Radiated Emissions

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (mV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 30-88 | 100* | 3 |
| 88-216 | 150* | 3 |
| 216-960 | 200* | 3 |
| Above 960 | 500 | 3 |

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

| Frequency (Hz) | Field Strength (μ V/m at 3-meter) | Field Strength (dB μ V/m at 3-meter) |
|----------------|---|---|
| 30-88 | 100 | 40 |
| 88-216 | 150 | 43.5 |
| 216-960 | 200 | 46 |
| Above 960 | 500 | 54 |


MEASUREMENT EQUIPMENT USED


| 966 RF CHAMBER 2 | | | | |
|-------------------|--------------|-----------|--------------------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Spectrum Analyzer | Agilent | E4446A | US44300399 | 02/24/2009 |
| EMI Test Receiver | R&S | ESCI | 1166.5950 03 | 01/13/2009 |
| Pre-Amplifier | MITEQ | N/A | AFS42-00102650-42-10P-42 | 02/14/2009 |
| Bilog Antenna | SCHWAZBECK | CBL6143 | 5082 | 06/09/2009 |
| Turn Table | EMCO | 2081-1.21 | N/A | N.C.R |
| Antenna Tower | CT | N/A | N/A | N.C.R |
| Controller | CT | N/A | N/A | N.C.R |
| RF Comm. Test set | HP | 8920B | US36142090 | N.C.R |
| Site NSA | C&C | N/A | N/A | 06/09/2009 |
| Horn Antenna | TRC | N/A | N/A | 03/04/2009 |
| Signal Generator | Anritsu | MG3694A | #050125 | 02/24/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration

Below 1 GHz



Above 1 GHz**TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.



TEST RESULTS

Below 1 GHz

Operation Mode: Normal**Test Date:** August 06,2008**Temperature:** 20°C**Tested by:** Breeze Jiang**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

| Freq. (MHz) | Ant.Pol. H/V | Detector Mode (PK/QP) | Reading (dBuV) | Factor (dB) | Actual FS (dBuV/m) | Limits 3m (dBuV/m) | Safe Margin (dBuV/m) |
|----------------|-----------------|-----------------------------|-------------------|----------------|-----------------------|-----------------------|-------------------------|
| 103.800 | V | Peak | 44.18 | -20.20 | 23.98 | 43.50 | -19.52 |
| 112.800 | V | Peak | 49.11 | -19.85 | 29.26 | 43.50 | -14.24 |
| 207.750 | V | Peak | 47.84 | -17.31 | 30.53 | 43.50 | -12.97 |
| 417.833 | V | Peak | 33.43 | -11.08 | 22.35 | 46.00 | -23.65 |
| 428.333 | V | Peak | 35.88 | -10.80 | 25.08 | 46.00 | -20.92 |
| 568.333 | V | Peak | 39.80 | -7.62 | 32.18 | 46.00 | -13.82 |
| 87.600 | H | Peak | 44.79 | -20.25 | 24.54 | 40.00 | -15.46 |
| 160.500 | H | Peak | 48.02 | -18.97 | 29.05 | 43.50 | -14.45 |
| 268.950 | H | Peak | 43.37 | -15.72 | 27.65 | 46.00 | -18.35 |
| 400.333 | H | Peak | 40.18 | -11.55 | 28.63 | 46.00 | -17.37 |
| 702.500 | H | Peak | 34.98 | -4.88 | 30.10 | 46.00 | -15.90 |
| 903.166 | H | Peak | 35.42 | -2.54 | 32.88 | 46.00 | -13.12 |

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Above 1 GHz****Operation Mode:** TX(CH Low)**Test Date:** August 06, 2008**Temperature:** 20°C**Tested by:** Breeze Jiang**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1300.00 | V | 50.85 | --- | -10.52 | 40.33 | --- | 74.00 | 54.00 | -13.67 | Peak |
| 1710.00 | V | 49.57 | --- | -7.76 | 41.81 | --- | 74.00 | 54.00 | -12.19 | Peak |
| 2850.00 | V | 50.10 | --- | -2.51 | 47.59 | --- | 74.00 | 54.00 | -6.41 | Peak |
| 3866.67 | V | 45.99 | --- | 0.96 | 46.95 | --- | 74.00 | 54.00 | -7.05 | Peak |
| N/A | | | | | | | | | | |
| | | | | | | | | | | |
| 1326.67 | H | 49.34 | --- | -10.37 | 38.97 | --- | 74.00 | 54.00 | -15.03 | Peak |
| 1966.67 | H | 47.90 | --- | -5.72 | 42.18 | --- | 74.00 | 54.00 | -11.82 | Peak |
| 2663.33 | H | 47.96 | --- | -3.03 | 44.93 | --- | 74.00 | 54.00 | -9.07 | Peak |
| 3933.33 | H | 45.21 | --- | 1.04 | 46.25 | --- | 74.00 | 54.00 | -7.75 | Peak |
| N/A | | | | | | | | | | |
| | | | | | | | | | | |

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.



Operation Mode: TX(CH Mid)

Test Date: August 06,2008

Temperature: 20°C

Tested by: Breeze Jiang

Humidity: 70 % RH

Polarity: Ver. / Hor.

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1380.00 | V | 49.89 | --- | -10.08 | 39.81 | --- | 74.00 | 54.00 | -14.19 | Peak |
| 1713.33 | V | 46.87 | --- | -7.73 | 39.14 | --- | 74.00 | 54.00 | -14.86 | Peak |
| 2633.33 | V | 47.46 | --- | -3.11 | 44.35 | --- | 74.00 | 54.00 | -9.65 | Peak |
| 3583.33 | V | 47.41 | --- | -0.53 | 46.88 | --- | 74.00 | 54.00 | -7.12 | Peak |
| N/A | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| 1410.00 | H | 50.94 | --- | -9.91 | 41.03 | --- | 74.00 | 54.00 | -12.97 | Peak |
| 1793.33 | H | 49.91 | --- | -7.10 | 42.81 | --- | 74.00 | 54.00 | -11.19 | Peak |
| 2640.00 | H | 49.72 | --- | -3.09 | 46.63 | --- | 74.00 | 54.00 | -7.37 | Peak |
| 3716.67 | H | 46.07 | --- | -0.96 | 45.11 | --- | 74.00 | 54.00 | -8.89 | Peak |
| N/A | | | | | | | | | | |
| | | | | | | | | | | |

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.



Operation Mode: TX(CH High)

Test Date: August 06,2008

Temperature: 20°C

Tested by: Breeze Jiang

Humidity: 70 % RH

Polarity: Ver. / Hor.

| Freq. (MHz) | Ant. Pol H/V | Peak Reading (dBuV) | AV Reading (dBuV) | Ant. / CL CF (dB) | Actual Fs | | Peak Limit (dBuV/m) | AV Limit (dBuV/m) | Margin (dB) | Remark |
|----------------|-----------------|---------------------------|-------------------------|-------------------------|------------------|----------------|---------------------------|-------------------------|----------------|--------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | | |
| 1380.00 | V | 49.61 | --- | -10.08 | 39.53 | --- | 74.00 | 54.00 | -14.47 | Peak |
| 2090.00 | V | 48.67 | --- | -5.10 | 43.57 | --- | 74.00 | 54.00 | -10.43 | Peak |
| 2663.33 | V | 48.41 | --- | -3.03 | 45.38 | --- | 74.00 | 54.00 | -8.62 | Peak |
| 4608.33 | V | 45.38 | --- | 2.31 | 47.69 | --- | 74.00 | 54.00 | -6.31 | Peak |
| N/A | | | | | | | | | | |
| | | | | | | | | | | |
| 1223.33 | H | 51.28 | --- | -10.94 | 40.34 | --- | 74.00 | 54.00 | -13.66 | Peak |
| 1810.00 | H | 49.95 | --- | -6.96 | 42.99 | --- | 74.00 | 54.00 | -11.01 | Peak |
| 2630.00 | H | 49.53 | --- | -3.12 | 46.41 | --- | 74.00 | 54.00 | -7.59 | Peak |
| 3933.33 | H | 45.21 | --- | 1.04 | 46.25 | --- | 74.00 | 54.00 | -7.75 | Peak |
| N/A | | | | | | | | | | |
| | | | | | | | | | | |

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

7.8 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

| Frequency Range (MHz) | Limits (dBμV) | |
|-----------------------|---------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

| Conducted Emission Test Site G | | | | |
|--------------------------------|---------------|--------------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| ESCI EMI TEST RECEIV.ESCI | ROHDE&SCHWARZ | 1166.5950 03 | 100088 | 02/24/2009 |
| LISN | EMCO | 3825/2 | 1371 | 02/24/2009 |
| LISN | EMCO | 3825/2 | 8901-1459 | 02/24/2009 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Operation Mode: Normal **Test Date:** August 06,2008
Temperature: 22°C **Humidity:** 67% RH
Tested by: Breeze Jiang

| FREQ MHz | PEAK RAW dBuV | Q.P. RAW dBuV | AVG RAW dBuV | Q.P. Limit dBuV | AVG Limit dBuV | Q.P. Margin dB | AVG Margin dB | NOTE |
|-------------|---------------------|---------------------|--------------------|-----------------------|----------------------|----------------------|---------------------|------|
| 0.283 | 46.40 | --- | --- | 62.19 | 52.19 | --- | -5.79 | L1 |
| 0.561 | 46.75 | 51.06 | 41.28 | 56.00 | 46.00 | -4.94 | -4.72 | L1 |
| 0.713 | 47.24 | 49.67 | 40.51 | 56.00 | 46.00 | -6.33 | -5.49 | L1 |
| 0.861 | 47.80 | 50.89 | 40.32 | 56.00 | 46.00 | -5.11 | -5.68 | L1 |
| 1.043 | 42.93 | 48.63 | 38.79 | 56.00 | 46.00 | -7.37 | -7.21 | L1 |
| 10.601 | 42.88 | 52.41 | 43.51 | 60.00 | 50.00 | -7.59 | -6.49 | L1 |
| 0.213 | 49.05 | --- | --- | 64.20 | 54.20 | --- | -5.15 | L2 |
| 0.287 | 47.43 | --- | --- | 62.08 | 52.08 | --- | -4.65 | L2 |
| 0.772 | 47.13 | 50.88 | 39.58 | 56.00 | 46.00 | -5.12 | -6.42 | L2 |
| 0.876 | 44.96 | 48.22 | 38.46 | 56.00 | 46.00 | -7.78 | -7.54 | L2 |
| 1.073 | 43.79 | --- | --- | 56.00 | 46.00 | --- | -2.21 | L2 |
| 1.295 | 43.26 | --- | --- | 56.00 | 46.00 | --- | -2.74 | L2 |

Note:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. “---” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9KHz.
5. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

APPENDIX 1

PHOTOGRPHS OF TEST SETUP

Radiated Emission Set up Photos



Conducted Emission Set Up Photos

