APPLICATION FOR CERTIFICATION On Behalf of

RedOctane, Inc.

Guitar Hero World Tour - PS2 Wireless Guitar

Model Number: 95449.806

FCC ID: VFIBW95449806

Prepared for: RedOctane, Inc.

955 Benecia Avenue Sunnyvale, CA 94085, United States

Prepared By: Audix Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F08325

Date of Test : Jun.17~24, 2008

Date of Report : Jul.08, 2008

TABLE OF CONTENTS

De	scripti	on	Page
1.	SUN	MARY OF STANDARDS AND RESULTS	1-1
	1.1.	Description of Standards and Results	1-1
2.	GEN	NERAL INFORMATION	2-1
	2.1.	Description of Device (EUT)	2-1
	2.2.	Tested Supporting System Details	
	2.3.	Test Facility	2-2
	2.4.	Test Uncertainty	
3.	POV	WER LINE CONDUCTED EMISSION TEST	3-1
	3.1.	Test Equipments	3-1
	3.2.	Block Diagram of Test Setup	
	3.3.	Power Line Conducted Emission Test Limits	
	3.4.	Configuration of EUT on Test	
	3.5.	Operating Condition of EUT	
	3.6.	Test Procedure	
	3.7.	Power Line Conducted Emission Test Results	
4.		DIATED EMISSION TEST	
	4.1.	Test Equipment	
	4.2.	Block Diagram of Test Setup	
	4.3. 4.4.	Radiated Emission Limit Standard: FCC 15.249 EUT Configuration on Test	
	4.4. 4.5.	Operating Condition of EUT	
	4.6.	Test Procedure	
	4.7.	Radiated Emission Test Results	
5.	BAN	ND EDGE COMPLIANCE TEST	
	5.1.	Test Equipment	
	5.2.	Limit	
	5.3.	Test Produce	
	5.4.	Test Results	5-1
6.	20D	B BANDWIDTH TEST	6-1
	6.1.	Test Equipment	6-1
	6.2.	Test Information	6-1
	6.3.	Test Results	6-1
7.	DEV	VIATION TO TEST SPECIFICATIONS	7-1
8.	PHO	OTOGRAPH	8-1
	8.1.	Photos of Power Line Conducted Emission Test	8-1
	8.2.	Photos of Radiated Emission Test (In Anechoic Chamber)	

REPORT CERTIFICATION TEST

Applicant

RedOctane, Inc.

Manufacturer

Berway Technology Ltd.

EUT Description

Guitar Hero World Tour - PS2 Wireless Guitar

FCC ID

VFIBW95449806

(A) MODEL NO.

: 95449.806

(B) SERIAL NO.

: N/A

(C) POWER SUPPLY : DC 3.3V

(D) TEST VOLTAGE : DC 3.3V From PS2 AC 120V/60Hz

Test Procedure Used:

FCC Rules and Regulations Part 15 Subpart C 2007

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits for radiated and conducted emissions.

The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of tests. Also, this report shows that EUT is technically compliant with FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd.

Date of Test:

Jun.17~ 24, 2008

Prepared by:

Yo Yo Wang / Assistant

Reviewer:

Jamy Yu / Senior Engineer

Jamy Yu

图 信备料故(蓬納)有限公司 Audix Technology (Shenzhen) Co., Ltd.

EMC部門報告專用章

Stamp only for ENG Dept. Report

Signature:

Approved & Authorized Signer:

Ken Lu / Deputy Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION									
Description of Test Item	Standard	Results							
Power Line Conducted Emission Test	FCC Part 15C: 15.207 ANSI C63.4-2003	PASS							
Radiated Emission Test	FCC Part 15C: 15.249 ANSI C63.4-2003	PASS							
Band Edge Compliance Test	FCC Part 15: 15.249	PASS							
20dB Bandwidth Test	FCC Part 15: 15.215	PASS							

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Product name : Guitar Hero World Tour - PS2 Wireless Guitar

Model Number : 95449.806

FCC ID : VFIBW95449806

Operation frequency: 2410MHz~2470MHz

Modulation : MSK

Power Supply : DC 3.3V From PS2

(The supply voltage was varied between 85% and 115% of the nominal rated (120V/60Hz) supply voltage. And all the emissions include fundamental emissions had no change. So only the nominal power supply test data were recorded.)

Applicant : RedOctane, Inc.

955 Benecia Avenue Sunnyvale, CA 94085, United States

Manufacturer : Berway Technology Ltd.

Unit 1301-03, 13/F., No.88 Kwai Cheong Road, Kwai Chung,

N.T., H.K.

Date of Test : Jun.17~24, 2008

Date of Receipt : Jun.16, 2008

Sample Type : Prototype production

Note: This EUT has two parts, one is guitar, the other one is dongle. We test "dongle" in this report.

2.2. Tested Supporting System Details

2.2.1.TV

EMC CODE : ACS-EMC-TV01T

M/N : 1419A Manufacturer : TCL

Power cord : Unshielded, Undetachabled, 1.8m

2.2.2.PS2

Manufacturer : SONY

M/N : SCPH-39004

2.3. Test Facility

Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong,

China

3m Anechoic Chamber : Jun. 13, 2006 File on Federal Communication

Commission

Registration Number: 90454

3m & 10m Anechoic Chamber : Jan. 31, 2007 File on Federal Communication

Commission

Registration Number: 794232

EMC Lab. : Accredited by DATech, German

Registration Number: DAT-P-091/99-01

Dec. 20, 2007

Accredited by NVLAP, USA NVLAP Code: 200372-0

Apr.01, 2008

2.4. Test Uncertainty

No.	Item	MU	Remark
1.	Uncertainty for Conducted Emission Test	2.02dB	
2	Uncertainty for Radiation Emission test	3.44 dB	Polarize: V
Ζ.	in 3m chamber	3.96 dB	Polarize: H
		3.46 dB	Distance: 10m Polarize: V
2	Uncertainty for Radiation Emission test	3.82 dB	Distance: 10m Polarize: H
3.	in 10m chamber	3.64 dB	Distance: 3m Polarize: V
		4.02 dB	Distance: 3m Polarize: H


3. POWER LINE CONDUCTED EMISSION TEST

3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS10	844077/020	Mar 07, 08	1 Year
2.	L.I.S.N.#2	Kyoritsu	KNW-407	8-1636-1	May 10,08	1 Year
3.	L.I.S.N.#3	EMCO	3825/2	9006-1660	May 10,08	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 1	May 10,08	1 Year
5.	RF Cable	Fujikura	3D-2W	LISN Cable 1#	Jan 09, 08	1/2 Year
6.	Coaxial	Anritsu	MP59B	M55367	Jan 09, 08	1/2 Year
	Switch					
7.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100340	Jan 09, 08	1/2 Year

3.2. Block Diagram of Test Setup

3.2.1. Block diagram of connection between the EUT and simulators



(EUT: Guitar Hero World Tour - PS2 Wireless Guitar)

3.3. Power Line Conducted Emission Test Limits

	Maximum RF Line Voltage				
Frequency	Quasi-Peak Level	Average Level			
	$dB(\mu V)$	$dB(\mu V)$			
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*			
500kHz ~ 5MHz	56	46			
5MHz ~ 30MHz	60	50			

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Guitar Hero World Tour - PS2 Wireless Guitar (EUT)

Model Number : 95449.806 Serial Number : N/A

3.4.2. Support Equipment: As Tested Supporting System Detail, in Section 2.2..

3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT as shown in Section 3.2..
- 3.5.2. Let the EUT work in test modes (TX Mode) and test it.

3.6. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PS2 connected to the power mains through a line impedance stabilization network (L.I.S.N. 2#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#3). Power on the PS2 and let it work normally, we use a test software, let EUT working in test mode, then test it. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2003 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESHS10) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

The test result are reported on Section 3.7.

3.7. Power Line Conducted Emission Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)




NO.6 Ke Feng Road, Block 52, Shenzhen Science&Industry Park Nantou, Shenzhen, Guang dong, China. Te1:+86-755-26639495

Fax: +86-755-26632877 Postcode: 518057

Data no :2

LISN phase:





Trace: (Discrete)

Site no : Audix No.1 Conduction ;--KNU407 1# VA Dis./Ant.

:FCC PART 15 C

Env./Ins. :29.5*C/55% ESHS 10

Engineer :Longe :Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating :DC 3.3V From PS2 AC 120V/60Hz

Test Mode :TX

Limit

M/N:95449.806 (Dongle)

		LISN	Cable		Emissio	n		
No	Freq (MHz)	Factor (dB)	Loss (dB)	Reading (dBuV)	Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18	0.29	10.15	39.08	49.52	64.49	14.97	QP
2	0.24	0.28	10.15	36.31	46.74	62.11	15.37	QP
3	0.30	0.26	10.15	29.90	40.31	60.26	19.95	QP
4	0.84	0.15	10.14	27.64	37.93	56.00	18.07	QP
5	2.54	0.10	10.16	27.70	37.96	56.00	18.04	QP
6	21.22	0.46	10.38	30.42	41.26	60.00	16.74	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss+Reading.

2. If the average limit is met when useing a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




NO.6 Ke Feng Road, Block 52, Shenzhen Science&Industry Park Nantou, Shenzhen, Guang dong, China. Te1:+86-755-26639495

Fax: +86-755-26632877 Postcode: 518057

Data no :1

Engineer :Longe

LISN phase:



Site no : Audix No.1 Conduction :--KNU407 1# VB Dis./Ant. Limit

:FCC PART 15 C

Env./Ins. :29.5*C/55% ESHS 10

:Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating :DC 3.3V From PS2 AC 120V/60Hz

Test Mode :TX

M/N:95449.806 (Dongle)

		LISN	Cable		Emission			
No	Freq (MHz)	Factor (dB)	Loss (dB)	Reading (dBuV)	Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	0.24	10.15	39.61	50.00	66.00	16.00	QP
2	0.54	0.18	10.14	27.15	37.47	56.00	18.53	QP
3	0.90	0.10	10.15	27.47	37.72	56.00	18.28	QP
4	1.31	0.07	10.15	27.31	37.53	56.00	18.47	QP
5	2.60	0.03	10.16	28.21	38.40	56.00	17.60	QP
6	21.02	0.44	10.38	31.27	42.09	60.00	17.91	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss+Reading.

2. If the average limit is met when useing a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION TEST

4.1. Test Equipment

Frequency rang: 30~1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Jun 09,08	1/2 Year
2.	EMI Spectrum	Agilent	E7403A	MY42000106	May 10, 08	1 Year
3.	Test Receiver	Rohde & Schwarz	ESVS20	830350/005	May 10, 08	1 Year
4.	Amplifier	HP	8447D	2648A04738	Jan 09, 08	1/2 Year
5.	Bilog Antenna	Schaffner	CBL6112D	25237	Feb 21, 08	1 Year
6.	RF Cable	JINGCHENG	KLMR400	3# Chamber No.1	Jan 09, 08	1/2 Year
7.	RF Cable	JINGCHENG	JBY400	3# Chamber No.2	Jan 09, 08	1/2 Year
8.	RF Cable	JINGCHENG	JBY400	3# Chamber No.3	Jan 09, 08	1/2 Year
9.	RF Cable	JINGCHENG	JBY400	3# Chamber No.4	Jan 09, 08	1/2 Year
10.	Coaxial Switch	Anritsu	MP59B	M73989	Jan 09, 08	1/2 Year

Frequency rang: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	MY41440292	May 10, 08	1 Year
2.	Amp	HP	8449B	3008A00863	May 10, 08	1 Year
3.	Antenna	EMCO	3115	9607-4877	May 27, 08	1.5 Year
4	Antenna	EMCO	3116	00060088	May 28, 07	1.5Year
5.	HF Cable	Hubersuhne	Sucoflex 104	-	May 10, 08	1 Year

4.2. Block Diagram of Test Setup


4.2.1. Block Diagram of connection between EUT and simulators



(EUT: Guitar Hero World Tour - PS2 Wireless Guitar)

4.2.2. Anechoic Chamber Setup Diagram

ANTENNA TOWER



GROUND PLANE

4.3. Radiated Emission Limit Standard: FCC 15.249

FREQUENCY	DISTANCE	FIELD STRENGTHS LIMIT		
MHz	Meters	μV/m	$dB(\mu V)/m$	
30 ~ 88	3	100	40.0	
88 ~ 216	3	150	43.5	
216 ~ 960	3	200	46.0	
960 ~ 1000	3	500	54.0	
Fundamental frequency	3	114.0 dB(μ	V)/m (Peak)	
2.4GHz2.4835GHz:		94.0 dB(μV	/)/m (Average)	
Above 1000	3	Other:		
		74.0 dB(µV	/)/m (Peak)	
		54.0 dB(μV	V)/m (Average)	

Remark : (1) Emission level $dB\mu V = 20 \log Emission$ level $\mu V/m$

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Guitar Hero World Tour - PS2 Wireless Guitar (EUT)

Model Number : 95449.806 Serial Number : N/A

4.4.2. Support Equipment: As Tested Supporting System Detail, in Section 2.2.

4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT as shown in Section 4.2..
- 4.5.2. Let the EUT work in test modes (TX Mode) and test it.

4.6. Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2003 on radiated emission Test.

The bandwidth of the EMI test receiver (R&S ESVS20) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW 10Hz VBW for average emission above 1GHz

The frequency range from 30MHz to 10th (25GHz) harmonic are checked.

4.7. Radiated Emission Test Results


PASS.


All the emissions from 18GHz~25GHz are Peak measured and comply with Average limit.



No.6 Ke Feng Road, B1;ck 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China

Tel:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057





Trace: (Discrete)

Site no. : 3m chamber Data no. : 11

Dis. / Ant. : 3m CBL6112D Ant. pol. : HORIZONTAL

Limit : FCC PART15 C

Env. / Ins.: 24*C/56% ESVS20 Engineer : Jamy EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx

Model No. : 95449.806(Dongle)

	Freq.	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emissio Level (dBuV/m)	n Limits (dBuV/m)	Margin (dB)	Remark
1	130.88	10.83	1.54	12.55	24.92	43.50	18.58	QP
2	293.84	15.07	2.18	15.94	33.19	46.00	12.81	QP
3	305.48	16.00	2.21	21.52	39.73	46.00	6.27	QP
4	552.83	19.32	2.88	11.82	34.02	46.00	11.98	QP
5	589.69	19.90	3.09	18.09	41.08	46.00	4.92	QP
6	643.04	20.22	3.26	15.27	38.75	46.00	7.25	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.



No.6 Ke Feng Road, B1;ck 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China

Tel:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057

File: D:\2008 report data\R\RedOctane\AC\$8QH105-1.EMI (11) 80 Level (dBuV/m)



Trace: (Discrete)

: 3m chamber Data no. : 10 Site no. Dis. / Ant. : 3m CBL6112D Ant. pol. : VERTICAL

: FCC PART15 C

Env. / Ins.: 24*C/56% ESVS20 Engineer : Jamy : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx


Model No. : 95449.806(Dongle)

		Cable		Emissio	n		
Freq.	Factor (dB/m)	Loss (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
.94	10.10	1.55	14.78	26.43	43.50	17.07	QP
.84	12.43	2.18	21.43	36.04	46.00	9.96	QP
.38	15.00	2.51	16.19	33.70	46.00	12.30	QP
.69	18.70	3.09	19.01	40.80	46.00	5.20	QP
.04	19.50	3.26	16.66	39.42	46.00	6.58	QP
.94	20.40	3.50	14.93	38.83	46.00	7.17	QP
	.04	.04 19.50	.04 19.50 3.26	.04 19.50 3.26 16.66	.04 19.50 3.26 16.66 39.42	.04 19.50 3.26 16.66 39.42 46.00	.04 19.50 3.26 16.66 39.42 46.00 6.58

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.



Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 29

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH Low 2410MHz M/N : 95449.806(Dongle)

		Ant.	Cable	Amp		Emission	L		
	Freq. (MHz)				_		Limits (dBuV/m)	_	Remark
1 2	2410.00 4820.00						114.00 74.00	28.19 19.73	Peak Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 30

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH Low 2410MHz M/N : 95449.806(Dongle)

	Freq.	Ant. Factor (dB/m)	Cable Loss (dB)		Reading		Limits (dBuV/m)	_	Remark
1 2	2410.00 4820.00			35.18 34.49		84.56 50.50	94.00 54.00	9.44 3.50	Average Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 27
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH Low 2410MHz M/N : 95449.806(Dongle)


		Ant.	Cable	Amp		Emission	ι		
	Freq. (MHz)				_		Limits (dBuV/m)	_	Remark
1 2	2410.00 4820.00					83.98 54.72		30.02 19.28	Peak Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057





Site no. : 3# Chamber Data no. : 28 Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

: FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Low 2410MHz : 95449.806(Dongle)


		Ant.	Cable	Amp		Emission			
	Freq.				_		Limits	_	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2410.00	29.03	6.73	35.18	73.41	73.99	94.00	20.01	Average
2	4820.00	34.02	10.54	34.49	40.52	50.59	54.00	3.41	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.

2. The emission levels that are 20dB below the official $% \left(1\right) =\left(1\right) ^{2}$ limit are not reported.



Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 31

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH Mid 2440MHz M/N : 95449.806(Dongle)


		Ant.	Cable	Amp		Emission			
	Freq.				_		Limits (dBuV/m)	_	Remark
1 2	2440.00 4880.00							26.09 20.82	Peak Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057





Site no. : 3# Chamber Data no. : 32

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH Mid 2440MHz M/N : 95449.806(Dongle)

Ant	. Cable Amp	Emission	
•		_	mits Margin Remark
(MHz) (dB/	'm) (dB) (dB)	(dBuV) (dBuV/m)(dI	BuV/m) (dB)
1 2440.00 29.1	l1 6.80 35.17	' 84.00 84.74 9 ⁴	1.00 9.26 Average
2 4880.00 34.1	l6 10.56 34.48	40.45 50.69 54	1.00 3.31 Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 33
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH Mid 2440MHz M/N : 95449.806(Dongle)


		Ant.	Cable	Amp		Emission			
	Freq. (MHz)				_		Limits (dBuV/m)	_	Remark
1 2	2440.00 4880.00							28.18 22.66	Peak Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057





Site no. : 3# Chamber Data no. : 34
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH Mid 2440MHz M/N : 95449.806(Dongle)

	Freq.	Factor	Factor	Reading	Emission Level (dBuV/m)	Limits	_	Remark
1 2	2440.00 4880.00		 				11.12 4.52	Average Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 37

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH High 2470MHz M/N : 95449.806(Dongle)


	Freq. (MHz)	Factor	Factor	Reading	Limits (dBuV/m)	_	Remark
1 2	2470.00 4940.00					26.23 18.34	Peak Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057





Site no. : 3# Chamber Data no. : 38

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH High 2470MHz M/N : 95449.806(Dongle)

	Freq.	Factor	Factor	Reading	Emission Level (dBuV/m)	Limits	_	Remark
1 2	2470.00 4940.00		 		85.16 50.39		8.84 3.61	Average Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 35
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH High 2470MHz M/N : 95449.806(Dongle)


	Freq. (MHz)	Factor	Factor	Reading	Limits (dBuV/m)	_	Remark
1 2	2470.00 4940.00		 		 	28.23 19.34	Peak Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



Fax:+86-755-26632877 Postcode:518057





Site no. : 3# Chamber Data no. : 36
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz


Test Mode : Tx CH High 2470MHz M/N : 95449.806(Dongle)

	Ant.	Cable	Amp		Emission			
Freq.				_	Level		_	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1 2470.00	29.15	6.87	35.16	83.87	84.73	94.00	9.27	Average
2 4940.00	34.34	10.58	34.46	39.64	50.10	54.00	3.90	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



No.6 Ke Feng Road, B1; ck 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China Te1:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057




Site no. : 3# Chamber Data no. : 39
Dis. / Ant. : 3m 3116 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Low 2410MHz M/N : 95449.806(Dongle)



Site no. : 3# Chamber Data no. : 40
Dis. / Ant. : 3m 3116 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 AV 2.4


Env. / Ins.: 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Low 2410MHz M/N : 95449.806(Dongle)



No.6 Ke Feng Road, B1;ck 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China Te1:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057




Site no. : 3# Chamber Data no. : 42
Dis. / Ant. : 3m 3116 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins.: 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Mid 2440MHz M/N : 95449.806(Dongle)



Site no. : 3# Chamber Data no. : 41
Dis. / Ant. : 3m 3116 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 AV 2.4


Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Mid 2440MHz M/N : 95449.806(Dongle)



No.6 Ke Feng Road, B1; ck 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China Te1:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057




Site no. : 3# Chamber Data no. : 43
Dis. / Ant. : 3m 3116 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins.: 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH High 2470MHz M/N : 95449.806(Dongle)



Site no. : 3# Chamber Data no. : 44
Dis. / Ant. : 3m 3116 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour -PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH High 2470MHz M/N : 95449.806(Dongle)

5. BAND EDGE COMPLIANCE TEST

5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May,10, 08	1 Year
2	Horn Antenna	EMCO	3115	9607-4877	May,27, 08	1.5 Year
3	Amplifier	HP	8449B	3008A00863	May,10, 08	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX	182769/4	May,28, 08	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX	182768/4	May,28, 08	1 Year
6	RF Cable	Hubersuhner	SUCOFLEX	182771/4	May,28, 08	1 Year

5.2. Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in section 15.209, which is the lesser attenuation.

5.3. Test Produce

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
- 2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO


5.4. Test Results

Pass (The testing data was attached in the next pages.)



No.6 Ke Feng Road,B1;ck 52, ShenZhen Science & Industry Park Noutou,ShenZhen,GuangDong,China

Tel:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 45

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Low 2410MHz Model No. : 95449.806(Dongle)


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	•	Reading		Limits (dBuV/m)	Margin (dB)	Remark
1	2352.65	28.91	6.67	35.19	51.61	52.00	74.00	22.00	Peak
2	2358.89	28.91	6.69	35.19	52.31	52.72	74.00	21.28	Peak
3	2390.00	28.99	6.71	35.18	49.34	49.86	74.00	24.14	Peak
4	2400.00	28.99	6.73	35.18	49.73	50.27	74.00	23.73	Peak
5	2409.98	29.03	6.73	35.18	88.97	89.55	114.00	24.45	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.





Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 46

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Low 2410MHz Model No. : 95449.806(Dongle)


	Freq.	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
 1	2336.79	28.87	6.67	35.20	33.34	33.68	54.00	20.32	Average
2	2359.15	28.91	6.69	35.19	33.32	33.73	54.00	20.27	Average
3	2370.85	28.95	6.69	35.19	33.51	33.96	54.00	20.04	Average
4	2390.00	28.99	6.71	35.18	32.83	33.35	54.00	20.65	Average
5	2400.00	28.99	6.73	35.18	33.17	33.71	54.00	20.29	Average
6	2409.98	29.03	6.73	35.18	84.35	84.93	94.00	9.07	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.





Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 47
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Low 2410MHz Model No. : 95449.806(Dongle)


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading	Emission Level (dBuV/m)		Margin (dB)	Remark
1	2331.98	28.83	6.65	35.20	48.03	48.31	74.00	25.69	Peak
2	2359.15	28.91	6.69	35.19	48.64	49.05	74.00	24.95	Peak
3	2377.35	28.95	6.71	35.19	48.37	48.84	74.00	25.16	Peak
4	2390.00	28.99	6.71	35.18	46.23	46.75	74.00	27.25	Peak
5	2400.00	28.99	6.73	35.18	46.30	46.84	74.00	27.16	Peak
6	2409.98	29.03	6.73	35.18	85.54	86.12	114.00	27.88	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.





Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 48
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH Low 2410MHz Model No. : 95449.806(Dongle)


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2	2336.79 2359.15	28.87 28.91	6.67 6.69		32.75 36.64	33.09 37.05	54.00 54.00	20.91 16.95	Average Average
3	2390.00	28.99			31.81	32.33	54.00	21.67	Average
4 5	2400.00 2409.98	28.99 29.03	6.73 6.73	35.18 35.18	32.13 83.37	32.67 83.95	54.00 94.00	21.33 10.05	Average Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



No.6 Ke Feng Road,B1;ck 52, ShenZhen Science & Industry Park Noutou,ShenZhen,GuangDong,China

Tel:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 49
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 PEAK 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH High 2470MHz Model No. : 95449.806(Dongle)


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	•	Reading			Margin (dB)	Remark
1	2469.96	29.15	6.87	35.16	85.00	85.86	114.00	28.14	Peak
2	2483.50	29.19	6.87	35.16	46.21	47.11	74.00	26.89	Peak
3	2485.20	29.19	6.87	35.16	47.12	48.02	74.00	25.98	Peak
4	2500.00	29.23	6.91	35.15	46.49	47.48	74.00	26.52	Peak
5	2533.92	29.35	6.96	35.14	47.16	48.33	74.00	25.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



No.6 Ke Feng Road,B1;ck 52, ShenZhen Science & Industry Park Noutou,ShenZhen,GuangDong,China

Tel:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 50
Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : VERTICAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH High 2470MHz Model No. : 95449.806(Dongle)


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)		Reading (dBuV)	Emission Level (dBuV/m)	Limits	Margin (dB)	Remark
1 2	2469.96	29.15	6.87	35.16	83.63	84.49	94.00	9.51	Average
	2483.50	29.19	6.87	35.16	31.98	32.88	54.00	21.12	Average
3	2496.00	29.23		35.15	32.89	33.88	54.00	20.12	Average
4	2500.00	29.23	6.91	35.15	31.94	32.93	54.00	21.07	Average
5	2535.12	29.35	6.96	35.14	32.04	33.21	54.00	20.79	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



No.6 Ke Feng Road, B1; ck 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China

Tel:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057



Data no. : 51

Site no. : 3# Chamber Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

: FCC PART 15 PEAK 2.4 Limit

Env. / Ins. : 23*C/54% Engineer : Sunny : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH High 2470MHz Model No. : 95449.806(Dongle)


	_	Ant.	Cable	•		Emission			
	Freq.	Factor	Loss		Reading			_	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(aBuv)	(aBuv/m)	(dBuV/m)	(dB)	
1	2469.96	29.15	6.87	35.16	87.96	 88.82	114.00	25.18	Peak
2	2483.50	29.19	6.87	35.16	43.80	44.70	74.00	29.30	Peak
3	2484.36	29.19	6.87	35.16	46.64	47.54	74.00	26.46	Peak
4	2493.72	29.23	6.91		45.95	46.94	74.00	27.06	Peak
5	2500.00	29.23	6.91	35.15	44.40	45.39	74.00	28.61	Peak
6	2544.00	29.41	6.96	35.13	46.00	47.24	74.00	26.76	Peak
7	2563.32	29.47	6.98	35.13	46.04	47.36	74.00	26.64	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.



No.6 Ke Feng Road,B1;ck 52, ShenZhen Science & Industry Park Noutou,ShenZhen,GuangDong,China

Tel:+86-755-26639495-7 Fax:+86-755-26632877 Postcode:518057



Site no. : 3# Chamber Data no. : 52

Dis. / Ant. : 3m 3115 FACTOR Ant. pol. : HORIZONTAL

Limit : FCC PART 15 AV 2.4

Env. / Ins. : 23*C/54% Engineer : Sunny
EUT : Guitar Hero World Tour-PS2 Wireless Guitar

Power Rating: DC 3.3V From PS2 AC 120V/60Hz

Test Mode : Tx CH High 2470MHz Model No. : 95449.806(Dongle)

:	•		Cable Loss (dB)	Amp Factor (dB)	Reading	Emission Level (dBuV/m) (Margin :	Remark
2 2: 3 2: 4 2:	483.50 : 496.00 : 500.00 :	29.19 29.23 29.23	6.87 6.91 6.91	35.16 35.15 35.15	32.94 33.89 32.94	33.84 34.88	54.00	8.60 20.16 19.12 20.07 19.73	Average Average Average Average Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.

6. 20DB BANDWIDTH TEST

6.1. Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.
						Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May,10, 08	1 Year
2	Attenuator	Agilent	8491B	MY39262165	May,28, 08	1 Year
3	Bilog Antenna	Schaffner	CBL6112D	25238	Feb,21, 08	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX 102	2861812	May,28, 08	1Year
5	RF Cable	Hubersuhner	SUCOFLEX 102	28862212	May,28, 08	1 Year


6.2. Test Information


EUT:	Guitar Hero World Tour - PS2 Wireless Guitar
M/N:	95449.806
Test Date:	Jul.04, 2008
Ambient Temperature:	23℃
Relative Humidity:	54%
Test standard:	FCC PART 15C: 15.215
Test mode:	Transmitting
Test Frequency:	Low: 2410MHz Mid: 2440MHz High: 2470MHz
Test By:	Power

6.3. Test Results

СН	20dB Bandwidth (kHz)	Limit (kHz)	Conclusion
(Low)	1000		PASS
(Mid)	1008		PASS
(High)	908		PASS







7. DEVIATION TO TEST SPECIFICATIONS

[NONE]