



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822

Tel: +82-31-323-6008 Fax: +82-31-323-6010

<http://www.ltalab.com>

Dates of Tests: July 02 ~ 09, 2007

Test Report S/N: LR500190707B

Test Site : LTA CO., LTD.

## CERTIFICATIO OF COMPLIANCE

FCC ID.

**VFQ-NS-XV24**

APPLICANT

**JOYTOTO.CO.Ltd**

FCC Classification	:	FHSS Sequence Spread Spectrum (FHSS)
Manufacturing Description	:	Digital Audio Player
Manufacturer List	:	JOYTOTO.CO.Ltd
Model name	:	NS-4V24 , NS-8V24
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C; ANSI C-63.4-2003
Frequency Range	:	2402 ~ 2480MHz
RF power Class	:	2 (-6dBm ~ +4dBm)
Data of issue	:	July 10, 2007

This test report is issued under the authority of:

The test was supervised by:

Dong -Min JUNG, Technical Manager

Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION'S .....	3
2. INFORMATION'S ABOUT TEST ITEM .....	4
3. TEST REPORT .....	6
3.1 SUMMARY OF TESTS .....	6
3.2 TECHNICAL CHARACTERISTICS TEST .....	7
3.2.1 CARRIER FREQUENCY SEPARATION .....	7
3.2.2 NUMBER OF HOPPING FREQUENCIES .....	9
3.2.3 20 dB BANDWIDTH .....	12
3.2.4 TIME OF OCCUPANCY (Dwell Time) .....	14
3.2.5 TTANSMITTER OUTPUT POWER .....	16
3.2.6 BAND – EDGE (Conducted) .....	18
3.2.7 BAND - EDGE (Radiated) .....	27
3.2.8 FIELD STRENGTH OF HARMONICS .....	30
3.2.9 AC CONDUCTED EMISSIONS .....	34
 <b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS .....	37

## 1. General information's

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2007-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2009-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2008-03-28	FCC filing
VCCI	JAPAN	R2133, C2307	2008-06-22	VCCI registration
IC	CANADA	IC5799	2008-04-23	IC filing

## 2. Information's about test item

### 2-1 Applicant

Company name : JOYTOTO.CO.Ltd  
 Address : 3Fl.Sungwoo Bldg.,717-3 sooseo-dong, Kangnam-gu,  
 Seoul,Korea(Zip-code:135-220)  
 Tel / Fax : +82-2-2194-5499 / +82-2-2194-5498

### 2-2 Manufacturer List

Company name : JOYTOTO.CO.Ltd  
 Address : 3Fl.Sungwoo Bldg.,717-3 sooseo-dong, Kangnam-gu,  
 Seoul,Korea(Zip-code:135-220)  
 Tel / Fax : +82-2-2194-5499 / +82-2-2194-5498

### 2-3 Equipment Under Test (EUT)

Trade name : Digital Audio Player  
 FCC ID : VFQ-NS-XV24  
 Model name : NS-4V24, NS-8V24  
 → NS-4V24 : Flash memory(4GBytes), NS-8V24: Flash memory(8 GBytes)  
 Serial number : Identical prototype  
 Date of receipt : June 30, 2007  
 EUT condition : Pre-production, not damaged  
 Antenna type : Chip antenna  
 Frequency Range : 2402 ~ 2480MHz  
 RF output power Range : -6dBm~+4dBm (Class 2)  
 Number of channels : 79  
 Channel spacing : 1MHz  
 Channel Access Protocol : Frequency Hopping  
 Type of Modulation : GFSK  
 Power Source : 3.7V (Li-Polymer Rechargeable) (Recharging – by USB Cable)

### 2-4 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

**2-5 Ancillary Equipment – Bluetooth + Play mode**

Equipment	Model No.	Serial No.	Manufacturer
earphone	N/A	N/A	N/A
-	-	-	-

**2-6 Ancillary Equipment – USB mode**

Equipment	Model No.	Serial No.	Manufacturer
PC	dx2200Microtower	CNG6500RX9	HP
Monitor	VS11353	E060T4021/1-1	View Sonic
Keyboard	SK-8115	641-OEWW	DELL
Mouse	MO56UO	510022473	DELL
Print	Deskjet 600K	SG7631B1XX	HP
earphone	N/A	N/A	N/A
-	-	-	-

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 75 hops		C
15.247(a)	20 dB Bandwidth	< 1 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.247(d)	Band Edge	< 54 dBuV (at 3m)	Radiated	C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)		C
15.109	Field Strength	-		C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

## 3.2 Transmitter requirements

### 3.2.1 Carrier Frequency Separation

#### Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz (1% of the span or more)      Sweep = auto

VBW = 30 kHz      Detector function = peak

Trace = max hold

#### Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
1.013	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

#### Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency Separation





3.2.2 Number of Hopping Frequencies

Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

- Frequency range
- 1: Start = 2389.5MHz, Stop = 2414.5 MHz
- 2: Start = 2414.5MHz, Stop = 2439.5 MHz
- 3: Start = 2439.5MHz, Stop = 2464.5 MHz
- 4: Start = 2464.5MHz, Stop = 2489.5 MHz
- RBW = 300 kHz (1% of the span or more)
- Sweep = auto
- VBW = 300 kHz (VBW ≥ RBW)
- Detector function = peak
- Trace = max hold
- Span = 25MHz

Measurement Data: Complies

Total number of Hopping Channels	79
----------------------------------	----

- See next pages for actual measured spectrum plots.



Minimum Standard:

At least 15 hopes



Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Number of Hopping Frequencies



## Number of Hopping Frequencies



### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 2 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency (MHz)	Channel No.	Test Results	
		Measured Bandwidth (MHz)	Result
2402	0	0.945	Complies
2441	39	0.950	Complies
2480	78	0.950	Complies

- See next pages for actual measured spectrum plots.




#### Minimum Standard:

The transmitter shall have a maximum 20dB bandwidth of 1 MHz.

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

## 20 dB Bandwidth



### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data:

Channel Number	Channel Frequency (MHz)	Packet Type	Test Results	
			Dwell Time (ms)	Result
39	2441	DH 1	136.05	Complies
		DH 3	185.33	Complies
		DH 5	310.15	Complies




- See next pages for actual measured spectrum plots.

#### Minimum Standard:

0.4 seconds within a 30 second period per any frequency

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

DH 1DH 3DH 5

### 3.2.5 Transmitter Output Power

#### Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 1 MHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data:

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>-3.08</b>	<b>0.492</b>	Complies
2441	39	<b>-2.33</b>	<b>0.585</b>	Complies
2480	78	<b>-1.72</b>	<b>0.673</b>	Complies

- See next pages for actual measured spectrum plots.




<b>Minimum Standard:</b>	< 1W
--------------------------	------

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)



## Peak Output Power



### 3.2.6 Band Edge – Conducted Measurement

#### Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 10 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies



- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------



#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)



### Band - edge (with Hopping)



## Band - edge (without Hopping)




**Band - edge (at 20 dB blow) – Low channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**





Band - edge (at 20 dB blow) – Low channel  
Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonics.

- Continues




**Band - edge (at 20 dB blow) – Mid channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**





**Band - edge (at 20 dB blow) – Mid channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonics.**

- Continues






**Band - edge (at 20 dB blow) – High channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



Band - edge (at 20 dB blow) – High channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonics.

- Continues



### 3.2.7 Band Edge – Radiated Measurement

#### Procedure:

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK: RBW = VBW = 1MHz, Sweep=Auto

Average: RBW = 1MHz, VBW=10Hz, Sweep=Auto

Measurement Distance: 3m

Polarization: Horizontal / Vertical


#### Measurement Data:

- Refer to the next page.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

## Radiated Band Edge – CH-LOW




Frequency (MHz)	Pol.	Reading Value (dBuV/m)		T.F (dB)	Result Value (dBuV/m)		Limit (dBuV/m)	
		PK	AV		PK	AV	PK	AV
2387.2	H	54.0	-	-2.5	51.5	-	74	54
2368.2	V	51.7	-	-2.5	49.2	-	74	54
-	-	-	-	-	-	-	74	54
-	-	-	-	-	-	-	74	54

Note 1: T.F = Antenna Factor + Cable Loss – AMP Factor

Note 2: Result Value = Reading Value + T.F

## Radiated Band Edge – CH-High



Frequency (MHz)	Pol.	Reading Value (dBuV/m)		T.F (dB)	Result Value (dBuV/m)		Limit (dBuV/m)	
		PK	AV		PK	AV	PK	AV
2483.5	H	67.53	54.97	-2.5	65.03	52.47	74	54
2483.5	V	59.42	49.41	-2.5	56.92	46.91	74	54
-	-	-	-	-	-	-	74	54
-	-	-	-	-	-	-	74	54

Note 1: T.F = Antenna Factor + Cable Loss – AMP Factor

Note 2: Result Value = Reading Value + T.F

### 3.2.8 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic )

Span = 100 MHz

Trace = max hold

Peak:VBW  $\geq$  RBW

Average:VBW=10Hz

Detector function = Average

Sweep = auto

#### Measurement Data: Complies

Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV)	Frequency (MHz)	Level (dBuV)	Frequency (MHz)	Level (dBuV)
4804	51.5	2882	46.7	4960	43.9
-	-	-	-	-	-
Measurement uncertainty		$\pm 6$ dB			

No other emissions were detected at a level greater than 20dB below limit.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500


\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.



TEST MODE: MP3 + BT mode

Tested by: B. S. KIM

Date: 2007-07-09



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	QK dBuV/m	dBuV/m	dB	cm	deg	
1	180.71	31.20	-11.51	19.69	43.50	23.81	281	119	HORIZONTAL
2	220.70	41.00	-12.56	28.44	46.00	17.56	270	341	HORIZONTAL
3	230.70	40.70	-11.96	28.74	46.00	17.26	271	44	HORIZONTAL
4	396.24	33.20	-7.55	25.65	46.00	20.35	300	119	HORIZONTAL
5	500.20	33.10	-5.64	27.46	46.00	18.54	381	111	HORIZONTAL
6	700.24	32.74	-1.45	31.29	46.00	14.71	100	291	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




TEST MODE: SD + BT mode

Tested by: B. S. KIM

Level (dBuV/m)

Date: 2007-07-09



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	QK dBuV/m	dBuV/m	dB	cm	deg	
1	180.71	30.80	-11.51	19.29	43.50	24.21	281	119	HORIZONTAL
2	220.70	36.40	-12.56	23.84	46.00	22.16	270	341	HORIZONTAL
3	230.70	41.20	-11.96	29.24	46.00	16.76	271	44	HORIZONTAL
4	396.24	36.10	-7.55	28.55	46.00	17.45	300	119	HORIZONTAL
5	500.20	32.70	-5.64	27.06	46.00	18.94	381	111	HORIZONTAL
6	700.24	32.10	-1.45	30.65	46.00	15.35	100	291	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain





### 3.2.9 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50


\* Decreases with the logarithm of the frequency

AC Conducted Emissions –Line



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-323-6008  
Fax: +82-31-323-6010

EUT / Model No. : NS-XV24	Phase : LINE
Test Mode : File up / down mode	Test Power : 120 / 60
Temp./Humi. : 24 / 61	Test Engineer : B.S.KIM



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.171	44.20	40.30	0.41	44.61	40.71	64.91	54.91	20.30	14.20
0.242	41.20	39.30	0.22	41.42	39.52	62.03	52.03	20.60	12.50
0.993	29.60	29.00	0.32	29.92	29.32	56.00	46.00	26.08	16.68
3.156	29.10	23.00	0.63	29.73	23.63	56.00	46.00	26.27	22.37
9.999	20.20	18.10	0.90	21.10	19.00	60.00	50.00	38.90	31.00
11.185	33.50	32.10	0.96	34.46	33.06	60.00	50.00	25.54	16.94
17.667	17.20	13.00	1.34	18.54	14.34	60.00	50.00	41.46	35.66


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions -Neutral



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : NS-XV24	Phase : NEUTRAL
Test Mode : File up / down mode	Test Power : 120 / 60
Temp./Humi. : 24 / 61	Test Engineer : B.S.KIM



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.169	43.00	39.30	0.42	43.42	39.72	65.01	55.01	21.58	15.28
0.244	38.50	35.10	0.22	38.72	35.32	61.96	51.96	23.23	16.63
0.991	28.50	27.80	0.31	28.81	28.11	56.00	46.00	27.19	17.89
3.139	30.80	23.40	0.60	31.40	24.00	56.00	46.00	24.60	22.00
11.185	34.10	32.70	0.93	35.03	33.63	60.00	50.00	24.97	16.37
17.626	21.80	18.40	1.21	23.01	19.61	60.00	50.00	36.99	30.39

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

**APPENDIX**

**TEST EQUIPMENT USED FOR TESTS**

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	8594E	3649A03649	HP	Apr-08
2	Signal Generater	8648C	3623A02597	HP	Apr-08
3	Attenuator (3dB)	8491A	37822	HP	Nov-07
4	Attenuator (10dB)	8491A	63196	HP	Nov-07
5	EMI Test Receiver	ESVD	843748/001	R&S	Jan-08
6	LISN	KNW-407	8-1430-1	Kyoritsu	Jan-08
7	Two-Line V-Network	ESH3-Z5	893045/017	R&S	Jan-08
8	RF Amplifier	8447D	2949A02670	HP	Jan-08
9	RF Amplifier	8447D	2439A09058	HP	Jan-08
10	RF Amplifier	8449B	3008A02126	HP	Apr-09
11	Test Receiver	ESHS10	828404009	R&S	Jan-08
12	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Jul-07
13	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-09
14	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-09
15	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-09
16	Dipole Antenna	VHA9103	2116	Schwarzbeck	Nov-07
17	Dipole Antenna	VHA9103	2117	Schwarzbeck	Nov-07
18	Dipole Antenna	UHA9105	2261	Schwarzbeck	Nov-07
19	Dipole Antenna	UHA9105	2262	Schwarzbeck	Nov-07
20	Spectrum Analyzer	8591E	3649A05888	HP	Jan-08
21	Spectrum Analyzer	8563E	3425A02505	HP	Apr-08
22	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Feb-08
23	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	Jun-08
24	RF Switch	MP59B	6200414971	ANRITSU	Jun-08
25	RF Switch	MP59B	6200438565	ANRITSU	Jun-08
26	Power Divider	11636A	6243	HP	Nov-07
27	DC Power Supply	6622A	3448A03079	HP	Oct-07
28	Attenuator (30dB)	11636A	6243	HP	Nov-07
29	Frequency Counter	5342A	2826A12411	HP	Apr-08
30	Power Meter	EPM-441A	GB32481702	HP	Apr-08
31	Power Sensor	8481A	2702A64048	HP	Apr-08
32	Audio Analyzer	8903B	3729A18901	HP	Nov-07
33	Modulation Analyzer	8901B	3749A05878	HP	Nov-07
34	TEMP & HUMIDITY Chamber	YJ-500	L05022	JinYoung Tech	Oct-07
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-09