## APPLICATION FOR CERTIFICATION

On Behalf of

Harmonix Music Systems, Inc.

P9 Wii Gretsch Wireless Guitar

Model Number: NWGTS4

FCC ID: VFRNWGTS4

Prepared for: Harmonix Music Systems, Inc.

675 Massachusetts Avenue, 6th Floor, Cambridge, MA

02139 US

Prepared By: Audix Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F09102 Date of Test : May.21~24, 2009

Date of Report : Jun.03, 2009

## TABLE OF CONTENTS

Des	scription	Page
1.	SUMMARY OF STANDARDS AND RESULTS	1-1
	1.1. Description of Standards and Results	1-1
2.	GENERAL INFORMATION	<b>2-</b> 1
	2.1. Description of Device (EUT)	2-1
	2.2. Test Facility	
	2.3. Measurement Uncertainty (95% confidence levels, k=2)	
3.	POWER LINE CONDUCTED EMISSION TEST	3-1
4.	RADIATED EMISSION TEST	<b>4-</b> 1
	4.1. Test Equipment	
	4.2. Block Diagram of Test Setup	
	4.3. Radiated Emission Limit	
	<ul><li>4.4. EUT Configuration on Test</li><li>4.5. Operating Condition of EUT</li></ul>	
	4.6. Test Procedure	
	4.7. Radiated Emission Test Results	
5.	CARRIER FREQUENCY SEPARATION TEST	
	5.1. Test Equipment	
	5.2. Limit	
	5.3. Test Results (Pass.)	5-1
<b>6.</b>	20 DB BANDWIDTH TEST	6-1
	6.1. Test Equipment	6-1
	6.2. Limit	
	6.3. Test Results	
7.	NUMBER OF HOPPING FREQUENCY TEST	
	7.1. Test Equipment	
	7.2. Limit	
0	7.3. Test Results	
8.	DWELL TIME	
	8.1. Test Equipment	
	8.2. Limit	
9.	MAXIMUM PEAK OUTPUT POWER TEST	
<b>9.</b>	9.1. Test Equipment	
	9.2. Limit	
	9.3. Test Procedure	
	9.4. Test Results	
10.	BAND EDGE COMPLIANCE TEST	10-1
	10.1. Test Equipment	10-1
	10.2. Limit	
	10.3. Test Produce	
	10.4. Test Results	
11.	ANTENNA REQUIREMENT	11-1
<b>12.</b>	DEVIATION TO TEST SPECIFICATIONS	12-1
13.	PHOTOGRAPH OF TEST	13-1
,	13.1. Photos of Radiated Emission Test	
14.	PHOTOGRAPH OF EUT	
•		

#### TEST REPORT CERTIFICATION

Applicant Harmonix Music Systems, Inc.

Manufacturer Contel Electronics Technology Co., Ltd.

**EUT Description** P9 Wii Gretsch Wireless Guitar

FCC ID VFRNWGTS4

> (A) MODEL NO. : NWGTS4 (B) SERIAL NO. : N/A (C) POWER SUPPLY : DC 4.5V (D) TEST VOLTAGE : DC 4.5V

Test Procedure Used:

FCC Rules and Regulations Part 15 Subpart C 2008

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both radiated and conducted emissions.

The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Date of Test:		May.21~24, 2009	
Prepared by:		Edie Huang  Edie Huang / Assistant	
Reviewer:	-	Jamy Yu / Senior Engineer	

舊華科技(深圳)有限公司 AUDI) Audix Technology (Shenzhen) Co., 14 EMC部門報告專用章 Stamp only for EMC Dept. Report Signature:

Approved & Authorized Signer:

Ken Lu / Manager

# 1. SUMMARY OF STANDARDS AND RESULTS

# 1.1.Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION						
Description of Test Item	Standard	Results				
	FCC Part 15: 15.207					
Power Line Conducted Emission Test	ANSI C63.4: 2003	N/A				
	DA 00-705					
	FCC Part 15: 15.209					
Radiated Emission Test	FCC Part 15: 15.247(d)	PASS				
Radiated Emission Test	ANSI C63.4: 2003	rass				
	DA 00-705					
Comica European en Compantion Toot	FCC Part 15: 15.247(a)(1)	PASS				
Carrier Frequency Separation Test	DA 00-705	rass				
2010 0 1 111 7	FCC Part 15: 15.215	PASS				
20dB Bandwidth Test	DA 00-705	PASS				
	FCC Part 15: 15.247(a)(1)(iii)	DAGG				
Number Of Hopping Frequency Test	DA 00-705	PASS				
D 11 m	FCC Part 15: 15.247(a)(1)(iii)	DAGG				
Dwell Time Test	DA 00-705	PASS				
	FCC Part 15: 15.247(b)(1)	DAGG				
Maximum Peak Output Power Test	DA 00-705	PASS				
D 151 G " "	FCC Part 15: 15.247(d)	D.4.00				
Band Edge Compliance Test	DA 00-705	PASS				
Antenna requirement	FCC Part 15: 15.203	PASS				

N/A is an abbreviation for Not Applicable.

## 2. GENERAL INFORMATION

2.1.Description of Device (EUT)

Description : P9 Wii Gretsch Wireless Guitar

Model Number : NWGTS4

FCC ID : VFRNWGTS4

Operation frequency : 2.408GHz----2.476GHz

Operation Channel : 16 Channels

Modulation Technology **GFSK** 

Output power : 0.82dBm (maximum measured)

Antenna Assembly

Gain

Integrated PCB antenna with 0dBi gain (maximum)

Power Supply : DC 4.5V

(Note: New batteries were used for all test)

Applicant : Harmonix Music Systems, Inc.

675 Massachusetts Avenue, 6th Floor, Cambridge, MA 02139 US

Manufacturer : Contel Electronics Technology Co., Ltd.

13/F, Dawning BLDG, 12 KejiNan Rd., SHIP, Shenzhen, China

Date of Test : May.21~24, 2009

Date of Receipt : May.21, 2009

Sample Type : Prototype production

## 2.2.Test Facility

Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen,

Guangdong, China

3m Anechoic Chamber : Mar.31, 2009 File on Federal Communication

Commission

Registration Number: 90454

3m & 10m Anechoic Chamber: Jan. 31, 2007 File on Federal Communication

Commission

Registration Number: 794232

EMC Lab. : Accredited by DATech, German

Registration Number: DAT-P-091/99-01

Feb. 02, 2009

Accredited by NVLAP, USA NVLAP Code: 200372-0

Apr. 01, 2009

# 2.3. Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.88dB	
Uncertainty for Radiation Emission test in 3m	3.86dB	Polarize: V
chamber(30MHz to 1GHz)	4.3dB	Polarize: H
Uncertainty for Radiation Emission test in 3m	2.78dB	Polarize: H
chamber(1GHz to 25GHz)	2.82dB	Polarize: V
Uncertainty for radio frequency	1×10 <sup>-9</sup>	
Uncertainty for conducted RF Power	0.34dB	
Uncertainty for temperature	$0.2^{\circ}\!\mathbb{C}$	
Uncertainty for humidity	1%	
Uncertainty for DC and low frequency voltages	0.06%	

## 3. POWER LINE CONDUCTED EMISSION TEST

According to Paragraph (f) of FCC Part 15 section 15.207, Tests to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

# 4. RADIATED EMISSION TEST

# 4.1.Test Equipment

Frequency rang: 30~1000MHz

	· · · · · ·			<b>.</b>	1	·
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Dec.05, 08	1/2 Year
2.	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 09	1 Year
3.	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 09	1 Year
4.	Amplifier	HP	8447D	2648A04738	May.08, 09	1/2 Year
5.	Bilog Antenna	Schaffner	CBL6111C	2598	Nov.10, 08	1 Year
6.	RF Cable	JINGCHENG	JBY400	3# Chamber No.1	May.08, 09	1/2 Year
7.	RF Cable	JINGCHENG	JBY400	3# Chamber No.2	May.08, 09	1/2 Year
8.	RF Cable	JINGCHENG	JBY400	3# Chamber No.3	May.08, 09	1/2 Year
9.	RF Cable	JINGCHENG	JBY400	3# Chamber No.4	May.08, 09	1/2 Year
10.	Coaxial Switch	Anritsu	MP59B	M73989	May.08, 09	1/2 Year

Frequency rang: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08, 09	1 Year
2.	Horn Antenna	EMCO	3115	9607-4877	May.27, 08	1.5 Year
3.	Horn Antenna	EMCO	3116	00060088	May.27, 08	1.5Year
4	Amplifier	Agilent	8449B	3008A02495	Nov.24, 08	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	May.08, 09	1 Year
6	RF Cable	Hubersuhner	SUCOFLEX102	271471/4	May.08, 09	1 Year
7	RF Cable	Hubersuhner	SUCOFLEX102	29086/2	May.08, 09	1 Year

# 4.2.Block Diagram of Test Setup


4.2.1.Block diagram of connection between the EUT and simulators

EUT

(EUT: P9 Wii Gretsch Wireless Guitar)

### 4.2.2.In Anechoic Chamber

## ANTENNA TOWER



**GROUND PLANE** 

## 4.3. Radiated Emission Limit

4.3.1.15.209 limits

FREQUENCY	DISTANCE	FIELD STRENGTHS LIMIT			
MHz	Meters	$\mu V/m$	$dB(\mu V)/m$		
30 ~ 88	3	100	40.0		
88 ~ 216	3	150	43.5		
216 ~ 960	3	200	46.0		
960 ~ 1000	3	500	54.0		
Above 1000	3	74.0 dB(μV)/m (Peak)			
		54.0 dB(µV)/m (Average)			

Remark: (1) Emission level  $dB\mu V = 20 \log Emission$  level  $\mu V/m$ 

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.3.2.15.205	Restricted	bands	of o	peration
--------------	------------	-------	------	----------

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

## 4.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

## 4.4.1.P9 Wii Gretsch Wireless Guitar (EUT)

Model Number : NWGTS4 Serial Number : N/A

## 4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT as shown in Section 4.2..
- 4.5.2.Let the EUT worked in test modes (Tx Mode) and test it.

### 4.6.Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10<sup>th</sup> harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

## 4.7. Radiated Emission Test Results

PASS.


All the emissions from 30MHz to 25 GHz are comply with 15.209 limits

## Test Frequency: 30MHz-1000MHz



No.6, Ke Feng Road, Block 52, Shenzhen Science&Industry Park Nantou Shenzhen, Guangdong, China

Tel:+86-755-26639495 Fax:+86-755-26632877 Postcode:518057



Frequency (MHz)

Data no. : 2

Site no. : 3m Chamber
Dis. / Ant. : 3m CBL6111C Ant. pol. : HORIZONTAL

: FCC PART 15 C (3M) Limit

Env. / Ins. : 24\*C/56% Engineer : Sunny-lu

: P9 Wii Gretsch Wireless Guitar

Power Rating : DC 4.5V Test Mode : Tx Mode M/N:NWGTS4

_		Freq.	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
	1	30.000	19.86	0.28	31.18	23.38	40.00	16.62	QP
	2	70.740	6.69	0.57	47.25	26.68	40.00	13.32	QP
	3	109.540	11.22	0.80	46.73	31.15	43.50	12.35	QP
	4	167.740	10.33	0.97	40.17	24.09	43.50	19.41	QP
	5	284.140	13.26	1.50	31.80	19.64	46.00	26.36	QP
	6	636.250	20.03	2.55	31.25	25.71	46.00	20.29	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.

2. The emission levels that are 20dB below the official  $\ensuremath{\text{c}}$ limit are not reported.



No.6, Ke Feng Road, Block 52, Shenzhen Science&Industry Park Nantou Shenzhen, Guangdong, China Tel:+86-755-26639495

Fax:+86-755-26632877 Postcode:518057



: 3m Chamber Site no. Data no. : 1

Dis. / Ant. : 3m CBL6111C Ant. pol. : VERTICAL

Limit : FCC PART 15 C (3M) Env. / Ins. : 24\*C/56% Engineer : Sunny-lu

: P9 Wii Gretsch Wireless Guitar EUT

Power Rating : DC 4.5V Test Mode : Tx Mode M/N:NWGTS4

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	19.86	0.28	42.33	34.53	40.00	5.47	QP
2	68.800	6.45	0.55	55.52	34.68	40.00	5.32	QP
3	109.540	11.22	0.80	47.55	31.97	43.50	11.53	QP
4	156.100	11.18	0.98	38.30	23.03	43.50	20.47	QP
5	171.620	9.97	1.04	38.91	22.56	43.50	20.94	QP
6	243.400	11.97	1.36	33.10	19.37	46.00	26.63	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.

2. The emission levels that are 20dB below the official limit are not reported.


## **Test Frequency: 1GHz-4GHz**



No.6 Ke Feng Road, Block 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China Tel:+86-755-26639495-7 Fax:+86-755-26632877

Postcode:518057





Site no. : 3m Chamber

Data no. : 2 Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK

Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar

Power
Test mode : Tx 2
: NWGTS4 Power : DC 4.5V 2408MHz

	Freq. (MHz)	Factor		Factor	Reading (dbuv)		Limits	_	Remark
1	1840.000	27.23	5.86	35.37	46.46	44.18	74.00	29.82	Peak
2	1984.000	27.83	6.16	35.20	45.81	44.60	74.00	29.40	Peak
3	2410.000	28.48	6.73	35.12	97.06	97.15	74.00	-23.15	Peak
4	3211.000	30.78	8.13	34.96	47.05	51.00	74.00	23.00	Peak

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 1 Ant. pol. : VERTICAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


: P9 Wii Gretsch Wireless Guitar EUT


Power : DC 4.5V Test mode : Tx 2408MHz M/N : NWGTS4

	Ant. Cable Amp				Emission				
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)	
1	1840.000	27.23	5.86	35.37	46.42	44.14	74.00	29.86	Peak
2	1984.000	27.83	6.16	35.20	46.40	45.19	74.00	28.81	Peak
3	2408.000	28.48	6.73	35.12	90.80	90.89	74.00	-16.89	Peak

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 7

Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2440MHz M/N : NWGTS4

		Ant.	Cable	Amp.		Emissio	n			
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)		
1	1840.000	27.23	5.86	35.37	46.10	43.82	74.00	30.18	Peak	
2	1984.000	27.83	6.16	35.20	45.90	44.69	74.00	29.31	Peak	
3	2440.000	28.53	6.80	35.11	95.29	95.51	74.00	-21.51	Peak	

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 8 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar


Power : DC 4.5V Test mode : Tx 2440MHz M/N : NWGTS4

		Ant.	Cable	Amp.		Emissio:	n			
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	) (dB)		
1	1840.000	27.23	5.86	35.37	47.86	45.58	74.00	28.42	Peak	
2	1984.000	27.83	6.16	35.20	47.53	46.32	74.00	27.68	Peak	
3	2440.000	28.53	6.80	35.11	90.75	90.97	74.00	-16.97	Peak	

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







: 3m Chamber Site no. Data no. : 13

Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar


: DC 4.5V Power Test mode : Tx 2476MHz : NWGTS4 M/N

Margin Remark
(dB)
30.10 Peak
31.34 Peak
-19.62 Peak
_

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







: 3m Chamber Site no. Data no. : 14 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EHT : P9 Wii Gretsch Wireless Guitar

Power : DC 4.5V Test mode : Tx 2476MHz : NWGTS4 M/N

		Ant.	Cable	Amp.		Emissio:	n			
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)		
1	1840.000	27.23	5.86	35.37	45.31	43.03	74.00	30.97	Peak	
2	2014.000	27.92	6.23	35.19	45.76	44.72	74.00	29.28	Peak	
3	2476.000	28.58	6.87	35.10	90.04	90.39	74.00	-16.39	Peak	


- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.

## **Test Frequency: 4GHz-18GHz**



No.6 Ke Feng Road, Block 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China Tel:+86-755-26639495-7 Fax:+86-755-26632877

Postcode:518057



Site no. : 3m Chamber

Data no. : 3 Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK


Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar

Power : DC 4.5V Test mode : Tx 2408MHz

: NWGTS4 M/N







Site no. : 3m Chamber Data no. : 4

Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

: P9 Wii Gretsch Wireless Guitar FIIT

Power : DC 4.5V Test mode : Tx 2408MHz

	Ant. Cable Amp.			Emission				
	-			Reading (dbuv)			_	Remark
_	4816.000 4816.000			 45.28 38.68	55.59 48.99	74.00 54.00	18.41 5.01	Peak Average


- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.



No.6 Ke Feng Road, Block 52, ShenZhen Science & Industry Park Noutou, ShenZhen, GuangDong, China Tel:+86-755-26639495-7

Fax:+86-755-26632877 Postcode:518057





Site no. : 3m Chamber Data no. : 5


Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL


Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

Power : DC 4.5V Test mode : Tx 2408MHz







Site no. : 3m Chamber Data no. : 6

Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar


Power : DC 4.5V Test mode : Tx 2408MHz

	Freq.	Ant. Factor (dB/m)	Cable loss (dB)	Factor	Reading (dbuv)		Limits	_	Remark
_	4816.000 4816.000				46.35 38.64	56.66 48.95	74.00 54.00	17.34 5.05	Peak Average

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Dis. / Ant. : 3m 3115

Data no. : 9 Ant. pol. : VERTICAL

: FCC PART 15C PEAK Limit


Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2440MHz







Site no. : 3m Chamber Data no. : 10 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

: P9 Wii Gretsch Wireless Guitar : DC 4.5V EUT

Power Test mode : Tx 2440MHz M/N: NWGTS4


		Ant.	Cable	Amp.		Emissio	n		
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)	
1	4880.000	34.78	10.56	34.58	46.69	57.45	74.00	16.55	Peak
2	4880.000	34.78	10.56	34.58	36.98	47.74	54.00	6.26	Average

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.



Postcode:518057





Data no. : 11 Site no. : 3m Chamber

Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL


Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2440MHz M/N : NWGTS4







: 3m Chamber Site no. Data no. : 12

Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

: P9 Wii Gretsch Wireless Guitar EHT

: DC 4.5V Power Test mode : Tx 2440MHz M/N : NWGTS4


		Ant.	Cable	Amp.		Emission	n			
	•				Reading (dbuv)			_	Remark	
1	4880.000	34.78	10.56	34.58	47.35	58.11	74.00	15.89	Peak	
2	4880.000	34.78	10.56	34.58	36.58	47.34	54.00	6.66	Average	

- 1. Emission Level= Antenna Factor + Cable Loss Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.



Postcode:518057





Site no. : 3m Chamber Data no. : 15 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL


Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2476MHz M/N: NWGTS4







Data no. : 16 Site no. : 3m Chamber Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

Power : DC 4.5V Test mode : Tx 2476MHz M/N : NWGTS4

	Freq. (MHz)	_	Factor	Reading (dbuv)		Limits	_	Remark	
_	4952.000 4952.000		 	47.63 36.89	58.84 48.10	74.00 54.00	15.16 5.90	Peak Average	-


- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.



Postcode:518057

15200.

18000



Site no. : 3m Chamber Data no. : 17

9600.

Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL

Frequency (MHz)

12400.

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2476MHz M/N : NWGTS4

6800.







Data no. : 18 Site no. : 3m Chamber

Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2476MHz M/N : NWGTS4

		Ant.	Cable	Amp.		Emission	n		
	-				Reading (dbuv)			_	Remark
_	4952.000 4952.000					57.60 47.79		16.40 6.21	Peak Average

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.

# 5. CARRIER FREQUENCY SEPARATION TEST

# 5.1.Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May,08, 09	1 Year


## 5.2.Limit


Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

## 5.3.Test Results

СН	Channel separation	Conclusion	
Low	2.02MHz	PASS	
Mid	4.02MHz	PASS	
High	8.00MHz	PASS	







# 6. 20 DB BANDWIDTH TEST

# 6.1. Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.
						Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May,08, 09	1 Year
2	Attenuator	Agilent	8491B	MY39262165	May,08, 09	1 Year
3	RF Cable	Hubersuhner	SUCOFLEX 102	28618/2	May,08, 09	1Year


## 6.2. Limit


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


## 6.3. Test Results


СН	20dB Bandwidth (MHz)	Limit (MHz)	Conclusion
(Low)	1.23		PASS
(Mid)	1.22		PASS
(High)	1.27		PASS














# 7. NUMBER OF HOPPING FREQUENCY TEST

# 7.1.Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.
						Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May,08, 09	1 Year
2	Attenuator	Agilent	8491B	MY39262165	May,08, 09	1 Year
3	RF Cable	Hubersuhner	SUCOFLEX 102	28618/2	May,08, 09	1Year

# 7.2.Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

# 7.3.Test Results

Number of channel	Limit	Conclusion
16	>=15	PASS



# 8. DWELL TIME

# 8.1.Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May,08, 09	1 Year
2	Attenuator	Agilent	8491B	MY39262165	May,08, 09	1 Year
3	RF Cable	Hubersuhner	SUCOFLEX 102	28618/2	May,08, 09	1Year


# 8.2.Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

# 8.3.Test Results

dwell time	Limit	Conclusion
16hops/5s*0.4*16chanels*0.9ms=18.43 ms	<400ms	PASS





## 9. MAXIMUM PEAK OUTPUT POWER TEST

## 9.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08, 09	1 Year
2.	Horn Antenna	EMCO	3115	9607-4877	May. 27, 08	1.5 Year
3.	Horn Antenna	EMCO	3115	9510-4580	May.10, 09	1.5 Year
4.	Signal Generator	HP	83732B	VS3449051	May.08, 09	1 Year
5.	Amplifier	Agilent	8449B	3008A02495	Nov.24.08	1 Year
6.	RF Cable	Hubersuhner	SUCOFLEX 102	28620/2	May.08, 09	1 Year
7.	RF Cable	Hubersuhner	SUCOFLEX 102	271471/4	May.08, 09	1 Year
8.	RF Cable	Hubersuhner	SUCOFLEX 102	29086/2	May.08, 09	1 Year
9.	RF Cable	Hubersuhner	SUCOFLEX 102	271473/4	May.08, 09	1 Year
10.	RF Cable	Hubersuhner	SUCOFLEX 102	29091/2	May.08, 09	1 Year

## 9.2.Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

## 9.3.Test Procedure

- (1). The EUT was placed on a 0.8m high table in the chamber and turned on in continuously transmitting mode.
- (2). The maximum fundamental emission at 3m distance was measured and recorded with receive antenna in both vertical and horizontal by rotating the turntable and by lowering the receive antenna.
- (3). The EUT was then removed and replaced with a substitution antenna in the same position and the substitution antenna must have the same polarization with the receive antenna.
- (4). A signal which have the same frequency obtained in step 2 was fed to the substitution, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver, the level of the signal generator was adjusted until the measured field strength level in step 2 was obtained, recorded the level of the signal generator.
- (5). Repeated step 4 with both antenna polarizations
- (6). The radiated power is equal to the power supplied by the signal generator and corrections due to the gain of the substitution antenna and the cable loss between the signal generator and the substitution antenna.

# 9.4.Test Results

EUT	: P9 Wii	Grets	ch Wireless	Guitar	M/N: N	WGTS	4			
Pow	er: DC 4.	5V								
Test	Date: 20	09/05	/22	Test site:	RF Chamber		Eng	gineer: Sunn	ıy-lu	
Amb	oient Tem	perati	ure: 25°℃	Relative I	Humidity: 56%					
Test mode: TX Mode										
CH   -     Reading   Capie Loss								Margin (dB)		
Low	2408	Н	97.15	-2.37	6.06	9.25	5	0.82	20.97	20.15
Low	2408	V	90.89	-3.12	6.06	9.25	5	0.07	20.97	20.90
Mid	2440	Н	95.51	-2.50	6.08	9.30	)	0.72	20.97	20.25
IVIIU	2440	V	90.97	-3.10	6.08	9.30	)	0.12	20.97	20.85
Hig	2476	Н	93.62	-2.54	6.15	9.33	3	0.64	20.97	20.33
Ing	2476	V	90.39	-3.10	6.15	9.33	3	0.08	20.97	20.89
Resul	t = SGR	eading	g – Tx Cable	$\overline{\text{Loss} + \text{Tx}}$	Antenna Gain	– EUT A	Anter	nna Gain(0d	Bi)	

## 10.BAND EDGE COMPLIANCE TEST

## 10.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May,08, 09	1 Year
2	Horn Antenna	EMCO	3115	9607-4877	May, 27, 08	1.5 Year
3	Amplifier	Agilent	8449B	3008A02495	Nov. 24.08	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX 102	28620/2	May,08, 09	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX 102	271471/4	May,08, 09	1 Year
6	RF Cable	Hubersuhner	SUCOFLEX 102	29086/2	May,08, 09	1 Year

## 10.2.Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.


## 10.3.Test Produce

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
- 2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz, PK detector, Sweep=AUTO

## 10.4.Test Results

Pass (The testing data was attached in the next pages.)





Site no. : 3m Chamber Data no. : 19 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar


Power : DC 4.5V Test mode : Tx 2408MHz M/N : NWGTS4

		Ant.	Cable	Amp.		Emissio	n		
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)	
1	2336.214	28.38	6.65	35.13	45.61	45.51	74.00	28.49	Peak
2	2390.000	28.46	6.71	35.12	46.79	46.84	74.00	27.16	Peak
3	2400.000	28.46	6.73	35.12	43.42	43.49	74.00	30.51	Peak
4	2407.920	28.48	6.73	35.12	89.88	89.97	74.00	-15.97	Peak

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 20 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C AV Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar


: DC 4.5V Power Test mode : Tx 2408MHz : NWGTS4 M/N

		Ant.	Cable	Amp.		Emissio:	n			
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)		
1	2317.956	28.36	6.65	35.13	33.38	33.26	54.00	20.74	Average	
2	2390.000	28.46	6.71	35.12	38.26	38.31	54.00	15.69	Average	
3	2400.000	28.46	6.73	35.12	32.67	32.74	54.00	21.26	Average	
4	2407.920	28.48	6.73	35.12	87.67	87.76	54.00	-33.76	Average	

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Data no. : 21 Site no. : 3m Chamber

Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar


: DC 4.5V Power Test mode : Tx 2408MHz M/N : NWGTS4

		Ant.	Cable	Amp.		Emissio	n			
	Freq.			Factor (dB)	Reading (dbuv)	Level (dBuV/m)		_	Remark	
1	2327.136	28.36	6.65	35.13	45.67	45.55	74.00	28.45	Peak	_
2	2390.000	28.46	6.71	35.12	49.50	49.55	74.00	24.45	Peak	
3	2400.000	28.46	6.73	35.12	44.25	44.32	74.00	29.68	Peak	
4	2407.920	28.48	6.73	35.12	95.22	95.31	74.00	-21.31	Peak	

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 22

Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL

Limit : FCC PART 15C AV Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2408MHz


M/N : NWGTS4

	Freq.	Ant. Factor (dB/m)		Amp. Factor (dB)	Reading (dbuv)		-	_	Remark
		(42, 11,	(42)	(42)	(000047)	(abar, m,	(4247 111)	(42)	
1	2317.956	28.36	6.65	35.13	34.40	34.28	54.00	19.72	Average
2	2390.000	28.46	6.71	35.12	41.00	41.05	54.00	12.95	Average
3	2400.000	28.46	6.73	35.12	32.80	32.87	54.00	21.13	Average
4	2407.920	28.48	6.73	35.12	93.77	93.86	54.00	-39.86	Average

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 23

Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EIIT : P9 Wii Gretsch Wireless Guitar


: DC 4.5V Power Test mode : Tx 2476MHz : NWGTS4 M/N

		Ant.	Cable	Amp.		Emissio:	n			
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)		
1	2475.914	28.58	6.87	35.10	96.50	96.85	74.00	-22.85	Peak	
2	2483.500	28.58	6.87	35.10	43.51	43.86	74.00	30.14	Peak	
3	2493.926	28.60	6.91	35.10	49.83	50.24	74.00	23.76	Peak	
4	2500.000	28.60	6.91	35.10	44.46	44.87	74.00	29.13	Peak	

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Data no. : 24 Site no. : 3m Chamber

Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL

Limit : FCC PART 15C AV Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar


: DC 4.5V Power Test mode : Tx 2476MHz M/N : NWGTS4

	Ant. Cable				Amp. Emission				
	Freq. (MHz)	Factor (dB/m)	loss (dB)	Factor (dB)	Reading (dbuv)		Limits (dBuV/m)	_	Remark
1 2 3	2475.990 2483.500 2493.964	28.58	6.87	35.10	96.40 32.63 44.46	96.75 32.98 44.87	54.00 54.00 54.00	-42.75 21.02 9.13	Average Average Average
-	2500.000		6.91		32.52	32.93	54.00	21.07	Average

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 25 Ant. pol. : VERTICAL Dis. / Ant. : 3m 3115

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EIIT : P9 Wii Gretsch Wireless Guitar


: DC 4.5V Power Test mode : Tx 2476MHz M/N : NWGTS4

	-	Factor (dB/m)	loss	Factor	Reading (dbuv)		Limits	_	Remark
1	2475.914	28.58	6.87	35.10	90.08	90.43	74.00	-16.43	Peak
2	2483.500	28.58	6.87	35.10	43.75	44.10	74.00	29.90	Peak
3	2494.230	28.60	6.91	35.10	46.60	47.01	74.00	26.99	Peak
4	2500.000	28.60	6.91	35.10	44.71	45.12	74.00	28.88	Peak

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 26 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C AV Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx 2476MHz : NWGTS4 M/N

		Ant.	Cable	Amp.	Amp. Emission				
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)	
1	2475.990	28.58	6.87	35.10	88.55	88.90	54.00	-34.90	Average
2	2483.500	28.58	6.87	35.10	32.25	32.60	54.00	21.40	Average
3	2493.926	28.60	6.91	35.10	37.73	38.14	54.00	15.86	Average
4	2500.000	28.60	6.91	35.10	32.46	32.87	54.00	21.13	Average

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 27

Ant. pol. : HORIZONTAL Dis. / Ant. : 3m 3115

Frequency (MHz)

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian


EIIT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx Hopping : NWGTS4 M/N

		Ant.	Cable	Amp.	Emission				
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)	
1	2366.160	28.41	6.69	35.12	46.45	46.43	74.00	27.57	Peak
2	2390.000	28.46	6.71	35.12	44.60	44.65	74.00	29.35	Peak
3	2400.000	28.46	6.73	35.12	45.77	45.84	74.00	28.16	Peak
4	2410.048	28.48	6.73	35.12	91.57	91.66	74.00	-17.66	Peak

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 28 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EIIT : P9 Wii Gretsch Wireless Guitar


: DC 4.5V Power Test mode : Tx Hopping M/N : NWGTS4

		Ant.	Cable	Amp.		Emissio	n		
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)	
1	2338.808	28.38	6.67	35.13	45.74	45.66	74.00	28.34	Peak
2	2338.808	28.38	6.67	35.13	32.54	32.46	54.00	21.54	Average
3	2390.000	28.46	6.71	35.12	33.68	33.73	54.00	20.27	Average
4	2390.000	28.46	6.71	35.12	44.60	44.65	74.00	29.35	Peak
5	2400.000	28.46	6.73	35.12	32.57	32.64	54.00	21.36	Average
6	2400.000	28.46	6.73	35.12	45.77	45.84	74.00	28.16	Peak
7	2410.048	28.48	6.73	35.12	85.36	85.45	54.00	-31.45	Average
8	2410.048	28.48	6.73	35.12	89.57	89.66	74.00	-15.66	Peak

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 29

Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49%

Engineer : Paul Tian

EHT : P9 Wii Gretsch Wireless Guitar


Power : DC 4.5V Test mode : Tx Hopping M/N: NWGTS4

		Ant.	Cable	Amp.		Emission				
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)		
1	2475.908	28.58	6.87	35.10	95.70	96.05	74.00	-22.05	Peak	
2	2475.908	28.58	6.87	35.10	90.23	90.58	54.00	-36.58	Average	
3	2483.500	28.58	6.87	35.10	48.81	49.16	74.00	24.84	Peak	
4	2483.500	28.58	6.87	35.10	32.65	33.00	54.00	21.00	Average	
5	2500.000	28.60	6.91	35.10	43.46	43.87	74.00	30.13	Peak	
6	2500.000	28.60	6.91	35.10	33.69	34.10	54.00	19.90	Average	

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 30 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL

Limit : FCC PART 15C PEAK Env. / Ins. : 25\*C/49% Engineer : Paul Tian

EUT : P9 Wii Gretsch Wireless Guitar

: DC 4.5V Power Test mode : Tx Hopping : NWGTS4 M/N

		Ant.	Cable	Amp.		Emissio:	n		
	Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dbuv)	(dBuV/m)	(dBuV/m)	(dB)	
1	2476.088	28.58	6.87	35.10	89.76	90.11	74.00	-16.11	Peak
2	2476.088	28.58	6.87	35.10	85.36	85.71	54.00	-31.71	Average
3	2483.500	28.58	6.87	35.10	44.55	44.90	74.00	29.10	Peak
4	2483.500	28.58	6.87	35.10	32.54	32.89	54.00	21.11	Average
5	2500.000	28.60	6.91	35.10	46.81	47.22	74.00	26.78	Peak
6	2500.000	28.60	6.91	35.10	33.54	33.95	54.00	20.05	Average

- 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- 2. The emission levels that are 20dB below the official limit are not reported.

# 11. ANTENNA REQUIREMENT

## 11.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

## 11.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used for this product is a PCB integral antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of this antenna is only 0dBi.

# 12.DEVIATION TO TEST SPECIFICATIONS

[NONE]