

20910003

Windows® XP Pro for Embedded Systems
OEM Software

082-00004

60045-147-534-885

Product Key M2HFX-KJTBX-4PK6G-6YQ7P-3MD20

Microsoft

Proof of License
Certificate of Authenticity

Label not to be
used separately

X12-51823

www.microsoft.com/embedded



0017253 A0 0728

84040080



1000A12



SAFETY WARNING

Do not crush.
Do not short circuit
Do not heat or incinerate
Do not dismantle.
Do not immerse in any liquid
The cells inside may vent or rupture
Observe charging instructions
Charge: $-20^{\circ}\text{C} < T < 60^{\circ}\text{C}$ (Consult
SAFT for optimized charging below 0°C)
Discharge: $-50^{\circ}\text{C} < T < 60^{\circ}\text{C}$
For best performance :
Store at 15 - 50% state of charge,
with T not exceeding 30°C .



SAFT

Li-ion

Rechargeable battery
2S1P MP174365 CCSJ

P/N : 074342 0003

Nominal voltage : 7.5 V

Rated capacity : 5.3 Ah

Charge

Charge voltage : $8.4\text{ V} \pm 0.08\text{ V}$

Recommended max. current : 5A

Discharge

Max. current : 5A to 5.4V

For rebalancing : 1A max to 0V

Made in France W 42 2007







JLT8404

JLT8404







