	1	2	3	4		5	(	
			REVISIONS					
A	2.整體尺寸公差爲 +/-0.3	,表面上亮膜(需可印條碼) 3mm 000pcs,每一張貼紙與貼紙之 i漆/電鍍/染色/上光/背膠/薄	之間要加虛線刀		ECN	DESCRIPTION	DATE	APPROVED
	原科與外加工(印刷/噴 須符合規範如下: 項次 系列元素 1 鉛(Pb) 2 鎘(Cd) 3 汞(Hg) 4 六價鉻(Cr+6) 5 多溴聯苯(PBBs) 6 多溴二苯醚(PBD 以上六大元素	会量  <80 ppm  <80 ppm	- 限/ 裕 削 等 ) 初 負					
FNAME @			Model:	INTER www.draytek.com support@draytek.com / Start P 903 Upda Band Security Firewall consumption: 16W(MAX.) uput: 12V == 1.4A(from PoE) / Start == 0.55A(from PoE) / Start == 0.55A(from PoE)	SYAP903			В
TEO			導角 2.7-	60 mm	>	3-R1.5		С
REVDATE						底色 : 文字 : LOGO	PANTONE PANTONE	黑
D			暦 紀代 紀 Hsir Droy Tek Taiw TEL Http	26,Fu Shing Road.,Hun-Chu Industrial Park,Ivan 303 R.O.C.:886-3-5972727 FAX	Hsin-Chu, 886-3-597212	VigorAP 903	Model label  No. Rev.	olerances unless otherwise specified  Angle ± 1/2/± 1°  500 ± 0.5 ± 1
_USER				UED DATE Heat Tr	al SEE NOTES: eatment Treatment	Checked Date UNIT	Y 1 Scale 1:1	$\begin{array}{c} 100 & 500 \pm 0/3 & \pm 0.5 \\ 50 & 100 \pm 0.2 & \pm 0.3 \\ 10 & 50 & \pm 0.1 & \pm 0.2 \\ 0 & 10 & \pm 0.05 \pm 0.1 \end{array}$
	1	2	3	4		5	Sheet l of l	CLASS A B

