

47 CFR PART 15 SUBPART C

# TEST REPORT

of

**Zigbee**

Model Name: FX-903C  
Brand Name: (n.a)  
Report No.: SZ08090153E02  
FCC ID: VH4FX803CB

*prepared for*

**LINKTOP TECHNOLOGY CO., LTD.**

Guangye Building, Torch Hi-Tech Industrial Development Zone, Xiamen, China



**Shenzhen Electronic Product Quality Testing Center  
Morlab Laboratory**

3/F, Electronic Testing Building, Shahe Road, Xili,  
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



*NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.*

## TABLE OF CONTENTS

<b>1.</b>	<b>TEST CERTIFICATION .....</b>	<b>4</b>
<b>2.</b>	<b>GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1</b>	<b>EUT Description .....</b>	<b>5</b>
<b>2.2</b>	<b>Test Standards and Results .....</b>	<b>7</b>
<b>2.3</b>	<b>Facilities and Accreditations .....</b>	<b>8</b>
2.3.1	Facilities .....	8
2.3.2	Test Environment Conditions .....	8
<b>3.</b>	<b>47 CFR PART 15C REQUIREMENTS .....</b>	<b>9</b>
<b>3.1</b>	<b>Peak Output Power .....</b>	<b>9</b>
3.1.1	Requirement .....	9
3.1.2	Test Description .....	9
3.1.3	Test Result .....	10
<b>3.2</b>	<b>Bandwidth .....</b>	<b>12</b>
3.2.1	Definition .....	12
3.2.2	Test Description .....	12
<b>3.3</b>	<b>Conducted Spurious Emissions .....</b>	<b>14</b>
3.3.1	Requirement .....	14
3.3.2	Test Description .....	14
3.3.3	Test Result .....	14
<b>3.4</b>	<b>Power spectral density (PSD) .....</b>	<b>18</b>
3.4.1	Requirement .....	18
3.4.2	Test Description .....	18
3.4.3	Test Result .....	18
<b>3.5</b>	<b>Band Edge .....</b>	<b>21</b>
3.5.1	Requirement .....	21
3.5.2	Test Description .....	21
3.5.3	Test Result .....	22
<b>3.6</b>	<b>Conducted Emission .....</b>	<b>24</b>
3.5.4	Requirement .....	24
3.5.5	Test Description .....	24

3.5.6	Test Result .....	25
<b>3.6</b>	<b>Radiated Emission .....</b>	<b>27</b>
3.6.1	Requirement .....	27
3.6.2	Test Description .....	27
3.6.3	Test Result .....	28

## 1. TEST CERTIFICATION

Equipment under Test: Zigbee

Brand Name: (n.a)  
Model Name: FX-903C  
FCC ID: VH4FX803CB

Applicant: LINKTOP TECHNOLOGY CO., LTD.  
Guangye Building, Torch Hi-Tech Industrial Development Zone,  
Xiamen, China

Manufacturer: LINKTOP TECHNOLOGY CO., LTD.  
Guangye Building, Torch Hi-Tech Industrial Development Zone,  
Xiamen, China

Test Standards: 47 CFR Part 15 Subpart C

Test Date(s): November 10, 2008 - November 26, 2008

Test Result: PASS

### \* We Hereby Certify That:


The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by: Li Yi Dated: 2008.12.03  
Li Yi

Reviewed by: Wei Yanquan Dated: 2008.12.03  
Wei Yanquan

Approved by: Shu Luan Dated: 2008.12.03  
Shu Luan




## 2. GENERAL INFORMATION

### 2.1 EUT (Desk Charge ) Description

EUT .....: Zigbee  
Model Name .....: FX-903C  
Serial No.....: (n.a, marked #1 by test site)  
IMEI .....: (n.a)  
Hardware Version .....: FX-803C-02  
Software Version .....: LT\_WP821NV1.0.0B09\_0905.bin  
Modulation Type.....: OQPSK  
Frequency .....: 2.405GHz - 2.480GHz (at interval of 5MHz)  
Power Supply.....: The EUT can working normal under the mode of powered by  
Accessory Equipment 1 or Accessory Equipment 2.  
Accessory Equipment 1 .....: Battery (Powered for EUT)  
Brand name: SHIDE  
Model Name: FX-803C (PN: 11W0020)  
Capacitance: 350mAh  
Rated voltage: 3.6V  
Charge limited: 4.3V  
Manufacturer: SHIDA BATTERY TECHNOLOGY CO.,LTD  
Manufacturer Address: No.30, Xingyue Road, C district, Shishan  
Technology Industrial Park, Nanhai district,  
Foshan, China.  
Accessory Equipment 2 .....: AC Adapter (Charger for Accessory Equipment 1)  
Brand Name: RUIDE  
Model Name: STC-A22O50C55-C  
Serial No.: (n.a. marked #1 by test site)  
Rated Input: 100-240V, 0.2A,50/60Hz  
Rated Output: 5.0V, 650mA  
Manufacturer: Ruide Electronical Industrial Co.Ltd  
Manufacturer Address: Floor 2nd, Buidling 2nd, Mingqi  
Technology Park, Honghualing North district, Xili Town, Nanshan  
District, Shenzhen, China.  
Wire Length: 145cm

Test Sample Skech.....:



The EUT is used to keep the handset in leash. When the handset works normally, a communication link is eastablished to the EUT(2.4G). The handset can work appropriately only if this 2.4G communication link is eastablished.

- Note 1:* By the FX803C composition of the Handset and the Desk Charger (EUT), and only the Desk Charger tested in this report.
- Note 2:* The EUT as a Module is positioned on the Evaluation Board, it operating at 2.4GHz band; the frequencies allocated is  $F(\text{MHz})=2405+5*(n-11)$  ( $11 \leq n \leq 26$ ). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2405MHz), 7 (2440MHz) and 16 (2480MHz).
- Note 3:* For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Wi-Fi, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-05 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.247(a)	Number of Hopping Frequency	(n.a)
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	Bandwidth	PASS
4	15.247(a)	Carrier Frequency Separation	(n.a)
5	15.247(a)	Time of Occupancy (Dwell time)	(n.a)
6	15.247(c)	Conducted Spurious Emission	PASS
7	15.247(c)	Band Edge	PASS
8	15.207	Conducted Emission	PASS
9	15.209 15.247(c)	Radiated Emission	PASS
10	15.247(d)	Power spectral density (PSD)	PASS

## **2.3 Facilities and Accreditations**

### **2.3.1 Facilities**

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### **2.3.2 Test Environment Conditions**

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	96



### 3. 47 CFR PART 15C REQUIREMENTS


#### 3.1 Peak Output Power

##### 3.1.1 Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

##### 3.1.2 Test Description

###### A. Test Setup:



The EUT of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Wi-Fi Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

###### B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Service Simulator	Agilent	E5515C	GB43130131	2008.06	1year
Spectrum Analyzer	Agilent	E7405A	US44210471	2008.09	1year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)	(n.a.)


### 3.1.3 Test Result

The EUT operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.


#### A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power			Limit		Verdict
		dBm	W	Refer to Plot	dBm	W	
11	2405	-6.919	0.0002	Plot A	21	0.125	PASS
17	2440	-4.871	0.0032	Plot B			PASS
26	2480	-6.52	0.0002	Plot C			PASS


#### B. Test Plot:



(Plot A: Channel= 2405)



(Plot B: Channel = 2440)



(Plot C: Channel = 2480)

## 3.2 Bandwidth

### 3.2.1 Definition

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 20 dB bandwidth must be greater than 500 kHz.

### 3.2.2 Test Description

See section 3.1.2 of this report.


#### 3.2.2.1 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.


#### A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Refer to Plot	Limits (kHz)	Result
11	2405	520	Plot A	$\geq 500$	PASS
17	2440	505	Plot B	$\geq 500$	PASS
26	2480	505	Plot C	$\geq 500$	PASS


#### B. Test Plot:



(Plot A: Channel = 2405)



(Plot B: Channel = 2440)



(Plot C: Channel = 2480)

### 3.3 Conducted Spurious Emissions

#### 3.3.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 3.3.2 Test Description

See section 3.1.2 of this report.

#### 3.3.3 Test Result


The EUT operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

##### A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
11	2405	---	Plot A.1/A.2	6.877	-13.12	PASS
17	2440	---	Plot B.1/B.2	7.04	-12.96	PASS
26	2480	---	Plot C.1/C.2	7.052	-12.95	PASS

##### B. Test Plot:


Note: the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 11, 30MHz to 3GHz)



(Plot A.2: Channel = 11, 3GHz to 25GHz)




(Plot B.1: Channel = 17, 30MHz to 3GHz)




(Plot B.2: Channel = 17, 3GHz to 25GHz)





(Plot C.1: Channel = 26, 30MHz to 3GHz)



(Plot C.2: Channel = 26, 3GHz to 25Gz)

### 3.4 Power spectral density (PSD)

#### 3.4.1 Requirement

According to FCC section 15.247(d), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

#### 3.4.2 Test Description

See section 3.1.2 of this report.


#### 3.4.3 Test Result

The lowest, middle and highest channels are tested to verify the band edge emissions.


##### A. Test Verdict:

Spectral power density (dBm)					
Channel: 11 Frequency, 2405MHz		Channel: 17 Frequency, 2440MHz		Channel: 26 Frequency, 2480MHz	
Test Result	Test plot	Test Result	Test plot	Test Result	Test plot
-7.818	Plot A	-5.792	Plot B	-7.271	Plot C
Measurement uncertainty: $\pm 1.3\text{dB}$					


Test Plot:



(Plot A: Channel = 11)



(Plot B: Channel = 17)



(Plot C: Channel = 26)


### 3.5 Band Edge

#### 3.5.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 3.5.2 Test Description

##### A. Test Setup



The Module of the EUT is powered by the Battery charged with the AC Adapter. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength..

##### B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
-------------	--------------	-------	------------	-----------	----------

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2008.9	1year
Receiver	Agilent	E7405A	US44210471	2008.9	1year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2008.8	2year
Test Antenna	Schwarzbeck	BBHA 9120C	9120C-384	2008.8	1year


### 3.5.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.


#### A. Test Verdict:.

Channel	Frequency (MHz)	Max. Emission in the Restricted Bands (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Verdict
		PK	AV	PK	AV	
11	2402	66.38	39.98	74	54	PASS
26	2480	63.83	42.7	74	54	PASS


#### B. Test Plot:




(Plot A1: Frequency=2405 PEAK)



(Plot A2: Frequency=2405 AVERAGE)



(Plot B1: Frequency=2480 PEAK)



(PlotB2: Frequency=2480 AVERAGE)

### 3.6 Conducted Emission

#### 3.5.4 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

#### 3.5.5 Test Description

##### A. Test Setup:





## B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2008.09	1year
LISN	Schwarzbeck	NSLK 8127	812744	2008.09	1year
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)


## 3.5.6 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.


### A. Test Verdict Recorded for Suspicious Points:

No.	@Frequency (MHz)	Measured Emission Level (dBμV)				Limit (dBμV)		Verdict
		PK	QP	AV	Phase	QP	AV	
1	2.09	40.12	--	--	L	--	--	PASS
2	24.06	42.58	--	--	L	--	--	PASS
3	(n.a)	(n.a)	(n.a)	(n.a)	L	(n.a)	(n.a)	(n.a)
4	(n.a)	(n.a)	(n.a)	(n.a)	L	(n.a)	(n.a)	(n.a)
5	(n.a)	(n.a)	(n.a)	(n.a)	L	(n.a)	(n.a)	(n.a)
6	(n.a)	(n.a)	(n.a)	(n.a)	L	(n.a)	(n.a)	(n.a)
7	2.21	--	--	--	N	--	--	PASS
8	24.06	--	--	--	N	--	--	PASS
9	(n.a)	(n.a)	(n.a)	(n.a)	N	(n.a)	(n.a)	(n.a)
10	(n.a)	(n.a)	(n.a)	(n.a)	N	(n.a)	(n.a)	(n.a)
11	(n.a)	(n.a)	(n.a)	(n.a)	N	(n.a)	(n.a)	(n.a)
12	(n.a)	(n.a)	(n.a)	(n.a)	N	(n.a)	(n.a)	(n.a)

### B. Test Plot:



(Plot A: L Phase)



(Plot B: N Phase)

### 3.6 Radiated Emission

#### 3.6.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

#### 3.6.2 Test Description

##### A. Test Setup:



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

## B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2008.09	1year
Semi-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2008.08	2year
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2008.08	1year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2008.08	1year

## 3.6.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors.

## A. Test Verdict for Harmonics:

### The Fundamental Emissions

The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dB $\mu$ V/m)		Antenna Polarization	Refer to Plot
		PK	AV		
11	2405	100.15	92.15	Horizontal	Plot A.3
		100.57	94.27	Vertical	Plot A.7
17	2440	100.35	93.21	Horizontal	Plot B.3
		100.49	93.68	Vertical	Plot B.7
26	2480	101.24	95.87	Horizontal	Plot C.3
		102.21	96.10	Vertical	Plot C.7


### The Radiated Emissions Fall in the Restricted Bands

Channel	Frequency (MHz)	Antenna Polarization	Max. Emission in the Restricted Bands (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Verdict
			PK	AV	PK	AV	
11	2405	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS
17	2440	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS
26	2480	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS


Also refer to following plots for the emissions falling in the restricted bands.

## B. Test Plot for the Whole Measurement Frequency Range:


### Plots for Channel = 11




(Plot A.1: 9kHz to 30MHz)




(Plot A.2: Antenna Horizontal, 30MHz to 1GHz)



(Plot A.3: Antenna Horizontal, 1GHz to 25GHz)




(Plot A.4: Antenna Vertical, 30MHz to 1GHz)




(Plot A.5: Antenna Vertical, 1GHz to 25GHz)

Plot for Channel = 17




(Plot B.1: 9kHz to 30MHz)




(Plot B.2: Antenna Horizontal, 30MHz to 1GHz)






(Plot B.3: Antenna Horizontal, 1GHz to 25GHz)




(Plot B.4: Antenna Vertical, 30MHz to 1GHz)




(Plot B.5: Antenna Vertical, 1GHz to 25GHz)


Plot for Channel = 26




(Plot C.1: 9kHz to 30MHz)




(Plot C.2: Antenna Horizontal, 30MHz to 1GHz)



(Plot C.3: Antenna Horizontal, 1GHz to 25GHz)



(Plot C.4: Antenna Vertical, 30MHz to 1GHz)



(Plot C.5: Antenna Vertical, 1GHz to 25GHz)

**\*\* END OF REPORT \*\***