

WP635Z-0.22 list (with GPRS)

	material code	type	component	parameter	encapsulation	quantity	tab
		circuit board	WP635Z-0.22			1	
m a i n  b o a r d		chip resistance	0	±5%	0603	5	7,R50,R14,R20,R9
		chip resistance	0	±5%	1206	2	R2,L1
		chip resistance	0.1R	±5%	1206	1	R41
		chip resistance	100	±5%	0603	20	R40, R53, R39, R38, R37, R36, R34, R33, R32, R31, R30, R29, R28, R27, R26, R25, R24, R52, R55, R63
		chip resistance	100K	±5%	0603	2	R23,R22
		chip resistance	10K	±5%	0603	8	R61,R60,R35,R6,R4,R57
		chip resistance	1K	±5%	0603	3	R45,R44,R43
		chip resistance	1M	±5%	0603	1	R58
		chip resistance	20	±5%	0603	1	R17
		chip resistance	20K	±5%	0603	1	R16
		chip resistance	4.7K	±5%	0603	2	R10,R42
		chip resistance	47.5K	±5%	0603	1	R1
		chip capacitance	0.1uF	-20%+80%	0603	4	C4,C2,C1,R8
		chip capacit	0.22UF	-20%+80%	0603	4	C41,C44,C43,C45
		chip capacit	1UF	-20%+80%	0603	7	C31,C30,C21,C18,C33
		chip capacitance	22PF	-20%+80%	0603	35	C35,C36,C27,C26,C25,C24,C23,C22,C19,C17,C16,C15,C14,C13,C12,C11,C10,C9,C8,C7,C6,C5,C46,C50,C51,C52,C47,C48,C49,C53,C54,C55,C56,C57,C20
		chip capacit	47PF	%+80%(风华	0603	2	R3,C3
		chip magnetic bead	1UH magnetic bead	±20%	0603	4	L7,L6,L5,L4
		chip inducta	330UH	±20%	1210	1	L1
		diode	IN4148	column	SMD	1	VD2
		diode	SK24		SMD	1	VD5
		diode	5.1V IC	±5%	SMD	1	D1
		dynatron	9014		SOT23	3	BG5,BG4,BG2
		MOFT	SM9435	(CEM9435)	SMD	1	VT1
		IC	MC34119		SO-8	1	U1

	IC	MAX3238		SMD	1	U4
	IC	R1111/AP5151	3.2V	STO-25	1	U3
	something can be inserted	30PINFPC seat(touch point is under)	space between feet is 0.5MM	SMD	1	JP1
	something can be inserted	SIM card seat	Fushikang(W L608C3-M04-TF)	SMD	1	U2
	module	ZTE MG630		SMD	1	U5
	electrolysis capacitance	1000UF/10V/16V	-20%+80%	THT	2	C37,C29
	something can be inserted	DC seat	DC470-2.5	THT	1	J2
	something can be inserted	DB9 tie-in		THT	1	X3
	something can be inserted	two-core seat	space between feet is 2.54MM	THT	1	X2
	something can be inserted	part reed on-	HS-2203	THT	1	SW6
	something can be inserted	double row on-off	SS-22F04G5	THT	1	S1
	something can be inserted	line whice change antenna (SMA)	line length43.1 ±1.5MM		1	
	MIC(work for hand-free)	small electret B6027AP-111B607AL-89	-41~-45dB 2.2k 2.0v D57		1	
	chip capacitance	56PF		0603	1	two ends of electret in the hand-free
	something can be inserted	616E line	long 8cm(4*8	THT	1	JP2
	circuit board	LCD board (thick 1.0mm)			1	WP635Z-LCD-0.1
	chip resistance	140K(for Guoxian LCD)	R3 not weld	0805	1	R2
	chip resistance	180K(for Gaozhuoli LCD)	R2 not weld	1206	1	R3
	chip resistance	300K		0805	2	R4,R5
	chip resistance	820K	for Guoxian LED	0805	1	R1

L  
C  
D  
板

chip resistance	845K	for Gaozhuoli LED	0805	1	R1
diode	IN4148		SMD	1	VD1
chip capacitance	56PF		0805	1	C11
chip capacitance	1UF/25V	Sunsang	0805	10	B,C4,C5,C6,C7,C8,C9,C10
something can be inserted	30PINFPC seat	space between is 0.5, under side connect	THT	1	JP1
diode	LEB	red Φ 5MM	THT	1	D2
something can be inserted	LED (Guoli, G aozhuoli)	GXT13064- 11 (olivine film) GDSC-VT- 13064WM-01		1	
something ca	parcel which be in a poor light	kelly64313		1	
something ca	small iron frame	see drawing		1	
something ca	LCD pressurize mat	WP635H-01		1	
something ca	red-black line	line length is 90mm, both ends dip stannum		2	J2,J3
something can be inserted	14PIN row line	space between feet 2.0MM, both ends dip stannum, line length 36mm		1	J1
MIC	small electret B6027AP- 111B607AL- 89	-41~-45dB 2.2k 2.0v D57		1	
something can be inserted	red-black line (MIC)	120mm long, both ends dip stannum		1	
something can be inserted	616E line	2*150 2*40mm		1	
something can be inserted	receiver sponge mat	see drawing		1	
something can be inserted	electret cover	see drawing		1	
something can be inserted	screw cover A,B	see drawing		2	

		something can be inserted	handle crinkle line	see drawing(line length2440±30m m)		1	
		circuit board	Y (thick 1.6mm)			1	WP635Z-KEY-0.21
包 装		screw	PA2.6*6	plating color Zn	board,insert reed	10	
		screw	PA2.6*6	plating color Zn	key-press board, loudspea ker	11	
		screw	PA3*10	plating color Zn	machine shell	1	
		screw	PA3*8	plating color Zn	machine shell	3	
		screw	FA2.6*6Φ4	black crew cut	cover can lock battery	1	
		screw	PA2.5*8	plating color Zn	handle shell	2	
		screw	PWA2.6*6*8 .5	plating color Zn	iron in the hand-free	2	
		label	backbody label			1	
		label	on-off label			1	
			loudspeaker	Φ50mm		1	
			feet mat			4	
			loudspeaker dustproof net	Φ51mm		1	
			loudspeaker press mat			2	
			4.6V power supply on-off	90-300VDC- Φ2.5		1	
			user manual			1	
			eligibility certificate			1	
			PE bag	1 set		1	
			sth serving as a support made from paper pulp	see drawing		1	
			colorful box			1	
			warranty stick paper			1	
			producing area label			1	
			receiver dustproof net	Φ37mm		1	

		iron which in the hand- free	48±3g		1	
		30PINFPC line	line length 13MM		1	
		L double frequency antenna	TQZ-WZ- 900/1800/70		1	
		battery mat1	34*14.5*78		1	
		battery mat2	50*40*72.5		1	
		on-off keep off parcel	61.4*12.8*0 .3 (PVC black)		1	
		electret cover	D10*D3*T2		1	
		receiver	SD150		1	
		battery	li-ion battery 3.6V/850mAh		1	
		box			1	
		SMN number	3*0.7cm single row		2	
		IMEI number	3.8*1.2cm double row		2	
		shell material			1	

workout:

Auditing:

authorize: