

Prüfbericht-Nr.:

10053160 001

Auftrags-Nr.:

114036792

Seite 1 von 45

Test Report No .:

Order No.:

Page 1 of 45

Kunden-Referenz-Nr.: Client Reference No.:

N/A

Auftragsdatum: Order date:

5-Jun-2015

VENCER CO., LTD., 14F-12, No.79, Sec.1, Hsin Tai Wu Rd., Hsi-Chih, New Taipei

Auftraggeber: Client:

City, Taiwan 22101

Prüfgegenstand:

Bluetooth USB Dongle

Test item:

Bezeichnung / Typ-Nr.: VD-21x4 (x=0-9)

Identification | Type No.:

Auftrags-Inhalt:

FCC Part 15C Test report (BR/EDR)

Order content:

Prüfgrundlage: Test specification:

FCC 47CFR Part 15: Subpart C Section 15.247

Wareneingangsdatum: 9-Jun-2015

Date of receipt:

Prüfmuster-Nr.:

A000211659-001 A000211659-002

Test sample No.:

15-Aug-2015 - 21-Sep-2015

Prüfzeitraum: Testing period:

EMC Laboratory Taipei

Ort der Prüfung: Place of testing:

Prüflaboratorium: TUV Rheinland Taiwan Ltd.

Testing laboratory:

geprüft von / tested by:

Prüfergebnis*:

Test result*:

Pass

kontrolliert von I reviewed by:

2015-10-28

Ryan W. T. Chen / Project Manager

Datum Date

Name / Stellung Name / Position

Unterschrift Signature

2015-10-28

Datum

Date

Arvin Ho/Department Manager

Name / Stellung Name / Position

Unterschrift Signature

Sonstiges / Other:

Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:

Prüfmuster vollständig und unbeschädigt Test item complete and undamaged

* Legende:

1 = sehr gut

2 = gut

3 = befriedigend

4 = ausreichend

5 = mangelhaft N/T = nicht getestet

P(ass) = entspricht o.g. Prüfgrundlage(n)

F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar

Legend:

1 = very good 2 = goodP(ass) = passed a.m. test specification(s) 3 = satisfactory

F(ail) = failed a.m. test specification(s)

4 = sufficient N/A = not applicable 5 = poorN/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark. V04



> 10053160 001 Seite 2 von 45 Prüfbericht - Nr.: Page 2 of 45

Test Report No.

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Passed

5.1.2 PEAK OUTPUT POWER

RESULT: Passed

5.1.3 20DB BANDWIDTH

RESULT: Passed

5.1.4 99% BANDWIDTH

RESULT: Passed

5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100kHz BANDWIDTH

RESULT: Passed

5.1.6 Spurious Emission

RESULT: Passed

5.1.7 Frequency Separation

RESULT: Passed

5.1.8 NUMBER OF HOPPING FREQUENCY

RESULT: Passed

5.1.9 TIME OF OCCUPANCY

RESULT: Passed

5.2.1 Mains Conducted Emissions

RESULT: Passed

6.1.1 ELECTROMAGNETIC FIELDS

RESULT: Passed



Prüfbericht - Nr.: 10053160 001 Test Report No.

Seite 3 von 45 Page 3 of 45

Contents

	Contents	
1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2.	TEST SITES	6
2.1	TEST LABORATORY	6
2.2	TEST FACILITY	6
2.3	LIST OF TEST AND MEASUREMENT INSTRUMENTS	7
2.4	TRACEABILITY	8
2.5	CALIBRATION	8
2.6	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	SYSTEM DETAILS AND RATINGS	9
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	11
3.5	SUBMITTED DOCUMENTS	11
4.	TEST SET-UP AND OPERATION MODES	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION	12
4.2	TEST OPERATION AND TEST SOFTWARE	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	13
4.5	TEST SETUP DIAGRAM	13
5.	TEST RESULTS	15
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	
5.1. 5.1.	7 · · · · · · · · · · · · · · · · · · ·	
5.1. 5.1.		
5.1. 5.1.	.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz	
5.1	Bandwidth	_
5.1	.7 Frequency Separation	32
5.1. 5.1.		
5.2	Mains Emissions	
5.2 5.2.		



Produkte

	bericht - Nr.: Report No.	10053160 001	Seite 4 von 4 Page 4 of 48
6.	SAFETY HUMAN E	XPOSURE	40
6.1 6.1		EY EXPOSURE COMPLIANCE	
7.	PHOTOGRAPHS OF	THE TEST SET-UP	41
8.	LIST OF TABLES		45
9.	LIST OF PHOTOGE	APHS	45



10053160 001 Seite 5 von 45 Prüfbericht - Nr.: Page 5 of 45

Test Report No.

1. General Remarks

Complementary Materials

The following attachments are integral parts of this test report:

Appendix P: Photo Documentation

(File Name: 10053160APPENDIX P)

Appendix D: Test Result of Radiated Emissions

(File Name: 10053160APPENDIX D)

Test Specifications

The following standards were applied

Table 1: Applied Standard and Test Levels

Radio

FCC CFR47 Part 15: Subpart C Section 15.247 RSS-247 Issue 1 May 2015 RSS-Gen, Issue 4, November 2014 ANSI C63.10:2013 Public Notice DA 00-705

NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2011)(100年6月28日)



 Prüfbericht - Nr.:
 10053160 001
 Seite 6 von 45

 Test Report No.
 Page 6 of 45

2. Test Sites

2.1 Test Laboratory

TUV Rheinland Taiwan Ltd. Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District, Taichung City 428
Taiwan (R.O.C.)

2.2 Test Facility

TUV Rheinland Taiwan Ltd. Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist. Taipei City 105
Taiwan (R.O.C.)

FCC Registration No.: 365730 IC Canada Registration No.: 9465A-1 TAF Accredited NCC Test Lab. No.:0759

TAF ISO17025 Certification effective periods: 2013-Jul-1st to 2016-Jun-30th



Testing Laboratory 0759

> Prüfbericht - Nr.: 10053160 001

Seite 7 von 45 Page 7 of 45 Test Report No.

2.3 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Туре	S/N	Last Calibration	Next Calibration
EMI Test Receiver	R&S	ESR7	101062	10-Sep-15	19-Sep-16
Bilog Antenna	TESEQ	CBL6111D	29802	4-Jul-14	3-Jul-16
Spectrum Analyzer	R&S	FSV 40	100921	17-Dec-14	16-Dec-15
Spectrum Analyzer	Agilent	N9010A	MY53470241	1-Apr-15	30-Mar-16
Horn Antenna	ETS-Lindgren	3117	138160	12-Jan-15	11-Jan-17
Horn Antenna (18GHz~40GHz)	COM- POWER	AH840	101031	30-Oct-13	29-Oct-15
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	24-Dec-14	24-Dec-15
Preamplifier (18 GHz -40 GHz)	COM- POWER	PAM-840	461257	26-Aug-14	26-Aug-16
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM30180	60558	4-Nov-14	3-Nov-15
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	22-Oct-14	21-Oct-15
EMI Test Receiver	R&S	ESCI7	100797	28-Dec-14	27-Dec-15
Spectrum Analyzer	R&S	FSL3	101943	7-Sep-15	7-Sep-16
LISN (1 phase)	R&S	ENV216	101243	1-Jun-15	31-May-16
LISN	R&S	ENV216	101262	16-Jun-15	15-Jun-16

 Prüfbericht - Nr.:
 10053160 001
 Seite 8 von 45

 Test Report No.
 Page 8 of 45

2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.5 Calibration

requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basics using in house standards or comparisons.

2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements:.

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
RF power, conducted	± 1.5 dB
Adjacent channel power	±3 dB
Radiated emission of transmitter, valid up to 26 GHz	± 6 dB
Radiated emission of receiver, valid up to 26 GHz	± 6 dB
Temperature	± 2 °C
Humidity	± 10 %



 Prüfbericht - Nr.:
 10053160 001
 Seite 9 von 45

 Test Report No.
 Page 9 of 45

3. General Product Information

3.1 Product Function and Intended Use

A class of Bluetooth low energy devices that broadcast their identifier to nearby portable devices. The technology enables smartphones, tablets and other devices to perform actions by APP when in close proximity to an Beacon

For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment	Bluetooth 4.0 Class I USB dongle
Type Designation	VD-2104
FCC ID	VHVBTVD2104

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Spacing	1 MHz
Channel number	79
Operation Voltage	5Vdc
Modulation	GFSK, π /4 DQPSK, 8 DPSK
Antenna gain	-1.72 dBi

 Prüfbericht - Nr.:
 10053160 001
 Seite 10 von 45

 Test Report No.
 Page 10 of 45

Table 6: Frequency hopping information

Technical Specification	Description
Hopping Range	Hereby we declare that the maximum frequency of this device is: 2402-2480MHz. This is according the Bluetooth Core Specification V2.1+EDR for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04).
Hopping Sequence	Example of a 79 hopping sequence in data mode: 33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73, 07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56, 69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43, 15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47,
Receiver input bandwidth	The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings. Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

3.3 Independent Operation Modes

The basic operation modes are:

- A. Transmitting
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. Receiving



Prüfbericht - Nr.:	10053160 001	Seite 11 von 45
Test Report No.		Page 11 of 45

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description



 Prüfbericht - Nr.:
 10053160 001
 Seite 12 von 45

 Test Report No.
 Page 12 of 45

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 4. All testing were performed according to the procedures in ANSI C63.10: 2013 and DA 00-705 of March 30, 2000.

The samples were used as follows: Conducted: **A000211659-002**Radiation: **A000211659-001**

Full test was applied on all test modes, but only worst case was shown.

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Kind of Equipment	Manufacturer	S/N
Laptop	HP	CNF0339QBM

 Prüfbericht - Nr.:
 10053160 001
 Seite 13 von 45


 Test Report No.
 Page 13 of 45

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested containing the noise suppression parts as in the Photo Appendix and the Test Setup Photos. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m



Test Report No.

Prüfbericht - Nr.: 10053160 001

Seite 14 von 45 *Page 14 of 45*

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement





Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement





 Prüfbericht - Nr.:
 10053160 001
 Seite 15 von 45

 Test Report No.
 Page 15 of 45

5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT: Passed

Test standard : LP0002(2011): 2.2, 3.10.1, (3)

FCC Part 15.247(b)(4), Part 15.203 and RSS-

Gen 8.3

Requirement : use of approved antennas only with directional gains that

do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of -1.72 dBi dBi. The antenna is a printed PCB trace with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.



10053160 001 Seite 16 von 45 Prüfbericht - Nr.: Page 16 of 45

Test Report No.

5.1.2 Peak Output Power

RESULT: Passed

Test standard FCC Part 15.247(b)(1),

RSS-247 5.4(2)

LP0002(2011): 3.10.1, (2)

Basic standard DA 00-705 of March 30, 2000

LP0002(2011) Appendix II

Kind of test site Shielded room

Test setup

Low/ Middle/ High A Test Channel

Operation Mode

22-26 °C 50-65 % Ambient temperature : Relative humidity : Atmospheric pressure : 100-103 kPa

Table 7: Test result of Peak Output Power, GFSK modulation

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	9.91	0.00979	0.125
Middle Channel	2441	7.91	0.00618	0.125
High Channel	2480	8.95	0.00785	0.125

Table 8: Test result of Peak Output Power, 8DPSK modulation

Channel	Channel Frequency	Peak Outpu	t Power	Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	8.31	0.00678	0.125
Middle Channel	2441	7.03	0.00505	0.125
High Channel	2480	8.18	0.00658	0.125

Pmax: 9.8 mW



Test Report No.

Prüfbericht - Nr.: 10053160 001

0053160 001

Seite 17 von 45Page 17 of 45

5.1.3 20dB Bandwidth

RESULT: Passed

Test standard : FCC Part 15.247(a)(1),

RSS-247 5.1(1)

LP0002(2011): 3.10.1, (6.1.1)

Basic standard : DA 00-705 of March 30, 2000

LP0002(2011) Appendix II

Test setup

Test Channel : Low/ Middle/ High

Operation Mode : A

Ambient temperature : 22-26°C
Relative humidity : 50-65%
Atmospheric pressure : 100-103kPa

Table 9: Test result of 20dB Bandwidth, GFSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	975	1.5	Pass
Mid Channel	2441	1027	1.5	Pass
High Channel	2480	1028	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.

Table 10: Test result of 20dB Bandwidth, 8DPSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	1300	1.5	Pass
Mid Channel	2441	1300	1.5	Pass
High Channel	2480	1299	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.

If the carrier separation frequency of a Bluetooth Device is set at 1 MHz due to the firmware setting and the Bluetooth Standard, then the limit for the 20 dB Bandwidth, becomes 1 MHZ / 0.66666 = 1.5 MHz.




Prüfbericht - Nr.: 10053160 001

Test Report No.


Seite 18 von 45Page 18 of 45

Test Plot of 20dB Bandwidth, GFSK modulation

Low Channel



Middle Channel






Prüfbericht - Nr.: 10053160 001

Seite 19 von 45Page 19 of 45


Test Report No.





Test Plot of 20dB Bandwidth, 8DPSK modulation

Low Channel






Prüfbericht - Nr.: 10053160 001


Seite 20 von 45Page 20 of 45

Test Report No.

Middle Channel



High Channel





10053160 001 Seite 21 von 45 Prüfbericht - Nr.: Page 21 of 45

Test Report No.

5.1.4 99% Bandwidth

RESULT: Passed

Test standard RSS-Gen (Issue 4) Basic standard RSS-Gen (Issue 4) Kind of test site Shielded room

Test setup

Test Channel Low/ Middle/ High

Operation Mode Α

Ambient temperature : Relative humidity : Atmospheric pressure : 22-26°C 50-65% 100-103kPa

Table 11: Test result of 99% Bandwidth, GFSK modulation

Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)
Mid Channel	2441	881.76

Table 12: Test result of 99% Bandwidth, PSK modulation

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Mid Channel	2441	1.174

Prüfbericht - Nr.: 10053160 001

Test Report No.

Seite 22 von 45Page 22 of 45


Test Plot of 99% Bandwidth, GFSK modulation

Middle Channel



Test Plot of 99% Bandwidth, 8DPSK modulation

Middle Channel





Prüfbericht - Nr.: 10053160 001 Seite 23 von 45 Page 23 of 45

Test Report No.

5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

RESULT: Passed

FCC part 15.247(d), Test standard

RSS-247 5.5

LP0002(2011): 3.10.1, (5)

Basic standard DA 00-705 of March 30, 2000

LP0002(2011) Appendix II

Limit 20dB (below that in the 100kHz bandwidth within the

band that contains the highest level of the desired power)

Kind of test site Shielded room

Test setup

Test Channel Low/ Middle/ High

Operation Mode

Ambient temperature 22-26°C Relative humidity 50-65% Atmospheric pressure 100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.

Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.



Prüfbericht - Nr.: 10053160 001 Test Report No.

3160 001 Seite 24 von 45
Page 24 of 45

Test Plot of 100kHz Conducted Emissions, GFSK modulation

Low Channel



Middle Channel





Prüfbericht - Nr.: 10053160 001

Seite 25 von 45 *Page 25 of 45*


High Channel

Test Report No.



Test Plot of 100kHz Conducted Emissions, 8DPSK modulation

Low Channel






Prüfbericht - Nr.: 10053160 001


Seite 26 von 45Page 26 of 45

Middle Channel

Test Report No.



High Channel




Prüfbericht - Nr.: 10053160 001

Test Report No.


Seite 27 von 45Page 27 of 45

Test Plot of 100kHz Bandwidth of Frequency Band Edge, GFSK modulation

Low Channel



High Channel






Prüfbericht - Nr.: 10053160 001

Seite 28 von 45Page 28 of 45

Test Report No.

Hopping ON




Prüfbericht - Nr.: 10053160 001 Test Report No.


Seite 29 von 45Page 29 of 45

Test Plot of 100kHz Bandwidth of Frequency Band Edge, 8DPSK modulation

Low Channel



High Channel





Prüfbericht - Nr.: 10053160 001

Seite 30 von 45 *Page 30 of 45*

Test Report No.

Hopping ON





Seite 31 von 45 Prüfbericht - Nr.: 10053160 001 Page 31 of 45

Test Report No.

5.1.6 Spurious Emission

RESULT: Passed

Test standard FCC part 15.247(d), FCC 15.205, FCC 15.209, RSS-

210 2.2, RSS-247 5.5 and RSS-Gen 8.9

LP0002(2011): 3.10.1, (5)

Basic standard ANSI C63.10

Limits Radiated emissions which fall in the restricted bands,

> as defined in FCC 15.205(a) and RSS-Gen i4, 8.9 (Table 6), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen i4,

8.9 (Table 4 and 5).

Radiated emissions which fall in the restricted bands, as defined in LP0002(2011): 2.7, must comply with

the radiated emission limits specified in

LP0002(2011): 2.8

Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.249(a), RSS-Gen i4, 8.9 (Table 4 and 5) and RSS-210 A2.9(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits

specified in LP0002(2011): 2.8

Kind of test site 3m Semi-Anechoic Chamber

Test setup

Test Channel Low/ Middle/ High

Operation Mode A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix D. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.



10053160 001 Seite 32 von 45 Prüfbericht - Nr.:

Page 32 of 45 Test Report No.

5.1.7 Frequency Separation

RESULT: Passed

Test standard FCC part 15.247(a)(1)

RSS-247 5.1

LP0002(2011): 3.10.1, (6.1.1)

Basic standard DA 00-705 of March 30, 2000

LP0002(2011) Appendix II

≥ 25kHz or 2/3 of 20dB bandwidth, whichever is greater Limit

Test setup

Test Channel Low/ Middle/ High

Operation Mode Ambient temperature **24**℃ 53% Relative humidity

Table 13: Test result of Frequency Separation

Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
Record Channel	2441		> 05111 0/0 (
Record Channel adj 1	2440	1	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
Record Channel adj 2	2442		200D bandwidth	



Prüfbericht - Nr.: 10053160 001

Seite 33 von 45 *Page 33 of 45*

Test Report No.

Test Plot of Frequency Separation

GFSK





Prüfbericht - Nr.: 10053160 001 Seite 34 von 45

Page 34 of 45

Test Report No.

5.1.8 Number of hopping frequency

RESULT: Passed

Test standard : FCC part 15.247(a)(1)(iii)

RSS-247 5.1(5)

LP0002(2011): 3.10.1, (6.1.2)

Basic standard : DA 00-705 of March 30, 2000

LP0002(2011) Appendix II

Test setup

Test Channel : Hopping On

Ambient temperature : 22-26°C
Relative humidity : 50-65%
Atmospheric pressure : 100-103 kPa

Table 14: Test result of Number of hopping frequency


Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
2400 to 2483.5 MHz	79	≥15	Pass

Test Report No.

10053160 001 Prüfbericht - Nr.:

Seite 35 von 45 Page 35 of 45

Test Plot of Number of hopping frequencies





Seite 36 von 45

Page 36 of 45

Produkte Products

Prüfbericht - Nr.: 10053160 001

Test Report No.

5.1.9 Time of Occupancy

RESULT: Passed

Test standard : FCC part 15.247(a)(1)(iii)

RSS-247 5.1(5)

LP0002(2011): 3.10.1, (6.1.2)

Basic standard : DA 00-705 of March 30, 2000

LP0002(2011) Appendix II

Limits : 0.4s

Kind of test site : Shield room

Test setup

Test Channel : Low/ Middle/ High

Operation Mode : A

Ambient temperature : 22-26°C
Relative humidity : 50-65%
Atmospheric pressure : 100-103 kPa

Table 15: Test result of Time of Occupancy

Data Mode	Captured Burst (s)	Dwell time (s)	On+Off time (s)	Limit (s)	Result
DH5	0.00294	0.3128	0.00376	0.4	Pass
3DH5	0.00294	0.3144	0.00374	0.4	Pass

Note:

Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds.


Hopping rate = 1 / (On+Off time) = 266 Hz

Test Report No.

Prüfbericht - Nr.: 10053160 001

Seite 37 von 45 *Page 37 of 45*

Test Plot of Time of Occupancy, GFSK modulation




Test Report No.

Prüfbericht - Nr.: 10053160 001

Seite 38 von 45 *Page 38 of 45*

Test Plot of Time of Occupancy, 8DPSK modulation





> Seite 39 von 45 Prüfbericht - Nr.: 10053160 001 Page 39 of 45

Test Report No.

5.2 Mains Emissions

5.2.1 Mains Conducted Emissions

RESULT: Passed

Test standard FCC Part 15.207

> FCC Part 15.107 RSS-Gen 8.8

LP0002: 2.3

Limits Mains Conducted emissions as defined in

> above test standards must comply with the mains conducted emission limits specified

Kind of test site Shielded Room

Test setup

Middle Test Channel Operation mode

Remark: For details refer to Appendix D.



Prüfbericht - Nr.:	10053160 001	Seite 40 von 45
Test Report No.		Page 40 of 45

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: Passed

Test standard : FCC KDB Publication 447498

The maximum peak output power of the transmitter is 9.8 mW.

Hence the EUT is excluded from SAR evaluation.
Please also refer to FCC KDB publication 447498 D01 v05: Mobile Portable RF Exposure




Prüfbericht - Nr.: 10053160 001

Test Report No.

Seite 41 von 45Page 41 of 45

7. Photographs of the Test Set-Up

Photograph 1: Set-up for Spurious Emissions (Front View)







 Prüfbericht - Nr.:
 10053160 001
 Seite 42 von 45

 Test Report No.
 Page 42 of 45

Photograph 2: Set-up for Spurious Emissions (Back View 1)



Photograph 3: Set-up for Spurious Emissions (Back View 2)





Prüfbericht - Nr.: 10053160 001 Test Report No.

Seite 43 von 45 *Page 43 of 45*

Photograph 4: Set-up for Conducted testing



Photograph 5: Set-up for for Mains Conducted testing Back





Prüfbericht - Nr.: 10053160 001 Test Report No.

Seite 44 von 45Page 44 of 45

Photograph 6: Set-up for for Mains Conducted testing Front





Prüfbericht - Nr.: 10053160 001 Test Report No.

Seite 45 von 45Page 45 of 45

8. List of Tables

Table 1: Applied Standard and Test Levels	5
Table 2: List of Test and Measurement Equipment	
Table 3: Emission Measurement Uncertainty	8
Table 4: Basic Information of EUT	9
Table 5: Technical Specification of EUT	9
Table 6: Frequency hopping information	
Table 7: Test result of Peak Output Power, GFSK modulation	16
Table 8: Test result of Peak Output Power, 8DPSK modulation	16
Table 9: Test result of 20dB Bandwidth, GFSK modulation	17
Table 10: Test result of 20dB Bandwidth, 8DPSK modulation	17
Table 11: Test result of 99% Bandwidth, GFSK modulation	21
Table 12: Test result of 99% Bandwidth, PSK modulation	21
Table 13: Test result of Frequency Separation	32
Table 14: Test result of Number of hopping frequency	34
Table 15: Test result of Time of Occupancy	

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View)	41
Photograph 2: Set-up for Spurious Emissions (Back View 1)	
Photograph 3: Set-up for Spurious Emissions (Back View 2)	
Photograph 4: Set-up for Conducted testing	
Photograph 5: Set-up for for Mains Conducted testing Back	
Photograph 6: Set-up for for Mains Conducted testing Front	
3 · · · · · · · · · · · · · · · · · · ·	