# FCC RF EXPOSURE REPORT FCC ID: VJA-RJ1301

Project No. : 1402132

Equipment : Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz

Model: RJ-1301

Applicant: RAJANT CORPORATION

Address: 400 EAST KING STREET, MALVERN PA 19355

According: : FCC Guidelines for Human Exposure IEEE C95.1

## Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL: (0769) 8318-3000 FAX: (0769) 8319-6000

### **MPE CALCULATION METHOD:**

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

#### Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	PCTEL	BOA24005NM-RJT	DIPOLE OMNI-DIRECTIO NAL	N-Type	5dBi
2	PCTEL	BOA24005NM-RJT	DIPOLE OMNI-DIRECTIO NAL	N-Type	5dBi

# **TEST RESULTS**

EUT:	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name:	RJ-1301		
Temperature:	26°C	Relative Humidity:	46%		
Pressure:	1009 hPa	Test Voltage:	AC 120V/60Hz		
Test Mode:	TX B MODE /CH01, CH06, CH11				

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
5	3.1623	23.34	215.7744	0.13581582	1	Complies
5	3.1623	25.10	323.5937	0.20368093	1	Complies
5	3.1623	22.02	159.2209	0.10021907	1	Complies

EUT:	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name:	RJ-1301
Temperature:	26°C	Relative Humidity:	46%
Pressure:	1009 hPa	Test Voltage:	AC 120V/60Hz
Test Mode:	TX G MODE /CH01, CH06, 0	CH11	

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
5	3.1623	24.89	308.3188	0.19406641	1	Complies
5	3.1623	26.62	459.1980	0.28903496	1	Complies
5	3.1623	26.08	405.5085	0.25524096	1	Complies

EUT:	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name:	RJ-1301	
Temperature:	26°C	Relative Humidity:	46%	
Pressure:	1009 hPa	Test Voltage:	AC 120V/60Hz	
Test Mode:	TX N-20M MODE /CH01, CH06, CH11 Ant1+Ant2 total			

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
5	3.1623	25.52	356.4511	0.22436255	1	Complies
5	3.1623	27.89	615.1769	0.38721339	1	Complies
5	3.1623	27.46	557.1857	0.35071179	1	Complies

EUT:	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name:	RJ-1301	
Temperature:	26°C	Relative Humidity:	46%	
Pressure:	1009 hPa	Test Voltage:	AC 120V/60Hz	
Test Mode: TX N-40M MODE /CH03, CH06, CH09 Ant1+Ant2 total				

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
5	3.1623	22.77	189.2344	0.11911059	1	Complies
5	3.1623	27.12	515.2286	0.32430255	1	Complies
5	3.1623	26.85	484.1724	0.30475467	1	Complies

The calculated distance is 20cm