

July 14, 2008

MLWI01– A6 – Meshlinx Multi-Radio Access Point MWI5000

Maximum Permissible Exposure Calculations

FCC, Part 90 Subpart C §90.1217

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm^2) = $\text{EIRP}/(4\pi d^2)$

$\text{EIRP} = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is $1.0 \text{ mW}/\text{cm}^2$

Freq. Band (GHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ $1\text{mW}/\text{cm}^2$ Limit (cm)
4.9	+9.0	7.95	+14.6	28.85	4.3*

*Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

§15.247(i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines.

Limit $S = 1\text{mW} / \text{cm}^2$ from 1.310 Table 1

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

RSS-Gen §5.5 Before equipment certification is granted, the applicable requirements of RSS-102 shall be met.