



FCC PART 15.247 TEST REPORT

For

Binatone Electronics International Ltd.

Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong, China

FCC ID: VLJ-SM320

Tangxia, Dongguan, Guangdong, China

Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2).

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT Exercise Software	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL CABLE	6
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	8
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT Setup	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS.	
TEST RESULTS SUMMARY TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTYEUT SETUP	
EUT SETUP EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	13
TEST PROCEDURE	
TEST FROEEBORE TEST EQUIPMENT LIST AND DETAILS.	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	17
Test Data	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	26
APPLICABLE STANDARD	26
TEST EQUIPMENT LIST AND DETAILS.	
TEST PATA	
TEST DATA	
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	32

Report No.: R2DG130917002-00B

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Binatone Electronics International Ltd*.'s product, model number: *SM320 (FCC ID: VLJ-SM320)* (the "EUT") in this report was a *GSM Mobile Phone*, which was measured approximately: 13.0 cm (L) x 5.5 cm (W) x1.5 cm (H), input voltage: DC 3.7V from lithium battery or DC 5.0V from adapter.

Report No.: R2DG130917002-00B

Adapter Information: Model: A31-501000

Input: 100-240VAC, 50/60Hz, 0.2A

Output: DC 5.0V, 1000mA

Manufacturer: Shenzhen Aohai Technology Co.,Ltd

Note: The series product, model Voxtel-SM320, SM320 are electrically identical, the difference between them is just the model name, we selected The SM320 for fully testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 130917002 (Assigned by BACL, Dongguan). The EUT was received on 2013-10-11.

Objective

This report is prepared on behalf of *Binatone Electronics International Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission rules

The tests were performed in order to determine the Bluetooth of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H&24E PCE submissions with FCC ID: VLJ-SM320.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 68

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No.: R2DG130917002-00B

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at http://ts.nist.gov/standards/scopes/5000690.htm

FCC Part 15.247 Page 5 of 68

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer. The engineering mode was controlled by the Bluetooth Tester.

Report No.: R2DG130917002-00B

EUT Exercise Software

No software was used in the testing.

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
TESCOM	Bluetooth Tester	TC-3000B	3000B650083

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
USB Cable	yes	No	1.2	USB Port of Adapter	EUT

Block Diagram of Test Setup



FCC Part 15.247 Page 6 of 68

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliace
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliace
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

Report No.: R2DG130917002-00B

FCC Part 15.247 Page 7 of 68

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: R2DG130917002-00B

According to KDB 447498 D01 Mobile Portable RF Exposure V05 Appendix A, SAR can be exempted if the output power is less than the SAR exclusion threshold:

For f=2450MHz, the output power is less 10mW at distance of 5mm.

Measurement Result

Peak conducted output power= 5.39 dBm SAR exclusion threshold 10 mW (10dBm) > 5.39 dBm

So the stand alone SAR evaluation is not necessary.

FCC Part 15.247 Page 8 of 68

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: R2DG130917002-00B

Antenna Connector Construction

The EUT has an internal antenna, which was permanently attached to the EUT, and the maximum gain is -2.0dBi, please refer to the internal photos.

Result: Compliance.

FCC Part 15.247 Page 9 of 68

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG130917002-00B

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of
$$U_{\rm cispr}$$

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 10 of 68

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

Report No.: R2DG130917002-00B

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C: corrected voltage amplitude V_R: reading voltage amplitude A_c: attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 11 of 68

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCS 30	830245/006	2012-11-29	2013-11-28
R&S	Two-line V-network	ENV216	3560.6550.12	2013-2-18	2014-2-17
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

Report No.: R2DG130917002-00B

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

12.26 dB at 0.420 MHz in the Neutral conducted mode.

Test Data

Environmental Conditions

Temperature:	25.8 °C
Relative Humidity:	44 %
ATM Pressure:	101.2 kPa


The testing was performed by Ares Liu on 2013-10-17.

FCC Part 15.247 Page 12 of 68

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting

AC 120V/60 Hz, Line



Report No.: R2DG130917002-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/ QP/Ave.)
0.420	41.19	9.67	57.45	16.26	QP
0.420	35.18	9.67	47.45	12.27	AV
0.755	33.07	9.67	56.00	22.93	QP
0.755	28.00	9.67	46.00	18.00	AV
1.000	37.55	9.68	56.00	18.45	QP
1.000	32.14	9.68	46.00	13.86	AV
1.485	36.95	9.68	56.00	19.05	QP
1.495	30.05	9.68	46.00	15.95	AV
2.100	31.13	9.68	56.00	24.87	QP
2.105	26.28	9.68	46.00	19.72	AV
2.705	29.44	9.69	56.00	26.56	QP
2.705	22.97	9.69	46.00	23.03	AV

FCC Part 15.247 Page 13 of 68

AC 120V/60 Hz, Neutral



Report No.: R2DG130917002-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/ QP/Ave.)
0.420	40.02	9.67	57.45	17.43	QP
0.420	35.19	9.67	47.45	12.26	AV
0.780	33.40	9.68	56.00	22.60	QP
0.780	29.12	9.68	46.00	16.88	AV
1.000	37.66	9.69	56.00	18.34	QP
1.000	31.87	9.69	46.00	14.13	AV
1.360	37.78	9.69	56.00	18.22	QP
1.360	30.93	9.69	46.00	15.07	AV
1.505	38.96	9.68	56.00	17.04	QP
1.505	31.21	9.68	46.00	14.79	AV
2.030	31.68	9.68	56.00	24.32	QP
2.055	26.93	9.68	46.00	19.07	AV

FCC Part 15.247 Page 14 of 68

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG130917002-00B

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 1 – Values of $U_{\rm cispr}$

Measurement		
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB	
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB	
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB	


EUT Setup

Below 1GHz:



FCC Part 15.247 Page 15 of 68

Above 1GHz:



Report No.: R2DG130917002-00B

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above I GHZ	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 16 of 68

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	ЈВ3	A060611-1	2011-9-6	2014-9-5
HP	HP AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM	DE31388	2013-5-7	2014-5-6
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	N/A	N/A
R&S	Spectrum Analyzer	FSP 38	100478	2013-6-16	2014-6-15
Ducommun Technolagies	horn antenna	ARH-4223-02	1007726-01 1304	2013-6-16	2014-6-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	N/A	N/A

Report No.: R2DG130917002-00B

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit - Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C</u>, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

2.89 dB at **7440 MHz** in the Vertical polarization of EDR Mode (π /4-DQPSK)

Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	61 %
ATM Pressure:	100.8 kPa

The testing was performed by Ares Liu on 2013-10-15.

Mode: Transmitting

FCC Part 15.247 Page 17 of 68

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

BDR Mode (GFSK):

BDR Mod									BDR Mode (GFSK):							
Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	15.247							
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)							
			I	ow Channe	el: 2402(N	ИHz)										
2402	64.83	PK	Н	25.65	3.90	0.00	94.38	N/A	N/A							
2402	52.29	AV	Н	25.65	3.90	0.00	81.84	N/A	N/A							
2402	62.81	PK	V	25.65	3.90	0.00	92.36	N/A	N/A							
2402	51.17	AV	V	25.65	3.90	0.00	80.72	N/A	N/A							
2390	27.69	PK	Н	25.61	3.84	0.00	57.14	74.00	16.86							
2390	14.33	AV	Н	25.61	3.84	0.00	43.78	54.00	10.22							
4804	37.13	PK	V	30.59	4.67	27.26	45.13	74.00	28.87							
4804	20.88	AV	V	30.59	4.67	27.26	28.88	54.00	25.12							
7206	56.06	PK	V	34.09	6.50	26.30	70.35	74.00	3.65*							
7206	28.94	AV	V	34.09	6.50	26.30	43.23	54.00	10.77							
9608	44.68	PK	V	35.96	8.75	26.22	63.17	74.00	10.83							
9608	25.81	AV	V	35.96	8.75	26.22	44.30	54.00	9.70							
1593.66	30.97	PK	V	23.79	3.16	26.90	31.02	74.00	42.98							
1593.66	16.98	AV	V	23.79	3.16	26.90	17.03	54.00	36.97							
325.1	32.16	QP	V	14.61	2.16	21.58	27.35	46.00	18.65							
				iddle Chanı												
2441	65.03	PK	Н	25.75	3.99	0.00	94.77	N/A	N/A							
2441	52.37	AV	Н	25.75	3.99	0.00	82.11	N/A	N/A							
2441	62.99	PK	V	25.75	3.99	0.00	92.73	N/A	N/A							
2441	51.41	AV	V	25.75	3.99	0.00	81.15	N/A	N/A							
4882	37.21	PK	V	30.79	4.75	27.26	45.49	74.00	28.51							
4882	20.66	AV	V	30.79	4.75	27.26	28.94	54.00	25.06							
7323	56.19	PK	V	34.38	6.72	26.53	70.76	74.00	3.24*							
7323	28.84	AV	V	34.38	6.72	26.53	43.41	54.00	10.59							
9764	44.64	PK	V	36.33	8.58	25.62	63.93	74.00	10.07							
9764	25.73	AV	V	36.33	8.58	25.62	45.02	54.00	8.98							
1593.6	30.93	PK	V	23.79	3.16	26.90	30.98	74.00	43.02							
1593.6	16.91	AV	V	23.79	3.16	26.90	16.96	54.00	37.04							
6200	39.72	PK	V	32.24	6.01	26.46	51.51	74.00	22.49							
6200	22.28	AV	V	32.24	6.01	26.46	34.07	54.00	19.93							
325.2	31.9	QP	V	14.61 ligh Channe	2.16 el: 2480(N	21.58 (Hz)	27.09	46.00	18.91							
2480	65.21	PK	Н	25.85	3.82	0.00	94.88	N/A	N/A							
2480	53.19	AV	Н	25.85	3.82	0.00	82.86	N/A	N/A							
2480	63.76	PK	V	25.85	3.82	0.00	93.43	N/A	N/A							
2480	52.06	AV	V	25.85	3.82	0.00	81.73	N/A	N/A							
2483.5	29.7	PK	H	25.86	3.80	0.00	59.36	74.00	14.64							
2483.5	14.52	AV	Н	25.86	3.80	0.00	44.18	54.00	9.82							
4960	37.41	PK	V	31.00	4.70	27.27	45.84	74.00	28.16							
4960	20.65	AV	V	31.00	4.70	27.27	29.08	54.00	24.92							
7440	55.97	PK	V	34.66	6.95	26.56	71.02	74.00	2.98*							
7440	29.01	AV	V	34.66	6.95	26.56	44.06	54.00	9.94							
9920	44.69	PK	V	36.71	8.41	25.50	64.31	74.00	9.69							
9920	25.7	AV	V	36.71	8.41	25.50	45.32	54.00	8.68							
1593.6	31.01	PK	V	23.79	3.16	26.90	31.06	74.00	42.94							
1593.6	17.14	AV	V	23.79	3.16	26.90	17.19	54.00	36.81							
325.2	32.1	QP	V	14.61	2.16	21.58	27.29	46.00	18.71							

FCC Part 15.247 Page 18 of 68

^{*}Within measurement uncertainty!

EDR Mode (π/4-DQPSK):

Frequency	Re	eceiver	Rx Antenna Ca	Cable	le Amplifier	Corrected	FCC 15.247		
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			I	ow Channe	el: 2402(N	ИHz)			
2402	64.71	PK	Н	25.65	3.90	0.00	94.26	N/A	N/A
2402	52.00	AV	Н	25.65	3.90	0.00	81.55	N/A	N/A
2402	62.73	PK	V	25.65	3.90	0.00	92.28	N/A	N/A
2402	51.05	AV	V	25.65	3.90	0.00	80.60	N/A	N/A
2390	27.49	PK	Н	25.61	3.84	0.00	56.94	74.00	17.06
2390	14.2	AV	Н	25.61	3.84	0.00	43.65	54.00	10.35
4804	37.1	PK	V	30.59	4.67	27.26	45.10	74.00	28.90
4804	20.9	AV	V	30.59	4.67	27.26	28.90	54.00	25.10
7206	56.1	PK	V	34.09	6.50	26.30	70.39	74.00	3.61*
7206	28.87	AV	V	34.09	6.50	26.30	43.16	54.00	10.84
9608	44.49	PK	V	35.96	8.75	26.22	62.98	74.00	11.02
9608	25.82	AV	V	35.96	8.75	26.22	44.31	54.00	9.69
1593.5	30.72	PK	V	23.79	3.16	26.90	30.77	74.00	43.23
1593.5	16.8	AV	V	23.79	3.16	26.90	16.85	54.00	37.15
325.3	32.31	QP	V	14.61	2.16	21.58	27.50	46.00	18.50
			M	iddle Chanı	nel: 2441((MHz)			
2441	64.99	PK	Н	25.75	3.99	0.00	94.73	N/A	N/A
2441	52.2	AV	Н	25.75	3.99	0.00	81.94	N/A	N/A
2441	62.77	PK	V	25.75	3.99	0.00	92.51	N/A	N/A
2441	51.39	AV	V	25.75	3.99	0.00	81.13	N/A	N/A
4882	37.2	PK	V	30.79	4.75	27.26	45.48	74.00	28.52
4882	20.5	AV	V	30.79	4.75	27.26	28.78	54.00	25.22
7323	56.03	PK	V	34.38	6.72	26.53	70.60	74.00	3.40*
7323	28.91	AV	V	34.38	6.72	26.53	43.48	54.00	10.52
9764	44.89	PK	V	36.33	8.58	25.62	64.18	74.00	9.82
9764	25.62	AV	V	36.33	8.58	25.62	44.91	54.00	9.09
1593.6	30.84	PK	V	23.79	3.16	26.90	30.89	74.00	43.11
1593.6	17.16	AV	V	23.79	3.16	26.90	17.21	54.00	36.79
6200	39.66	PK	V	32.24	6.01	26.46	51.45	74.00	22.55
6200	22.08	AV	V	32.24	6.01	26.46	33.87	54.00	20.13
325.1	32.25	QP	V	14.61 ligh Channe	2.16 el: 2480(N	21.58 MHz)	27.44	46.00	18.56
2480	65.11	PK	Н	25.85	3.82	0.00	94.78	N/A	N/A
2480	53.1	AV	Н	25.85	3.82	0.00	82.77	N/A	N/A
2480	63.5	PK	V	25.85	3.82	0.00	93.17	N/A	N/A
2480	51.9	AV	V	25.85	3.82	0.00	81.57	N/A	N/A
2483.5	29.53	PK	Н	25.86	3.80	0.00	59.19	74.00	14.81
2483.5	14.27	AV	Н	25.86	3.80	0.00	43.93	54.00	10.07
4960	37.27	PK	V	31.00	4.70	27.27	45.70	74.00	28.30
4960	20.81	AV	V	31.00	4.70	27.27	29.24	54.00	24.76
7440	56.06	PK	V	34.66	6.95	26.56	71.11	74.00	2.89*
7440	28.88	AV	V	34.66	6.95	26.56	43.93	54.00	10.07
9920	44.68	PK	V	36.71	8.41	25.50	64.30	74.00	9.70
9920	25.94	AV	V	36.71	8.41	25.50	45.56	54.00	8.44
1593.6	30.82	PK	V	23.79	3.16	26.90	30.87	74.00	43.13
1593.6	17.04	AV	V	23.79	3.16	26.90	17.09	54.00	36.91
325.2	32.06	QP	V	14.61	2.16	21.58	27.25	46.00	18.75

FCC Part 15.247 Page 19 of 68

^{*}Within measurement uncertainty!

EDR Mode (8-DPSK):

EDR Mod	EDR Mode (8-DPSK):								
Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	15.247
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			I	ow Channe	el: 2402(N	ИHz)			
2402	64.59	PK	Н	25.65	3.90	0.00	94.14	N/A	N/A
2402	52.01	AV	Н	25.65	3.90	0.00	81.56	N/A	N/A
2402	62.75	PK	V	25.65	3.90	0.00	92.30	N/A	N/A
2402	50.94	AV	V	25.65	3.90	0.00	80.49	N/A	N/A
2390	27.52	PK	Н	25.61	3.84	0.00	56.97	74.00	17.03
2390	14.12	AV	Н	25.61	3.84	0.00	43.57	54.00	10.43
4804	36.93	PK	V	30.59	4.67	27.26	44.93	74.00	29.07
4804	20.91	AV	V	30.59	4.67	27.26	28.91	54.00	25.09
7206	56.22	PK	V	34.09	6.50	26.30	70.51	74.00	3.49*
7206	28.65	AV	V	34.09	6.50	26.30	42.94	54.00	11.06
9608	44.57	PK	V	35.96	8.75	26.22	63.06	74.00	10.94
9608	25.81	AV	V	35.96	8.75	26.22	44.30	54.00	9.70
1593.6	30.83	PK	V	23.79	3.16	26.90	30.88	74.00	43.12
1593.6	16.8	AV	V	23.79	3.16	26.90	16.85	54.00	37.15
325.3	32.18	QP	V	14.61	2.16	21.58	27.37	46.00	18.63
				iddle Chanı					
2441	65.03	PK	Н	25.75	3.99	0.00	94.77	N/A	N/A
2441	52.27	AV	Н	25.75	3.99	0.00	82.01	N/A	N/A
2441	62.96	PK	V	25.75	3.99	0.00	92.70	N/A	N/A
2441	51.31	AV	V	25.75	3.99	0.00	81.05	N/A	N/A
4882	37.08	PK	V	30.79	4.75	27.26	45.36	74.00	28.64
4882	20.57	AV	V	30.79	4.75	27.26	28.85	54.00	25.15
7323	56.11	PK	V	34.38	6.72	26.53	70.68	74.00	3.32*
7323	29.09	AV	V	34.38	6.72	26.53	43.66	54.00	10.34
9764	44.92	PK	V	36.33	8.58	25.62	64.21	74.00	9.79
9764	25.72	AV	V	36.33	8.58	25.62	45.01	54.00	8.99
1593.5	30.79	PK	V	23.79	3.16	26.90	30.84	74.00	43.16
1593.5	17.01	AV	V	23.79	3.16	26.90	17.06	54.00	36.94
6200	39.47	PK	V	32.24	6.01	26.46	51.26	74.00	22.74
6200	22.06	AV	V	32.24	6.01	26.46	33.85	54.00	20.15
325.3	32.07	QP	V	14.61 ligh Channe	2.16 al: 2480(N	21.58 MHz)	27.26	46.00	18.74
2480	65.04	PK	Н	25.85	3.82	0.00	94.71	N/A	N/A
2480	52.92	AV	Н	25.85	3.82	0.00	82.59	N/A	N/A
2480	63.49	PK	V	25.85	3.82	0.00	93.16	N/A	N/A
2480	51.92	AV	V	25.85	3.82	0.00	81.59	N/A	N/A
2483.5	29.63	PK	Н	25.86	3.80	0.00	59.29	74.00	14.71
2483.5	14.34	AV	Н	25.86	3.80	0.00	44.00	54.00	10.00
4960	37.23	PK	V	31.00	4.70	27.27	45.66	74.00	28.34
4960	20.93	AV	V	31.00	4.70	27.27	29.36	54.00	24.64
7440	56.02	PK	V	34.66	6.95	26.56	71.07	74.00	2.93*
7440	28.86	AV	V	34.66	6.95	26.56	43.91	54.00	10.09
9920	44.45	PK	V	36.71	8.41	25.50	64.07	74.00	9.93
9920	25.89	AV	V	36.71	8.41	25.50	45.51	54.00	8.49
1593.5	30.96	PK	V	23.79	3.16	26.90	31.01	74.00	42.99
1593.5	17.11	AV	V	23.79	3.16	26.90	17.16	54.00	36.84
325.3	32.25	QP	V	14.61	2.16	21.58	27.44	46.00	18.56

FCC Part 15.247 Page 20 of 68


^{*}Within measurement uncertainty!

Conducted Spurious Emissions at Antenna Port

Report No.: R2DG130917002-00B


BDR Mode (GFSK):

Low Channel



Date: 15.0CT.2013 14:44:58

Middle Channel




Date: 15.OCT.2013 14:45:15

FCC Part 15.247 Page 21 of 68

High Channel


Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:45:33

EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 15.0CT.2013 14:45:51

FCC Part 15.247 Page 22 of 68


Middle Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:46:08

High Channel




Date: 15.0CT.2013 14:46:26

FCC Part 15.247 Page 23 of 68


Low Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:46:44

Middle Channel




Date: 15.0CT.2013 14:47:01

FCC Part 15.247 Page 24 of 68

High Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:47:19

FCC Part 15.247 Page 25 of 68

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: R2DG130917002-00B

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another truce
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	28.3 °C
Relative Humidity:	57 %
ATM Pressure:	100.8 kPa

^{*} The testing was performed by Ares Liu on 2013-10-15.

Test Result: Compliance.

Please refer to following tables and plots


FCC Part 15.247 Page 26 of 68

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
	Low	2402	1.102	0.62	Pass
	Adjacent	2403	1.102	0.02	1 488
BDR Mode	Middle	2441	1.002	0.62	Pass
(GFSK)	Adjacent	2442	1.002	0.02	rass
	High	2480	1.000	0.62	Pass
	Adjacent	2479	1.000	0.62	rass
	Low	2402	1.000	0.86	D
	Adjacent	2403	1.000	0.86	Pass
EDR Mode	Middle	2441	1.000	0.86	D
$(\pi/4\text{-DQPSK})$:	Adjacent	2442	1.009		Pass
	High	2480	1.007		D
	Adjacent	2479	1.006		Pass
	Low	2402	1.010	0.96	D
	Adjacent	2403	1.010	0.86	Pass
EDR Mode	Middle	2441	1 1 004		D
(8-DPSK):	Adjacent	2442	1.004	0.86	Pass
	High	2480	1.000	0.06	Dogg
	Adjacent	2479	1.000	0.86	Pass

BDR Mode (GFSK):

Low Channel




Date: 15.OCT.2013 14:30:30

FCC Part 15.247 Page 27 of 68


Middle Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:30:48

High Channel




Date: 15.0CT.2013 14:31:07

FCC Part 15.247 Page 28 of 68

EDR Mode ($\pi/4$ -DQPSK):


Low Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:31:25

Middle Channel



Date: 15.OCT.2013 14:31:44

FCC Part 15.247 Page 29 of 68

High Channel


Report No.: R2DG130917002-00B



Date: 15.0CT.2013 14:32:03

EDR Mode (8-DPSK):

Low Channel




Date: 15.0CT.2013 14:32:21

FCC Part 15.247 Page 30 of 68


Middle Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:32:40

High Channel



Date: 15.0CT.2013 14:32:58

FCC Part 15.247 Page 31 of 68

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: R2DG130917002-00B

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.3 °C
Relative Humidity:	57 %
ATM Pressure:	100.8 kPa

^{*} The testing was performed by Ares Liu on 2013-10-15.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 32 of 68


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
22214	Low	2402	0.925
BDR Mode (GFSK)	Middle	2441	0.927
(GF5K)	High	2480	0.925
	Low	2402	1.295
EDR Mode (π/4-DQPSK):	Middle	2441	1.289
(M+DQI SIX).	High	2480	1.293
EDD 14.1	Low	2402	1.287
EDR Mode (8-DPSK):	Middle	2441	1.297
(6-DF5K).	High	2480	1.297

Please refer to the following plots.

BDR Mode (GFSK):

Low Channel




Date: 15.OCT.2013 14:27:22

FCC Part 15.247 Page 33 of 68


Middle Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:27:42

High Channel




Date: 15.0CT.2013 14:28:03

FCC Part 15.247 Page 34 of 68

EDR Mode ($\pi/4$ -DQPSK):

Low Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:28:23

Middle Channel




Date: 15.OCT.2013 14:28:43

FCC Part 15.247 Page 35 of 68

High Channel


Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:29:03

EDR Mode (8-DPSK):

Low Channel




Date: 15.0CT.2013 14:29:23

FCC Part 15.247 Page 36 of 68


Middle Channel

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:29:44

High Channel



Date: 15.0CT.2013 14:30:04

FCC Part 15.247 Page 37 of 68

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Report No.: R2DG130917002-00B

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.6 °C
Relative Humidity:	53 %
ATM Pressure:	101.2 kPa

^{*} The testing was performed by Ares Liu on 2013-10-30.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 38 of 68


Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Report No.: R2DG130917002-00B

Number of Hopping Channels



Date: 30.OCT.2013 13:28:14


FCC Part 15.247 Page 39 of 68

EDR Mode (\pi/4-DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Report No.: R2DG130917002-00B

Number of Hopping Channels



Date: 30.OCT.2013 13:50:05


FCC Part 15.247 Page 40 of 68

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Report No.: R2DG130917002-00B

Number of Hopping Channels



Date:

30.OCT.2013 13:59:47

FCC Part 15.247 Page 41 of 68

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: R2DG130917002-00B

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.6 °C
Relative Humidity:	53 %
ATM Pressure:	101.2 kPa

^{*} The testing was performed by Ares Liu on 2013-10-30.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 42 of 68


Test Mode: Transmitting

BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.396	0.127	0.4	Pass	
DH1	Middle	0.400	0.128	0.4	Pass	
DHI	High	0.400	0.128	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.670	0.267	0.4	Pass	
DH3	Middle	1.670	0.267	0.4	Pass	
DH3	High	1.670	0.267	0.4	Pass	
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s					
	Low	2.920	0.311	0.4	Pass	
DH5	Middle	2.920	0.311	0.4	Pass	
	High	2.940	0.314	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s					

Report No.: R2DG130917002-00B

DH1: Low Channel




Date: 30.OCT.2013 13:35:05

FCC Part 15.247 Page 43 of 68


DH1: Middle Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:35:47

DH1: High Channel




Date: 30.OCT.2013 13:36:14

FCC Part 15.247 Page 44 of 68


DH3: Low Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:37:42

DH3: Middle Channel




Date: 30.OCT.2013 13:38:25

FCC Part 15.247 Page 45 of 68


DH3: High Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:38:52

DH5: Low Channel




Date: 30.OCT.2013 13:41:00

FCC Part 15.247 Page 46 of 68


DH5: Middle Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:41:27

DH5: High Channel



Date: 30.OCT.2013 13:41:59


FCC Part 15.247 Page 47 of 68

EDR Mode (\pi/4-DQPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.404	0.129	0.4	Pass	
DH1	Middle	0.404	0.129	0.4	Pass	
DIII	High	0.404	0.129	0.4	Pass	
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s					
	Low	1.664	0.266	0.4	Pass	
DH3	Middle	1.664	0.266	0.4	Pass	
DHS	High	1.664	0.266	0.4	Pass	
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s					
	Low	2.944	0.314	0.4	Pass	
DH5	Middle	2.944	0.314	0.4	Pass	
DHS	High	2.944	0.314	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s					

Report No.: R2DG130917002-00B

DH1: Low Channel




Date: 30.OCT.2013 13:50:36

FCC Part 15.247 Page 48 of 68


DH1: Middle Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:50:48

DH1: High Channel




Date: 30.OCT.2013 13:51:07

FCC Part 15.247 Page 49 of 68


DH3: Low Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:52:55

DH3: Middle Channel




Date: 30.OCT.2013 13:54:05

FCC Part 15.247 Page 50 of 68


DH3: High Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:54:35

DH5: Low Channel




Date: 30.OCT.2013 13:56:10

FCC Part 15.247 Page 51 of 68


DH5: Middle Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 13:56:37

DH5: High Channel




Date: 30.OCT.2013 13:56:48

FCC Part 15.247 Page 52 of 68

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.404	0.129	0.4	Pass	
DH1	Middle	0.404	0.129	0.4	Pass	
DIII	High	0.404	0.129	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.664	0.266	0.4	Pass	
DH3	Middle	1.664	0.266	0.4	Pass	
DH3	High	1.664	0.266	0.4	Pass	
	=Pulse time (ms	(1600/4/7)	9) ×31.6 s			
	Low	2.944	0.314	0.4	Pass	
DH5	Middle	2.944	0.314	0.4	Pass	
DHS	High	2.944	0.314	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s					

Report No.: R2DG130917002-00B

DH1: Low Channel




Date: 30.OCT.2013 14:00:30

FCC Part 15.247 Page 53 of 68


DH1: Middle Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 14:00:48

DH1: High Channel




Date: 30.OCT.2013 14:01:10

FCC Part 15.247 Page 54 of 68


DH3: Low Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 14:03:19

DH3: Middle Channel




Date: 30.OCT.2013 14:03:29

FCC Part 15.247 Page 55 of 68


DH3: High Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 14:03:38

DH5: Low Channel




Date: 30.OCT.2013 14:06:26

FCC Part 15.247 Page 56 of 68


DH5: Middle Channel

Report No.: R2DG130917002-00B



Date: 30.OCT.2013 14:06:55

DH5: High Channel



Date: 30.OCT.2013 14:07:20

FCC Part 15.247 Page 57 of 68

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Report No.: R2DG130917002-00B

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
- 3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.3 °C
Relative Humidity:	57 %
ATM Pressure:	100.8 kPa

^{*} The testing was performed by Ares Liu on 2013-10-15.

Test Result: Compliance.

FCC Part 15.247 Page 58 of 68

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	3.84	30
	Middle	2441	4.66	30
	High	2480	5.39	30
EDR Mode (π/4- DQPSK)	Low	2402	3.44	30
	Middle	2441	4.32	30
	High	2480	5.08	30
EDR Mode (8- DPSK)	Low	2402	3.56	30
	Middle	2441	4.32	30
	High	2480	5.14	30

Report No.: R2DG130917002-00B

Note: The data above was tested in conducted mode.

BDR Mode (GFSK):

Output Power, Low




Date: 15.OCT.2013 14:25:51

FCC Part 15.247 Page 59 of 68


Output Power, Middle

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:26:01

Output Power, High




Date: 15.OCT.2013 14:26:11

FCC Part 15.247 Page 60 of 68

EDR Mode (\pi/4-DQPSK):


Output Power, Low

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:26:21

Output Power, Middle




Date: 15.OCT.2013 14:26:30

FCC Part 15.247 Page 61 of 68

Output Power, High


Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:26:40

EDR Mode (8-DPSK):

Output Power, Low




Date: 15.OCT.2013 14:26:50

FCC Part 15.247 Page 62 of 68


Output Power, Middle

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:27:00

Output Power, High



Date: 15.OCT.2013 14:27:10

FCC Part 15.247 Page 63 of 68

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: R2DG130917002-00B

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	ESPI	100337	2012-11-10	2013-11-9

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.3 °C		
Relative Humidity:	57 %		
ATM Pressure:	100.8 kPa		

^{*} The testing was performed by Ares Liu on 2013-10-15.


FCC Part 15.247 Page 64 of 68

Test Result: Compliance

BDR Mode (GFSK):


Band Edge, Left Side

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:51:08

Band Edge, Right Side




Date: 15.OCT.2013 14:52:05

FCC Part 15.247 Page 65 of 68

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:52:44

Band Edge, Right Side




Date: 15.OCT.2013 14:53:40

FCC Part 15.247 Page 66 of 68

EDR Mode (8-DPSK):


Band Edge, Left Side

Report No.: R2DG130917002-00B



Date: 15.OCT.2013 14:54:25

Band Edge, Right Side



Date: 15.0CT.2013 14:54:42

FCC Part 15.247 Page 67 of 68

DECLARATION OF SIMILARITY



Binatone Electronics International Ltd.

Add: Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong, China

Tel: 00852-28027388 Fax: 00852-28028138

DECLARATION OF SIMILARITY

Report No.: R2DG130917002-00B

October 14, 2013

Dear Sir or Madam:

We, Binatone Electronics International Ltd., hereby declare that our product: GSM Mobile Phone, models: Voxtel-SM320 is electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics as SM320. And they are tested by BACL, the results of which are featured in BACL project: R2DG130917002, R2DG130917003, R2DG130917003-03, R1DG130917002-20, R1DG130917003-20

A description of the differences between the tested model and those that are declared similar areas follows:

Models: Voxtel-SM320, SM320 the only difference is the model name.

Please contact me should there be need for any additional clarification or information.

Best Regards,

Patrick Cheung, Senior Product Manager

(Legally valid signature)

***** END OF REPORT *****

FCC Part 15.247 Page 68 of 68