
	SAR MEASUREMENT REPORT
	Project name :
	KS070924A01

Test date: 10/26/2007

I. RESULTS

	<u>TYPE</u>	<u>PARAMETERS</u>
<u>GSM850</u>	<u>Noise</u>	--
	<u>Validation</u>	--
	<u>Phone</u>	--
<u>GSM900</u>	<u>Noise</u>	--
	<u>Validation</u>	--
	<u>Phone</u>	--
<u>GSM1800</u>	<u>Noise</u>	--
	<u>Validation</u>	--
	<u>Phone</u>	--
<u>GSM1900</u>	<u>Noise</u>	--
	<u>Validation</u>	<u>Measurement 1:</u> Validation Plane with Cheek device position on Middle Channel in CW mode
	<u>Phone</u>	--
<u>IMT2000</u>	<u>Noise</u>	--
	<u>Validation</u>	--
	<u>Phone</u>	--

<u>CUSTOM</u>	<u>Noise</u>	--
	<u>Validation</u>	--
	<u>Phone</u>	--

Ambient temperature:19C

Liquid Temperature:20C__

MEASUREMENT 1

1900 head validation

Type: Validation measurement (Complete)

Date of measurement: 26/10/2007

Measurement duration: 7 minutes 3 seconds

Mobile Phone IMEI number: --

A. Experimental conditions.

Phantom File	surf_sam_plan.txt, Adaptive 2 max
Phantom	Validation plane
Device Position	Cheek
Band	GSM1900
Channels	Middle
Signal	CW

B. Instrumentations.


PC	HP (Pentium(R) V 3.06GHz375052-AA1, SN:375052-AA1)
Network Emulator	Agilent (E5071B, SN:B23-03291)
Voltmeter	Keithley (2000, SN:1015843)
Synthesizer	Agilent (E8257C, SN:MY43321570)
Amplifier	Mini-Circuits (ZHL-42, SN:110405)
Power Meter	Agilent (E4416A, SN:QB41292714)
Probe	Antennessa (SN:SN_0807_EP_74)
Phantom	Antennessa (SN:SN41_05_SAM29)
Liquid	Antennessa (Last Calibration:02/2006)

C. SAR Measurement Results

Middle Band SAR (Channel 661):

Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.796869
Relative permittivity (imaginary part)	13.731020
Conductivity (S/m)	1.377880
Variation (%)	0.085000

SURFACE SAR	VOLUME SAR
--------------------	-------------------



Maximum location: X=-1.00, Y=-1.00

SAR 10g (W/Kg)	19.426230
SAR 1g (W/Kg)	38.198223

Z Axis Scan

