序号	商品编号		名 称	<b>X</b>	型	号 规	格	数 量		元 件	位号		备 注	更改
1		成品板			A6-20			1	自制;材料如下					
1.1		贴片电容			1uF±20% 6.3V		7	C13、C14、C17、C18、C19、C24、C30、			C24、	0402		
1.2		贝	片电容	•	10uF±20% 16V			1	C23				0805	
1.3	贴片电容		片电容	(	330nF±20% 16V		V	2	C20、C21				0402	
1.4	贴片电容		片电容	(	0.1uF±20% 16V		V	2	C11、C16				0402	
1.5	贴片电容			4	4.7uF±20% 10V			2	C2、C22	0603				
1.6		贴片电容			15pF±5% 50V			2	C12、C15				0402	
1.7		贴片电容			0.5pF±5% 50V			3	C7、C8、C10			0402		
1.8		贴片电容			1pF±20% 50V			1	C9			0402		
1.9		贴片电阻			4.7K±5%			1	R11			0402		
1.10		贴片电阻			47K±5%			1	R10				0402	
1.11		贴片电阻			10K±5%			2	R31、R5				0402	
1.12		贴片电阻			2.4K±5%			1	R13		0402			
1.13		贴片电阻			1K±5%			6	R1、R4、R14、R15、R16、R17				0402	
1.14		贴片电阻			3.3K±5%			2	R7、R12				0402	
1.15		贴片电阻			<b>330</b> Ω ±5%			1	R9				0402	
1.16		贴片电感			3.9nH±5% S			1	L1				0402	
1.17		贴片电感			2.7nH±5% S			1	L2				0402	
1.18		贴片三极管			MMBT3904			1	Q1				S0T23	
1.19		贴片 IC			XC6204B282MR			1	U2				S0T23-5	;
1.20		贴片 IC			IS1610N-002			1	U3				QFN56	
1.21		EEPROM			AT24C08			1	U4				TSSOP-8	
1.22		侧按开关			SS305GS16 (A6)			1	SW1				侧按键	
1.23		贴片发光管			蓝色(束光)			1	LED1				0603	
1.24		贴片二极管			CDSH3-222N			1	D2				S0T-523	
1.25		贴片晶振			16MHz±10PPM 12PF			1	X1				5032	
1.26		天 线			A6			1	ANT1		定制			
1.27		目	刀制板	1	46-20	)		1						
2		轫	校板	1	46			1						
3	咪 头			-42dBm (A6)			1					4015		
4		聚合物电芯		4	441220			1						
5		喇 叭			Φ13*32Ω			1					长 25mm	
6		上壳		1	A6 蓝牙耳机			1						
7		下 壳		1	A6 蓝牙耳机			1						
8	侧按键		1	A6 蓝牙耳机		1								
9	电源指示				A6 蓝牙耳机			1						
10		电源座		1	A6 蓝牙耳机		1							
			T	ı		,		- 1		Т	T		ı	
0												, = ···		
l	版本号 修改		状态 数量 更		牧单号 签 名 日 :			期 修改标记 数量 更改单号 签			签	名 日期		
拟 制					│			<sub>天耳畑</sub> IHO			041	41WL		
审 核														
								清	单	<b>当</b>				张 共 2 张
批准														

序号	商品编号	名称	型号规格	数 量		元 件	位号		备 注	更改
11		电源触片	A6 蓝牙耳机	2						
12		螺 丝	M1.2*4CA	3						
13		耳 挂	A6	1						
14		听 筒	A6	1						
15		听筒盖	A6	1						
16		咪头胶套	A6	1						
17		充电座	P430			自朱	J; 材料如下	÷.		
17.1		贴片电容	10uF±20% 16V	1	C1				0805	
17.2		贴片电容	4.7uF±20% 10V	1	C18				0603	
17.3		贴片 IC	SE9016	1	U1			S	OT23-5	
17.4		贴片电阻	15K±5%	1	R1				0805	
17.5		贴片电阻	4.7K±5%	1	R3				0805	
17.6		贴片电阻	1.5K±5%	1	R2				0805	
17.7		贴片电阻	150K±5%	2	R4、R11	1			0805	
17.8		贴片三极管	MMBT3904	1	Q1			,	S0T23	
17.9		双色发光二极管	φ3 白发红绿(共阳)	1	D1				DIP	
17.10		DC 插座	3 脚 L10×W5×H3mm	1					A6	
17.11		PCB	A6 充电板	1						
17.12		接触母座	A6	1						
17.13		接触盖板	A6	1						
17.14		充电座指示	A6	1						
17.15		充电座前盖	A6	1						
17.16		充电座后盖	A6	1						
17.17		充电座下盖	A6	1						
17.18		座充五金	878	2						
17.19		小弹簧	F508	2						
17.20		红色导线	28#₭ 45mm	1						
17.21		黑色导线	28#₭ 45mm	1						
17.22		螺 丝	M2*4KB	2						
18		包装盒	A6	1						
19	吸 塑		A 系列	1						
20		说明书	A 系列	1						
21	充电器			1					根据订	「单
						LHO41WL				
0	0					等级 标记 第2张 共			共 :	2 张
版本号 修改状		态 数量 更	牧单号 签 名	日期		·4 4A	h4. AC	>14 = 4K	/\ 2	- 111
						ı	1	1	1	