"High Frequency Ceramic Solutions"

Preliminary

915 MHz Antenna P/N 0915AT43A0042

Detail Specification: 11/30/2009 Page 1 of 3

General Specifications


Part Number	0915AT43A0042
Frequency Range	894 - 936 MHz
Peak Gain	-1.0 dBi typ. (XZ-total)
Average Gain	-4.0 dBi typ. (XZ-total)
Return Loss	8.5 dB min.
Impedance	50 Ω
Input Power	2W max.

Operating Temperature	-40 to +85°C
Storage Temperature Range	+5 ~ +35 °C, Humidity 45~75%RH, 12 mos. max
Reel Quanity	1,000

No.	Function	Terminal Configuration
1	Feeding Point	
2	NC	2 1 1

Mechanical Dimensions

	In	mm
L	0.276 ± 0.008	7.00 ± 0.20
W	0.079 ± 0.008	2.00 ± 0.20
Т	0.031 +.004/008	0.80 +0.1/-0.2
а	0.020 ± 0.012	0.50 ± 0.30



Mounting Considerations

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50 Ω impedance matching characteristics.

**Matching circuit and component values will be different, depending on PCB layout

With Matching Circuit

Ground

5.6 pF

1.0

4.0

Matching circuits**


Johanson Technology, Inc. reserves the right to make design changes without notice. All sales are subject to Johanson Technology, Inc. terms and conditions.



"High Frequency Ceramic Solutions"

Preliminary

915 MHz Antenna P/N 0915AT43A0042 Page 2 of 3 Detail Specification: 11/30/2009



Johanson Technology, Inc. reserves the right to make design changes without notice. All sales are subject to Johanson Technology, Inc. terms and conditions.




"High Frequency Ceramic Solutions"

Preliminary

915 MHz AntennaDetail Specification: 11/30/2009

Page 3 or 3



Johanson Technology, Inc. reserves the right to make design changes without notice. All sales are subject to Johanson Technology, Inc. terms and conditions.

