


Appendix D. Co-location

1. Results of Radiated Emissions for Co-located

<For Antenna A>

Temperature	23°C	Humidity	56%
Test Engineer	Alan Huang	Configurations	2.4GHz Bluetooth + 2.4GHz WLAN


Horizontal



.L

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	3247.22	35.74	54.00	-18.26	38.22	2.69	34.95	29.78	243	100	Average	HORIZONTAL
2 p	3248.46	42.67	74.00	-31.33	45.15	2.69	34.95	29.78	243	100	Peak	HORIZONTAL

Vertical




	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	3248.21	44.65	74.00	-29.35	47.13	2.69	34.95	29.78	85	121	Peak	VERTICAL
2 a	3249.20	37.88	54.00	-16.12	40.36	2.69	34.95	29.78	85	121	Average	VERTICAL

<For Antenna B>


Temperature	23°C	Humidity	56%
Test Engineer	Alan Huang	Configurations	2.4GHz Bluetooth + 2.4GHz WLAN

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	3249.35	37.56	54.00	-16.44	40.04	2.69	34.95	29.78	352	100	Average	HORIZONTAL
2 p	3249.53	45.20	74.00	-28.80	47.68	2.69	34.95	29.78	352	100	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	3249.29	46.12	74.00	-27.88	48.60	2.69	34.95	29.78	85	121	Peak	VERTICAL
2 a	3249.33	39.84	54.00	-14.16	42.32	2.69	34.95	29.78	85	121	Average	VERTICAL