

## FCC Test Report

### (PART 22)

**Report No.:** RF171221C06-6 R1

**FCC ID:** VQK-F04K

**Test Model:** F-04K

**Received Date:** Dec. 21, 2017

**Test Date:** Feb. 17, 2018 ~ Feb. 23, 2018

**Issued Date:** Apr. 16, 2018

**Applicant:** Fujitsu Limited

**Address:** 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki 211-8588, Japan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
( R.O.C )

**Test Location (1):** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan  
Hsien 333, Taiwan, R.O.C.

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1 Certificate of Conformity .....</b>	<b>4</b>
<b>2 Summary of Test Results.....</b>	<b>5</b>
2.1 Measurement Uncertainty.....	5
2.2 Test Site and Instruments .....	6
<b>3 General Information .....</b>	<b>8</b>
3.1 General Description of EUT .....	8
3.2 Configuration of System under Test.....	9
3.2.1 Description of Support Units .....	10
3.3 Test Mode Applicability and Tested Channel Detail .....	11
3.4 EUT Operating Conditions .....	13
3.5 General Description of Applied Standards.....	13
<b>4 Test Types and Results .....</b>	<b>14</b>
4.1 Output Power Measurement.....	14
4.1.1 Limits of Output Power Measurement .....	14
4.1.2 Test Procedures.....	14
4.1.3 Test Setup.....	15
4.1.4 Test Results .....	16
4.2 Frequency Stability Measurement .....	21
4.2.1 Limits of Frequency Stability Measurement.....	21
4.2.2 Test Procedure .....	21
4.2.3 Test Setup.....	21
4.2.4 Test Results .....	22
4.3 Occupied Bandwidth Measurement.....	28
4.3.1 Test Procedure .....	28
4.3.2 Test Setup.....	28
4.3.3 Test Result .....	29
4.4 Band Edge Measurement .....	32
4.4.1 Limits of Band Edge Measurement .....	32
4.4.2 Test Setup.....	32
4.4.3 Test Procedures.....	32
4.4.4 Test Results .....	33
4.5 Peak to Average Ratio .....	38
4.5.1 Limits of Peak to Average Ratio Measurement .....	38
4.5.2 Test Setup.....	38
4.5.3 Test Procedures.....	38
4.5.4 Test Results .....	39
4.6 Conducted Spurious Emissions.....	42
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	42
4.6.2 Test Setup.....	42
4.6.3 Test Procedure .....	42
4.6.4 Test Results .....	43
4.7 Radiated Emission Measurement.....	49
4.7.1 Limits of Radiated Emission Measurement .....	49
4.7.2 Test Procedure .....	49
4.7.3 Deviation from Test Standard .....	49
4.7.4 Test Setup.....	50
4.7.5 Test Results .....	51
<b>5 Pictures of Test Arrangements.....</b>	<b>81</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>82</b>

### Release Control Record

Issue No.	Description	Date Issued
RF171221C06-6	Original Release	Mar. 05, 2018
RF171221C06-6 R1	Revise battery voltage	Apr. 16, 2018

## 1 Certificate of Conformity

**Product:** Smart Phone

**Brand:** FUJITSU

**Test Model:** F-04K

**Sample Status:** Identical Prototype

**Applicant:** Fujitsu Limited

**Test Date:** Feb. 17, 2018 ~ Feb. 23, 2018

**Standards:** FCC Part 22, Subpart H

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :**



**Date:**

Apr. 16, 2018

Ivonne Wu / Supervisor

**Approved by :**



**Date:**

Apr. 16, 2018

Dylan Chiou / Project Engineer

## 2 Summary of Test Results

Applied Standard: FCC Part 22 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 22.913 (a)	Effective Radiated Power	Pass	Meet the requirement of limit.
---	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
22.917	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -26.86 dB at 2509.20 MHz.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

## 2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY52260177	Jul. 05, 2017	Jul. 04, 2018
Spectrum Analyzer Agilent	N9010A	MY52220314	Nov. 24, 2017	Nov. 23, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	100115	Nov. 23, 2017	Nov. 22, 2018
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 23, 2017	Jun. 22, 2018
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 24, 2017	Oct. 23, 2018
Preamplifier EMCI	EMC 012645	980115	Oct. 20, 2017	Oct. 19, 2018
Preamplifier EMCI	EMC 184045	980116	Oct. 20, 2017	Oct. 19, 2018
Preamplifier EMCI	EMC 330H	980112	Oct. 13, 2017	Oct. 12, 2018
Power Meter Anritsu	ML2495A	1012010	Aug. 15, 2017	Aug. 14, 2018
Power Sensor Anritsu	MA2411B	1315050	Aug. 15, 2017	Aug. 14, 2018
RF Coaxial Cable HUBER+SUHNNER	EMC104-SM-SM-8 000&3000	140811+170717	Oct. 20, 2017	Oct. 19, 2018
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM- 1000(140807)	Oct. 20, 2017	Oct. 19, 2018
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 20, 2017	Oct. 19, 2018
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Temperature & Humidity Chamber	GTH-120-40-CP-A R	MAA1306-019	Sep. 08, 2017	Sep. 07, 2018
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jun. 30, 2017	Jun. 29, 2018

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The IC Site Registration No. is IC7450F-10.

### 3 General Information

#### 3.1 General Description of EUT

<b>Product</b>	Smart Phone	
<b>Brand</b>	FUJITSU	
<b>Test Model</b>	F-04K	
<b>Status of EUT</b>	Identical Prototype	
<b>Power Supply Rating</b>	5.0 Vdc (adapter or host equipment) 3.8 Vdc (Li-ion battery)	
<b>Normal Testing Voltage</b>	3.9 Vdc	
<b>Modulation Type</b>	GSM/GPRS	GMSK
	WCDMA	QPSK
	LTE	QPSK, 16QAM
<b>Frequency Range</b>	GSM/GPRS	824.2 ~ 848.8 MHz
	WCDMA	826.4 ~ 846.6 MHz
	LTE 5 (Channel Bandwidth: 1.4 MHz)	824.7 ~ 848.3 MHz
	LTE 5 (Channel Bandwidth: 3 MHz)	825.5 ~ 847.5 MHz
	LTE 5 (Channel Bandwidth: 5 MHz)	826.5 ~ 846.5 MHz
	LTE 5 (Channel Bandwidth: 10 MHz)	829 ~ 844 MHz
<b>Max. ERP Power</b>	GSM/GPRS	1247.38 mW
	WCDMA	162.93 mW
	LTE 5 (Channel Bandwidth: 1.4 MHz)	102.80 mW
	LTE 5 (Channel Bandwidth: 3 MHz)	105.68 mW
	LTE 5 (Channel Bandwidth: 5 MHz)	108.64 mW
	LTE 5 (Channel Bandwidth: 10 MHz)	109.90 mW
<b>Emission Designator</b>	GSM/GPRS	244KGXW
	WCDMA	4M14F9W
	LTE 5 (Channel Bandwidth: 1.4 MHz)	1M09W7D
	LTE 5 (Channel Bandwidth: 3 MHz)	2M70G7D
	LTE 5 (Channel Bandwidth: 5 MHz)	4M48W7D
	LTE 5 (Channel Bandwidth: 10 MHz)	8M97W7D
<b>Antenna Type</b>	$\lambda$ /4 Monopole Antenna	
<b>Accessory Device</b>	Refer to Note as below	
<b>Data Cable Supplied</b>	Refer to Note as below	

Note:

- The EUT contains following accessory devices.

Product	Brand	Model	Description
Battery	FUJITSU CONNECTED TECHNOLOGIES Ltd.	CA54310-0067	3.8 Vdc, 2580 mAh

- The EUT uses following adapter which provided by client as support unit.


Product	Brand	Model	Description
Adapter	NTT docomo	AC Adapter 01	I/P: 100-240Vac, 0.8A, O/P: 5.0Vdc, 3.0A

- The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.




### 3.2 Configuration of System under Test

#### <Radiated Emission Test>



#### <E.R.P. Test>



### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Communications Tester-Wireless	Agilent	8960 Series 10	MY53201073	N/A
2.	Radio Communication Analyzer	Anritsu	MT8820C	6201300640	N/A
3.	Earphone	Apple	MD827FE	N/A	N/A

No.	Signal Cable Description Of The Above Support Units
1.	N/A
2.	N/A
3.	N/A

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items 1~2 acted as communication partners to transfer data.

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP	Radiated Emission
GSM	X-plane	Y-axis
WCDMA	X-plane	Y-axis
LTE Band 5	X-plane	Y-axis

#### GSM

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	ERP	128 to 251	128, 189, 251	GSM
-	Frequency Stability	128 to 251	128, 251	GSM
-	Occupied Bandwidth	128 to 251	128, 189, 251	GSM
-	Band Edge	128 to 251	128, 251	GSM
-	Peak to Average Ratio	128 to 251	128, 189, 251	GSM
-	Conducted Emission	128 to 251	128, 189, 251	GSM
-	Radiated Emission	128 to 251	128, 189, 251	GSM

#### WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
-	Frequency Stability	4132 to 4233	4132, 4233	WCDMA
-	Occupied Bandwidth	4132 to 4233	4132, 4182, 4233	WCDMA
-	Band Edge	4132 to 4233	4132, 4233	WCDMA
-	Peak to Average Ratio	4132 to 4233	4132, 4182, 4233	WCDMA
-	Conducted Emission	4132 to 4233	4132, 4182, 4233	WCDMA
-	Radiated Emission	4132 to 4233	4132, 4182, 4233	WCDMA

## LTE Band 5

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	20407 to 20643	20407, 20643	1.4 MHz	QPSK	1 RB / 0 RB Offset
		20415 to 20635	20415, 20635	3 MHz	QPSK	1 RB / 0 RB Offset
		20425 to 20625	20425, 20625	5 MHz	QPSK	1 RB / 0 RB Offset
		20450 to 20600	20450, 20600	10 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Band Edge	20407 to 20643	20407	1.4MHz	QPSK	1 RB / 0 RB Offset
			20643	1.4MHz	QPSK	6 RB / 0 RB Offset
		20415 to 20635	20415	3 MHz	QPSK	1 RB / 5 RB Offset
			20635	3 MHz	QPSK	15 RB / 0 RB Offset
		20425 to 20625	20425	5 MHz	QPSK	1 RB / 0 RB Offset
			20625	5 MHz	QPSK	25 RB / 0 RB Offset
		20450 to 20600	20450	10 MHz	QPSK	1 RB / 24 RB Offset
			20600	10 MHz	QPSK	25 RB / 0 RB Offset
						1 RB / 0 RB Offset
						50 RB / 0 RB Offset
						1 RB / 49 RB Offset
						50 RB / 0 RB Offset
-	Peak to Average Ratio	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Conducted Emission	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK	1 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3 MHz	QPSK	1 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5 MHz	QPSK	1 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK	1 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5 MHz	QPSK	1 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10 MHz	QPSK	1 RB / 0 RB Offset

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

### **Test Condition:**

Test Item	Environmental Conditions	Input Power	Tested By
ERP	25 deg. C, 65 % RH	3.9 Vdc	Getaz Yang
Frequency Stability	25 deg. C, 65 % RH	3.9 Vdc	Carlos Chen
Occupied Bandwidth	25 deg. C, 65 % RH	3.9 Vdc	Carlos Chen
Band Edge	25 deg. C, 65 % RH	3.9 Vdc	Carlos Chen
Peak to Average Ratio	25 deg. C, 65 % RH	3.9 Vdc	Carlos Chen
Conducted Emission	25 deg. C, 65 % RH	3.9 Vdc	Carlos Chen
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Getaz Yang & Jisyong Wang

### **3.4 EUT Operating Conditions**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

### **3.5 General Description of Applied Standards**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 22**

**KDB 971168 D01 Power Meas License Digital Systems v02r02**

**ANSI/TIA/EIA-603-E 2016**

**ANSI 63.26-2015**

**Note:** All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 7 watts e.r.p.

#### 4.1.2 Test Procedures

##### **EIRP / ERP Measurement:**

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1 MHz for GSM, GPRS, 5 MHz for WCDMA, and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$ .


##### **Conducted Power Measurement:**

The EUT was set up for the maximum power with GSM, GPRS, WCDMA, and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


#### 4.1.3 Test Setup

##### EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>




<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

##### Conducted Power Measurement:



#### 4.1.4 Test Results

##### Conducted Output Power (dBm)

Band	GSM850		
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
GSM (GMSK, 1Tx-slot)	32.16	32.55	32.52
GPRS (GMSK, 1Tx-slot)	32.07	32.46	32.43
GPRS (GMSK, 2Tx-slot)	29.08	29.47	29.44
GPRS (GMSK, 3Tx-slot)	27.20	27.59	27.56
GPRS (GMSK, 4Tx-slot)	25.84	26.23	26.20
DTM (GMSK, 2Tx-slot)	28.93	29.32	29.29
DTM (GMSK, 3Tx-slot)	27.07	27.46	27.43

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.73	23.75	23.91
HSDPA Subtest-1	23.10	23.12	23.28
HSDPA Subtest-2	23.02	23.04	23.20
HSDPA Subtest-3	22.49	22.51	22.67
HSDPA Subtest-4	22.48	22.50	22.66
HSUPA Subtest-1	22.99	23.01	23.17
HSUPA Subtest-2	20.97	20.99	21.15
HSUPA Subtest-3	22.05	22.07	22.23
HSUPA Subtest-4	21.04	21.06	21.22
HSUPA Subtest-5	23.08	23.10	23.26



LTE Band 5															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600				Channel		20425	20525	20625	
		Frequency (MHz)		829.0	836.5	844.0				Frequency (MHz)		826.5	836.5	846.5	
10M	QPSK	1	0	22.95	23.00	22.85	0	5M	QPSK	1	0	22.90	22.95	22.78	0
		1	24	22.83	22.91	22.79	0			1	12	22.74	22.85	22.61	0
		1	49	22.68	22.74	22.62	0			1	24	22.59	22.66	22.49	0
		25	0	21.96	21.99	21.88	1			12	0	21.84	21.89	21.72	1
		25	12	21.89	21.96	21.80	1			12	6	21.77	21.85	21.67	1
		25	25	21.85	21.90	21.75	1			12	13	21.70	21.79	21.62	1
		50	0	21.78	21.87	21.72	1			25	0	21.63	21.74	21.57	1
	16QAM	1	0	21.98	22.00	21.87	1		16QAM	1	0	21.94	22.00	21.81	1
		1	24	21.89	21.94	21.77	1			1	12	21.85	21.89	21.74	1
		1	49	21.66	21.75	21.60	1			1	24	21.59	21.69	21.56	1
		25	0	20.94	20.98	20.83	2			12	0	20.84	20.89	20.65	2
		25	12	20.85	20.95	20.74	2			12	6	20.78	20.85	20.61	2
		25	25	20.83	20.88	20.69	2			12	13	20.69	20.78	20.54	2
		50	0	20.79	20.84	20.67	2			25	0	20.66	20.72	20.53	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20415	20525	20635				Channel		20407	20525	20643	
		Frequency (MHz)		825.5	836.5	847.5				Frequency (MHz)		824.7	836.5	848.3	
3M	QPSK	1	0	22.85	22.90	22.74	0	1.4M	QPSK	1	0	22.80	22.85	22.66	0
		1	7	22.70	22.81	22.63	0			1	2	22.69	22.74	22.57	0
		1	14	22.51	22.58	22.36	0			1	5	22.42	22.52	22.26	0
		8	0	21.75	21.80	21.57	1			3	0	22.25	22.33	22.05	0
		8	3	21.68	21.75	21.54	1			3	1	22.17	22.26	22.03	0
		8	7	21.61	21.68	21.46	1			3	3	22.08	22.18	22.00	0
		15	0	21.49	21.61	21.43	1			6	0	21.40	21.52	21.29	1
	16QAM	1	0	21.86	21.91	21.71	1		16QAM	1	0	21.81	21.89	21.65	1
		1	7	21.75	21.81	21.62	1			1	2	21.68	21.76	21.47	1
		1	14	21.52	21.58	21.37	1			1	5	21.36	21.51	21.25	1
		8	0	20.73	20.78	20.62	2			3	0	21.30	21.36	21.19	1
		8	3	20.63	20.75	20.44	2			3	1	21.23	21.32	21.03	1
		8	7	20.55	20.65	20.40	2			3	3	21.12	21.25	21.01	1
		15	0	20.51	20.61	20.37	2			6	0	20.37	20.47	20.24	2

# ERP Power (dBm)

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	128	824.2	0.49	32.62	30.96	1247.38	H
	189	836.4	0.00	32.52	30.37	1088.93	
	251	848.8	-0.46	32.65	30.04	1009.25	
	128	824.2	-6.64	32.76	23.97	249.46	V
	189	836.4	-6.60	32.39	23.64	231.21	
	251	848.8	-6.98	32.54	23.41	219.28	

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	4132	826.4	-13.54	32.62	16.93	49.32	H
	4182	836.4	-12.93	32.52	17.44	55.46	
	4233	846.6	-12.73	32.65	17.77	59.84	
	4132	826.4	-9.29	32.76	21.32	135.52	V
	4182	836.4	-8.48	32.39	21.76	149.97	
	4233	846.6	-8.27	32.54	22.12	162.93	

LTE Band 5							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20407	824.7	-10.58	32.62	19.89	97.50	H
	20525	836.5	-10.52	32.52	19.85	96.61	
	20643	848.3	-10.38	32.65	20.12	102.80	
	20407	824.7	-13.62	32.76	16.99	50.00	V
	20525	836.5	-13.41	32.39	16.83	48.19	
	20643	848.3	-13.71	32.54	16.68	46.56	
Channel Bandwidth: 1.4 MHz / 16QAM							
X	20407	824.7	-10.67	32.62	19.80	95.50	H
	20525	836.5	-10.61	32.52	19.76	94.62	
	20643	848.3	-10.49	32.65	20.01	100.23	
	20407	824.7	-13.71	32.76	16.90	48.98	V
	20525	836.5	-13.50	32.39	16.74	47.21	
	20643	848.3	-13.79	32.54	16.60	45.71	

LTE Band 5							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20415	825.5	-10.46	32.62	20.01	100.23	H
	20525	836.5	-10.41	32.52	19.96	99.08	
	20635	847.5	-10.26	32.65	20.24	105.68	
	20415	825.5	-13.51	32.76	17.10	51.29	V
	20525	836.5	-13.29	32.39	16.95	49.55	
	20635	847.5	-13.62	32.54	16.77	47.53	
Channel Bandwidth: 3 MHz / 16QAM							
X	20415	825.5	-10.55	32.62	19.92	98.17	H
	20525	836.5	-10.52	32.52	19.85	96.61	
	20635	847.5	-10.35	32.65	20.15	103.51	
	20415	825.5	-13.62	32.76	16.99	50.00	V
	20525	836.5	-13.41	32.39	16.83	48.19	
	20635	847.5	-13.70	32.54	16.69	46.67	

LTE Band 5							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20425	826.5	-10.32	32.62	20.15	103.51	H
	20525	836.5	-10.29	32.52	20.08	101.86	
	20625	846.5	-10.14	32.65	20.36	108.64	
	20425	826.5	-13.39	32.76	17.22	52.72	V
	20525	836.5	-13.18	32.39	17.06	50.82	
	20625	846.5	-13.49	32.54	16.90	48.98	
Channel Bandwidth: 5 MHz / 16QAM							
X	20425	826.5	-10.39	32.62	20.08	101.86	H
	20525	836.5	-10.37	32.52	20.00	100.00	
	20625	846.5	-10.22	32.65	20.28	106.66	
	20425	826.5	-13.45	32.76	17.16	52.00	V
	20525	836.5	-13.26	32.39	16.98	49.89	
	20625	846.5	-13.57	32.54	16.82	48.08	

LTE Band 5							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20450	829.0	-10.21	32.62	20.26	106.17	H
	20525	836.5	-10.15	32.52	20.22	105.20	
	20600	844.0	-10.09	32.65	20.41	109.90	
	20450	829.0	-13.25	32.76	17.36	54.45	V
	20525	836.5	-13.01	32.39	17.23	52.84	
	20600	844.0	-13.38	32.54	17.01	50.23	
Channel Bandwidth: 10 MHz / 16QAM							
X	20425	826.5	-10.29	32.62	20.18	104.23	H
	20525	836.5	-10.21	32.52	20.16	103.75	
	20625	846.5	-10.18	32.65	20.32	107.65	
	20425	826.5	-13.39	32.76	17.22	52.72	V
	20525	836.5	-13.11	32.39	17.13	51.64	
	20625	846.5	-13.49	32.54	16.90	48.98	

## 4.2 Frequency Stability Measurement

### 4.2.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

### 4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5$  °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 4.2.3 Test Setup



#### 4.2.4 Test Results

##### Frequency Error vs. Voltage

Voltage (Volts)	GSM				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.9	824.200002	0.002	848.800002	0.002	2.5
3.51	824.200001	0.002	848.800002	0.002	2.5
4.29	824.200003	0.004	848.800002	0.002	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.51 Vdc to 4.29 Vdc.

##### Frequency Error vs. Temperature

Temp. (°C)	GSM				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	824.200003	0.004	848.800004	0.004	2.5
-20	824.200002	0.002	848.800004	0.005	2.5
-10	824.200003	0.004	848.800004	0.004	2.5
0	824.200003	0.003	848.800003	0.003	2.5
10	824.200001	0.002	848.800003	0.004	2.5
20	824.199996	-0.005	848.799999	-0.001	2.5
30	824.199998	-0.002	848.799998	-0.003	2.5
40	824.199997	-0.004	848.799999	-0.001	2.5
50	824.199998	-0.003	848.799999	-0.002	2.5
55	824.199999	-0.001	848.799997	-0.004	2.5

#### Frequency Error vs. Voltage

Voltage (Volts)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.9	826.400002	0.003	846.600004	0.004	2.5
3.51	826.400001	0.001	846.600003	0.003	2.5
4.29	826.400003	0.004	846.600001	0.001	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.51 Vdc to 4.29 Vdc.

#### Frequency Error vs. Temperature

Temp. (°C)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	826.400002	0.002	846.600004	0.004	2.5
-20	826.400002	0.003	846.600002	0.002	2.5
-10	826.400003	0.003	846.600002	0.003	2.5
0	826.400002	0.002	846.600001	0.001	2.5
10	826.400003	0.003	846.600004	0.004	2.5
20	826.399999	-0.002	846.599998	-0.002	2.5
30	826.399996	-0.004	846.599997	-0.003	2.5
40	826.399998	-0.003	846.599996	-0.004	2.5
50	826.399997	-0.004	846.599997	-0.003	2.5
55	826.399999	-0.002	846.599996	-0.005	2.5

### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.9	824.700003	0.004	848.300003	0.004	2.5
3.51	824.700001	0.002	848.300003	0.004	2.5
4.29	824.700002	0.003	848.300003	0.003	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.51 Vdc to 4.29 Vdc.

### Frequency Error vs. Temperature

Temp. (°C)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	824.700003	0.004	848.300002	0.002	2.5
-20	824.700003	0.004	848.300002	0.003	2.5
-10	824.700003	0.003	848.300003	0.004	2.5
0	824.700002	0.002	848.300001	0.002	2.5
10	824.700003	0.004	848.300002	0.003	2.5
20	824.699996	-0.005	848.299998	-0.003	2.5
30	824.699998	-0.003	848.299997	-0.003	2.5
40	824.699998	-0.003	848.299997	-0.003	2.5
50	824.699998	-0.003	848.299997	-0.003	2.5
55	824.699997	-0.004	848.299997	-0.004	2.5



### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.9	825.500003	0.004	847.500004	0.004	2.5
3.51	825.500004	0.005	847.500002	0.002	2.5
4.29	825.500003	0.004	847.500004	0.004	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.51 Vdc to 4.29 Vdc.

### Frequency Error vs. Temperature

Temp. (°C)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	825.500002	0.003	847.500003	0.003	2.5
-20	825.500002	0.003	847.500002	0.002	2.5
-10	825.500002	0.002	847.500003	0.003	2.5
0	825.500002	0.002	847.500002	0.003	2.5
10	825.500003	0.003	847.500003	0.004	2.5
20	825.499997	-0.003	847.499996	-0.005	2.5
30	825.499998	-0.003	847.499997	-0.003	2.5
40	825.499998	-0.002	847.499997	-0.003	2.5
50	825.499998	-0.003	847.499998	-0.003	2.5
55	825.499998	-0.002	847.499999	-0.002	2.5

### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.9	826.500003	0.004	846.500003	0.003	2.5
3.51	826.500002	0.003	846.500004	0.004	2.5
4.29	826.500003	0.003	846.500002	0.002	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.51 Vdc to 4.29 Vdc.

### Frequency Error vs. Temperature

Temp. (°C)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	826.500002	0.002	846.500002	0.002	2.5
-20	826.500003	0.004	846.500002	0.003	2.5
-10	826.500002	0.002	846.500002	0.003	2.5
0	826.500002	0.002	846.500003	0.004	2.5
10	826.500002	0.002	846.500003	0.003	2.5
20	826.499998	-0.002	846.499998	-0.002	2.5
30	826.499999	-0.002	846.499996	-0.004	2.5
40	826.499998	-0.002	846.499999	-0.002	2.5
50	826.499997	-0.004	846.499998	-0.002	2.5
55	826.499999	-0.001	846.499999	-0.002	2.5

### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.9	829.000003	0.003	844.000002	0.002	2.5
3.51	829.000001	0.001	844.000002	0.002	2.5
4.29	829.000003	0.003	844.000001	0.001	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.51 Vdc to 4.29 Vdc.

### Frequency Error vs. Temperature


Temp. (°C)	LTE Band 5				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	829.000003	0.003	844.000002	0.002	2.5
-20	829.000002	0.002	844.000003	0.003	2.5
-10	829.000003	0.003	844.000003	0.004	2.5
0	829.000002	0.002	844.000002	0.002	2.5
10	829.000004	0.004	844.000001	0.002	2.5
20	828.999997	-0.004	843.999998	-0.002	2.5
30	828.999997	-0.004	843.999998	-0.002	2.5
40	828.999997	-0.004	843.999997	-0.004	2.5
50	828.999999	-0.002	843.999999	-0.001	2.5
55	828.999996	-0.005	843.999996	-0.005	2.5

### 4.3 Occupied Bandwidth Measurement

#### 4.3.1 Test Procedure


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

#### 4.3.2 Test Setup




#### 4.3.3 Test Result


Channel	Frequency (MHz)	99 % Occupied Bandwidth (kHz)	Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)
		GSM			WCDMA
128	824.2	244.14	4132	826.4	4.1326
189	836.4	244.00	4182	836.4	4.1430
251	848.8	243.23	4233	846.6	4.1318



LTE Band 5							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.0877	1.0910	20415	825.5	2.6977	2.6936
20525	836.5	1.0886	1.0899	20525	836.5	2.7024	2.6953
20643	848.3	1.0858	1.0906	20635	847.5	2.7002	2.6942



LTE Band 5							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.4787	4.4837	20450	829.0	8.9452	8.9502
20525	836.5	4.4842	4.4846	20525	836.5	8.9623	8.9720
20625	846.5	4.4798	4.4826	20600	844.0	8.9327	8.9301




## 4.4 Band Edge Measurement

### 4.4.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

### 4.4.2 Test Setup





### 4.4.3 Test Procedures


- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 10 kHz and VB of the spectrum is 30 kHz (GSM/GPRS).
- The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 13 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 5 MHz/10 MHz).
- Record the max trace plot into the test report.




#### 4.4.4 Test Results















## 4.5 Peak to Average Ratio

### 4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 4.5.2 Test Setup




### 4.5.3 Test Procedures

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

#### 4.5.4 Test Results


Channel	Frequency (MHz)	Peak to Average Ratio (dB)	Channel	Frequency (MHz)	Peak to Average Ratio (dB)
		GSM			WCDMA
128	824.2	0.12	4132	826.4	2.91
189	836.4	0.12	4182	836.4	2.99
251	848.8	0.12	4233	846.6	2.93



### LTE Band 5


Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	4.16	4.96	20415	825.5	4.14	5.03
20525	836.5	4.55	5.30	20525	836.5	4.56	5.37
20643	848.3	4.29	5.11	20635	847.5	4.21	5.09

### Spectrum Plot of Worst Value





LTE Band 5							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.15	4.96	20450	829.0	4.14	4.99
20525	836.5	4.50	5.27	20525	836.5	4.41	5.24
20625	846.5	4.16	5.02	20600	844.0	4.45	5.25




## 4.6 Conducted Spurious Emissions

### 4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to -13 dBm.


### 4.6.2 Test Setup



### 4.6.3 Test Procedure


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 10 GHz. 20 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz is used for conducted emission measurement.

#### 4.6.4 Test Results




## WCDMA Channel 4132

**Frequency Range: 30 MHz ~ 1 GHz**




**Frequency Range: 1 GHz ~ 10 GHz**




## Channel 4182

**Frequency Range: 30 MHz ~ 1 GHz**




**Frequency Range: 1 GHz ~ 10 GHz**




## Channel 4233

**Frequency Range: 30 MHz ~ 1 GHz**



**Frequency Range: 1 GHz ~ 10 GHz**







## LTE Band 5

Channel Bandwidth: 1.4 MHz

Channel 20407

Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



## Channel 20525

Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




## Channel 20643

Frequency Range: 30 MHz ~ 1 GHz

Frequency Range: 1 GHz ~ 10 GHz









## LTE Band 5

Channel Bandwidth: 5 MHz

Channel 20425

Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



## Channel 20525

Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



## Channel 20625

Frequency Range: 30 MHz ~ 1 GHz

Frequency Range: 1 GHz ~ 10 GHz





## LTE Band 5

Channel Bandwidth: 10 MHz

Channel 20450

Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



## Channel 20525

Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



## Channel 20600

Frequency Range: 30 MHz ~ 1 GHz

Frequency Range: 1 GHz ~ 10 GHz





## 4.7 Radiated Emission Measurement

### 4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit is equal to -13 dBm.

### 4.7.2 Test Procedure

- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}.$


**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.

### 4.7.3 Deviation from Test Standard


No deviation.

#### 4.7.4 Test Setup

##### <Radiated Emission below or equal 1 GHz>



##### <Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.7.5 Test Results

GSM:

Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2018-02-23



Site : 966 Chamber 5

Condition: PART22/24 HORIZONTAL

Remak : GSM 850 Link\_L-CH

Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1648.40	-45.57	-30.84	-13.00	-32.57	-14.73	Peak
2 pp	2472.60	-43.67	-33.23	-13.00	-30.67	-10.44	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2018-02-23



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : GSM 850 Link\_L-CH

Tested by: Getaz Yang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1648.40	-42.71	-27.98	-13.00	-29.71	-14.73	Peak
2	2472.60	-47.34	-36.90	-13.00	-34.34	-10.44	Peak


## Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
 Condition: PART22/24 HORIZONTAL  
 Remak : GSM 850 Link\_M-CH  
 Tested by: Getaz Yang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1672.80	-46.05	-31.37	-13.00	-33.05	-14.68	Peak
2 pp	2509.20	-39.86	-28.95	-13.00	-26.86	-10.91	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2018-02-23



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : GSM 850 Link\_M-CH

Tested by: Getaz Yang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1672.80	-42.82	-28.14	-13.00	-29.82	-14.68	Peak
2	2509.20	-43.03	-32.12	-13.00	-30.03	-10.91	Peak


## High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
 Condition: PART22/24 HORIZONTAL  
 Remak : GSM 850 Link\_H-CH  
 Tested by: Getaz Yang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1697.60	-44.14	-29.61	-13.00	-31.14	-14.53	Peak
2 pp	2546.40	-43.09	-32.32	-13.00	-30.09	-10.77	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2018-02-23



Site : 966 Chamber 5  
Condition: PART22/24 VERTICAL  
Remak : GSM 850 Link\_H-CH  
Tested by: Getaz Yang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1697.60	-42.50	-27.97	-13.00	-29.50	-14.53	Peak
2	2546.40	-44.48	-33.71	-13.00	-31.48	-10.77	Peak




WCDMA:  
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
Condition: PART22/24 HORIZONTAL  
Remak : WCDMA Band 5 Link\_L-CH  
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1652.80	-56.33	-41.60	-13.00	-43.33	-14.73	Peak
2 pp	2479.20	-52.83	-42.39	-13.00	-39.83	-10.44	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2018-02-23



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : WCDMA Band 5 Link\_L-CH

Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1652.80	-54.65	-39.92	-13.00	-41.65	-14.73	Peak
2 pp	2479.20	-51.94	-41.50	-13.00	-38.94	-10.44	Peak


## Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
 Condition: PART22/24 HORIZONTAL  
 Remak : WCDMA Band 5 Link\_L-CH Link\_M-CH  
 Tested by: Getaz Yang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1672.80	-55.18	-40.50	-13.00	-42.18	-14.68	Peak
2 pp	2509.20	-52.61	-41.70	-13.00	-39.61	-10.91	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2018-02-23



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : WCDMA Band 5 Link\_L-CH Link\_M-CH

Tested by: Getaz Yang

Freq	Level	Read	Limit	Over	Factor	Remark
		Level	Line	Limit		
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1672.80	-53.14	-38.46	-13.00	-40.14	-14.68	Peak


# High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
Condition: PART22/24 HORIZONTAL  
Remak : WCDMA Band 5 Link\_H-CH  
Tested by: Getaz Yang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1693.20	-53.64	-39.11	-13.00	-40.64	-14.53	Peak
2 pp	2539.80	-48.83	-38.06	-13.00	-35.83	-10.77	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2018-02-23



Site : 966 Chamber 5  
Condition: PART22/24 VERTICAL  
Remak : WCDMA Band 5 Link\_H-CH  
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1693.20	-51.97	-37.44	-13.00	-38.97	-14.53	Peak
2 pp	2539.80	-49.97	-39.20	-13.00	-36.97	-10.77	Peak




LTE Band 5  
Channel Bandwidth: 1.4 MHz / QPSK  
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART22/24 HORIZONTAL  
Remak : LTE Band 5 QPSK\_1.4M Link\_L-CH  
Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1649.40	-48.65	-33.92	-13.00	-35.65	-14.73	Peak
2 pp	2474.10	-46.67	-36.23	-13.00	-33.67	-10.44	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2018-02-21



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : LTE Band 5 QPSK\_1.4M Link\_L-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1649.40	-51.20	-36.47	-13.00	-38.20	-14.73	Peak
2 pp	2474.10	-47.60	-37.16	-13.00	-34.60	-10.44	Peak




## Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 7



Site : 966 Chamber 5  
 Condition: PART22/24 HORIZONTAL  
 Remak : LTE Band 5 QPSK\_1.4M Link\_M-CH  
 Tested by: Jisyoung Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	43.50	-57.04	-55.57	-13.00	-44.04	-1.47	Peak
2	53.22	-57.89	-52.08	-13.00	-44.89	-5.81	Peak
3	193.89	-50.94	-43.48	-13.00	-37.94	-7.46	Peak
4	370.00	-63.86	-57.74	-13.00	-50.86	-6.12	Peak
5	638.80	-64.79	-63.93	-13.00	-51.79	-0.86	Peak
6	922.30	-63.80	-64.92	-13.00	-50.80	1.12	Peak
7 pp	1673.00	-42.26	-27.58	-13.00	-29.26	-14.68	Peak
8	2509.50	-48.08	-37.17	-13.00	-35.08	-10.91	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 8

Date: 2018-02-21



Site : 966 Chamber 5  
Condition: PART22/24 VERTICAL  
Remak : LTE Band 5 QPSK\_1.4M Link\_M-CH  
Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	40.80	-56.07	-56.19	-13.00	-43.07	0.12	Peak
2	53.49	-58.36	-52.55	-13.00	-45.36	-5.81	Peak
3	194.43	-55.47	-47.92	-13.00	-42.47	-7.55	Peak
4	363.00	-66.25	-60.09	-13.00	-53.25	-6.16	Peak
5	616.40	-65.21	-64.41	-13.00	-52.21	-0.80	Peak
6	937.70	-63.88	-65.39	-13.00	-50.88	1.51	Peak
7 pp	1673.00	-46.60	-31.92	-13.00	-33.60	-14.68	Peak
8	2509.50	-50.48	-39.57	-13.00	-37.48	-10.91	Peak


## High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5

Condition: PART22/24 HORIZONTAL

Remak : LTE Band 5 QPSK\_1.4M Link\_H-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1696.60	-51.03	-36.50	-13.00	-38.03	-14.53	Peak
2 pp	2544.90	-50.03	-39.26	-13.00	-37.03	-10.77	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2018-02-21



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : LTE Band 5 QPSK\_1.4M Link\_H-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1696.60	-50.25	-35.72	-13.00	-37.25	-14.53	Peak
2	2544.90	-53.04	-42.27	-13.00	-40.04	-10.77	Peak


LTE Band 5  
Channel Bandwidth: 5 MHz / QPSK  
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART22/24 HORIZONTAL  
Remak : LTE Band 5 QPSK\_5M Link\_L-CH  
Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1653.00	-50.11	-35.38	-13.00	-37.11	-14.73	Peak
2 pp	2479.50	-46.66	-36.22	-13.00	-33.66	-10.44	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2018-02-21



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : LTE Band 5 QPSK\_5M Link\_L-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1653.00	-49.48	-34.75	-13.00	-36.48	-14.73	Peak
2 pp	2479.50	-48.93	-38.49	-13.00	-35.93	-10.44	Peak




## Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5

Condition: PART22/24 HORIZONTAL

Remak : LTE Band 5 QPSK\_5M Link\_M-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	1673.00	-49.80	-35.12	-13.00	-36.80	-14.68	Peak
2	2509.50	-50.89	-39.98	-13.00	-37.89	-10.91	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2018-02-21



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : LTE Band 5 QPSK\_5M Link\_M-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1673.00	-49.14	-34.46	-13.00	-36.14	-14.68	Peak
2	2509.50	-53.28	-42.37	-13.00	-40.28	-10.91	Peak




## High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5

Condition: PART22/24 HORIZONTAL

Remak : LTE Band 5 QPSK\_5M Link\_H-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1693.00	-50.95	-36.35	-13.00	-37.95	-14.60	Peak
2	2539.50	-51.09	-40.32	-13.00	-38.09	-10.77	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2018-02-21



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : LTE Band 5 QPSK\_5M Link\_H-CH

Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1693.00	-47.41	-32.81	-13.00	-34.41	-14.60	Peak
2	2539.50	-53.82	-43.05	-13.00	-40.82	-10.77	Peak


LTE Band 5  
Channel Bandwidth: 10 MHz / QPSK  
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART22/24 HORIZONTAL  
Remak : LTE Band 5 QPSK\_10M Link\_L-CH  
Tested by: Jisyong Wang


			Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	1658.00	-53.02	-38.34	-13.00	-40.02	-14.68	Peak
2	2487.00	-50.29	-39.85	-13.00	-37.29	-10.44	Peak



# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART22/24 VERTICAL  
 Remak : LTE Band 5 QPSK\_10M Link\_L-CH  
 Tested by: Jisyong Wang

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1658.00	-52.46	-37.78	-13.00	-39.46	-14.68	Peak
2	2487.00	-52.71	-42.27	-13.00	-39.71	-10.44	Peak


# Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART22/24 HORIZONTAL  
Remak : LTE Band 5 QPSK\_10M Link\_M-CH  
Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1673.00	-49.77	-35.09	-13.00	-36.77	-14.68	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2018-02-21



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : LTE Band 5 QPSK\_10M Link\_M-CH

Tested by: Jisyong Wang

Freq	Level	Read	Limit	Over		Factor	Remark
		Level	Line	Limit	Limit		
MHz	dBm	dBm	dBm	dB	dB	dB	
1 pp 1673.00	-47.14	-32.46	-13.00	-34.14	-14.68		Peak




## High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5

Condition: PART22/24 HORIZONTAL

Remak : LTE Band 5 QPSK\_10M Link\_H-CH

Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1688.00	-51.04	-36.44	-13.00	-38.04	-14.60	Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2018-02-21



Site : 966 Chamber 5

Condition: PART22/24 VERTICAL

Remak : LTE Band 5 QPSK\_10M Link\_H-CH

Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	

1 pp 1688.00 -47.94 -33.34 -13.00 -34.94 -14.60 Peak



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---