

TEST REPORT

For

Mobile Phone

In conformity with

FCC Part22H (01 Oct, 2008)

Model: F-02B

FCC ID: VQK-F02B

Test Item: Mobile Phone

Report No: RY0908P12R2

Issue Date: 12 Aug, 2009

Prepared for

Fujitsu Limited.
4-1-1, Kamikodanaka, Nakahara, Kawasaki 211-8588, Japan

Prepared by

RF Technologies Ltd.
472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45- 534-0645
FAX: +81+(0)45- 534-0646

This report shall not be reproduced, except in full, without the written permission of RF Technologies Ltd. The test results in this report apply only to the sample(s) tested. RF Technologies Ltd. is managed to ISO17025 and has the necessary knowledge and test facilities for testing according to the referenced standards.

Table of Contents

1	General information	3
1.1	Product description	3
1.2	Test(s) performed/ Summary of test result	3
1.3	Test facility	4
1.4	Measurement uncertainty	4
1.5	Description of essential requirements and test results.....	5
1.5.1	Transmitter requirements	5
1.5.2	Receiver requirements.....	5
1.5.3	AC Power Line Parameters.....	5
1.5.4	Normal test conditions	5
1.5.5	Extreme test conditions	5
1.6	Setup of equipment under test (EUT)	6
1.6.1	Test configuration of EUT	6
1.6.2	Operating condition:	6
1.6.3	Setup diagram of tested system:.....	7
1.7	Equipment modifications	7
1.8	Deviation from the standard.....	7
2	Test procedure and result.....	8
2.1	Transmitter requirements	8
2.1.1	Carrier Output Power (Conducted)	8
2.1.2	Carrier Output Power (Radiated)	10
2.1.3	Frequency Stability (Temperature)	13
2.1.4	Frequency Stability (Voltage)	15
2.1.5	Occupied Bandwidth.....	17
2.1.6	Transmitter Out of Band Spurious Emissions (Conducted).....	22
2.1.7	Transmitter Out of Band Spurious Emissions (Radiated).....	28
2.1.8	Band Edge Emissions.....	32
2.1.9	Transmitter AC Power Line Emission requirement.....	35
2.2	Receiver requirement	37
2.2.1	Receiver Spurious Emissions (Radiated)	37
2.2.2	Receiver AC Power Line Emission requirement	40
3	Test setup photographs.....	42
4	List of utilized test equipment/ calibration.....	44

History

Report No.	Issue Date	Revision Contents	Issued by
RY0908P12R2	12 Aug, 2009	Initial Issue	T.Kato

1 General information

1.1 Product description

Test item : Mobile phone
Manufacturer : Fujitsu Limited
Address : 4-1-1, Kamikodanaka, Nakahara, Kawasaki, 211-8588, Japan
Model : F-02B
FCC ID : VQK-F02B
Operating frequency range : TX 826.4-846.6 MHz (WCDMA850, HSDPA 7.2M)
: RX 871.4-891.6 MHz (WCDMA850, HSDPA 7.2M)
Type of Modulation : QPSK
Receipt date of EUT : 27 July, 2009
Nominal power voltages : 3.7VDC (Lithium-ion battery)
Power Class : 3 (Maximum power 24dBm nominal)
Antenna Type : Integral antenna
Serial numbers : 3567 7402 0004 495 (for Radiated test)
: 3567 7402 0004 438 (for Conducted test)

1.2 Test(s) performed/ Summary of test result

Applicable Standard(s) : FCC Part22H (01 Oct, 2008)
Test(s) started : 31 Jul, 2009
Test(s) completed : 11 Aug, 2009
Purpose of test(s) : Grant for Certification of FCC

Summary of test result : Complied

Note: The above judgment is only based on the measurement data and it does not include the measurement uncertainty. Accordingly, the statement below is applied to the test result. The EUT complies with the limit required in the standard in case that the margin is not less than the measurement uncertainty in the Laboratory. Compliance of the EUT is more probable than non-compliance is case that the margin is less than the measurement uncertainty in the Laboratory.

Test engineer : 
T. Kato (Engineer, EMC testing department)

Reviewer : 
K. Ohnishi (Manager, EMC testing department)

1.3 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at RF Technologies Ltd., located in 472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per 01 October, 2008.

The description of the test facilities has been filed under registration number 319924 at the Office of the Federal Communications Commission. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

Registered by Voluntary Control Council for Interference by Information Technology Equipment (VCCI).

Each registered facility number is as follows;

Test site (Semi-anechoic chamber 3m) R-2393

Test site (Shielded room) C-2617

Registered by Industry Canada (IC). The registered facility number is as follows;

Test site No.1(Semi-anechoic chamber 3m) : 6974A-1

Accredited by **National Voluntary Laboratory Accreditation Program** (NVLAP) for the emission tests stated in the scope of the certificate under Certificate Number 200780-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200780-0

1.4 Measurement uncertainty

The treatment of uncertainty is based on the general matters on the definition of uncertainty in “Guide to the expression of uncertainty in measurement (GUM)” published by ISO. The Lab’s uncertainty is determined by referring UKAS Publication LAB34: 2002 “The Expression of Uncertainty in EMC Testing” and CISPR16-4-2: 2003 “Uncertainty in EMC Measurements”.

The uncertainty of the measurement result in the level of confidence of approximately 95% (k=2) is as follows;

RF frequency: $\pm 1 \times 10^{-7}$

RF power conducted: ± 1.0 dB

AC Power line emission: ± 1.9 dB

Radiated emission (30MHz - 1000MHz): ± 5.7 dB

Radiated emission (1GHz - 20GHz): ± 5.8 dB

Temperature: ± 1 degree

Humidity: ± 5 %

1.5 Description of essential requirements and test results

An overview of radio requirements, as laid out in FCC Part22 are given below.

1.5.1 Transmitter requirements

Test Description	Section in this report	Applicable	Result
Carrier Output Power (Conducted)	2.1.1	Yes	Passed
Carrier Output Power (Radiated)	2.1.2	Yes	Passed
Frequency Stability (Temperature Variation)	2.1.3	Yes	Passed
Frequency Stability (Voltage Variation)	2.1.4	Yes	Passed
Occupied Bandwidth	2.1.5	Yes	Passed
Out of Band Emissions (Conducted)	2.1.6	Yes	Passed
Out of Band Emissions (Radiated)	2.1.7	Yes	Passed
Band Edge Emissions	2.1.8	Yes	Passed

1.5.2 Receiver requirements

Test Description	Section in this report	Applicable	Result
Spurious Radiated Emissions	2.2.1	Yes	Passed

1.5.3 AC Power Line Parameters

Test Description	Section in this report	Applicable	Result
AC power line Spurious Emissions (Idle mode)	2.2.2	Yes	Passed
AC power line Spurious Emissions (Traffic mode)	2.1.9	Yes	Passed

1.5.4 Normal test conditions

Temperature(*) : +15 degC to +35 degC
Relative humidity(*) : 20 % to 75 %
Supply voltage : 3.7 VDC (Nominal)
Measurement Frequency : 826.4 MHz(4132ch), 836.4 MHz(4182ch), 846.6 MHz(4233ch)

* When it is impracticable to carry out tests under these conditions, a note to this effect, stating the ambient temperature and relative humidity during the tests, must be stated separately.

1.5.5 Extreme test conditions

Temperature : -30 °C (min) to +50 °C (max)
Supply voltage : 3.33 VDC (min) to 4.07 VDC (max)
The equipment has a function that it is automatically turned off when min. battery voltage (3.33 V) is detected.

1.6 Setup of equipment under test (EUT)

1.6.1 Test configuration of EUT

Equipment(s) under test:

	Item	Manufacturer	Model No.	Serial No.	FCC ID
A	Mobile phone	Fujitsu Limited	F-02B	3567 7402 0004 495	VQK-F02B
B	Mobile phone	Fujitsu Limited	F-02B (RF cable is attached instead of integral antenna)	3567 7402 0004 438	VQK-F02B
C	Battery pack	Fujitsu Limited	F09	None	N/A
D	AC adapter	Fujitsu Limited.	FOMA AC adapter02	None	N/A

Connected cable(s):


No.	Item	Identification (Manu.e.t.c)	Shielded YES / NO	Ferrite Core YES / NO	Connector Type Shielded YES / NO	Length (m)
1	DC power cable	-	No	No	No	2.32

1.6.2 Operating condition:


Traffic mode : EUT is connected with RF tester in Max power level. (Normal and HSDPA mode)
Idle mode : EUT is under idle mode, no output power is transmitted.

1.6.3 Setup diagram of tested system:

[Configuration I]



[Configuration II]



1.7 Equipment modifications

No modifications have been made to the equipment in order to achieve compliance with the applicable standards described in clause 1.2.

1.8 Deviation from the standard

No deviations from the standards described in clause 1.2.

2 Test procedure and result

2.1 *Transmitter requirements*

2.1.1 Carrier Output Power (Conducted)

Reference Standard

Part22.913, 2.0146

Test Conditions

Date: 31 Jul, 2009
Ambient Temperature: 26 degC
Relative humidity: 60 %
Test Voltage: 3.7 V


Test Sample

Configuration II

Test Method

- a) EUT is connected to RF tester with pseudo random data modulation and set to maximum output power level.
- b) The output power is measured with RF tester (CMU200 etc.).

Test Setup



Test Results

Channel	Frequency (MHz)	Output Power (dBm)		Limit (dBm)	Result
		Normal	HSDPA		
Bottom (4132ch)	826.4	22.7	21.7	38.4	Pass
Middle (4182ch)	836.4	23.4	22.5	38.4	Pass
Top (4233ch)	846.6	22.4	21.6	38.4	Pass

Test Equipment Used

Equipment name	RFT ID No.
RF tester	RC03
RF cable	CL27

Final Result

The EUT met the requirements of the standard for this test.

2.1.2 Carrier Output Power (Radiated)

Reference Standard

Part22.913, 2.0146

Test Conditions

Date: 10 Aug, 2009
Ambient Temperature: 21 degC
Relative humidity: 51 %
Test Voltage: 3.7 V

Test Sample

Configuration I

Test Method

Substitution method is used for this test.

- a) EUT is set on non-conducting turntable and the output power is set to the maximum level.
- b) As a receive antenna, Horn antenna is used for high frequency range (above 1GHz), and Bilogical antenna is used for low frequency range (30MHz to 1GHz).
- c) Maximum power is measured by a spectrum analyzer (SA) in below conditions.

Turntable is rotated 360 degrees.

The height of receive antenna is changed from 1m to 4m.

Receive antenna polarization is set to vertical and horizontal.

This maximum power is recorded.


During this measurement, receive antenna is adjusted the direction to keep the EUT within the beamwidth of receive antenna.

- d) Reference antenna is replaced with EUT, and connected with signal generator (SG).
SG output power is adjusted to get same level as the recorded maximum radiated EUT power by SA.
- e) Radiated output power (Pout) is calculated with adjusted SG output (Psg) [dBm], reference antenna gain (Gref) [dBd] and cable loss between SG and reference antenna (Lcab) [dB].


$$P_{out} [dBm \text{ e.r.p}] = P_{sg} + G_{ref} + L_{cab}$$

Test Setup

[Measurement]



[Substitution]



Test Results

Channel	Frequency (MHz)	Output Power (dBm)		Limit (dBm e.r.p)	Result
		Normal	HSDPA		
Bottom (4132ch)	826.4	21.4	21.7	38.4	Pass
Middle (4182ch)	836.4	23.6	23.6	38.4	Pass
Top (4233ch)	846.6	22.8	22.9	38.4	Pass

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
Receive Antenna	DH02
Reference Antenna	LA02
Signal Generator	SG05
Power Meter	PM03
RF tester	RC03
RF cable	CL24

Final Result

The EUT met the requirements of the standard for this test.

2.1.3 Frequency Stability (Temperature)

Reference Standard

Part22.355, 2.1055

Test Conditions

Date: 03 Aug, 2009
Ambient Temperature: 28 degC
Relative humidity: 60 %
Test Voltage: 3.7 V

Test Sample


Configuration II

Test Method

To measure the carrier frequency, “Frequency error measurement” function of RF tester is used.

- a) EUT is hold about 30 minutes under measurement temperature condition.
 - b) EUT is powered on with nominal voltage.
 - c) EUT is connected to RF tester with Max transmit power level.
 - d) Frequency error is measured by RF tester.
- Process b) to d) must be finished within 2 minutes to prevent EUT warming.
- e) Process a) to d) is repeated at 10deg increments from -30 to +50degC.

Test Setup



Test Results**Middle Channel (4182ch, Nominal Freq.:836.4MHz)**

Temperature (deg C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Result
-30	29	+0.03	± 2.5	Passed
-20	22	+0.03	± 2.5	Passed
-10	-17	-0.02	± 2.5	Passed
0	-11	-0.01	± 2.5	Passed
10	13	+0.02	± 2.5	Passed
20	11	+0.01	± 2.5	Passed
30	-9	-0.01	± 2.5	Passed
40	12	+0.01	± 2.5	Passed
50	15	+0.02	± 2.5	Passed

Test Equipment Used

Equipment name	RFT ID No.
RF tester	RC03
Temp Chamber	TC01

Final Result

The EUT met the requirements of the standard for this test

2.1.4 Frequency Stability (Voltage)

Reference Standard

Part22.355, 2.1055

Test Conditions

Date: 03 Jul, 2009
Ambient Temperature: 28 degC
Relative humidity: 60 %
Test Voltage: 3.33 V to 4.07 V

Test Sample


Configuration II

Test Method

To measure the carrier frequency, “Frequency error measurement” function of RF tester is used.

- a) EUT is powered on with nominal voltage. Temperature is 20degC.
- b) EUT is connected to RF tester with Max transmitter power level.
- c) Frequency error is measured by RF tester.
- d) Process a) to c) is repeated at minimum and maximum voltage condition.

Test Setup



Test Results**Middle Channel (4182ch, Nominal Freq.:836.4MHz)**

Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Result
3.33	-15	-0.02	± 2.5	Passed
3.7	11	+0.01	± 2.5	Passed
4.07	-11	-0.01	± 2.5	Passed

Test Equipment Used

Equipment name	RFT ID No.
RF tester	RC03
Temp chamber	TC01

Final Result

The EUT met the requirements of the standard for this test

2.1.5 Occupied Bandwidth

Reference Standard

Part2.1049

Test Conditions

Date: 31 Jul, 2009
Ambient Temperature: 26 degC
Relative humidity: 60 %
Test Voltage: 3.7 V


Test Sample

Configuration II

Test Method

- EUT is connected to RF tester with Max transmitter power level.
- 26dB bandwidth is measured by Spectrum Analyzer.
- 99% occupied bandwidth of transmitter spectrum is measured by Spectrum Analyzer.


Test Setup




Test Results

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Bottom (4132ch)	826.4	4.647	4.155
Middle (4182ch)	836.4	4.663	4.153
Top (4233ch)	846.6	4.651	4.161


Graphical Data




4132ch Occupied Bandwidth




4182ch Occupied Bandwidth




4233ch Occupied Bandwidth



4132ch 26dB Bandwidth



4182ch 26dB Bandwidth



4233ch 26dB Bandwidth

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
RF tester	RC03
RF cable	CL27
Directional coupler	DC01

2.1.6 Transmitter Out of Band Spurious Emissions (Conducted)

Reference Standard

Part22.917

Test Conditions

Date: 31 Jul, 2009
Ambient Temperature: 26 degC
Relative humidity: 60 %
Test Voltage: 3.7 V

Test Sample


Configuration II

Test Method


- EUT is connected to RF tester with Max transmitter power level.
- Out of band Spurious is measured by Spectrum Analyzer.
- Resolution band width of spectrum analyzer is set to 1MHz (above 1GHz) or 100kHz (below 1GHz).

Test Setup

30MHz to 1500MHz



above 1500MHz



Test Results**Bottom Channel (4132ch, Nominal Freq.:826.4MHz)**

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)	Limit (dBm)	Result Pass/Fail
1652.8	1	-41.7	-13.0	Pass
2479.2	1	-55.7	-13.0	Pass
3305.6	1	-58.2	-13.0	Pass
4132.0	1	-58.3	-13.0	Pass
4958.4	1	< -60.0	-13.0	Pass
5784.8	1	< -60.0	-13.0	Pass
6611.2	1	< -60.0	-13.0	Pass
7437.6	1	< -60.0	-13.0	Pass
8264.0	1	< -60.0	-13.0	Pass
others		-	-13.0	Pass


Middle Channel (4182ch, Nominal Freq.:836.4MHz)



Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)	Limit (dBm)	Result Pass/Fail
1672.8	1	-45.9	-13.0	Pass
2509.2	1	-54.9	-13.0	Pass
3345.6	1	-56.6	-13.0	Pass
4182.0	1	-60.0	-13.0	Pass
5018.4	1	< -60.0	-13.0	Pass
5854.8	1	< -60.0	-13.0	Pass
6691.2	1	< -60.0	-13.0	Pass
7527.6	1	< -60.0	-13.0	Pass
8364.0	1	< -60.0	-13.0	Pass
others		-	-13.0	Pass



Top Channel (4233ch, Nominal Freq.:846.6MHz)


Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)	Limit (dBm)	Result Pass/Fail
1693.2	1	-46.2	-13.0	Pass
2539.8	1	-56.4	-13.0	Pass
3386.4	1	-54.4	-13.0	Pass
4233.0	1	-58.8	-13.0	Pass
5079.6	1	< -60.0	-13.0	Pass
5926.2	1	< -60.0	-13.0	Pass
6772.8	1	< -60.0	-13.0	Pass
7619.4	1	< -60.0	-13.0	Pass
8466.0	1	< -60.0	-13.0	Pass
others		-	-13.0	Pass

Graphical Data (4182ch, Pre-scan)









Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
RF tester	RC03
RF cable	CL27
Directional coupler	DC01
High pass filter	HPF2

Final Result

The EUT met the requirements of the standard for this test.

2.1.7 Transmitter Out of Band Spurious Emissions (Radiated)

Reference Standard

Part22.917

Test Conditions

Date: 11 Aug, 2009 (Above 1GHz), 06 Aug, 2009 (Below 1GHz)
Ambient Temperature: 20 degC (11 Aug), 20 degC (06 Aug)
Relative humidity: 58 % (11 Aug), 57% (06 Aug)
Test Voltage: 3.7 V

Test Sample

Configuration I

Test Method

Substitution method is used for this test.

- a) EUT is set on non-conducting turntable and the output power is set to the maximum level.
- b) As a receive antenna, Horn antenna is used for high frequency range (above 1GHz), and Bilogical antenna is used for low frequency range (30MHz to 1GHz).
- c) The maximum level of each spurious emission is measured by a spectrum analyzer (SA) in below conditions.

Turntable is rotated 360 degrees.

The height of receive antenna is changed from 1m to 4m.

Receive antenna polarization is set to vertical and horizontal.

EUT was placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

This emission level is recorded.

During this measurement, receive antenna is adjusted the direction to keep the EUT within the beamwidth of receive antenna.


- d) Reference antenna is replaced with EUT, and connected with signal generator (SG).
SG output power is adjusted to get same level as the recorded maximum radiated EUT power by SA.

- e) Radiated output power (Pout) is calculated with adjusted SG output (Psg) [dBm], reference antenna gain (Gref) [dBd] and cable loss between SG and reference antenna (Lcab) [dB].


$$P_{out} [\text{dBm e.r.p}] = P_{sg} + G_{ref} + L_{cab}$$

Test Setup

[Measurement]



[Substitution]



Test Results

Bottom Channel (4132ch, Nominal Freq.:826.4MHz)

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)		Limit (dBm)	Result Pass/Fail
		Vertical	Horizontal		
1652.8	1	-35.5	-36.2	-13.0	Pass
2479.2	1	-33.9	-35.8	-13.0	Pass
3305.6	1	-35.0	-34.0	-13.0	Pass
4132.0	1	-32.0	-26.5	-13.0	Pass
4958.4	1	-38.1	-37.5	-13.0	Pass
5784.8	1	< -49.1	< -49.2	-13.0	Pass
6611.2	1	< -46.4	< -45.8	-13.0	Pass
7437.6	1	< -46.7	< -46.9	-13.0	Pass
8264.0	1	< -43.4	< -43.1	-13.0	Pass
others		-	-	-13.0	Pass

Middle Channel (4182ch, Nominal Freq.:836.4MHz)

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)		Limit (dBm)	Result Pass/Fail
		Vertical	Horizontal		
1672.8	1	-37.3	-37.8	-13.0	Pass
2509.2	1	-36.3	-36.2	-13.0	Pass
3345.6	1	-35.3	-36.3	-13.0	Pass
4182.0	1	-32.2	-26.7	-13.0	Pass
5018.4	1	-40.4	-37.6	-13.0	Pass
5854.8	1	< -48.3	< -48.3	-13.0	Pass
6691.2	1	< -46.6	< -46.0	-13.0	Pass
7527.6	1	< -45.6	< -46.6	-13.0	Pass
8364.0	1	< -43.6	< -43.9	-13.0	Pass
others		-	-	-13.0	Pass

Top Channel (4233ch, Nominal Freq.:846.6MHz)

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level(dBm)		Limit (dBm)	Result Pass/Fail
		Vertical	Horizontal		
1693.2	1	-38.0	-37.6	-13.0	Pass
2539.8	1	-37.6	-35.6	-13.0	Pass
3386.4	1	-33.6	-36.6	-13.0	Pass
4233.0	1	-31.6	-26.5	-13.0	Pass
5079.6	1	-40.1	-37.5	-13.0	Pass
5926.2	1	< -47.8	< -47.7	-13.0	Pass
6772.8	1	< -46.5	< -47.4	-13.0	Pass
7619.4	1	< -45.9	< -46.2	-13.0	Pass
8466.0	1	< -44.3	< -44.0	-13.0	Pass
others		-	-	-13.0	Pass

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
Receive Antenna	DH02, BA04
Reference Antenna	DH01
Signal Generator	SG05
Power Meter	PM03
RF tester	RC03
RF cable	CL11, CL23, CL24, CL27
Filter	BRF4, HPF2

Final Result

The EUT met the requirements of the standard for this test.

2.1.8 Band Edge Emissions

Reference Standard

Part22.917

Test Conditions

Date: 31 Jul, 2009
Ambient Temperature: 26 degC
Relative humidity: 60 %
Test Voltage: 3.7 V


Test Sample

Configuration II

Test Method

- EUT is connected to RF tester with Max transmitter power level.
- Lower band edge level is measured in bottom channel transmission.
- Higher band edge level is measured in top channel transmission.
- 1% of band width is used for resolution band width for spectrum analyzer.

Test Setup



Test Results


Bottom Band Edge

Measured Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Result
824.0	-20.2	-13.0	Passed


Top Band Edge

Measured Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Result
849.0	-17.4	-13.0	Passed

Graphical Data



Bottom band edge



Top band edge

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
RF tester	RC03
RF cable	CL27
Directional coupler	DC01

Final Result

The EUT met the requirements of the standard for this test.

2.1.9 Transmitter AC Power Line Emission requirement

Reference Standard

Part15.207

Test Conditions

Date: 07 Aug, 2009
Ambient Temperature: 21 degC
Relative humidity: 56 %
Test Voltage: 3.7 V


Test Sample

Configuration I

Test Method

- EUT is connected to RF tester with Max transmitter power level.
 - AC power is supplied to AC charger through LISN.
 - AC charger is connected to EUT.
 - AC Line conducted emission is measured by EMI receiver.
- Both Va/Vb line are measured emission level.

Test Setup




Limit

Frequency (MHz)	Limit QP (dBuV)	Limit AV (dBuV)
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

Test Results

Frequency (MHz)	Line (Va/Vb)	QP Reading [dBuV]	AVE Reading [dBuV]	Factor [dB]	QP Result [dBuV]	AVE Result [dBuV]	QP Limit (dBuV)	AVE Limit (dBuV)	Result
0.191	Va	33.5	25.7	0.3	33.8	26.0	64.0	54.0	Passed
0.839	Va	35.8	24.1	0.3	36.1	24.4	56.0	46.0	Passed
3.248	Va	38.7	22.5	0.5	39.2	23.0	56.0	46.0	Passed
25.174	Va	25.5	18.3	1.6	27.1	19.9	60.0	50.0	Passed
0.194	Vb	36.7	28.9	0.2	36.9	29.1	63.9	53.9	Passed
0.714	Vb	37.9	26.4	0.3	38.2	26.7	56.0	46.0	Passed
3.312	Vb	36.0	20.8	0.5	36.5	21.3	56.0	46.0	Passed
25.308	Vb	28.9	21.2	1.6	30.5	22.8	60.0	50.0	Passed

Graphical Data



Test Equipment Used

Equipment name	RFT ID No.
EMI Receiver	TR04
LISN	LN06
RF tester	RC03
RF cable	CL11

Final Result

The EUT met the requirements of the standard for this test

2.2 Receiver requirement

2.2.1 Receiver Spurious Emissions (Radiated)

Reference Standard

Part15.109

Test Conditions

Date: 10 Aug, 2009 (Above 1GHz), 06 Aug, 2009 (Below 1GHz)
Ambient Temperature: 21 degC (10 Aug), 20 degC (06 Aug)
Relative humidity: 51 % (10 Aug), 57% (06 Aug)
Test Voltage: 3.7 V


Test Sample

Configuration I

Test Method

- EUT is connected to RF tester with idle mode.
- Radiated receiver spurious emission is received by receive antenna.
- Turn table is rotated 360deg.
- Maximum level of each spurious is measured by spectrum analyzer.
- RBW of spectrum analyzer is set to 100kHz for 30 - 1000MHz, 1MHz for above 1GHz.
- Level is measured with QP detect for 30 - 1000MHz, Average detect for above 1GHz.
- EUT was placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

Test Setup



Limit


Frequency (MHz)	Distance (m)	Field strength (uV/m)	Field strength (dBuV/m)
30 - 88	3	100	40.0
88 - 216	3	150	43.5
216 - 960	3	200	46.0
above 960	3	500	53.9

Test Results


Frequency [MHz]	Antenna	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Field strength [dBuV/m]	Limit [dBuV/m]	Result
40.052	Hori.	27.2	13.1	7.5	29.7	18.1	40.0	Passed
68.402	Hori.	31.5	6.3	7.9	29.6	16.1	40.0	Passed
40.038	Vert.	38.1	13.1	7.5	29.7	29.0	40.0	Passed
66.610	Vert.	34.0	6.4	7.9	29.6	18.7	40.0	Passed

There was no other spurious emission greater than noise floor.

Graphical Data



Note : A spectrum @881MHz is downlink signal from RF tester. This is used to set EUT in idle mode.
This is not a spurious emission from EUT.



Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06, TR04
Receive Antenna	DH02, BA04
Pre-AMP	PR12, PR03
RF tester	RC03
RF cable	CL11, CL23, CL24

Final Result

The EUT met the requirements of the standard for this test.

2.2.2 Receiver AC Power Line Emission requirement

Reference Standard

Part15.107

Test Conditions

Date: 07 Aug, 2009
Ambient Temperature: 21 degC
Relative humidity: 56 %
Test Voltage: 3.7 V


Test Sample

Configuration I

Test Method

- EUT is connected to RF tester with idle mode.
 - AC power is supplied to AC charger through LISN.
 - AC charger is connected to EUT.
 - AC Line conducted emission is measured by EMI receiver.
- Both Va/Vb line are measured emission level.

Test Setup




Limit

Frequency (MHz)	Limit QP (dBuV)	Limit AV (dBuV)
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

Test Results

Frequency (MHz)	Line (Va/Vb)	QP Reading [dBuV]	AVE Reading [dBuV]	Factor [dB]	QP Result [dBuV]	AVE Result [dBuV]	QP Limit (dBuV)	AVE Limit (dBuV)	Result
0.192	Va	42.9	32.8	0.3	43.2	33.1	63.9	53.9	Passed
0.834	Va	35.7	22.6	0.3	36.0	22.9	56.0	46.0	Passed
3.261	Va	39.1	23.7	0.5	39.6	24.2	56.0	46.0	Passed
0.194	Vb	39.5	30.9	0.2	39.7	31.1	63.9	53.9	Passed
0.720	Vb	38.2	25.6	0.3	38.5	25.9	56.0	46.0	Passed
3.343	Vb	36.8	21.2	0.5	37.3	21.7	56.0	46.0	Passed

Graphical Data



Test Equipment Used

Equipment name	RFT ID No.
EMI Receiver	TR04
LISN	LN06
RF tester	RC03
RF cable	CL11

Final Result

The EUT met the requirements of the standard for this test

4 List of utilized test equipment/ calibration

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AC01	Anechoic Chamber (1st test room)	JSE	203397C	-	2009/4/9	2010/4/30
BA04	Biological Antenna	SCHAFFNER	CA2855	2903	2009/1/6	2010/1/31
BRF4	Band Reject Filter (WCDMA850)	M-City	BRF0835-01	RF0004	2009/4/8	2010/4/30
CL11	Antenna Cable for RE	RFT	-	-	2009/4/13	2010/4/30
CL23	RF Cable 0.5m	SUCOFLEX	SF104PE	48773/4PE	2009/6/25	2010/6/30
CL24	RF Cable 5.0m	SUCOFLEX	SF104PE	48775/4PE	2009/6/25	2010/6/30
CL26	RF Cable 2.0m	SUCOFLEX	SF104	274754/4	2009/6/25	2010/6/30
CL27	RF Cable 0.5m	SUCOFLEX	SF104	230286/4	2009/6/29	2010/6/30
DC01	Directional Coupler	KRYTAR	1850	77202	2009/5/18	2010/5/31
HPF2	High Pass Filter (1500MHz)	M-City	HPF0900-01	RF0003-01	2009/6/25	2010/6/30
LA02	Logperiodic Antenna	SCHWARZBECK	USLP 9143	339	2009/7/22	2010/7/31
LN06	LISN	Kyoritsu	KNW-407	8-1773-3	2009/5/26	2010/5/31
PM03	Power Meter	Anritsu	ML2438A	99070001	2009/7/21	2010/7/31
PR03	Pre. Amplifier	Anritsu	MH648A	M41984	2009/5/26	2010/5/31
PR12	Pre. Amplifier (1-26G)	Agilent Technologies	8449B	3008A02513	2009/1/13	2010/1/31
PU03	Power Sensor	Anritsu	MA2472A	990103	2009/7/21	2010/7/31
TR04	Test Receiver (F/W : 3.82 SP1)	Rohde & Schwarz	ESCI	100447	2008/9/16	2009/9/30
TR06	Test Receiver (F/W : 3.93 SP2)	Rohde & Schwarz	ESU26	100002	2008/9/2	2009/9/30
DH01	DRG Horn Antenna	A.H. Systems	SAS-571	785	2008/1/31	2010/1/31
DH02	DRG Horn Antenna	A.H. Systems	SAS-200/571	239	2009/4/13	2011/4/30
RC03	Radio communication tester (F/W : 10.20 #005)	Anritsu	MT8820B	6200636657	2009/6/26	2010/6/30
SG05	Signal Generator	Rohde & Schwarz	SMR20	100905	2009/6/18	2010/6/30
TC01	Temperature Chamber	ESPEC	SH-641	92000964	2008/11/17	2009/11/30

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.