

TEST REPORT

For

Mobile Phone

In conformity with

FCC Part22H (01 Oct, 2008)

Model: F-04B

FCC ID: VQK-F04B

Test Item: Mobile Phone

Report No: RY1001P06R2

Issue Date: 06 Jan, 2010

Prepared for

Fujitsu Limited.
4-1-1, Kamikodanaka, Nakahara, Kawasaki 211-8588, Japan

Prepared by

RF Technologies Ltd.
472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45- 534-0645
FAX: +81+(0)45- 534-0646

This report shall not be reproduced, except in full, without the written permission of RF Technologies Ltd. The test results in this report apply only to the sample(s) tested. RF Technologies Ltd. is managed to ISO17025 and has the necessary knowledge and test facilities for testing according to the referenced standards.

Table of Contents

| | | |
|----------|-------------------------------------------------------------|-----------|
| 1 | General information | 3 |
| 1.1 | Product description | 3 |
| 1.2 | Test(s) performed/ Summary of test result | 3 |
| 1.3 | Test facility | 4 |
| 1.4 | Measurement uncertainty | 4 |
| 1.5 | Description of essential requirements and test results..... | 5 |
| 1.5.1 | Transmitter requirements | 5 |
| 1.5.2 | AC Power Line Parameters..... | 5 |
| 1.5.3 | Normal test conditions | 5 |
| 1.5.4 | Extreme test conditions..... | 5 |
| 1.6 | Setup of equipment under test (EUT) | 6 |
| 1.6.1 | Test configuration of EUT | 6 |
| 1.6.2 | Operating condition: | 6 |
| 1.6.3 | Setup diagram of tested system:..... | 7 |
| 1.7 | Equipment modifications | 8 |
| 1.8 | Deviation from the standard..... | 8 |
| 2 | Test procedure and result..... | 9 |
| 2.1 | Carrier Output Power (Conducted)..... | 9 |
| 2.2 | Carrier Output Power (Radiated) | 11 |
| 2.3 | Frequency Stability (Temperature) | 14 |
| 2.4 | Frequency Stability (Voltage)..... | 16 |
| 2.5 | Occupied Bandwidth..... | 18 |
| 2.6 | Transmitter Out of Band Spurious Emissions (Conducted)..... | 23 |
| 2.7 | Transmitter Out of Band Spurious Emissions (Radiated)..... | 29 |
| 2.8 | Band Edge Emissions..... | 35 |
| 2.9 | Transmitter AC Power Line Emission requirement..... | 38 |
| 3 | Test setup photographs..... | 40 |
| 4 | List of utilized test equipment/ calibration | 42 |

History

| Report No. | Issue Date | Revision Contents | Issued by |
|-------------|--------------|-------------------|-----------|
| RY1001P06R2 | 06 Jan, 2010 | Initial Issue | T.Kato |
| | | | |

1 General information

1.1 Product description

Test item : Mobile phone
Manufacturer : Fujitsu Limited
Address : 4-1-1, Kamikodanaka, Nakahara, Kawasaki 211-8588, Japan
Model : F-04B
FCC ID : VQK-F04B
Operating frequency range : TX 826.4-846.6 MHz (WCDMA850, HSDPA 7.2M)
: RX 871.4-891.6 MHz (WCDMA850, HSDPA 7.2M)
Type of Modulation : QPSK
Receipt date of EUT : 27 Nov, 2009
Nominal power voltages : 3.7VDC (Lithium-ion battery)
Power Class : 3 (Maximum power 24dBm nominal)
Antenna Type : Integral antenna
Serial numbers : 3531 6703 0003 651 (for Radiated test)
: 3531 6703 0003 859 (for Conducted test)


1.2 Test(s) performed/ Summary of test result

Applicable Standard(s) : FCC Part22H (01 Oct, 2008)
Test(s) started : 30 Nov, 2009
Test(s) completed : 26 Dec, 2009
Purpose of test(s) : Certification of FCC


Summary of test result : Complied

Note: The above judgment is only based on the measurement data and it does not include the measurement uncertainty. Accordingly, the statement below is applied to the test result.
The EUT complies with the limit required in the standard in case that the margin is not less than the measurement uncertainty in the Laboratory.
Compliance of the EUT is more probable than non-compliance is case that the margin is less than the measurement uncertainty in the Laboratory.

Test engineer

: 
T. Kato (Engineer, EMC testing department)

Reviewer

: 
K. Ohnishi (Manager, EMC testing department)

1.3 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at RF Technologies Ltd., located in 472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per 01 October, 2008.

The description of the test facilities has been filed under registration number 319924 at the Office of the Federal Communications Commission. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

Registered by Voluntary Control Council for Interference by Information Technology Equipment (VCCI).

Each registered facility number is as follows;

Test site (Semi-anechoic chamber 3m) R-2393

Test site (Shielded room) C-2617

Registered by Industry Canada (IC). The registered facility number is as follows;

Test site No.1(Semi-anechoic chamber 3m) : 6974A-1

Accredited by **National Voluntary Laboratory Accreditation Program** (NVLAP) for the emission tests stated in the scope of the certificate under Certificate Number 200780-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200780-0

1.4 Measurement uncertainty

The treatment of uncertainty is based on the general matters on the definition of uncertainty in “Guide to the expression of uncertainty in measurement (GUM)” published by ISO. The Lab’s uncertainty is determined by referring UKAS Publication LAB34: 2002 “The Expression of Uncertainty in EMC Testing” and CISPR16-4-2: 2003 “Uncertainty in EMC Measurements”.

The uncertainty of the measurement result in the level of confidence of approximately 95% (k=2) is as follows;

RF frequency: $\pm 1 \times 10^{-7}$

RF power conducted: ± 1.0 dB

AC Power line emission: ± 1.9 dB

Radiated emission (30MHz - 1000MHz): ± 5.7 dB

Radiated emission (1GHz - 20GHz): ± 5.8 dB

Temperature: ± 1 degree

Humidity: ± 5 %

1.5 Description of essential requirements and test results

An overview of radio requirements, as laid out in FCC Part22 are given below.

1.5.1 Transmitter requirements

| Test Description | Section in this report | Applicable | Result |
|---------------------------------------------|---------------------------|------------|--------|
| Carrier Output Power (Conducted) | 2.1 | Yes | Passed |
| Carrier Output Power (Radiated) | 2.2 | Yes | Passed |
| Frequency Stability (Temperature Variation) | 2.3 | Yes | Passed |
| Frequency Stability (Voltage Variation) | 2.4 | Yes | Passed |
| Occupied Bandwidth | 2.5 | Yes | Passed |
| Out of Band Emissions (Conducted) | 2.6 | Yes | Passed |
| Out of Band Emissions (Radiated) | 2.7 | Yes | Passed |
| Band Edge Emissions | 2.8 | Yes | Passed |

1.5.2 AC Power Line Parameters

| Test Description | Section in this report | Applicable | Result |
|-------------------------------------------------|---------------------------|------------|--------|
| AC power line Spurious Emissions (Traffic mode) | 2.9 | Yes | Passed |

1.5.3 Normal test conditions

Temperature(*) : +15 degC to +35 degC
 Relative humidity(*) : 20 % to 75 %
 Supply voltage : 3.7 VDC (Nominal)
 Measurement Frequency : 826.4 MHz(4132ch), 836.4 MHz(4182ch), 846.6 MHz(4233ch)

* When it is impracticable to carry out tests under these conditions, a note to this effect, stating the ambient temperature and relative humidity during the tests, must be stated separately.

1.5.4 Extreme test conditions

Temperature : -30 °C (min) to +50 °C (max)
 Supply voltage : 3.33 VDC (min) to 4.07 VDC (max)

The equipment has a function that it is automatically turned off when min. battery voltage (3.33 V) is detected.

1.6 Setup of equipment under test (EUT)

1.6.1 Test configuration of EUT

Equipment(s) under test:

| | Item | Manufacturer | Model No. | Serial No. | FCC ID |
|----|---------------------|-----------------|----------------------------------------------------------|--------------------|------------|
| A1 | Mobile phone (Main) | Fujitsu Limited | F-04B | 3531 6703 0003 651 | VQK-F04B |
| A2 | Mobile phone (Sub) | Fujitsu Limited | F-04B-S | 0000 0000 0003 087 | VQK-F04B-S |
| B | Mobile phone (Main) | Fujitsu Limited | F-04B (RF cable is attached instead of integral antenna) | 3531 6703 0003 859 | VQK-F04B |
| C1 | Battery pack (Main) | Fujitsu Limited | F13 | None | N/A |
| C2 | Battery pack (Sub) | Fujitsu Limited | F14 | None | N/A |

Support Equipment(s):

| | Item | Manufacturer | Model No. | Serial No. | FCC ID |
|---|------------|------------------|-------------------|------------|--------|
| D | AC adapter | Fujitsu Limited. | FOMA AC adapter02 | None | N/A |

Connected cable(s):


| No. | Item | Identification (Manu.e.t.c) | Shielded Yes / No | Ferrite Core Yes / No | Connector Type Shielded Yes / No | Length (m) |
|-----|----------------|-----------------------------|----------------------|--------------------------|----------------------------------------|------------|
| 1 | DC power cable | - | No | No | No | 2.32 |

1.6.2 Operating condition:


Traffic mode : EUT is connected with RF tester in Max power level. (Normal and HSDPA mode)
Idle mode : EUT is under idle mode, no output power is transmitted.

1.6.3 Setup diagram of tested system:

[Configuration I]




[Configuration II]



Note : All circuit for mobile phone operation is included in Main unit.

[Configuration III]



1.7 *Equipment modifications*

No modifications have been made to the equipment in order to achieve compliance with the applicable standards described in clause 1.2.

1.8 *Deviation from the standard*

No deviations from the standards described in clause 1.2.

2 Test procedure and result

2.1 Carrier Output Power (Conducted)

Reference Standard

Part22.913, 2.1046

Test Conditions

Date: 15 Dec, 2009
Ambient Temperature: 19 degC
Relative humidity: 31 %
Test Voltage: 3.7 V


Test Sample

Configuration III

Test Method

- a) EUT is connected to RF tester with pseudo random data modulation and set to maximum output power level.
- b) The output power is measured with RF tester (CMU200 etc.).

Test Setup



Test Results

| Channel | Frequency [MHz] | Output Power [dBm] | | Limit [dBm] | Result |
|-----------------|--------------------|--------------------|-------|----------------|--------|
| | | Normal | HSDPA | | |
| Bottom (4132ch) | 826.4 | 23.1 | 22.4 | 38.4 | Pass |
| Middle (4182ch) | 836.4 | 23.0 | 22.3 | 38.4 | Pass |
| Top (4233ch) | 846.6 | 22.7 | 21.9 | 38.4 | Pass |

Test Equipment Used

| Equipment name | RFT ID No. |
|----------------|------------|
| RF tester | RC03 |
| RF cable | CL27 |

Final Result

The EUT met the requirements of the standard for this test.

2.2 Carrier Output Power (Radiated)

Reference Standard

Part22.913, 2.1046

Test Conditions

Date: 21 Dec, 2009
Ambient Temperature: 15 degC
Relative humidity: 26 %
Test Voltage: 3.7 V

Test Sample

Configuration I and II

Test Method

Substitution method is used for this test.

- a) EUT is set on non-conducting table and the output power is set to the maximum level.
- b) As a receive antenna, Horn antenna is used.
- c) Maximum power is measured by a spectrum analyzer (SA) in below conditions.

Turntable is rotated 360 degrees.

The height of receive antenna is changed from 1m to 4m.

Receive antenna polarization is set to vertical and horizontal.

This maximum power is recorded.


During this measurement, receive antenna is adjusted the direction to keep the EUT within the beamwidth of receive antenna.

- d) Reference antenna is replaced with EUT, and connected with signal generator (SG).
SG output power is adjusted to get same level as the recorded maximum radiated EUT power by SA.
- e) Radiated output power (Pout) is calculated with adjusted SG output (Psg) [dBm], reference antenna gain (Gref) [dBd] and cable loss between SG and reference antenna (Lcab) [dB].


$$P_{out} \text{ [dBm e.r.p]} = P_{sg} + G_{ref} + L_{cab}$$

Test Setup

[Measurement]



[Substitution]



Test Results

[Configuration I]

| Channel | Frequency [MHz] | Output Power [dBm] | | Limit [dBm e.r.p] | Result |
|-----------------|-----------------|--------------------|-------|-------------------|--------|
| | | Normal | HSDPA | | |
| Bottom (4132ch) | 826.4 | 18.9 | 19.0 | 38.4 | Pass |
| Middle (4182ch) | 836.4 | 19.5 | 19.6 | 38.4 | Pass |
| Top (4233ch) | 846.6 | 17.6 | 17.4 | 38.4 | Pass |

[Configuration II]

| Channel | Frequency [MHz] | Output Power [dBm] | | Limit [dBm e.r.p] | Result |
|-----------------|-----------------|--------------------|-------|-------------------|--------|
| | | Normal | HSDPA | | |
| Bottom (4132ch) | 826.4 | 17.1 | 16.9 | 38.4 | Pass |
| Middle (4182ch) | 836.4 | 18.1 | 17.6 | 38.4 | Pass |
| Top (4233ch) | 846.6 | 16.8 | 15.2 | 38.4 | Pass |

Test Equipment Used

| Equipment name | RFT ID No. |
|-------------------|------------|
| Spectrum Analyzer | TR06 |
| Receive Antenna | DH02 |
| Reference Antenna | LA02 |
| Signal Generator | SG05 |
| Power Meter | PM03 |
| Power sensor | PU03 |
| RF tester | RC03 |
| RF cable | CL24 |

Final Result

The EUT met the requirements of the standard for this test.

2.3 Frequency Stability (Temperature)

Reference Standard

Part22.355, 2.1055

Test Conditions

Date: 10 Dec, 2009
Ambient Temperature: 16 degC
Relative humidity: 39 %
Test Voltage: 3.7 V

Test Sample


Configuration III

Test Method

To measure the carrier frequency, "Frequency error measurement" function of RF tester is used.

- a) EUT is hold about 30 minutes under measurement temperature condition.
- b) EUT is powered on with nominal voltage.
- c) EUT is connected to RF tester with Max transmit power level.
- d) Frequency error is measured by RF tester for 10 minutes.
- e) Process a) to d) is repeated at 10deg increments from -30 to +50degC.

Test Setup



Test Results**Middle Channel (4182ch, Nominal Freq.:836.4MHz)**

| Temperature [deg C] | Frequency Error [Hz] | Frequency Error [ppm] | Limit [ppm] | Result |
|------------------------|-------------------------|--------------------------|-------------|--------|
| -30 | -14 | -0.02 | ± 2.5 | Passed |
| -20 | -11 | -0.01 | ± 2.5 | Passed |
| -10 | -15 | -0.02 | ± 2.5 | Passed |
| 0 | -13 | -0.02 | ± 2.5 | Passed |
| 10 | -10 | -0.01 | ± 2.5 | Passed |
| 20 | -8 | -0.01 | ± 2.5 | Passed |
| 30 | -11 | -0.01 | ± 2.5 | Passed |
| 40 | -9 | -0.01 | ± 2.5 | Passed |
| 50 | -8 | -0.01 | ± 2.5 | Passed |

Test Equipment Used

| Equipment name | RFT ID No. |
|----------------|------------|
| RF tester | RC03 |
| Temp Chamber | TC01 |

Final Result

The EUT met the requirements of the standard for this test

2.4 Frequency Stability (Voltage)

Reference Standard

Part22.355, 2.1055

Test Conditions

Date: 10 Dec, 2009
Ambient Temperature: 16 degC
Relative humidity: 39 %
Test Voltage: 3.33 V to 4.07 V

Test Sample


Configuration III

Test Method

To measure the carrier frequency, "Frequency error measurement" function of RF tester is used.

- a) EUT is powered on with nominal voltage. Temperature is 20degC.
- b) EUT is connected to RF tester with Max transmitter power level.
- c) Frequency error is measured by RF tester for 10 minutes.
- d) Process a) to c) is repeated at minimum and maximum voltage condition.

Test Setup



Test Results**Middle Channel (4182ch, Nominal Freq.:836.4MHz)**

| Voltage [V] | Frequency Error [Hz] | Frequency Error [ppm] | Limit [ppm] | Result |
|-------------|----------------------|-----------------------|-------------|--------|
| 3.33 | -10 | -0.01 | ± 2.5 | Passed |
| 3.70 | -8 | -0.01 | ± 2.5 | Passed |
| 4.07 | -9 | -0.01 | ± 2.5 | Passed |

Test Equipment Used

| Equipment name | RFT ID No. |
|----------------|------------|
| RF tester | RC03 |
| Temp chamber | TC01 |

Final Result

The EUT met the requirements of the standard for this test

2.5 Occupied Bandwidth

Reference Standard

Part2.1049

Test Conditions

Date: 15 Dec, 2009
Ambient Temperature: 19 degC
Relative humidity: 31 %
Test Voltage: 3.7 V


Test Sample

Configuration III

Test Method

- EUT is connected to RF tester with Max transmitter power level.
- 26dB bandwidth is measured by Spectrum Analyzer.
- 99% occupied bandwidth of transmitter spectrum is measured by Spectrum Analyzer.


Test Setup




Test Results

| Channel | Frequency [MHz] | 26dB Bandwidth [MHz] | 99% Bandwidth [MHz] |
|-----------------|-----------------|----------------------|---------------------|
| Bottom (4132ch) | 826.4 | 4.647 | 4.151 |
| Middle (4182ch) | 836.4 | 4.647 | 4.167 |
| Top (4233ch) | 846.6 | 4.647 | 4.151 |


Graphical Data




4132ch Occupied Bandwidth




4182ch Occupied Bandwidth




4233ch Occupied Bandwidth



4132ch 26dB Bandwidth



4182ch 26dB Bandwidth



4233ch 26dB Bandwidth

Test Equipment Used

| Equipment name | RFT ID No. |
|---------------------|------------|
| Spectrum Analyzer | TR06 |
| RF tester | RC03 |
| RF cable | CL27 |
| Directional coupler | DC01 |

2.6 Transmitter Out of Band Spurious Emissions (Conducted)

Reference Standard

Part22.917

Test Conditions

Date: 15 Dec, 2009
Ambient Temperature: 19 degC
Relative humidity: 31 %
Test Voltage: 3.7 V

Test Sample


Configuration III

Test Method


- a) EUT is connected to RF tester with Max transmitter power level.
- b) Out of band Spurious is measured by Spectrum Analyzer.
- c) Resolution band width of spectrum analyzer is set to 1MHz (above 1GHz) or 100kHz (below 1GHz).

Test Setup

30MHz to 1500MHz



above 1500MHz



Test Results

Bottom Channel (4132ch, Nominal Freq.:826.4MHz)

| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | Limit [dBm] | Result Pass/Fail |
|-----------------------------|-----------------------------|----------------------|-------------|------------------|
| 1652.8 | 1 | -51.0 | -13.0 | Pass |
| 2479.2 | 1 | < -60.0 | -13.0 | Pass |
| 3305.6 | 1 | -59.9 | -13.0 | Pass |
| 4132.0 | 1 | -52.4 | -13.0 | Pass |
| 4958.4 | 1 | < -60.0 | -13.0 | Pass |
| 5784.8 | 1 | < -60.0 | -13.0 | Pass |
| 6611.2 | 1 | < -60.0 | -13.0 | Pass |
| 7437.6 | 1 | < -60.0 | -13.0 | Pass |
| 8264.0 | 1 | < -60.0 | -13.0 | Pass |
| others | | - | -13.0 | Pass |


Middle Channel (4182ch, Nominal Freq.:836.4MHz)



| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | Limit [dBm] | Result Pass/Fail |
|-----------------------------|-----------------------------|----------------------|-------------|------------------|
| 1672.8 | 1 | -53.1 | -13.0 | Pass |
| 2509.2 | 1 | -59.3 | -13.0 | Pass |
| 3345.6 | 1 | < -60.0 | -13.0 | Pass |
| 4182.0 | 1 | -51.6 | -13.0 | Pass |
| 5018.4 | 1 | -59.8 | -13.0 | Pass |
| 5854.8 | 1 | < -60.0 | -13.0 | Pass |
| 6691.2 | 1 | < -60.0 | -13.0 | Pass |
| 7527.6 | 1 | < -60.0 | -13.0 | Pass |
| 8364.0 | 1 | < -60.0 | -13.0 | Pass |
| others | | - | -13.0 | Pass |



Top Channel (4233ch, Nominal Freq.:846.6MHz)


| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | Limit [dBm] | Result Pass/Fail |
|-----------------------------|-----------------------------|----------------------|-------------|------------------|
| 1693.2 | 1 | -53.9 | -13.0 | Pass |
| 2539.8 | 1 | -58.9 | -13.0 | Pass |
| 3386.4 | 1 | < -60.0 | -13.0 | Pass |
| 4233.0 | 1 | -51.0 | -13.0 | Pass |
| 5079.6 | 1 | -59.0 | -13.0 | Pass |
| 5926.2 | 1 | < -60.0 | -13.0 | Pass |
| 6772.8 | 1 | < -60.0 | -13.0 | Pass |
| 7619.4 | 1 | < -60.0 | -13.0 | Pass |
| 8466.0 | 1 | < -60.0 | -13.0 | Pass |
| others | | - | -13.0 | Pass |

Graphical Data (4182ch, Pre-scan)









Test Equipment Used

| Equipment name | RFT ID No. |
|---------------------|------------|
| Spectrum Analyzer | TR06 |
| RF tester | RC03 |
| RF cable | CL27 |
| Directional coupler | DC01 |
| High pass filter | HPF2 |

Final Result

The EUT met the requirements of the standard for this test.

2.7 Transmitter Out of Band Spurious Emissions (Radiated)

Reference Standard

Part22.917

Test Conditions

Date: 22 Dec, 2009 (Above 1GHz), 24 and 26 Dec, 2009 (Below 1GHz)
Ambient Temperature: 16degC (22 Dec), 18degC (24 Dec), 18degC (26 Dec)
Relative humidity: 26% (22 Dec), 30% (24 Dec), 34% (26 Dec)
Test Voltage: 3.7 V

Test Sample

Configuration I and II

Test Method

Substitution method is used for this test.

- a) EUT is set on non-conducting table and the output power is set to the maximum level.
- b) As a receive antenna, Horn antenna is used for high frequency range (above 1GHz), and Bilogical antenna is used for low frequency range (30MHz to 1GHz).
- c) The maximum level of each spurious emission is measured by a spectrum analyzer (SA) in below conditions.

Turntable is rotated 360 degrees.

The height of receive antenna is changed from 1m to 4m.

Receive antenna polarization is set to vertical and horizontal.

EUT was placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

This emission level is recorded.

During this measurement, receive antenna is adjusted the direction to keep the EUT within the beamwidth of receive antenna.


- d) Reference antenna is replaced with EUT, and connected with signal generator (SG).
SG output power is adjusted to get same level as the recorded maximum radiated EUT power by SA.

- e) Radiated output power (Pout) is calculated with adjusted SG output (Psg) [dBm], reference antenna gain (Gref) [dBd] and cable loss between SG and reference antenna (Lcab) [dB].


$$P_{out} [dBm \text{ e.r.p}] = P_{sg} + G_{ref} + L_{cab}$$

Test Setup

[Measurement]



[Substitution]



Test Results

[Configuration I]

Bottom Channel (4132ch, Nominal Freq.:826.4MHz)

| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | | Limit [dBm] | Result Pass/Fail |
|-----------------------------|-----------------------------|----------------------|------------|-------------|------------------|
| | | Vertical | Horizontal | | |
| 1652.8 | 1 | -46.6 | -42.4 | -13.0 | Pass |
| 2479.2 | 1 | -47.9 | -47.2 | -13.0 | Pass |
| 3305.6 | 1 | -48.3 | -48.2 | -13.0 | Pass |
| 4132.0 | 1 | -50.2 | -47.6 | -13.0 | Pass |
| 4958.4 | 1 | < -51.2 | < -51.2 | -13.0 | Pass |
| 5784.8 | 1 | < -49.5 | < -49.5 | -13.0 | Pass |
| 6611.2 | 1 | < -46.7 | < -46.7 | -13.0 | Pass |
| 7437.6 | 1 | < -47.4 | < -47.4 | -13.0 | Pass |
| 8264.0 | 1 | < -44.8 | < -44.8 | -13.0 | Pass |
| others | | - | - | -13.0 | Pass |

Middle Channel (4182ch, Nominal Freq.:836.4MHz)

| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | | Limit [dBm] | Result Pass/Fail |
|-----------------------------|-----------------------------|----------------------|------------|-------------|------------------|
| | | Vertical | Horizontal | | |
| 1672.8 | 1 | -45.1 | -42.5 | -13.0 | Pass |
| 2509.2 | 1 | -50.7 | -47.7 | -13.0 | Pass |
| 3345.6 | 1 | -48.0 | -47.1 | -13.0 | Pass |
| 4182.0 | 1 | -49.6 | -47.0 | -13.0 | Pass |
| 5018.4 | 1 | < -50.0 | < -50.0 | -13.0 | Pass |
| 5854.8 | 1 | < -48.8 | < -48.8 | -13.0 | Pass |
| 6691.2 | 1 | < -47.0 | < -47.0 | -13.0 | Pass |
| 7527.6 | 1 | < -46.9 | < -46.9 | -13.0 | Pass |
| 8364.0 | 1 | < -44.7 | < -44.7 | -13.0 | Pass |
| others | | - | - | -13.0 | Pass |

Top Channel (4233ch, Nominal Freq.:846.6MHz)

| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | | Limit [dBm] | Result Pass/Fail |
|-----------------------------------|-----------------------------------|-------------------------|------------|----------------|---------------------|
| | | Vertical | Horizontal | | |
| 1693.2 | 1 | -44.6 | -43.9 | -13.0 | Pass |
| 2539.8 | 1 | -49.9 | -49.2 | -13.0 | Pass |
| 3386.4 | 1 | -47.8 | -46.3 | -13.0 | Pass |
| 4233.0 | 1 | -50.4 | -47.2 | -13.0 | Pass |
| 5079.6 | 1 | < -49.9 | < -49.9 | -13.0 | Pass |
| 5926.2 | 1 | < -47.6 | < -47.6 | -13.0 | Pass |
| 6772.8 | 1 | < -47.0 | < -47.0 | -13.0 | Pass |
| 7619.4 | 1 | < -45.9 | < -45.9 | -13.0 | Pass |
| 8466.0 | 1 | < -43.2 | < -43.2 | -13.0 | Pass |
| others | | - | - | -13.0 | Pass |

[Configuration II]

Bottom Channel (4132ch, Nominal Freq.:826.4MHz)

| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | | Limit [dBm] | Result Pass/Fail |
|-----------------------------|-----------------------------|----------------------|------------|-------------|------------------|
| | | Vertical | Horizontal | | |
| 1652.8 | 1 | -46.2 | -43.0 | -13.0 | Pass |
| 2479.2 | 1 | -50.9 | -49.3 | -13.0 | Pass |
| 3305.6 | 1 | -48.4 | -48.6 | -13.0 | Pass |
| 4132.0 | 1 | -50.1 | -47.8 | -13.0 | Pass |
| 4958.4 | 1 | < -51.2 | < -51.2 | -13.0 | Pass |
| 5784.8 | 1 | < -49.5 | < -49.5 | -13.0 | Pass |
| 6611.2 | 1 | < -46.7 | < -46.7 | -13.0 | Pass |
| 7437.6 | 1 | < -47.4 | < -47.4 | -13.0 | Pass |
| 8264.0 | 1 | < -44.8 | < -44.8 | -13.0 | Pass |
| others | | - | - | -13.0 | Pass |

Middle Channel (4182ch, Nominal Freq.:836.4MHz)

| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | | Limit [dBm] | Result Pass/Fail |
|-----------------------------|-----------------------------|----------------------|------------|-------------|------------------|
| | | Vertical | Horizontal | | |
| 1672.8 | 1 | -46.6 | -43.0 | -13.0 | Pass |
| 2509.2 | 1 | -45.8 | -47.4 | -13.0 | Pass |
| 3345.6 | 1 | -48.6 | -47.8 | -13.0 | Pass |
| 4182.0 | 1 | -49.5 | -47.3 | -13.0 | Pass |
| 5018.4 | 1 | < -50.0 | < -50.0 | -13.0 | Pass |
| 5854.8 | 1 | < -48.8 | < -48.8 | -13.0 | Pass |
| 6691.2 | 1 | < -47.0 | < -47.0 | -13.0 | Pass |
| 7527.6 | 1 | < -46.9 | < -46.9 | -13.0 | Pass |
| 8364.0 | 1 | < -44.7 | < -44.7 | -13.0 | Pass |
| others | | - | - | -13.0 | Pass |

Top Channel (4233ch, Nominal Freq.:846.6MHz)

| Measurement Frequency [MHz] | Measurement Bandwidth [MHz] | Emission Level [dBm] | | Limit [dBm] | Result Pass/Fail |
|-----------------------------------|-----------------------------------|-------------------------|------------|----------------|---------------------|
| | | Vertical | Horizontal | | |
| 1693.2 | 1 | -46.2 | -45.0 | -13.0 | Pass |
| 2539.8 | 1 | -46.4 | -45.4 | -13.0 | Pass |
| 3386.4 | 1 | -48.6 | -47.5 | -13.0 | Pass |
| 4233.0 | 1 | -49.9 | -47.3 | -13.0 | Pass |
| 5079.6 | 1 | < -49.9 | < -49.9 | -13.0 | Pass |
| 5926.2 | 1 | < -47.6 | < -47.6 | -13.0 | Pass |
| 6772.8 | 1 | < -47.0 | < -47.0 | -13.0 | Pass |
| 7619.4 | 1 | < -45.9 | < -45.9 | -13.0 | Pass |
| 8466.0 | 1 | < -43.2 | < -43.2 | -13.0 | Pass |
| others | | - | - | -13.0 | Pass |

Test Equipment Used

| | |
|-------------------|------------------------|
| Equipment name | RFT ID No. |
| Spectrum Analyzer | TR06 |
| Receive Antenna | DH02, BA04 |
| Reference Antenna | DH01 |
| Signal Generator | SG05 |
| Power Meter | PM03 |
| Power Sensor | PU03 |
| RF tester | RC03 |
| RF cable | CL11, CL23, CL24, CL27 |
| Filter | BRF4, HPF2 |

Final Result

The EUT met the requirements of the standard for this test.

2.8 Band Edge Emissions

Reference Standard

Part22.917

Test Conditions

Date: 15 Dec, 2009
Ambient Temperature: 19 degC
Relative humidity: 31 %
Test Voltage: 3.7 V


Test Sample

Configuration III

Test Method

- EUT is connected to RF tester with Max transmitter power level.
- Lower band edge level is measured in bottom channel transmission.
- Higher band edge level is measured in top channel transmission.
- 1% of band width is used for resolution band width for spectrum analyzer.

Test Setup



Test Results


Bottom Band Edge

| Measured Frequency [MHz] | Peak Level [dBm] | Limit [dBm] | Result |
|-----------------------------|---------------------|----------------|--------|
| 823.904 | -20.9 | -13.0 | Passed |


Top Band Edge

| Measured Frequency [MHz] | Peak Level [dBm] | Limit [dBm] | Result |
|-----------------------------|---------------------|----------------|--------|
| 849.0 | -20.7 | -13.0 | Passed |

Graphical Data



Bottom band edge



Top band edge

Test Equipment Used

| Equipment name | RFT ID No. |
|---------------------|------------|
| Spectrum Analyzer | TR06 |
| RF tester | RC03 |
| RF cable | CL27 |
| Directional coupler | DC01 |

Final Result

The EUT met the requirements of the standard for this test.

2.9 Transmitter AC Power Line Emission requirement

Reference Standard

Part15.207

Test Conditions

Date: 26 Dec, 2009
Ambient Temperature: 16 degC
Relative humidity: 44 %
Test Voltage: 3.7 V


Test Sample

Configuration I and II

Test Method

- EUT is connected to RF tester with Max transmitter power level.
 - AC power is supplied to AC charger through LISN.
 - AC charger is connected to EUT.
 - AC Line conducted emission is measured by EMI receiver.
- Both Va/Vb line are measured emission level.

Test Setup



Limit


| Frequency [MHz] | Limit QP [dBμV] | Limit AVE [dBμV] |
|-----------------|-----------------|------------------|
| 0.15 - 0.5 | 66 - 56 | 56 - 46 |
| 0.5 - 5 | 56 | 46 |
| 5 - 30 | 60 | 50 |

Test Results

[Configuration I (worst data)]

| Frequency [MHz] | Line (Va/Vb) | QP Reading [dBμV] | AVE Reading [dBμV] | Factor [dB] | QP Result [dBμV] | AVE Result [dBμV] | QP Limit [dBμV] | AVE Limit [dBμV] | Result |
|-----------------|--------------|-------------------|--------------------|-------------|------------------|-------------------|-----------------|------------------|--------|
| 0.193 | Va | 36.8 | 35.9 | 0.1 | 36.9 | 36.0 | 63.9 | 53.9 | Passed |
| 1.012 | Va | 34.8 | 27.2 | 0.0 | 34.8 | 27.2 | 56.0 | 46.0 | Passed |
| 3.120 | Va | 39.0 | 26.9 | 0.0 | 39.0 | 26.9 | 56.0 | 46.0 | Passed |
| 0.185 | Vb | 39.3 | 37.4 | 0.2 | 39.5 | 37.6 | 64.3 | 54.3 | Passed |
| 0.639 | Vb | 32.3 | 26.3 | 0.0 | 32.3 | 26.3 | 56.0 | 46.0 | Passed |
| 3.054 | Vb | 34.1 | 17.2 | 0.0 | 34.1 | 17.2 | 56.0 | 46.0 | Passed |

Graphical Data



Test Equipment Used

| Equipment name | RFT ID No. |
|----------------|------------|
| EMI Receiver | TR04 |
| LISN | LN06 |
| RF tester | RC03 |
| RF cable | CL18 |

Final Result

The EUT met the requirements of the standard for this test

4 List of utilized test equipment/ calibration

| RFT ID No. | Kind of Equipment and Precision | Manufacturer | Model No. | Serial Number | Calibration Date | Calibrated until |
|------------|-----------------------------------------------|----------------------|-------------|---------------|------------------|------------------|
| AC01(EM) | Anechoic Chamber (1st test room) | JSE | 203397C | - | 2009/4/9 | 2010/4/30 |
| AC01(EG) | Anechoic Chamber (1st test room) | JSE | 203397C | - | 2009/11/14 | 2010/11/30 |
| BA04 | Biological Antenna | SCHAFFNER | CA2855 | 2903 | 2009/1/6 | 2010/1/31 |
| BRF4 | Band Reject Filter (WCDMA850) | M-City | BRF0835-01 | RF0004 | 2009/4/8 | 2010/4/30 |
| CL11 | Antenna Cable for RE | RFT | - | - | 2009/4/13 | 2010/4/30 |
| CL18 | Antenna Cable for CE | RFT | - | - | 2009/5/21 | 2010/5/31 |
| CL23 | RF Cable 0.5m | SUCOFLEX | SF104PE | 48773/4PE | 2009/6/25 | 2010/6/30 |
| CL24 | RF Cable 5.0m | SUCOFLEX | SF104PE | 48775/4PE | 2009/6/25 | 2010/6/30 |
| CL27 | RF Cable 0.5m | SUCOFLEX | SF104 | 230286/4 | 2009/6/29 | 2010/6/30 |
| DC01 | Directional Coupler | KRYTAR | 1850 | 77202 | 2009/5/18 | 2010/5/31 |
| HPF2 | High Pass Filter (1500MHz) | M-City | HPF0900-01 | RF0003-01 | 2009/6/25 | 2010/6/30 |
| LA02 | Logperiodic Antenna | SCHWARZBECK | USLP 9143 | 339 | 2009/7/22 | 2010/7/31 |
| LN06 | LISN | Kyoritsu | KNW-407 | 8-1773-3 | 2009/5/26 | 2010/5/31 |
| PM03 | Power Meter | Anritsu | ML2438A | 99070001 | 2009/7/21 | 2010/7/31 |
| PR03 | Pre. Amplifier | Anritsu | MH648A | M41984 | 2009/5/26 | 2010/5/31 |
| PR12 | Pre. Amplifier (1-26G) | Agilent Technologies | 8449B | 3008A02513 | 2009/1/13 | 2010/1/31 |
| PU03 | Power Sensor | Anritsu | MA2472A | 990103 | 2009/7/21 | 2010/7/31 |
| TR04 | Test Receiver (F/W : 4.32) | Rohde & Schwarz | ESCI | 100447 | 2009/9/7 | 2010/9/30 |
| TR06 | Test Receiver (F/W : 3.93 SP2) | Rohde & Schwarz | ESU26 | 100002 | 2009/9/16 | 2010/9/30 |
| DH01 | DRG Horn Antenna | A.H. Systems | SAS-571 | 785 | 2008/1/31 | 2010/1/31 |
| DH02 | DRG Horn Antenna | A.H. Systems | SAS-200/571 | 239 | 2009/4/13 | 2011/4/30 |
| RC03 | Radio communication tester (F/W : 10.20 #005) | Anritsu | MT8820B | 6200636657 | 2009/6/26 | 2010/6/30 |
| SG05 | Signal Generator | Rohde & Schwarz | SMR20 | 100905 | 2009/6/18 | 2010/6/30 |
| TC01 | Temperature Chamber | ESPEC | SH-641 | 92000964 | 2009/11/13 | 2010/11/30 |

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.