



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

FCC Test Report

FCC ID : VQK-F07E
Equipment : Mobile Phone
Model No. : F-07E
Brand Name : Xi
Applicant : FUJITSU LIMITED
Address : 1-1, Kamikodanaka 4-chome, Nakahara-ku,
Kawasaki 211-8588, Japan
Standard : 47 CFR FCC Part 24 Subpart E
Received Date : Apr. 09, 2013
Tested Date : Apr. 18, 2013

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:


Gary Chang / Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List.....	6
1.3	Test Setup Chart.....	6
1.4	The Equipment List.....	7
1.5	Test Standards.....	8
1.6	Measurement Uncertainty	8
2	TEST CONFIGURATION	9
2.1	Testing Condition and Location Information.....	9
2.2	The Worst Test Modes and Channel Details.....	9
3	TEST RESULTS	10
3.1	Equivalent Isotropically Radiated Power.....	10
3.2	Radiated Emissions.....	13
3.3	Conducted Emissions	16
3.4	Band Edge.....	18
3.5	Occupied Bandwidth.....	20
3.6	Peak to Average Ratio.....	22
3.7	Frequency Stability.....	24



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Release Record

Report No.	Version	Description	Issued Date
FG331905-2	Rev. 01	Initial issue	May 30, 2013



Summary of Test Results

FCC Rules	Test Items	Measured	Result
2.1046 / 24.232(c)	Equivalent Isotropically Radiated Power	Power[dBm] : 29.17	Pass
2.1053 / 24.238(a)	Radiated Emissions	Meet the requirement of limit	Pass
2.1051 / 24.238(a)	Conducted Emissions	Meet the requirement of limit	Pass
2.1051 / 24.238(a)	Band Edge	Meet the requirement of limit	Pass
2.1049 / 24.238(a)	Occupied Bandwidth	Meet the requirement of limit	Pass
24.232(d)	Peak to average ratio	Meet the requirement of limit	Pass
2.1055 / 24.235	Frequency Stability	Meet the requirement of limit	Pass



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating band(MHz)	GSM : 1850.2-1909.8
Modulation	GSM / GPRS: GMSK
Multislot class	33
IMEI Code	355277050017131 & 355277050017453
H/W Version	V2.1.0
S/W Version	R13.1e

1.1.2 Maximum ERP, Frequency Tolerance and Emission Designator

System	Modulation	Maximum ERP(W)	Frequency Tolerance (ppm)	Emission Designator
GSM 1900	GMSK	0.8260	0.010	246KGXW

1.1.3 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	$\lambda/4$ Monopole	-2.4	---	---

1.1.4 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> External DC adapter	<input checked="" type="checkbox"/> Battery
Operational Voltage	<input checked="" type="checkbox"/> Vnom (3.9 V)	<input checked="" type="checkbox"/> Vmax (4.29 V)	<input checked="" type="checkbox"/> Vmin (3.51 V)
Operational Climatic	<input checked="" type="checkbox"/> Tnom (20°C)	<input checked="" type="checkbox"/> Tmax (55°C)	<input checked="" type="checkbox"/> Tmin (-30°C)

1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	Cradle	Brand Name: Fujitsu limited Model Name: CA50601-1801 Power Rating: O/P: 5Vdc, 1.5A
2	Battery	Brand Name: Fujitsu limited Model Name: CA54310-0045 Power Rating: O/P: 3.8Vdc, 2600mA



1.1.6 Operating Channel List


GSM & GPRS		
	Channel	Frequency (MHz)
Low	512	1850.2
Middle	661	1880.0
High	810	1909.8

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Adapter	NTT docomo	AC Adaptor 04	---	---	---
2	Earphone	APPLE	MD827FE/A	---	---	1.2m non-shielded w/o core

Note: Item 1 was provided by client.

1.3 Test Setup Chart





1.4 The Equipment List

EMI	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
3m semi-anechoic chamber	RIKEN	SAC-03	03CH01-WS	Jan. 04, 2013	Jan. 03, 2014
Amplifier	Burgeon	BPA-530	100219	Nov. 28, 2012	Nov. 27, 2013
Amplifier	Agilent	83017A	MY39501308	Dec. 18, 2012	Dec. 17, 2013
Bilog Antenna	Schwarzbeck	VULB9168	VULB9168-522	Jan. 11, 2013	Jan. 10, 2014
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 18, 2013	Feb. 17, 2014
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Jan. 14, 2013	Jan. 13, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-001	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-002	Dec. 25, 2012	Dec. 24, 2013
Spectrum Analyzer	R&S	FSV40	101498	Jan. 24, 2013	Jan. 23, 2014
Receiver	ROHDE&SCHWARZ	ESR3	101658	Jan. 30, 2013	Jan. 29, 2014
control	EM Electronics	EM1000	60612	N/A	N/A
Note: Calibration Interval of instruments listed above is one year.					

RF	RF Conducted				
Test Site	RF Conducted (TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV 40	101486	Nov. 14, 2012	Nov. 13, 2013
Spectrum Analyzer	R&S	FSP 40	100593	Aug. 14, 2012	Aug. 13, 2013
DC Power Source	G.W.	GPC-6030D	C671845	Jun. 19, 2012	Jun. 18, 2013
AC Power Source	G.W.	APS-9102	EL920581	Jul. 02, 2012	Jul. 01, 2013
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	Nov. 21, 2012	Nov. 20, 2013
Signal Generator	R&S	SMR40	100116	Jun. 26, 2012	Jun. 25, 2013
Power Sensor	Anritsu	MA2411B	1027452	Sep. 08, 2012	Sep. 07, 2013
Power Meter	Anritsu	ML2495A	1124009	Sep. 08, 2012	Sep. 07, 2013
RF Cable-2m	HUBER+SUHNER	SUCOFLEX_104	SN 345675/4	NA	NA
RF Cable-3m	HUBER+SUHNER	SUCOFLEX_104	SN 345669/4	NA	NA



1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards.

47 CFR FCC Part 24 Subpart E

ANSI C63.43-2003

ANSI / TIA / EIA-603-C -2004

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 40.246 Hz
Conducted power	± 0.552 dB
Frequency error	± 40.246 Hz
Temperature	± 0.3 °C
Conducted emission	± 2.946 dB
AC conducted emission	± 2.43 dB
Radiated emission	± 2.49 dB



2 Test Configuration

2.1 Testing Condition and Location Information

Test Item	Test Site	Ambient Condition	Tested By
RF conducted	TH01-WS	22°C / 63%	Brad Wu
Radiated Emissions	03CH01-WS	25°C / 65%	Aska Huang

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test channel
E.I.R.P	GSM	512, 661, 810
Radiated Emissions	GSM	512, 661, 810
Conducted Emissions	GSM	512, 661, 810
Band Edge	GSM	512, 810
Occupied Bandwidth	GSM	512, 661, 810
Frequency Stability	GSM	661

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
2. Adapter and cradle had been pretested and found adapter was the worst case and was selected for final test



3 Test Results

3.1 Equivalent Isotropically Radiated Power

3.1.1 Limit of Equivalent Isotropically Radiated Power

Mobile and portable stations are limited to 2 watts EIRP.

3.1.2 Test Procedures

1. The EUT links up with simulator and is set to maximum output power level at low / middle / high channel. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.
4. After finding the max radiated emission, substitution method will be used for getting effective radiated power. EUT will be removed and substitution antenna will be placed at same position. Signal generator will output CW signal to substitution antenna through a RF cable. Rotate turntable and move antenna to find maximum radiated emission. Adjust output power of signal generator to let the maximum radiated emission is same as step 3. Record the output power level.
5. E.I.R.P = output power of step 4 + gain of substitution antenna – cable loss of RF cable.


For Conducted power measurement

1. The EUT links up with simulator and is set to maximum output power level at low / middle / high channel.
2. Measure the output power of low / middle / high channel of the EUT




3.1.3 Test Setup

Equivalent Isotropically Radiated Power Measurement



Conducted Power Measurement





3.1.4 Test Result of Conducted power (dBm)

Mode	GSM					
Channel	Frequency (MHz)	GSM	GPRS 1 Slot	GPRS 2 Slots	GPRS 3 Slots	GPRS 4 Slots
512	1850.2	29.29	29.23	27.16	25.73	24.80
661	1880	29.51	29.48	27.34	25.78	24.82
810	1909.8	29.71	29.69	27.41	25.81	24.85

3.1.5 Test Result of Equivalent Isotropically Radiated Power (dBm)

Mode	GSM						
Channel	Frequency (MHz)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
512	1850.2	-10.99	24.55	4.62	29.17	33	-3.83
661	1880	-12.02	24.02	4.56	28.58	33	-4.42
810	1909.8	-12.65	23.89	4.50	28.39	33	-4.61

Note: EIRP = S.G Power value + Correction factor



3.2 Radiated Emissions


3.2.1 Limit of Radiated Emissions

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360° . A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360° , the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.
4. After finding the max radiated emission, substitution method will be used for getting effective radiated power. EUT will be removed and substitution antenna will be placed at same position. Signal generator will output CW signal to substitution antenna through a RF cable. Rotate turntable and move antenna to find maximum radiated emission. Adjust output power of signal generator to let the maximum radiated emission is same as step 3. Record the output power level.
5. E.I.R.P = output power of step 4 + gain of substitution antenna – cable loss of RF cable.

3.2.3 Test Setup





3.2.4 Test Result of Radiated Emissions below 1GHz

Mode	GSM, Channel : 512						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
113.42	H	-76.17	-13	-63.17	-63.8	-76.39	0.22
182.29	H	-74.90	-13	-61.90	-65.54	-78.85	3.95
265.71	H	-71.02	-13	-58.02	-62.39	-76.61	5.59
430.61	H	-79.28	-13	-66.28	-73.48	-84.49	5.21
683.78	H	-71.67	-13	-58.67	-70.10	-75.95	4.28
965.08	H	-72.52	-13	-59.52	-74.94	-75.99	3.47
30.00	V	-74.79	-13	-61.79	-62.09	-62.44	-12.35
130.88	V	-72.78	-13	-59.78	-67.99	-72.83	0.05
159.01	V	-76.14	-13	-63.14	-74.08	-76.84	0.70
496.57	V	-76.47	-13	-63.47	-74.32	-81.64	5.17
552.83	V	-77.76	-13	-64.76	-75.74	-82.67	4.91
958.29	V	-72.04	-13	-59.04	-75.08	-75.46	3.42

Note: EIRP = S.G Power value + Correction factor



3.2.5 Test Result of Radiated Emissions above 1GHz

Mode	GSM , Channel : 512						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
3700.4	H	-35.20	-13	-22.20	-47.26	-40.52	5.32
5550.6	H	-26.71	-13	-13.71	-44.65	-31.23	4.52
7400.8	H	-36.17	-13	-23.17	-58.17	-38.97	2.80
3700.4	V	-35.80	-13	-22.80	-47.94	-41.12	5.32
5550.6	V	-30.04	-13	-17.04	-46.74	-34.56	4.52
7400.8	V	-40.81	-13	-27.81	-60.59	-43.61	2.80

Mode	GSM , Channel : 661						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
3760	H	-35.02	-13	-22.02	-47.48	-40.27	5.25
5640	H	-26.45	-13	-13.45	-44.36	-30.80	4.35
7520	H	-37.17	-13	-24.17	-58.54	-39.71	2.54
3760	V	-36.05	-13	-23.05	-48.39	-41.30	5.25
5640	V	-29.93	-13	-16.93	-46.86	-34.28	4.35
7520	V	-42.44	-13	-29.44	-61.8	-44.98	2.54

Mode	GSM , Channel : 810						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
3819.6	H	-34.82	-13	-21.82	-47.58	-40.00	5.18
5729.4	H	-26.42	-13	-13.42	-44.57	-30.58	4.16
7639.2	H	-37.74	-13	-24.74	-58.65	-40.16	2.42
3819.6	V	-36.01	-13	-23.01	-48.55	-41.19	5.18
5729.4	V	-29.56	-13	-16.56	-46.77	-33.72	4.16
7639.2	V	-42.51	-13	-29.51	-61.56	-44.93	2.42

Note: EIRP = S.G Power value + Correction factor



3.3 Conducted Emissions


3.3.1 Limit of Conducted Emissions

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.3.2 Test Procedures


1. Lowest, middle and highest operating channels are tested for this item.
2. Scan frequency range is from 30MHz~19.1GHz.
3. Set RBW = 1MHz, VBW = 3MHz, detector = Peak, sweep time = auto.
4. Record the max trace value and capture the test plot of each sub frequency band.

3.3.3 Test Setup





3.3.4 Test Result of Conducted Emissions





3.4 Band Edge


3.4.1 Limit of Band Edge

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.4.2 Test Procedures


1. Lowest and highest operating channels are tested for this item.
2. The center frequency of spectrum analyzer will be set to 1850 and 1910 MHz.
3. Set RBW = VBW = 3 kHz, span = 1 MHz, detector = RMS, sweep time = auto.
4. Record the max trace value and capture the test plot.

3.4.3 Test Setup





3.4.4 Test Result of Band Edge






3.5 Occupied Bandwidth

3.5.1 Test Procedures

1. Set resolution bandwidth (RBW) = 10 kHz, Video bandwidth = 30kHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Using occupied bandwidth measurement function of spectrum analyzer to measure occupied bandwidth.


3.5.2 Test Setup





3.5.3 Test Result of Occupied Bandwidth

MODE	Channel	Frequency (MHz)	OBW (kHz)	26dB bandwidth(kHz)
GSM	512	1850.2	244.57	318.4
GSM	661	1880	246.02	315.5
GSM	810	1909.8	246.02	319.8





3.6 Peak to Average Ratio


3.6.1 Limit of Peak to Average Ratio

Peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

3.6.2 Test Procedures

1. Set RBW=1MHz, RBW=3MHz, Peak detector in Trace 1
2. Set RBW=1MHz, RBW=3MHz, RMs detector in Trace 2
3. Trigger function is enabled for measuring signal at burst on time. Measure the difference between trace1 and trace 2.


3.6.3 Test Setup





3.6.4 Test Result of Peak to Average ratio

MODE	Channel	Frequency (MHz)	Peak to Average ratio (dB)
GSM	512	1850.2	0.02
GSM	661	1880	0.12
GSM	810	1909.8	0.02





3.7 Frequency Stability


3.7.1 Limit of Frequency Stability

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures

1. EUT was placed at temperature chamber and connected to an external power supply.
2. Temperature and voltage condition shall be tested to confirm frequency stability.
3. Temperature range is from $-30\sim 50^{\circ}\text{C}$ and voltage range is from lowest to highest working voltage.
4. Tem Linkup EUT and simulator. Confirm frequency drift value of simulator and record it.

3.7.3 Test Setup





3.7.4 Test Result of Frequency Stability

Temperature (°C)	Voltage (dc)	Frequency Drift (ppm)	Limit (ppm)
50	3.9	0.005	2.5
40	3.9	0.005	2.5
30	3.9	0.006	2.5
20	3.9	0.006	2.5
10	3.9	0.007	2.5
0	3.9	0.007	2.5
-10	3.9	0.009	2.5
-20	3.9	0.009	2.5
-30	3.9	0.010	2.5
20	4.29	0.006	2.5
20	3.51	0.008	2.5

==END==