

FCC Test Report

Report No.: RF170808C08-3

FCC ID: VQK-F01K

Test Model: F-01K

Received Date: Aug. 08, 2017

Test Date: Sep. 15, 2017 ~ Sep. 30, 2017

Issued Date: Oct. 06, 2017

Applicant: FUJITSU CONNECTED TECHNOLOGIES Ltd.

Address: 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki 211-8588, Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results.....	6
2.1 Measurement Uncertainty.....	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes.....	8
3.2.1 Test Mode Applicability and Tested Channel Detail.....	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards.....	13
4 Test Types and Results	14
4.1 Radiated Emission and Bandedge Measurement	14
4.1.1 Limits of Radiated Emission and Bandedge Measurement	14
4.1.2 Limits of Unwanted Emission Out of the Restricted Bands	15
4.1.3 Test Instruments	16
4.1.4 Test Procedures.....	17
4.1.5 Deviation from Test Standard	17
4.1.6 Test Set Up	18
4.1.7 EUT Operating Conditions.....	19
4.1.8 Test Results	20
4.2 Conducted Emission Measurement.....	52
4.2.1 Limits of Conducted Emission Measurement	52
4.2.2 Test Instruments	52
4.2.3 Test Procedures.....	53
4.2.4 Deviation from Test Standard	53
4.2.5 Test Setup.....	53
4.2.6 EUT Operating Conditions.....	53
4.2.7 Test Results	54
4.3 Transmit Power Measurement.....	56
4.3.1 Limits of Transmit Power Measurement	56
4.3.2 Test Setup.....	56
4.3.3 Test Instruments	57
4.3.4 Test Procedure	57
4.3.5 Deviation from Test Standard	57
4.3.6 EUT Operating Conditions.....	57
4.3.7 Test Result	58
4.4 Occupied Bandwidth Measurement.....	64
4.4.1 Test Setup.....	64
4.4.2 Test Instruments	64
4.4.3 Test Procedure	64
4.4.4 Test Results	65
4.5 Peak Power Spectral Density Measurement	67
4.5.1 Limits of Peak Power Spectral Density Measurement	67
4.5.2 Test Setup.....	67
4.5.3 Test Instruments	67
4.5.4 Test Procedures.....	67
4.5.5 Deviation from Test Standard	68
4.5.6 EUT Operating Conditions.....	68
4.5.7 Test Results	69
4.6 Frequency Stability	72

4.6.1 Limit of Frequency Stability Measurement	72
4.6.2 Test Setup	72
4.6.3 Test Instruments	72
4.6.4 Test Procedure	72
4.6.5 Deviation from Test Standard	72
4.6.6 EUT Operating Condition	72
4.6.7 Test Results	73
5 Pictures of Test Arrangements.....	74
Appendix – Information on the Testing Laboratories	75

Release Control Record

Issue No.	Description	Date Issued
RF170808C08-3	Original Release	Oct. 06, 2017

1 Certificate of Conformity

Product: Smart Phone

Brand: FUJITSU

Test Model: F-01K

Sample Status: Identical Prototype

Applicant: FUJITSU CONNECTED TECHNOLOGIES Ltd.

Test Date: Sep. 15, 2017 ~ Sep. 30, 2017

Standards: 47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Rona Chen , **Date:** Oct. 06, 2017
Rona Chen / Specialist

Approved by : David Huang , **Date:** Oct. 06, 2017
David Huang / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
FCC Clause	Test Item	Result	Remarks
15.407(b)(6)	AC Power Conducted Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -16.22 dB at 4.53000 MHz.
15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions & Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -3.89 dB at 5352.86 MHz.
15.407(a)(1/2/3)	Max Average Transmit Power	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	-	Reference only
15.407(a)(1/2/3)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.407(e)	6 dB Bandwidth	Pass	Meet the requirement of limit. (U-NII-3 Band only)
15.407(g)	Frequency Stability	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

*For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Smart Phone	
Brand	FUJITSU	
Test Model	F-01K	
Status of EUT	Identical Prototype	
Power Supply Rating	5.0 Vdc (adapter or host equipment) 3.75 Vdc (Li-ion battery)	
Modulation Type	256QAM, 64QAM, 16QAM, QPSK, BPSK	
Modulation Technology	OFDM	
Transfer Rate	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0 Mbps 802.11n: up to MCS7 802.11ac: up to V9	
Operating Frequency	5180 ~ 5240 MHz, 5260 ~ 5320 MHz, 5500 ~ 5700 MHz,	
Number of Channel	5180 ~ 5240 MHz: 4 for 802.11a, 802.11n (HT20), 802.11ac (VHT20) 2 for 802.11n (HT40), 802.11ac (VHT40) 1 for 802.11ac (VHT80) 5260 ~ 5320 MHz: 4 for 802.11a, 802.11n (HT20), 802.11ac (VHT20) 2 for 802.11n (HT40), 802.11ac (VHT40) 1 for 802.11ac (VHT80) 5500 ~ 5700 MHz: 11 for 802.11a, 802.11n (HT20), 802.11ac (VHT20) 5 for 802.11n (HT40), 802.11ac (VHT40) 2 for 802.11ac (VHT80)	
Output Power	42.737 mW for 5180 ~ 5240 MHz 39.717 mW for 5260 ~ 5320 MHz 38.198 mW for 5500 ~ 5700 MHz	
Antenna Type	$\lambda/4$ Monopole antenna with	-2.9 dBi gain (Ant #0) -2.2 dBi gain (Ant #1)
Antenna Connector	N/A	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:

- The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

Modulation Mode	Tx Function
802.11a	1TX
802.11n (HT20)	2TX
802.11n (HT40)	2TX
802.11ac (HT20)	2TX
802.11ac (HT40)	2TX
802.11ac (VHT80)	2TX

* The modulation and bandwidth are similar for 802.11n mode for HT20 / HT40 and 802.11ac mode for HT20 / HT40, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

2. The EUT contains following accessory devices.

Product	Brand	Model	Description
Battery	FUJITSU CONNECTED TECHNOLOGIES Ltd.	CA54310-0067	3.75 Vdc, 2850 mAh

3. The EUT uses following adapter which provided by client as support unit.

Product	Brand	Model	Description
Adapter	NTT docomo	AC Adapter 06	I/P: 100-240Vac, 0.8A, O/P: 5.0Vdc, 3.0A

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

For 5180 ~ 5240 MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency (MHz)
42	5210

For 5260 ~ 5320 MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300
56	5280	64	5320

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
54	5270	62	5310

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency (MHz)
58	5290

For 5500 ~ 5700 MHz

11 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	124	5620
104	5520	128	5640
108	5540	132	5660
112	5560	136	5680
116	5580	140	5700
120	5600		

5 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
102	5510	126	5630
110	5550	134	5670
118	5590		

2 channels are provided for 802.11ac (VHT80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
106	5530	122	5610

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE \geq 1G	RE<1G	PLC	APCM	
A	√	-	√	√	1Tx
B	√	√	√	√	2Tx

Where **RE \geq 1G**: Radiated Emission above 1 GHz **RE<1G**: Radiated Emission below 1 GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
2. "-" means no effect.

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	5180-5240	802.11a	36 to 48	36, 44, 48	OFDM	BPSK	6.0
B		802.11ac (VHT20)	36 to 48	36, 44, 48	OFDM	BPSK	MCS0
		802.11n (HT40)	38 to 46	38, 46	OFDM	BPSK	MCS0
		802.11ac (VHT80)	42	42	OFDM	BPSK	MCS0
A	5260-5320	802.11a	52 to 64	52, 60, 64	OFDM	BPSK	6.0
B		802.11ac (VHT20)	52 to 64	52, 60, 64	OFDM	BPSK	MCS0
		802.11n (HT40)	54 to 62	54, 62	OFDM	BPSK	MCS0
		802.11ac (VHT80)	58	58	OFDM	BPSK	MCS0
A	5500-5700	802.11a	100 to 140	100, 116, 140	OFDM	BPSK	6.0
B		802.11ac (VHT20)	100 to 140	100, 116, 140	OFDM	BPSK	MCS0
		802.11n (HT40)	102 to 134	102, 110, 134	OFDM	BPSK	MCS0
		802.11ac (VHT80)	106 to 122	106, 122	OFDM	BPSK	MCS0

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
B	5180-5240	802.11ac (VHT80)	42	42	OFDM	BPSK	MCS0
B	5260-5320	802.11ac (VHT80)	58	58	OFDM	BPSK	MCS0
B	5500-5700	802.11ac (VHT80)	106 to 122	106	OFDM	BPSK	MCS0

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
B	5260-5320	802.11ac (VHT80)	58	58	OFDM	BPSK	MCS0

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	5180-5240	802.11a	36 to 48	36, 44, 48	OFDM	BPSK	6.0
B		802.11ac (VHT20)	36 to 48	36, 44, 48	OFDM	BPSK	MCS0
		802.11n (HT40)	38 to 46	38, 46	OFDM	BPSK	MCS0
		802.11ac (VHT80)	42	42	OFDM	BPSK	MCS0
A	5260-5320	802.11a	52 to 64	52, 60, 64	OFDM	BPSK	6.0
B		802.11ac (VHT20)	52 to 64	52, 60, 64	OFDM	BPSK	MCS0
		802.11n (HT40)	54 to 62	54, 62	OFDM	BPSK	MCS0
		802.11ac (VHT80)	58	58	OFDM	BPSK	MCS0
A	5500-5700	802.11a	100 to 140	100, 116, 140	OFDM	BPSK	6.0
B		802.11ac (VHT20)	100 to 140	100, 116, 140	OFDM	BPSK	MCS0
		802.11n (HT40)	102 to 134	102, 110, 134	OFDM	BPSK	MCS0
		802.11ac (VHT80)	106 to 122	106, 122	OFDM	BPSK	MCS0

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE \geq 1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Getaz Yang
APCM	25 deg. C, 65 % RH	3.8 Vdc	Anson Lin

3.3 Duty Cycle of Test Signal

MODULATION TYPE: BPSK


Duty cycle of test signal is < 98 %, duty factor is required.

802.11a: Duty cycle = $2.061/2.200 = 0.937$, Duty factor = $10 * \log(1/0.937) = 0.28$

802.11ac (VHT20): Duty cycle = $0.981/1.108 = 0.885$, Duty factor = $10 * \log(1/0.885) = 0.53$

802.11n (HT40): Duty cycle = $0.947/1.091 = 0.868$, Duty factor = $10 * \log(1/0.868) = 0.61$

802.11ac (VHT80): Duty cycle = $0.461/0.617 = 0.747$, Duty factor = $10 * \log(1/0.747) = 1.27$



3.4 Description of Support Units

The following support units or accessories were used to form a representative test configuration during the tests.


No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Earphone	N/A	N/A	N/A	N/A

No.	Signal Cable Description Of The Above Support Units
1.	N/A

Note:

1. All power cords of the above support units are non-shielded (1.8m).

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

789033 D02 General UNII Test Procedures New Rules v01r04

644545 D01 Guidance for IEEE 802 11ac v01r02

662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.1.2 Limits of Unwanted Emission Out of the Restricted Bands

Applicable To		Limit	
789033 D02 General UNII Test Procedures New Rules v01r04		Field Strength at 3 m	
		PK: 74 (dBμV/m)	AV: 54 (dBμV/m)
Frequency Band	Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
5150~5250 MHz	15.407(b)(1)	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)
5250~5350 MHz	15.407(b)(2)		
5470~5725 MHz	15.407(b)(3)		
5725~5850 MHz	15.407(b)(4)(i)	PK:-27 (dBm/MHz) ^{*1} PK:10 (dBm/MHz) ^{*2} PK:15.6 (dBm/MHz) ^{*3} PK:27 (dBm/MHz) ^{*4}	PK: 68.2 (dBμV/m) ^{*1} PK:105.2 (dBμV/m) ^{*2} PK: 110.8 (dBμV/m) ^{*3} PK:122.2 (dBμV/m) ^{*4}
	15.407(b)(4)(ii)	Emission limits in section 15.247(d)	

^{*1} beyond 75 MHz or more above of the band edge.

^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.

^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.

^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Jul. 05, 2017	Jul. 04, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 13, 2016	Dec. 12, 2017
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 16, 2016	Dec. 15, 2017
HORN Antenna ETS-Lindgren	3117	00143293	Dec. 29, 2016	Dec. 28, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 14, 2016	Dec. 13, 2017
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 17, 2017	Apr. 16, 2018
Bluetooth Tester	CBT	100980	Jun. 28, 2017	Jun. 27, 2019
Loop Antenna	HLA 6121	45745	May 19, 2017	May 18, 2018
Preamplifier Agilent	310N	187226	Jun. 23, 2017	Jun. 22, 2018
Preamplifier Agilent	83017A	MY39501357	Jun. 23, 2017	Jun. 22, 2018
Power Meter Anritsu	ML2495A	1012010	Aug. 15, 2017	Aug. 14, 2018
Power Sensor Anritsu	MA2411B	1315050	Aug. 15, 2017	Aug. 14, 2018
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 23, 2017	Jun. 22, 2018
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 23, 2017	Jun. 22, 2018
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The FCC Designation Number is TW0011. The number will be varied with the Lab location and scope as attached.
5. The IC Site Registration No. is IC7450I-1.

4.1.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1/T for Average (Duty cycle < 98 %) detection at frequency above 1 GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.1.5 Deviation from Test Standard


No deviation.

4.1.6 Test Set Up


<Radiated emission below 30MHz>



<Frequency Range below 1 GHz>



<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.7 EUT Operating Conditions

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.1.8 Test Results

Above 1 GHz Data :

Mode A

802.11a

EUT Test Condition		Measurement Detail	
Channel	Channel 36	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5128.1	42.95	34.73	54	-11.05	34.11	8.1	33.99	100	48	Average
5128.1	53.33	45.11	74	-20.67	34.11	8.1	33.99	100	48	Peak
5180	92.51	84.2			34.15	8.16	34	100	48	Average
5180	99.54	91.23			34.15	8.16	34	100	48	Peak
*10360	56.07	41.77	68.2	-12.13	37.12	12.3	35.12	106	258	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5143.85	42.83	34.58	54	-11.17	34.12	8.13	34	150	40	Average
5143.85	53.37	45.12	74	-20.63	34.12	8.13	34	150	40	Peak
5180	91.46	83.15			34.15	8.16	34	150	40	Average
5180	98.82	90.51			34.15	8.16	34	150	40	Peak
*10360	56.03	41.73	68.2	-12.17	37.12	12.3	35.12	117	19	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5180 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 44	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5146.25	42.75	34.5	54	-11.25	34.12	8.13	34	100	48	Average
5146.25	53.21	44.96	74	-20.79	34.12	8.13	34	100	48	Peak
5220	92.22	83.83			34.17	8.22	34	100	48	Average
5220	99.25	90.86			34.17	8.22	34	100	48	Peak
5416.11	42.88	34.15	54	-11.12	34.33	8.44	34.04	100	48	Average
5416.11	53.77	45.04	74	-20.23	34.33	8.44	34.04	100	48	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5124.35	42.82	34.6	54	-11.18	34.11	8.1	33.99	150	40	Average
5124.35	54.17	45.95	74	-19.83	34.11	8.1	33.99	150	40	Peak
5220	91.36	82.97			34.17	8.22	34	150	40	Average
5220	98.08	89.69			34.17	8.22	34	150	40	Peak
5445.59	42.93	34.1	54	-11.07	34.36	8.51	34.04	150	40	Average
5445.59	53.81	44.98	74	-20.19	34.36	8.51	34.04	150	40	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5220 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 48	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5240	92.74	84.3			34.19	8.26	34.01	100	48	Average
5240	99.56	91.12			34.19	8.26	34.01	100	48	Peak
5362.32	43.05	34.41	54	-10.95	34.29	8.38	34.03	100	48	Average
5362.32	53.3	44.66	74	-20.7	34.29	8.38	34.03	100	48	Peak
*10480	56.5	41.99	68.2	-11.7	37.19	12.53	35.21	199	157	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5240	91.36	82.92			34.19	8.26	34.01	150	40	Average
5240	98.34	89.9			34.19	8.26	34.01	150	40	Peak
5448.01	42.9	34.07	54	-11.1	34.36	8.51	34.04	150	40	Average
5448.01	54.33	45.5	74	-19.67	34.36	8.51	34.04	150	40	Peak
*10480	56.04	41.53	68.2	-12.16	37.19	12.53	35.21	107	243	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5240 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 52	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5129.3	42.69	34.47	54	-11.31	34.11	8.1	33.99	100	48	Average
5129.3	53.52	45.3	74	-20.48	34.11	8.1	33.99	100	48	Peak
5260	93.36	84.9			34.21	8.26	34.01	100	48	Average
5260	100.59	92.13			34.21	8.26	34.01	100	48	Peak
*10520	57.96	43.37	68.2	-10.24	37.21	12.61	35.23	158	315	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5098.4	42.75	34.59	54	-11.25	34.08	8.07	33.99	150	40	Average
5098.4	53.2	45.04	74	-20.8	34.08	8.07	33.99	150	40	Peak
5260	92.54	84.08			34.21	8.26	34.01	150	40	Average
5260	99.5	91.04			34.21	8.26	34.01	150	40	Peak
*10520	55.98	41.39	68.2	-12.22	37.21	12.61	35.23	114	213	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5260 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 60	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5128.4	42.72	34.5	54	-11.28	34.11	8.1	33.99	100	48	Average
5128.4	53.35	45.13	74	-20.65	34.11	8.1	33.99	100	48	Peak
5300	93.85	85.31			34.24	8.32	34.02	100	48	Average
5300	100.32	91.78			34.24	8.32	34.02	100	48	Peak
5352.75	42.99	34.36	54	-11.01	34.28	8.38	34.03	100	48	Average
5352.75	53.76	45.13	74	-20.24	34.28	8.38	34.03	100	48	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5142.2	42.72	34.46	54	-11.28	34.12	8.13	33.99	150	40	Average
5142.2	53.61	45.35	74	-20.39	34.12	8.13	33.99	150	40	Peak
5300	92.25	83.71			34.24	8.32	34.02	150	40	Average
5300	99.4	90.86			34.24	8.32	34.02	150	40	Peak
5355.94	43.19	34.56	54	-10.81	34.28	8.38	34.03	150	40	Average
5355.94	54.23	45.6	74	-19.77	34.28	8.38	34.03	150	40	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5300 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 64	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5320	93.46	84.88			34.25	8.35	34.02	100	48	Average
5320	100.21	91.63			34.25	8.35	34.02	100	48	Peak
5353.74	43.18	34.55	54	-10.82	34.28	8.38	34.03	100	48	Average
5353.74	54.25	45.62	74	-19.75	34.28	8.38	34.03	100	48	Peak
10640	46.94	32.21	54	-7.06	37.31	12.71	35.29	134	310	Average
10640	55.96	41.23	74	-18.04	37.31	12.71	35.29	134	310	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5320	92.11	83.53			34.25	8.35	34.02	150	40	Average
5320	99.29	90.71			34.25	8.35	34.02	150	40	Peak
5360.34	43.36	34.73	54	-10.64	34.28	8.38	34.03	150	40	Average
5360.34	54.16	45.53	74	-19.84	34.28	8.38	34.03	150	40	Peak
10640	47.02	32.29	54	-6.98	37.31	12.71	35.29	111	58	Average
10640	56.7	41.97	74	-17.3	37.31	12.71	35.29	111	58	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5320 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 100	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5453.52	43.37	34.55	54	-10.63	34.36	8.51	34.05	100	44	Average
5453.52	54.19	45.37	74	-19.81	34.36	8.51	34.05	100	44	Peak
*5470.48	52.28	43.45	68.2	-15.92	34.37	8.51	34.05	100	44	Peak
5500	91.44	82.52			34.4	8.57	34.05	100	44	Average
5500	98.51	89.59			34.4	8.57	34.05	100	44	Peak
11000	47.56	32.48	54	-6.44	37.6	12.96	35.48	139	66	Average
11000	57.96	42.88	74	-16.04	37.6	12.96	35.48	139	66	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5453.04	43.49	34.67	54	-10.51	34.36	8.51	34.05	176	40	Average
5453.04	54.97	46.15	74	-19.03	34.36	8.51	34.05	176	40	Peak
*5469.68	53.84	45.01	68.2	-14.36	34.37	8.51	34.05	176	40	Peak
5500	93.45	84.53			34.4	8.57	34.05	176	40	Average
5500	100.52	91.6			34.4	8.57	34.05	176	40	Peak
11000	47.1	32.02	54	-6.9	37.6	12.96	35.48	173	255	Average
11000	56.85	41.77	74	-17.15	37.6	12.96	35.48	173	255	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5500 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 116	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5448.88	42.81	33.98	54	-11.19	34.36	8.51	34.04	100	44	Average
5448.88	53.69	44.86	74	-20.31	34.36	8.51	34.04	100	44	Peak
*5470.64	53.31	44.48	68.2	-14.89	34.37	8.51	34.05	100	44	Peak
5580	91.26	82.27			34.47	8.6	34.08	100	44	Average
5580	98.23	89.24			34.47	8.6	34.08	100	44	Peak
*5724.2	52.65	43.49	68.2	-15.55	34.62	8.65	34.11	100	44	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5454.48	42.92	34.1	54	-11.08	34.36	8.51	34.05	176	40	Average
5454.48	54.19	45.37	74	-19.81	34.36	8.51	34.05	176	40	Peak
*5469.36	51.6	42.77	68.2	-16.6	34.37	8.51	34.05	176	40	Peak
5580	93.77	84.78			34.47	8.6	34.08	176	40	Average
5580	100.69	91.7			34.47	8.6	34.08	176	40	Peak
*5725.8	52.54	43.38	68.2	-15.66	34.62	8.65	34.11	176	40	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5580 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 140	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5700	91.11	81.98			34.59	8.64	34.1	100	44	Average
5700	98.2	89.07			34.59	8.64	34.1	100	44	Peak
*5725.4	53.55	44.39	68.2	-14.65	34.62	8.65	34.11	100	44	Peak
11400	47.35	32.25	54	-6.65	37.84	12.67	35.41	173	335	Average
11400	57.28	42.18	74	-16.72	37.84	12.67	35.41	173	335	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5700	93.55	84.42			34.59	8.64	34.1	185	40	Average
5700	100.51	91.38			34.59	8.64	34.1	185	40	Peak
*5725.08	53.04	43.88	68.2	-15.16	34.62	8.65	34.11	185	40	Peak
11400	47.27	32.17	54	-6.73	37.84	12.67	35.41	137	266	Average
11400	56.67	41.57	74	-17.33	37.84	12.67	35.41	137	266	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5700 MHz: Fundamental Frequency
- *: Out of Restricted Band

Mode B

802.11ac (VHT20)

EUT Test Condition		Measurement Detail	
Channel	Channel 36	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5142.05	42.84	34.58	54	-11.16	34.12	8.13	33.99	119	4	Average
5142.05	56.58	48.32	74	-17.42	34.12	8.13	33.99	119	4	Peak
5180	95.45	87.14			34.15	8.16	34	119	4	Average
5180	102.04	93.73			34.15	8.16	34	119	4	Peak
*10360	55.42	41.12	68.2	-12.78	37.12	12.3	35.12	159	25	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5146.7	42.79	34.54	54	-11.21	34.12	8.13	34	202	27	Average
5146.7	53.79	45.54	74	-20.21	34.12	8.13	34	202	27	Peak
5180	90.25	81.94			34.15	8.16	34	202	27	Average
5180	97.59	89.28			34.15	8.16	34	202	27	Peak
*10360	55.25	40.95	68.2	-12.95	37.12	12.3	35.12	182	2	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5180 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 44	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5147.9	42.9	34.65	54	-11.1	34.12	8.13	34	119	4	Average
5147.9	54.87	46.62	74	-19.13	34.12	8.13	34	119	4	Peak
5220	95.56	87.17			34.17	8.22	34	119	4	Average
5220	102.36	93.97			34.17	8.22	34	119	4	Peak
5448.34	42.91	34.08	54	-11.09	34.36	8.51	34.04	119	4	Average
5448.34	53.15	44.32	74	-20.85	34.36	8.51	34.04	119	4	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5131.25	42.74	34.52	54	-11.26	34.11	8.1	33.99	202	27	Average
5131.25	53.47	45.25	74	-20.53	34.11	8.1	33.99	202	27	Peak
5220	90.44	82.05			34.17	8.22	34	202	27	Average
5220	97.97	89.58			34.17	8.22	34	202	27	Peak
5445.15	42.98	34.16	54	-11.02	34.35	8.51	34.04	202	27	Average
5445.15	53.84	45.02	74	-20.16	34.35	8.51	34.04	202	27	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 5220 MHz: Fundamental Frequency
3. *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 48	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5240	95.85	87.41			34.19	8.26	34.01	119	4	Average
5240	102.43	93.99			34.19	8.26	34.01	119	4	Peak
5450.87	42.97	34.15	54	-11.03	34.36	8.51	34.05	119	4	Average
5450.87	53.42	44.6	74	-20.58	34.36	8.51	34.05	119	4	Peak
*10480	56.51	42	68.2	-11.69	37.19	12.53	35.21	105	194	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5240	90.36	81.92			34.19	8.26	34.01	202	27	Average
5240	97.07	88.63			34.19	8.26	34.01	202	27	Peak
5449.44	42.9	34.07	54	-11.1	34.36	8.51	34.04	202	27	Average
5449.44	54.02	45.19	74	-19.98	34.36	8.51	34.04	202	27	Peak
*10480	55.72	41.21	68.2	-12.48	37.19	12.53	35.21	175	11	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5240 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 52	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5141.45	42.68	34.42	54	-11.32	34.12	8.13	33.99	134	130	Average
5141.45	53.64	45.38	74	-20.36	34.12	8.13	33.99	134	130	Peak
5260	98.45	89.99			34.21	8.26	34.01	134	130	Average
5260	105.38	96.92			34.21	8.26	34.01	134	130	Peak
*10520	56.77	42.18	68.2	-11.43	37.21	12.61	35.23	121	184	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5105.3	42.71	34.55	54	-11.29	34.08	8.07	33.99	187	48	Average
5105.3	53.36	45.2	74	-20.64	34.08	8.07	33.99	187	48	Peak
5260	93.45	84.99			34.21	8.26	34.01	187	48	Average
5260	100.09	91.63			34.21	8.26	34.01	187	48	Peak
*10520	56.82	42.23	68.2	-11.38	37.21	12.61	35.23	125	174	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5260 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 60	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5127.2	42.73	34.51	54	-11.27	34.11	8.1	33.99	134	130	Average
5127.2	54.89	46.67	74	-19.11	34.11	8.1	33.99	134	130	Peak
5300	98.41	89.87			34.24	8.32	34.02	134	130	Average
5300	105.31	96.77			34.24	8.32	34.02	134	130	Peak
5354.51	43.43	34.8	54	-10.57	34.28	8.38	34.03	134	130	Average
5354.51	53.69	45.06	74	-20.31	34.28	8.38	34.03	134	130	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5105.3	42.82	34.66	54	-11.18	34.08	8.07	33.99	187	48	Average
5105.3	53.66	45.5	74	-20.34	34.08	8.07	33.99	187	48	Peak
5300	93.36	84.82			34.24	8.32	34.02	187	48	Average
5300	100.92	92.38			34.24	8.32	34.02	187	48	Peak
5357.92	43.43	34.8	54	-10.57	34.28	8.38	34.03	187	48	Average
5357.92	53.57	44.94	74	-20.43	34.28	8.38	34.03	187	48	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5300 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 64	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5320	98.45	89.87			34.25	8.35	34.02	134	130	Average
5320	105.42	96.84			34.25	8.35	34.02	134	130	Peak
5370.02	43.32	34.65	54	-10.68	34.29	8.41	34.03	134	130	Average
5370.02	56.43	47.76	74	-17.57	34.29	8.41	34.03	134	130	Peak
10640	48.36	33.63	54	-5.64	37.31	12.71	35.29	185	245	Average
10640	57.58	42.85	74	-16.42	37.31	12.71	35.29	185	245	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5320	93.35	84.77			34.25	8.35	34.02	187	48	Average
5320	100.46	91.88			34.25	8.35	34.02	187	48	Peak
5363.31	43.17	34.53	54	-10.83	34.29	8.38	34.03	187	48	Average
5363.31	55.72	47.08	74	-18.28	34.29	8.38	34.03	187	48	Peak
10640	47.54	32.81	54	-6.46	37.31	12.71	35.29	126	61	Average
10640	56.68	41.95	74	-17.32	37.31	12.71	35.29	126	61	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5320 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 100	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5451.92	43.04	34.22	54	-10.96	34.36	8.51	34.05	189	231	Average
5451.92	54.2	45.38	74	-19.8	34.36	8.51	34.05	189	231	Peak
*5470.32	53.16	44.33	68.2	-15.04	34.37	8.51	34.05	189	231	Peak
5500	95.06	86.14			34.4	8.57	34.05	189	231	Average
5500	102.86	93.94			34.4	8.57	34.05	189	231	Peak
11000	48.52	33.44	54	-5.48	37.6	12.96	35.48	196	248	Average
11000	57.48	42.4	74	-16.52	37.6	12.96	35.48	196	248	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5445.36	43.19	34.37	54	-10.81	34.35	8.51	34.04	171	34	Average
5445.36	54.03	45.21	74	-19.97	34.35	8.51	34.04	171	34	Peak
*5470.8	52.47	43.61	68.2	-15.73	34.37	8.54	34.05	171	34	Peak
5500	94.22	85.3			34.4	8.57	34.05	171	34	Average
5500	101.24	92.32			34.4	8.57	34.05	171	34	Peak
11000	48.17	33.09	54	-5.83	37.6	12.96	35.48	127	164	Average
11000	57.37	42.29	74	-16.63	37.6	12.96	35.48	127	164	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5500 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 116	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5459.6	42.81	33.99	54	-11.19	34.36	8.51	34.05	189	231	Average
5459.6	54.04	45.22	74	-19.96	34.36	8.51	34.05	189	231	Peak
*5470.96	52.86	44	68.2	-15.34	34.37	8.54	34.05	189	231	Peak
5580	95.11	86.12			34.47	8.6	34.08	189	231	Average
5580	102.76	93.77			34.47	8.6	34.08	189	231	Peak
*5726.04	53.84	44.68	68.2	-14.36	34.62	8.65	34.11	189	231	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5450.96	43.05	34.23	54	-10.95	34.36	8.51	34.05	170	34	Average
5450.96	54.23	45.41	74	-19.77	34.36	8.51	34.05	170	34	Peak
*5469.36	52.42	43.59	68.2	-15.78	34.37	8.51	34.05	170	34	Peak
5580	94.11	85.12			34.47	8.6	34.08	170	34	Average
5580	101.87	92.88			34.47	8.6	34.08	170	34	Peak
*5724.68	53.4	44.24	68.2	-14.8	34.62	8.65	34.11	170	34	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5580 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 140	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5700	95.43	86.3			34.59	8.64	34.1	179	314	Average
5700	102.24	93.11			34.59	8.64	34.1	179	314	Peak
*5724.6	60.22	51.06	68.2	-7.98	34.62	8.65	34.11	127	314	Peak
11400	48.09	32.99	54	-5.91	37.84	12.67	35.41	134	84	Average
11400	57.12	42.02	74	-16.88	37.84	12.67	35.41	134	84	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5700	94	84.87			34.59	8.64	34.1	162	33	Average
5700	101.8	92.67			34.59	8.64	34.1	162	33	Peak
*5725.32	58.62	49.46	68.2	-9.58	34.62	8.65	34.11	164	48	Peak
11400	47.15	32.05	54	-6.85	37.84	12.67	35.41	125	194	Average
11400	56.47	41.37	74	-17.53	37.84	12.67	35.41	125	194	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5700 MHz: Fundamental Frequency
- *: Out of Restricted Band

802.11n (HT40)

EUT Test Condition		Measurement Detail	
Channel	Channel 38	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5148.8	46.65	38.4	54	-7.35	34.12	8.13	34	101	50	Average
5148.8	55.5	47.25	74	-18.5	34.12	8.13	34	101	50	Peak
5190	93.66	85.32			34.15	8.19	34	119	4	Average
5190	100.56	92.22			34.15	8.19	34	119	4	Peak
5378.27	43.29	34.61	54	-10.71	34.31	8.41	34.04	119	4	Average
5378.27	54.03	45.35	74	-19.97	34.31	8.41	34.04	119	4	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5150	44.5	36.25	54	-9.5	34.12	8.13	34	202	27	Average
5150	53.37	45.12	74	-20.63	34.12	8.13	34	202	27	Peak
5190	88.52	80.18			34.15	8.19	34	202	27	Average
5190	95.63	87.29			34.15	8.19	34	202	27	Peak
5446.36	43.37	34.54	54	-10.63	34.36	8.51	34.04	202	27	Average
5446.36	53.29	44.46	74	-20.71	34.36	8.51	34.04	202	27	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5190 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 46	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5126.75	43.24	35.02	54	-10.76	34.11	8.1	33.99	119	4	Average
5126.75	53.5	45.28	74	-20.5	34.11	8.1	33.99	119	4	Peak
5230	92.52	84.12			34.19	8.22	34.01	119	4	Average
5230	99.72	91.32			34.19	8.22	34.01	119	4	Peak
5450.65	43.37	34.55	54	-10.63	34.36	8.51	34.05	119	4	Average
5450.65	53.49	44.67	74	-20.51	34.36	8.51	34.05	119	4	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5131.7	43.11	34.89	54	-10.89	34.11	8.1	33.99	202	27	Average
5131.7	53.66	45.44	74	-20.34	34.11	8.1	33.99	202	27	Peak
5230	87.49	79.09			34.19	8.22	34.01	202	27	Average
5230	94.36	85.96			34.19	8.22	34.01	202	27	Peak
5436.02	43.28	34.49	54	-10.72	34.35	8.48	34.04	202	27	Average
5436.02	53.71	44.92	74	-20.29	34.35	8.48	34.04	202	27	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5230 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 54	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5118.5	43.22	35.02	54	-10.78	34.09	8.1	33.99	134	130	Average
5118.5	53.02	44.82	74	-20.98	34.09	8.1	33.99	134	130	Peak
5270	95.65	87.16			34.21	8.29	34.01	134	130	Average
5270	102.04	93.55			34.21	8.29	34.01	134	130	Peak
5378.49	43.58	34.9	54	-10.42	34.31	8.41	34.04	134	130	Average
5378.49	53.9	45.22	74	-20.1	34.31	8.41	34.04	134	130	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5140.1	43.14	34.88	54	-10.86	34.12	8.13	33.99	187	48	Average
5140.1	53.87	45.61	74	-20.13	34.12	8.13	33.99	187	48	Peak
5270	90.25	81.76			34.21	8.29	34.01	187	48	Average
5270	97.47	88.98			34.21	8.29	34.01	187	48	Peak
5370.13	43.35	34.68	54	-10.65	34.29	8.41	34.03	187	48	Average
5370.13	53.8	45.13	74	-20.2	34.29	8.41	34.03	187	48	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5270 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 62	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5115.35	43.16	34.96	54	-10.84	34.09	8.1	33.99	134	130	Average
5115.35	53.47	45.27	74	-20.53	34.09	8.1	33.99	134	130	Peak
5310	95.63	87.08			34.25	8.32	34.02	134	130	Average
5310	102.36	93.81			34.25	8.32	34.02	134	130	Peak
5350.88	45.36	36.73	54	-8.64	34.28	8.38	34.03	134	4	Average
5350.88	56.18	47.55	74	-17.82	34.28	8.38	34.03	134	4	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5113.85	43.17	34.97	54	-10.83	34.09	8.1	33.99	187	48	Average
5113.85	53.74	45.54	74	-20.26	34.09	8.1	33.99	187	48	Peak
5310	90.43	81.88			34.25	8.32	34.02	187	48	Average
5310	97.71	89.16			34.25	8.32	34.02	187	48	Peak
5354.18	44.75	36.12	54	-9.25	34.28	8.38	34.03	187	48	Average
5354.18	54.33	45.7	74	-19.67	34.28	8.38	34.03	187	48	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5310 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 102	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5459.76	44.61	35.79	54	-9.39	34.36	8.51	34.05	196	207	Average
5459.76	54.53	45.71	74	-19.47	34.36	8.51	34.05	196	207	Peak
*5468.88	57.97	49.14	68.2	-10.23	34.37	8.51	34.05	196	207	Peak
5510	93.14	84.23			34.4	8.57	34.06	189	231	Average
5510	100.55	91.64			34.4	8.57	34.06	189	231	Peak
*5725.16	52.92	43.76	68.2	-15.28	34.62	8.65	34.11	189	231	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5452.72	43.85	35.03	54	-10.15	34.36	8.51	34.05	171	35	Average
5452.72	54.6	45.78	74	-19.4	34.36	8.51	34.05	171	35	Peak
*5469.68	53.88	45.05	68.2	-14.32	34.37	8.51	34.05	171	35	Peak
5510	92.94	84.03			34.4	8.57	34.06	171	35	Average
5510	99.92	91.01			34.4	8.57	34.06	171	35	Peak
*5724.36	52.31	43.15	68.2	-15.89	34.62	8.65	34.11	171	35	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5510 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 110	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5423.92	42.98	34.21	54	-11.02	34.33	8.48	34.04	189	231	Average
5423.92	54.33	45.56	74	-19.67	34.33	8.48	34.04	189	231	Peak
*5469.2	53.22	44.39	68.2	-14.98	34.37	8.51	34.05	189	231	Peak
5550	93.22	84.25			34.45	8.59	34.07	189	231	Average
5550	100.28	91.31			34.45	8.59	34.07	189	231	Peak
*5724.28	52.67	43.51	68.2	-15.53	34.62	8.65	34.11	189	231	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5453.04	43.02	34.2	54	-10.98	34.36	8.51	34.05	171	34	Average
5453.04	53.92	45.1	74	-20.08	34.36	8.51	34.05	171	34	Peak
*5468.56	53.13	44.3	68.2	-15.07	34.37	8.51	34.05	171	34	Peak
5550	92.68	83.71			34.45	8.59	34.07	171	34	Average
5550	99.85	90.88			34.45	8.59	34.07	171	34	Peak
*5725.48	53.58	44.42	68.2	-14.62	34.62	8.65	34.11	171	34	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5550 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 134	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5412.88	42.84	34.11	54	-11.16	34.33	8.44	34.04	179	314	Average
5412.88	53.32	44.59	74	-20.68	34.33	8.44	34.04	179	314	Peak
*5468.08	52.29	43.46	68.2	-15.91	34.37	8.51	34.05	179	314	Peak
5670	93.32	84.22			34.57	8.63	34.1	179	314	Average
5670	100.76	91.66			34.57	8.63	34.1	179	314	Peak
*5724.12	56.71	47.55	68.2	-11.49	34.62	8.65	34.11	196	245	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5441.68	42.81	34.02	54	-11.19	34.35	8.48	34.04	162	33	Average
5441.68	53.14	44.35	74	-20.86	34.35	8.48	34.04	162	33	Peak
*5469.84	52.35	43.52	68.2	-15.85	34.37	8.51	34.05	162	33	Peak
5670	92.72	83.62			34.57	8.63	34.1	162	33	Average
5670	99.8	90.7			34.57	8.63	34.1	162	33	Peak
*5726.04	53.45	44.29	68.2	-14.75	34.62	8.65	34.11	162	33	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5670 MHz: Fundamental Frequency
- *: Out of Restricted Band

802.11ac (VHT80)

EUT Test Condition		Measurement Detail	
Channel	Channel 42	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5142.95	48.54	40.28	54	-5.46	34.12	8.13	33.99	148	0	Average
5142.95	57.29	49.03	74	-16.71	34.12	8.13	33.99	148	0	Peak
5210	90.65	82.29			34.17	8.19	34	119	4	Average
5210	97.05	88.69			34.17	8.19	34	119	4	Peak
5424.8	43.66	34.89	54	-10.34	34.33	8.48	34.04	119	4	Average
5424.8	53.45	44.68	74	-20.55	34.33	8.48	34.04	119	4	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5149.85	44.89	36.64	54	-9.11	34.12	8.13	34	202	27	Average
5149.85	55.05	46.8	74	-18.95	34.12	8.13	34	202	27	Peak
5210	85.14	76.78			34.17	8.19	34	202	27	Average
5210	92.77	84.41			34.17	8.19	34	202	27	Peak
5445.7	43.66	34.83	54	-10.34	34.36	8.51	34.04	202	27	Average
5445.7	54.01	45.18	74	-19.99	34.36	8.51	34.04	202	27	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5210 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 58	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5134.4	43.5	35.25	54	-10.5	34.11	8.13	33.99	134	130	Average
5134.4	53.36	45.11	74	-20.64	34.11	8.13	33.99	134	130	Peak
5290	92.45	83.92			34.23	8.32	34.02	134	130	Average
5290	99.89	91.36			34.23	8.32	34.02	134	130	Peak
5352.86	50.11	41.48	54	-3.89	34.28	8.38	34.03	134	46	Average
5352.86	59.06	50.43	74	-14.94	34.28	8.38	34.03	134	46	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5096.45	43.49	35.33	54	-10.51	34.08	8.07	33.99	187	48	Average
5096.45	53.78	45.62	74	-20.22	34.08	8.07	33.99	187	48	Peak
5290	87.49	78.96			34.23	8.32	34.02	187	48	Average
5290	94.34	85.81			34.23	8.32	34.02	187	48	Peak
5358.8	48.43	39.8	54	-5.57	34.28	8.38	34.03	187	48	Average
5358.8	57.17	48.54	74	-16.83	34.28	8.38	34.03	187	48	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5290 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 106	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5458.64	49.07	40.25	54	-4.93	34.36	8.51	34.05	162	305	Average
5458.64	59.38	50.56	74	-14.62	34.36	8.51	34.05	162	305	Peak
*5470.8	59.78	50.92	68.2	-8.42	34.37	8.54	34.05	162	305	Peak
5530	90.04	81.11			34.42	8.58	34.07	189	229	Average
5530	97.75	88.82			34.42	8.58	34.07	189	229	Peak
*5724.04	52.74	43.58	68.2	-15.46	34.62	8.65	34.11	189	229	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5447.92	46.09	37.26	54	-7.91	34.36	8.51	34.04	153	12	Average
5447.92	56.14	47.31	74	-17.86	34.36	8.51	34.04	153	12	Peak
*5470	57.56	48.73	68.2	-10.64	34.37	8.51	34.05	153	12	Peak
5530	89.21	80.28			34.42	8.58	34.07	170	34	Average
5530	96.86	87.93			34.42	8.58	34.07	170	34	Peak
*5725.4	53.04	43.88	68.2	-15.16	34.62	8.65	34.11	170	34	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5530 MHz: Fundamental Frequency
- *: Out of Restricted Band

EUT Test Condition		Measurement Detail	
Channel	Channel 122	Frequency Range	1 GHz ~ 40 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5362.64	42.99	34.35	54	-11.01	34.29	8.38	34.03	189	231	Average
5362.64	53.66	45.02	74	-20.34	34.29	8.38	34.03	189	231	Peak
*5468.72	52.91	44.08	68.2	-15.29	34.37	8.51	34.05	189	231	Peak
5610	90.08	81.05			34.5	8.61	34.08	189	231	Average
5610	97.66	88.63			34.5	8.61	34.08	189	231	Peak
*5725.4	53.04	43.88	68.2	-15.16	34.62	8.65	34.11	189	231	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5433.84	42.91	34.12	54	-11.09	34.35	8.48	34.04	171	34	Average
5433.84	54.18	45.39	74	-19.82	34.35	8.48	34.04	171	34	Peak
*5470	53.15	44.32	68.2	-15.05	34.37	8.51	34.05	171	34	Peak
5610	89.66	80.63			34.5	8.61	34.08	171	34	Average
5610	96.25	87.22			34.5	8.61	34.08	171	34	Peak
*5725.88	52.28	43.12	68.2	-15.92	34.62	8.65	34.11	171	34	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5610 MHz: Fundamental Frequency
- *: Out of Restricted Band

9 kHz ~ 30 MHz DATA:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz WORST-CASE DATA:

Mode B

802.11ac (VHT80)

EUT Test Condition		Measurement Detail	
Channel	Channel 42	Frequency Range	30 MHz ~ 1 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
86.7	17.38	38.74	40	-22.62	9.44	1.11	31.91	154	352	Peak
157.44	11.13	33.24	43.5	-32.37	8.64	1.52	32.27	134	222	Peak
205.77	13.8	33.3	43.5	-29.7	11.12	1.65	32.27	144	205	Peak
454	15	29.03	46	-31	15.62	2.49	32.14	124	143	Peak
547.1	16.99	29.4	46	-29.01	17.02	2.76	32.19	150	60	Peak
652.1	18.88	29.56	46	-27.12	18.48	2.99	32.15	128	88	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
59.16	22.77	40.58	40	-17.23	13.52	0.9	32.23	119	9	Peak
151.77	6.56	28.84	43.5	-36.94	8.47	1.52	32.27	183	22	Peak
222.24	9.13	28.27	46	-36.87	11.42	1.65	32.21	124	33	Peak
475.7	16.12	29.7	46	-29.88	15.98	2.56	32.12	124	216	Peak
622.7	17.57	28.66	46	-28.43	18.15	2.93	32.17	187	8	Peak
799.1	20.74	29.16	46	-25.26	20.32	3.32	32.06	124	203	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value

802.11ac (VHT80)

EUT Test Condition		Measurement Detail	
Channel	Channel 58	Frequency Range	30 MHz ~ 1 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
85.08	17.74	39.4	40	-22.26	9.19	1.11	31.96	154	5	Peak
142.59	6.03	28.52	43.5	-37.47	8.4	1.38	32.27	150	142	Peak
185.52	15.81	36.24	43.5	-27.69	10.2	1.61	32.24	165	33	Peak
603.1	17.95	29.31	46	-28.05	17.96	2.87	32.19	189	331	Peak
741.7	19.64	28.89	46	-26.36	19.73	3.16	32.14	128	7	Peak
853	22.29	29.57	46	-23.71	21.06	3.44	31.78	185	229	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
32.43	23.42	43.19	40	-16.58	11.74	0.74	32.25	117	205	Peak
79.68	20.95	43.79	40	-19.05	8.26	1.11	32.21	168	9	Peak
213.87	12.12	31.48	43.5	-31.38	11.23	1.65	32.24	124	111	Peak
514.9	16.34	29.23	46	-29.66	16.54	2.7	32.13	114	326	Peak
664	18.63	29.09	46	-27.37	18.68	2.99	32.13	129	99	Peak
708.1	19.4	29.04	46	-26.6	19.35	3.11	32.1	170	181	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value

802.11ac (VHT80)

EUT Test Condition		Measurement Detail	
Channel	Channel 106	Frequency Range	30 MHz ~ 1 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
59.43	11.54	29.35	40	-28.46	13.52	0.9	32.23	200	0	Peak
118.29	12.3	32.65	43.5	-31.2	10.62	1.28	32.25	200	0	Peak
192.54	14.61	34.46	43.5	-28.89	10.81	1.61	32.27	200	0	Peak
344.8	14.33	30.06	46	-31.67	14.15	2.19	32.07	124	244	Peak
562.5	16.34	28.39	46	-29.66	17.33	2.82	32.2	152	56	Peak
698.3	20.09	29.86	46	-25.91	19.21	3.11	32.09	132	2	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
65.91	17.71	37.33	40	-22.29	11.7	0.9	32.22	200	1	Peak
154.47	5.58	27.8	43.5	-37.92	8.53	1.52	32.27	124	101	Peak
223.05	8.94	28.02	46	-37.06	11.47	1.65	32.2	154	255	Peak
423.2	13.85	28.37	46	-32.15	15.26	2.41	32.19	142	33	Peak
647.2	17.47	28.23	46	-28.53	18.4	2.99	32.15	154	176	Peak
713.7	20.18	29.74	46	-25.82	19.43	3.11	32.1	194	229	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBUV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Test Receiver ROHDE & SCHWARZ	ESCS 30	100288	Aug.17, 2017	Aug. 16, 2018
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond2-01	Sep. 09, 2017	Sep. 08, 2018
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Jan. 17, 2017	Jan. 16, 2018
LISN/AMN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Aug. 02, 2017	Aug. 01, 2018
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit -20 dB) was not recorded.

Note: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



- Note:** 1.Support units were connected to second LISN.
 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.


4.2.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/9/30

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15400	10.39	28.08	14.98	38.47	25.37	65.78	55.78	-27.31	-30.41
2	0.18600	10.39	22.13	9.45	32.52	19.84	64.21	54.21	-31.69	-34.37
3	0.34600	10.40	22.06	9.66	32.46	20.06	59.06	49.06	-26.60	-29.00
4	0.53000	10.41	24.64	15.88	35.05	26.29	56.00	46.00	-20.95	-19.71
5	4.44600	10.58	22.81	12.72	33.39	23.30	56.00	46.00	-22.61	-22.70
6	13.13400	11.01	9.60	4.73	20.61	15.74	60.00	50.00	-39.39	-34.26

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/9/30

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16105	10.16	25.84	13.29	36.00	23.45	65.41	55.41	-29.41	-31.96
2	0.18133	10.16	22.24	10.26	32.40	20.42	64.42	54.42	-32.02	-34.00
3	0.34214	10.17	22.22	10.24	32.39	20.41	59.15	49.15	-26.76	-28.74
4	0.52600	10.17	26.37	16.69	36.54	26.86	56.00	46.00	-19.46	-19.14
5	4.53000	10.35	29.43	14.83	39.78	25.18	56.00	46.00	-16.22	-20.82
6	6.08200	10.41	25.31	13.81	35.72	24.22	60.00	50.00	-24.28	-25.78

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 Transmit Power Measurement

4.3.1 Limits of Transmit Power Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p \leq 125 mW (21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
		Fixed point-to-point Access Point	1 Watt (30 dBm)
		Indoor Access Point	1 Watt (30 dBm)
	✓	Mobile and Portable client device	250 mW (24 dBm)
U-NII-2A	✓		250 mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C	✓		250 mW (24 dBm) or 11 dBm+10 log B*
U-NII-3			1 Watt (30 dBm)

*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;


Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20 MHz channel widths with $N_{ANT} \geq 5$.


For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.3.2 Test Setup


<Power Output Measurement>



or



<26 dB Bandwidth>



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

Average Power Measurement

<802.11a, 802.11n (HT20), 802.11n (HT40)>

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

<802.11ac (VHT80)>

Method SA-1 is used to perform output power measurement, trigger and gating function of spectrum analyzer is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

26 dB Bandwidth

- 1) Set RBW = approximately 1 % of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

Power Output:

Mode A

802.11a

Channel	Frequency (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
36	5180	18.836	12.75	24	Pass
44	5220	17.418	12.41	24	Pass
48	5240	18.365	12.64	24	Pass
52	5260	17.742	12.49	24	Pass
60	5300	17.298	12.38	24	Pass
64	5320	17.947	12.54	24	Pass
100	5500	17.865	12.52	24	Pass
116	5580	17.824	12.51	24	Pass
140	5700	17.498	12.43	24	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log (22.41) = 24.50 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log (22.35) = 24.49 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log (22.75) = 24.57 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log (22.83) = 24.59 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log (22.25) = 24.47 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log (22.20) = 24.46 \text{ dBm} > 24 \text{ dBm}$.

Mode B

802.11ac (VHT20)

Channel	Frequency (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	12.84	13.42	41.21	16.15	24	Pass
44	5220	13.14	13.45	42.737	16.31	24	Pass
48	5240	13.12	13.38	42.289	16.26	24	Pass
52	5260	12.61	13.32	39.717	15.99	24	Pass
60	5300	12.38	13.12	37.81	15.78	24	Pass
64	5320	12.41	12.67	35.911	15.55	24	Pass
100	5500	12.78	12.84	38.198	15.82	24	Pass
116	5580	12.41	12.48	35.119	15.46	24	Pass
140	5700	12.65	12.74	37.201	15.71	24	Pass

Note:

For U-NII-2A, U-NII-2C Band:

Chain 0

1. $11 \text{ dBm} + 10\log (24.74) = 24.93 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log (24.82) = 24.95 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log (24.87) = 24.96 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log (24.02) = 24.81 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log (24.07) = 24.81 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log (24.28) = 24.85 \text{ dBm} > 24 \text{ dBm}$.

Chain 1

1. $11 \text{ dBm} + 10\log (23.57) = 24.72 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log (23.58) = 24.73 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log (23.56) = 24.72 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log (23.72) = 24.75 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log (23.84) = 24.77 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log (23.37) = 24.69 \text{ dBm} > 24 \text{ dBm}$.

802.11n (HT40)

Channel	Frequency (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
38	5190	12.91	13.49	41.879	16.22	24	Pass
46	5230	12.44	13.01	37.538	15.74	24	Pass
54	5270	12.66	12.48	36.151	15.58	24	Pass
62	5310	12.51	12.85	37.099	15.69	24	Pass
102	5510	12.47	12.88	37.069	15.69	24	Pass
110	5550	12.71	12.89	38.118	15.81	24	Pass
134	5670	12.57	12.66	36.522	15.63	24	Pass

Note:

For U-NII-2A, U-NII-2C Band:

Chain 0

1. $11 \text{ dBm} + 10\log (42.19) = 27.25 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log (42.07) = 27.24 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log (42.07) = 27.24 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log (42.20) = 27.25 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log (42.19) = 27.25 \text{ dBm} > 24 \text{ dBm}$.

Chain 1

1. $11 \text{ dBm} + 10\log (42.04) = 27.24 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log (42.28) = 27.26 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log (42.20) = 27.25 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log (42.22) = 27.26 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log (42.21) = 27.25 \text{ dBm} > 24 \text{ dBm}$.

802.11ac (VHT80)

Channel	Frequency (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
42	5210	11.09	12.03	28.812	14.60	24	Pass
58	5290	10.34	11.34	24.428	13.88	24	Pass
106	5530	10.06	10.64	21.727	13.37	24	Pass
122	5610	10.40	10.23	21.509	13.33	24	Pass

Note:

For U-NII-2A, U-NII-2C Band:

Chain 0

1. $11 \text{ dBm} + 10\log (84.35) = 30.26 \text{ dBm} > 24 \text{ dBm}.$
2. $11 \text{ dBm} + 10\log (84.28) = 30.26 \text{ dBm} > 24 \text{ dBm}.$
3. $11 \text{ dBm} + 10\log (84.44) = 30.27 \text{ dBm} > 24 \text{ dBm}.$

Chain 1

1. $11 \text{ dBm} + 10\log (83.73) = 30.23 \text{ dBm} > 24 \text{ dBm}.$
2. $11 \text{ dBm} + 10\log (83.71) = 30.23 \text{ dBm} > 24 \text{ dBm}.$
3. $11 \text{ dBm} + 10\log (83.84) = 30.23 \text{ dBm} > 24 \text{ dBm}.$

26 dB Bandwidth:

Mode A

802.11a

Channel	Frequency (MHz)	26 dBc Bandwidth (MHz)
36	5180	22.73
44	5220	22.88
48	5240	22.25
52	5260	22.41
60	5300	22.35
64	5320	22.75
100	5500	22.83
116	5580	22.25
140	5700	22.20

Mode B

802.11ac (VHT20)


Channel	Frequency (MHz)	26 dBc Bandwidth (MHz)	
		Chain 0	Chain 1
36	5180	24.93	23.82
44	5220	24.43	23.42
48	5240	24.87	23.28
52	5260	24.74	23.57
60	5300	24.82	23.58
64	5320	24.87	23.56
100	5500	24.02	23.72
116	5580	24.07	23.84
140	5700	24.28	23.37

802.11n (HT40)

Channel	Frequency (MHz)	26 dBc Bandwidth (MHz)	
		Chain 0	Chain 1
38	5190	42.06	42.23
46	5230	42.15	42.28
54	5270	42.19	42.04
62	5310	42.07	42.28
102	5510	42.07	42.20
110	5550	42.20	42.22
134	5670	42.19	42.21


802.11ac (VHT80)

Channel	Frequency (MHz)	26 dBc Bandwidth (MHz)	
		Chain 0	Chain 1
42	5210	83.36	83.42
58	5290	84.35	83.73
106	5530	84.28	83.71
122	5610	84.44	83.84



4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to SAMPLE. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.4.4 Test Results

Mode A

802.11a

Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)
36	5180	16.73
40	5200	16.73
48	5240	16.73
52	5260	16.73
60	5300	16.73
64	5320	16.73
100	5500	16.77
116	5580	16.73
140	5700	16.77

Mode B

802.11ac (VHT20)


Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
36	5180	17.93	17.83
40	5200	17.93	17.78
48	5240	17.93	17.88
52	5260	17.93	17.88
60	5300	17.98	17.88
64	5320	17.93	17.83
100	5500	17.88	17.78
116	5580	17.93	17.83
140	5700	17.93	17.83

802.11n (HT40)

Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
38	5190	36.79	36.66
46	5230	36.79	36.66
54	5270	36.79	36.66
62	5310	36.79	36.53
102	5510	36.79	36.66
110	5550	36.79	36.66
134	5670	36.79	36.66

802.11ac (VHT80)

Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
42	5210	75.64	75.96
58	5290	75.80	75.80
106	5530	75.96	75.96
122	5610	76.12	75.80




4.5 Peak Power Spectral Density Measurement

4.5.1 Limits of Peak Power Spectral Density Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	17 dBm/MHz
		Fixed point-to-point Access Point	
		Indoor Access Point	
	√	Mobile and Portable client device	11 dBm/MHz
U-NII-2A	√		11 dBm/MHz
U-NII-2C	√		11 dBm/MHz
U-NII-3	-		30 dBm/500 kHz

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.5.4 Test Procedures

For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-2

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW ≥ 3 RBW, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value and add 10 log (1/duty cycle)

※For U-NII-3:

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 500 kHz, Set VBW ≥ 3 RBW, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
4. Sweep time = auto, trigger set to "free run".
5. Trace average at least 100 traces in power averaging mode.
6. Record the max value and add 10 log (1/duty cycle)

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

For U-NII-1, U-NII-2A, U-NII-2C Band

Mode A

802.11a

Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/MHz)	Duty Factor (dB)	PSD with Duty Factor (dBm/MHz)	Maximum Limit (dBm/MHz)	Pass / Fail
36	5180	1.88	0.28	2.16	11	Pass
44	5220	1.97	0.28	2.25	11	Pass
48	5240	1.83	0.28	2.11	11	Pass
52	5260	1.79	0.28	2.07	11	Pass
60	5300	2.43	0.28	2.71	11	Pass
64	5320	2.05	0.28	2.33	11	Pass
100	5500	1.78	0.28	2.06	11	Pass
116	5580	1.86	0.28	2.14	11	Pass
140	5700	2.12	0.28	2.40	11	Pass

Note: Refer to section 3.3 for duty cycle spectrum plot.

Mode B

802.11ac (VHT20)

Channel	Frequency (MHz)	PSD (dBm/MHz)		Duty Factor (dB)	Total PSD with Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
36	5180	0.26	1.77	0.53	4.62	11	Pass
44	5220	0.43	1.86	0.53	4.74	11	Pass
48	5240	0.60	1.65	0.53	4.70	11	Pass
52	5260	0.41	1.72	0.53	4.66	11	Pass
60	5300	0.19	1.74	0.53	4.57	11	Pass
64	5320	0.30	1.77	0.53	4.64	11	Pass
100	5500	0.32	1.87	0.53	4.70	11	Pass
116	5580	0.66	1.78	0.53	4.80	11	Pass
140	5700	0.55	1.98	0.53	4.85	11	Pass

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = $10\log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}] = 0.47 \text{ dBi} < 6 \text{ dBi}$, so the limit no need to reduced.
- Refer to section 3.3 for duty cycle spectrum plot.

802.11n (HT40)

Channel	Frequency (MHz)	PSD (dBm/MHz)		Duty Factor (dB)	Total PSD with Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
38	5190	-1.47	-1.28	0.61	2.25	11	Pass
46	5230	-1.93	-1.69	0.61	1.82	11	Pass
54	5270	-1.85	-1.72	0.61	1.84	11	Pass
62	5310	-1.58	-1.14	0.61	2.27	11	Pass
102	5510	-1.68	-1.46	0.61	2.06	11	Pass
110	5550	-1.70	-1.72	0.61	1.92	11	Pass
134	5670	-1.70	-1.71	0.61	1.92	11	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $10\log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}] = 0.47 \text{ dBi} < 6 \text{ dBi}$, so the limit no need to reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT80)


Channel	Frequency (MHz)	PSD (dBm/MHz)		Duty Factor (dB)	Total PSD with Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
42	5210	-5.07	-5.04	1.27	-0.78	11	Pass
58	5290	-4.86	-4.90	1.27	-0.60	11	Pass
106	5530	-4.77	-4.35	1.27	-0.28	11	Pass
122	5610	-4.88	-5.01	1.27	-0.67	11	Pass

Note:


1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $10\log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}] = 0.47 \text{ dBi} < 6 \text{ dBi}$, so the limit no need to reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11a




802.11ac (VHT20)



802.11n (HT40)



802.11ac (VHT80)




4.6 Frequency Stability

4.6.1 Limit of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation.

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.6.4 Test Procedure

- To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
- The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10 dB lower than the measured peak value.
- The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

4.6.7 Test Results

Frequency Stability Versus Temp.									
Operating Frequency: 5180 MHz									
Temp. (°C)	Power Supply (Vdc)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)
50	3.75	5179.9975	-0.48000	5179.9999	-0.02000	5179.9998	-0.04000	5179.9983	-0.33000
40	3.75	5179.9757	-4.69000	5179.9756	-4.71000	5179.9748	-4.86000	5179.975	-4.83000
30	3.75	5180.0229	4.42000	5180.0225	4.34000	5180.0225	4.34000	5180.0219	4.23000
20	3.75	5180.0045	0.87000	5180.006	1.16000	5180.0065	1.25000	5180.003	0.58000
10	3.75	5180.0218	4.21000	5180.0217	4.19000	5180.0214	4.13000	5180.0224	4.32000
0	3.75	5180.0203	3.92000	5180.0204	3.94000	5180.0211	4.07000	5180.021	4.05000
-10	3.75	5179.9911	-1.72000	5179.9915	-1.64000	5179.9911	-1.72000	5179.9957	-0.83000
-20	3.75	5180.0175	3.38000	5180.0199	3.84000	5180.0212	4.09000	5180.0204	3.94000
-30	3.75	5179.9808	-3.71000	5179.9771	-4.42000	5179.9771	-4.42000	5179.9776	-4.32000

Frequency Stability Versus Temp.									
Operating Frequency: 5180 MHz									
Temp. (°C)	Power Supply (Vdc)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)	Measured Frequency (MHz)	Frequency Drift (ppm)
20	4.485	5180.005	0.97000	5180.0053	1.02000	5180.0059	1.14000	5180.003	0.58000
	3.75	5180.0045	0.87000	5180.006	1.16000	5180.0065	1.25000	5180.003	0.58000
	3.315	5180.0047	0.91000	5180.0061	1.18000	5180.0059	1.14000	5180.0025	0.48000

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---