

# TEST REPORT

For

**Mobile phone incorporated with Bluetooth (Sub)**

In conformity with

**FCC CFR 47 Part15 (October 1, 2008)**

**Model: F-04B-S**

**FCC ID: VQK-F04B-S**

**Test Item: Mobile phone incorporated with Bluetooth (Sub)**

**Report No: RY1001J05R1**

**Issue Date: Jan. 05, 2010**

**Prepared for**

Fujitsu Limited  
4-1-1, Kamikodanaka, Nakahara, Kawasaki 211-8588, Japan

**Prepared by**

RF Technologies Ltd.  
472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan  
Telephone: +81+(0)45- 534-0645  
FAX: +81+(0)45- 534-0646

**This report shall not be reproduced, except in full, without the written permission of RF Technologies Ltd. The test results in this report apply only to the sample tested. RF Technologies Ltd. is managed to ISO17025 and has the necessary knowledge and test facilities for testing according to the referenced standards.**

## Table of contents

<b>1</b>	<b>General information.....</b>	<b>3</b>
1.1	Product description .....	3
1.2	Test(s) performed/ Summary of test result .....	3
1.3	Test facility .....	4
1.4	Measurement uncertainty.....	4
1.5	Summary of test results.....	5
1.5.1	Table of test summary.....	5
1.6	Setup of equipment under test (EUT) .....	5
1.6.1	Test configuration of EUT .....	5
1.6.2	Operating condition: .....	6
1.6.3	Setup diagram of tested system:.....	7
1.7	Equipment modifications.....	7
1.8	Deviation from the standard .....	7
<b>2</b>	<b>Test procedure and test data .....</b>	<b>8</b>
2.1	Occupied Bandwidth (20 dB / 99%).....	8
2.2	Hopping Carrier Frequency Separation .....	13
2.3	Number of Hopping Channel.....	16
2.4	Average Time of Occupancy .....	20
2.5	Peak Output Power .....	27
2.6	Conducted Spurious Emissions (Antenna Port).....	30
2.7	Transmitter Radiated spurious emissions .....	33
2.7.1	Below 30 MHz.....	35
2.7.2	Between 30 – 1000 MHz .....	36
2.7.3	Above 1000 MHz.....	38
<b>3</b>	<b>Test setup photographs.....</b>	<b>42</b>
3.1	Definition of the EUT configuration.....	42
3.2	Definition of the EUT axis.....	43
3.3	Antenna Port Measurements.....	45
3.4	Radiated spurious emissions.....	46
<b>4</b>	<b>List of utilized test equipment/ calibration .....</b>	<b>47</b>

## History

Report No.	Date	Revisions	Issued By
RY1001J05R1	Jan. 05, 2010	Initial Issue	R.Kojima

## 1 General information

### 1.1 Product description

Test item	: Mobile phone incorporated with Bluetooth (Sub)
Manufacturer	: Fujitsu Limited
Address	: 4-1-1, Kamikodanaka, Nakahara, Kawasaki 211-8588, Japan
Model	: F-04B-S
FCC ID	: VQK-F04B-S
Serial numbers	: 000000000003103 (for radiated), 000000000003244 (for conducted)
Fundamental Operated Frequency	: Tx/Rx Freq. (2402 - 2480 MHz)
Oscillator frequencies	: 26 MHz
Type of Modulation	: FHSS (GFSK, $\pi/4$ DQPSK, 8DPSK)
RF Output Power	: 1.68dBm (measured at the antenna terminal)
Antenna Gain	: -6.00 dBi ( $\lambda/4$ Monopole antenna)
Receipt date of EUT	: Nov. 27, 2009
Nominal power source voltages	: DC 3.7V (Battery)

### 1.2 Test(s) performed/ Summary of test result

Test specification(s)	: FCC CFR 47. Part 15 (October 1, 2008)
Test method(s)	: ANSI C63.4: 2003
Test(s) started	: Dec. 01, 2009
Test(s) completed	: Dec. 20, 2009
Purpose of test(s)	: Grant for Certification of FCC
Summary of test result	: Complied

Note: The above judgment is only based on the measurement data and it does not include the measurement uncertainty. Accordingly, the statement below is applied to the test result.  
The EUT complies with the limit required in the standard in case that the margin is not less than the measurement uncertainty in the Laboratory.  
Compliance of the EUT is more probable than non-compliance is case that the margin is less than the measurement uncertainty in the Laboratory.

Test engineer



R. Kojima  
Engineer  
EMC testing Department

Reviewer



K. Ohnishi  
Manager  
EMC testing Department

### 1.3 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at **RF Technologies Ltd.**, located in 472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 1, 2007. The description of the test facilities has been filed under registration number 319924 at the Office of the Federal Communications Commission. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

Registered by Voluntary Control Council for Interference by Information Technology Equipment (VCCI)

Each registered facility number is as follows;

Test site (Semi Anechoic chamber 3m) R-2393

Test site (Shielded room) C-2617

Registered by Industry Canada (IC) Each registered facility number is as follows;

Test site No.1 (Semi Anechoic chamber 3m): 6974A

Accredited by **National Voluntary Laboratory Accreditation Program (NVLAP)** for the emission tests stated in the scope of the certificate under Certificate Number 200780-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200780-0

### 1.4 Measurement uncertainty

The treatment of uncertainty is based on the general matters on the definition of uncertainty in "Guide to the expression of uncertainty in measurement (GUM)" published by ISO. The Lab's uncertainty is determined by referring UKAS Publication LAB34: 2002 "The Expression of Uncertainty in EMC Testing" and CISPR16-4-2: 2003 "Uncertainty in EMC Measurements".

The uncertainty of the measurement result in the level of confidence of approximately 95% (k=2) is as follows;

RF Conducted emission:  $\pm 1.0$  dB (9 kHz – 26 GHz)

Radiated emission (9 kHz - 30MHz):  $\pm 2.8$  dB

Radiated emission (30MHz - 1000MHz):  $\pm 5.7$  dB

Radiated emission (1.0GHz – 18.0GHz):  $\pm 5.8$  dB

Radiated emission (18.0GHz – 26.0GHz):  $\pm 5.9$  dB

## 1.5 Summary of test results

### 1.5.1 Table of test summary

Requirement of;	Section in FCC15	Result	Sample	Section in this report
1.5.1 Occupied Bandwidth (20 dB/99%)	15.247(a)(1)	-	B2	2.1
1.5.2 Hopping Carrier Frequency Separation	15.247(a)(1)	Complied	B2	2.2
1.5.3 Number of Hopping Channel	15.247(a)(1)(iii)	Complied	B2	2.3
1.5.4 Average Time of Occupancy	15.247(a)(1)(iii)	Complied	B2	2.4
1.5.5 Peak Output Power	15.247(a)(1)/(b)(1)	Complied	B2	2.5
1.5.6 Conducted Spurious Emissions	15.247(d)	Complied	B2	2.6
1.5.7 Transmitter Radiated Spurious Emissions	15.205(b)/15.209	Complied	B1	2.7

## 1.6 Setup of equipment under test (EUT)

### 1.6.1 Test configuration of EUT

#### Equipment(s) under test:

	Item	Manufacturer	Model No.	Serial No.	Remark
B1	Mobile phone incorporated with Bluetooth (Sub)	Fujitsu Limited	F-04B-S	000000000003103	For Radiated Test
B2	Mobile phone incorporated with Bluetooth (Sub)	Fujitsu Limited	F-04B-S	000000000003244	For Conducted Test
D	Li-ion Battery Pack (Sub)	Fujitsu Limited	F14	-	DC3.7V / 650mAh

#### Support Equipment(s):

	Item	Manufacturer	Model No.	Serial No.
A	Mobile phone incorporated with Bluetooth (Main)	Fujitsu Limited	F-04B	353167030003784
C	Li-ion Battery Pack	Fujitsu Limited	F13	-
E	AC Adapter	Fujitsu Limited.	FOMA AC adaptor02	SCB

#### Connected cable(s):

No.	Item	Identification (Manu.e.t.c)	Shielded YES / NO	Ferrite Core YES / NO	Connector Type Shielded YES / NO	Length (m)
1	DC power cable	Fujitsu Limited.	No	No	No	2.32



## 1.6.2 Operating condition:

Operating mode:

The EUT was tested under the following test mode prepared by the applicant:

- (1-1) GFSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2402MHz)
- (1-2) GFSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2441MHz)
- (1-3) GFSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2480MHz)
- (1-4)  $\pi/4$ DQPSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2402MHz)
- (1-5)  $\pi/4$ DQPSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2441MHz)
- (1-6)  $\pi/4$ DQPSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2480MHz)
- (1-7) 8DPSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2402MHz)
- (1-8) 8DPSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2441MHz)
- (1-9) 8DPSK, Max continuous transmission with DH1/3/5 PACKET at hopping off (2480MHz)
- (1-10) Continuous transmission with DH1/3/5 PACKET at hopping on

## 1.6.3 Setup diagram of tested system:



## 1.7 Equipment modifications

No modifications have been made to the equipment in order to achieve compliance with the applicable standards described in clause 1.2.

## 1.8 Deviation from the standard


No deviations from the standards described in clause 1.2.

## 2 Test procedure and test data

### 2.1 Occupied Bandwidth (20 dB / 99%)

#### Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



#### Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 13.1.7. The EUT antenna port connected to the spectrum analyzer. The RBW is set to  $\geq 1\%$  of the 20 dB bandwidth bandwidth. The VBW is set to 3 times of the RBW. The sweep time is coupled appropriate.

#### Limitation

There are no limitations. The measurement value is used to calculation of the limitation of the channel separation and the emission designator.

#### Test equipment used (refer to List of utilized test equipment)

SA06	CL26				
------	------	--	--	--	--

#### Test results

##### (Configuration 2)

Operating Mode	Transmission Channel	Transmission Frequency	Bandwidth [MHz]	
			20dB	99%
GFSK (1Mbps)	Low (0ch)	2402	1.128	0.984
	Middle (39ch)	2441	1.128	0.984
	High (78ch)	2480	1.134	0.990
$\pi/4$ DQPSK (2Mbps)	Low (0ch)	2402	1.380	1.212
	Middle (39ch)	2441	1.386	1.218
	High (78ch)	2480	1.386	1.212
8DPSK (3Mbps)	Low (0ch)	2402	1.392	1.212
	Middle (39ch)	2441	1.386	1.212
	High (78ch)	2480	1.386	1.212









## Test Data




Tested Date: Dec. 01, 2009

Temperature: 29 °C  
Humidity: 30 %  
Atmos. Press: 1018 hPa

## 20dB Bandwidth (Configuration 2)



## 20dB Bandwidth (Configuration 2)









## Test Data




Tested Date: Dec. 01, 2009

Temperature: 29 °C  
Humidity: 30 %  
Atmos. Press: 1018 hPa

## 99% Occupied Bandwidth (Configuration 2)




## 99% Occupied Bandwidth (Configuration 2)



## 2.2 Hopping Carrier Frequency Separation

### Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



### Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to more than 1% of its span. The VBW is set to more than RBW. The sweep time is coupled appropriate.

### Limitation

15.247(a)(1) frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### Test equipment used (refer to List of utilized test equipment)

SA06	CL26				
------	------	--	--	--	--

### Test results – comply with the limitation


Operating Mode	Measured Channel	Measured Frequency (MHz)	Two-third of the 20dB bandwidth (MHz)	Frequency Separation (MHz)
GFSK	Middle (39ch) Configuration 2	2441	0.756 (worst case)	1.0
$\pi/4$ DQPSK	Middle (39ch) Configuration 2	2441	0.924 (worst case)	1.0
8DPSK	Middle (39ch) Configuration 2	2441	0.928 (worst case)	1.0

## Test Data


Tested Date: Dec. 01, 2009

Temperature: 29 °C  
Humidity: 30 %  
Atmos. Press: 1018 hPa


## Operating mode: GFSK (Configuration 2)



## Operating mode: $\pi/4$ DQPSK (Configuration 2)




## Operating mode: 8DPSK (Configuration 2)



## 2.3 Number of Hopping Channel

### Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



### Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to more than 1% of its span. The VBW is set to more than RBW. The sweep time is coupled appropriate. The span is set to cover the authorized band. The analyzer is set to MAX HOLD. The EUT is hopping operation.

### Limitation

15.247(a) (1) (iii) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### Test equipment used (refer to List of utilized test equipment)

SA06	CL26				
------	------	--	--	--	--

### Test results – Comply with the limitation

Hopping channel: 79 channels






## Test Data




Tested Date: Dec. 01, 2009

Temperature: 29 °C  
Humidity: 30 %  
Atmos. Press: 1018 hPa




## Operating mode: GFSK (Configuration 2)



## Operating mode: $\pi/4$ DQPSK (Configuration 2)




## Operating mode: 8DPSK (Configuration 2)



## 2.4 Average Time of Occupancy

### Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



### Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 1 MHz. The VBW is set to more than RBW. The sweep time is coupled appropriate. The span is set to 0 MHz and single sweep with video triggered. The EUT is hopping operation.

The average time of occupancy within the 31.6 seconds (79 channels \* 0.4) is calculated as follows in accordance with Bluetooth formula;

In case of DH1: (average time of occupancy) = (pulse width) \* (1600 / 2) / 79 \* 31.6

In case of DH3: (average time of occupancy) = (pulse width) \* (1600 / 4) / 79 \* 31.6

In case of DH5: (average time of occupancy) = (pulse width) \* (1600 / 6) / 79 \* 31.6

### Limitation

15.247(a)(1)(iii) The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### Test equipment used (refer to List of utilized test equipment)

SA06	CL26				
------	------	--	--	--	--

### Test results – comply with the limitation. (Configuration 2)







Operating Mode	Frequency [MHz]	Transmission Packet Type	Pulse width (msec)	Time of occupancy (msec)
GFSK	2402	DH1	0.396	126.720
		DH3	1.673	267.680
		DH5	2.927	312.213
	2441	DH1	0.397	127.040
		DH3	1.672	267.520
		DH5	2.934	312.960
	2480	DH1	0.397	127.040
		DH3	1.674	267.840
		DH5	2.934	312.960
/4DQPSK	2402	DH1	0.412	131.840
		DH3	1.680	268.800
		DH5	2.936	313.173
	2441	DH1	0.413	132.160
		DH3	1.680	268.800
		DH5	2.941	313.707
	2480	DH1	0.412	131.840
		DH3	1.678	268.480
		DH5	2.935	313.067
8DPSK	2402	DH1	0.411	131.520
		DH3	1.676	268.160
		DH5	2.936	313.173
	2441	DH1	0.412	131.840
		DH3	1.682	269.120
		DH5	2.941	313.707
	2480	DH1	0.410	131.200
		DH3	1.682	269.120
		DH5	2.927	312.213

## Test Data




Tested Date: Dec. 01, 2009

Temperature: 29 °C  
Humidity: 30 %  
Atmos. Press: 1018 hPa







## Operating mode: GFSK (Configuration 2)






## Operating mode: GFSK (Configuration 2)



## Operating mode: /4DQPSK (Configuration 2)









## Operating mode: /4DQPSK (Configuration 2)








## Operating mode: 8DPSK (Configuration 2)




## Operating mode: 8DPSK (Configuration 2)



## 2.5 Peak Output Power

### Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



### Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to the greater than 20dB bandwidth. The VBW is set to three times of RBW. The sweep time is coupled appropriate. The span is set to cover the carrier output spectrum. The analyzer is set to MAX HOLD. The EUT is set measured transmission channel under hopping off mode.

### Limitation

15.247(a) (1) Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW(21dBm).

### Test equipment used (refer to List of utilized test equipment)

SA06	CL26				
------	------	--	--	--	--







### Test results – comply with the limitation.




Operating Mode	Transmission Channel (Frequency: MHz)	Cable loss (dB)	Output power (dBm) [Reading]	Output power (dBm) [Result]	Output power (mW) [Result]
GFSK	Low (2402)	0.90	0.03	0.93	1.24
	Middle (2441)	0.90	-0.11	0.79	1.20
	High (2480)	0.90	-0.49	0.41	1.10
$\pi/4$ DQPSK	Low (2402)	0.90	0.53	1.43	1.39
	Middle (2441)	0.90	-0.19	0.71	1.18
	High (2480)	0.90	-1.09	-0.19	0.96
8DPSK	Low (2402)	0.90	0.78	1.68	1.47
	Middle (2441)	0.90	0.09	0.99	1.26
	High (2480)	0.90	-0.83	0.07	1.02

## Test Data

Tested Date: Dec. 01, 2009

Temperature: 29 °C  
Humidity: 30 %  
Atmos. Press: 1018 hPa






## 2.6 Conducted Spurious Emissions (Antenna Port)

### Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



### Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 100 kHz. The VBW is set to 300 kHz. The sweep time is set to the coupled. The spectrum is checked from 30 MHz to 26 GHz.

The EUT is set measured transmission channel under hopping off mode.

### Limitation

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test equipment used (refer to List of utilized test equipment)

SA06	CL26				
------	------	--	--	--	--

### Test results – comply with the limitation.







There were no conducted spurious emissions with levels of more than 20 dB below the applicable limit.

## Test Data

Tested Date: Dec. 01, 2009

Temperature: 29 °C  
Humidity: 30 %  
Atmos. Press: 1018 hPa





## Restricted Band Edge



Date: 1.DEC.2009 18:39:02

Date: 1.DEC.2009 18:45:52

## Worst Configuration (2402MHz, 8DPSK, Configuration 2)






## 2.7 Transmitter Radiated spurious emissions

### Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clause 6 “General requirements for EUT equipment arrangements and operation”, clause 8.2 and Annex H.3 “Radiated emission measurements setup”.



## Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 8.2. The EUT is placed on a non-conducted table which is 0.8m height from a ground plane and the measurement antenna to EUT distance is 3 meters. The turn table is rotated for 360 degrees to determine the maximum emission level. In the frequency range of 9 kHz to 30 MHz, a calibrated loop antenna was positioned with its plane vertical at the distance 3m from the EUT with an extrapolation of corrected distance factor and rotated about its vertical axis for maximum response at each azimuth about the EUT. For certain applications, the loop antenna also needs to be positioned horizontally. The center of the loop shall be 1 m above the ground. In the frequency above 30 MHz, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. EUT is placed at three different orientations (X, Y and Z axis) in order to find the worst orientation. The spectrum analyzer and receiver is set to the followings;

Below 30 MHz:	RBW=10 kHz, VBW= 30 kHz Final measurement is carried out with a receiver RBW of 9 kHz (QP)
Between 30 - 1000 MHz:	RBW=100 kHz, VBW= 300 kHz Final measurement is carried out with a receiver RBW of 120 kHz (QP)
Above 1000 MHz:	Peak measurement- RBW=1 MHz, VBW= 1 MHz Average measurement – RBW=1 MHz, VBW=10 Hz

## Applicable rule and limitation

### §15.205 restricted bands of operation

Except as shown in paragraph 15.205 (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.490 - 0.510	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(1)

15.205(b) except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

15.209( a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

In the emission table above, the tighter limit applies at the band edges.

The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz.

Radiated emission limits in the above bands are based on measurements employing an average detector.

**Test results** - Complied with requirement.

## Test Data

### 2.7.1 Below 30 MHz

**Test equipment used (refer to List of utilized test equipment)**

LP01	CL11	TR04	AC01
------	------	------	------

Tested Date: Dec. 15, 2009

Temperature: 19 °C

Humidity: 31 %

Atmos. Press: 1019 hPa

## Result

**There is no spurious emission with levels of more than 20 dB below the applicable limit or floor noise.**

## 2.7.2 Between 30 – 1000 MHz

### Test equipment used (refer to List of utilized test equipment)

BA04	CL11	PR03	TR04	AC01
------	------	------	------	------

Tested Date: Dec. 15, 2009

Temperature: 19 °C  
Humidity: 31 %  
Atmos. Press: 1019 hPa

Operating mode: Continuous Communication (8DPSK, 2402MHz, Configuration 2: Worst configuration)

EUT position: Y-plane (Maximum position)

Measurement distance: 3 m

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	30.000	22.9	18.3	7.3	29.7	18.8	40.0	21.2	Hori.
2	30.000	22.9	18.3	7.3	29.7	18.8	40.0	21.2	Vert.
3	498.214	19.4	17.6	14.9	29.7	22.2	46.0	23.8	Hori.
4	502.100	19.6	17.6	14.9	29.7	22.4	46.0	23.6	Vert.
5	1000.000	20.7	21.5	14.6	28.1	28.7	53.9	25.2	Hori.
6	1000.000	20.7	21.5	14.6	28.1	28.7	53.9	25.2	Vert.

### Calculation method

The Correction Factors and RESULT are calculated as followings.

$$\text{Correction Factor [dB/m]} = \text{FACTOR [dB/m]} + \text{LOSS [dB]} - \text{GAIN [dB]}$$

$$\text{RESULT [dBuV/m]} = \text{READING [dBuV]} + \text{Correction Factor [dB/m]}$$


Sample calculation at 30.000 MHz vertical result as follow:

$$\text{Result [dBuV/m]} = \text{Reading} + \text{C.F} = 22.9 + 18.3 + 7.3 - 29.7 = 18.8$$


$$\text{Margin} = \text{Limit} - \text{Result} = 40.0 - 18.8 = 21.2 \text{ [dB]}$$

## Graphical express of test result (30MHz-1000MHz)

### Antenna polarization: Horizontal



### Antenna polarization: Vertical



## 2.7.3 Above 1000 MHz



### Test equipment used (refer to List of utilized test equipment)

PR12	SH01	TR06	CL23	CL24	HPF1	DH02	AC01
------	------	------	------	------	------	------	------



Tested Date: Dec. 15, 2009

Temperature: 19 °C  
Humidity: 31 %  
Atmos. Press: 1019 hPa



### Restricted Band Edge (GFSK, 2402MHz, Configuration 2: Worst configuration)





### Restricted Band Edge (GFSK, 2480MHz, Configuration 2: Worst configuration)





## Restricted Band Edge ( $\pi/4$ DQPSK, 2402MHz, Configuration 2: Worst configuration)



## Restricted Band Edge ( $\pi/4$ DQPSK, 2480MHz, Configuration 2: Worst configuration)







**Harmonics and Spurious Emission above 1000 MHz**

Tested Date: Dec. 08, 2009

Temperature: 17 °C  
Humidity: 36 %  
Atmos. Press: 1026 hPa

Tested Date: Dec. 14, 2009

Temperature: 18 °C  
Humidity: 37 %  
Atmos. Press: 1016 hPa**Result****There is no spurious emission with levels of more than 20 dB below the applicable limit or floor noise.**

## 4 List of utilized test equipment/ calibration

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AC01 (EM)	Anechoic Chamber (1st test room)	JSE	203397C	-	2009/4/9	2010/4/30
AC01 (EG)	Anechoic Chamber (1st test room)	JSE	203397C	-	2009/11/14	2010/11/30
BA04	Biological Antenna	SCHAFFNER	CA2855	2903	2009/1/6	2010/1/31
CL11	Antenna Cable for RE	RFT	-	-	2009/4/13	2010/4/30
CL23	RF Cable 0.5m	SUCOFLEX	SF104PE	48773/4PE	2009/6/25	2010/6/30
CL24	RF Cable 5.0m	SUCOFLEX	SF104PE	48775/4PE	2009/6/25	2010/6/30
CL26	RF Cable 2.0m	SUCOFLEX	SF104	274754/4	2009/6/25	2010/6/30
HPF1	High Pass Filter (3500MHz)	TOKIMEC	TF323DCA	603	2009/6/25	2010/6/30
LP01	Loop Antenna	EMCO	6502	3436	2009/6/23	2010/6/30
PR03	Pre. Amplifier	Anritsu	MH648A	M41984	2009/5/26	2010/5/31
PR12	Pre. Amplifier (1-26G)	Agilent Technologies	8449B	3008A02513	2009/1/13	2010/1/31
SA06	Spectrum Analyzer (F/W: 3.60 SP1)	Rohde & Schwarz	FSP40	100071	2009/11/10	2010/11/30
TR06	Test Receiver (F/W : 3.93 SP2)	Rohde & Schwarz	ESU26	100002	2009/9/16	2010/9/30
DH02	DRG Horn Antenna	A.H. Systems	SAS-200/571	239	2009/4/13	2011/4/30

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.