

# **FCC Test Report**

FCC ID : VQK-F04G

**Equipment**: Mobile Phone

Model No. : F-04G

Brand Name : FUJITSU

Applicant : FUJITSU LIMITED

Address : 1-1, Kamikodanaka 4-chome, Nakahara-ku,

Kawasaki 211-8588, Japan

Standard : 47 CFR FCC Part 15.247

Received Date : Dec. 17, 2014

Tested Date : Mar. 08 ~ Mar. 12, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Ilac-MRA

Tap Testing Laboratory

Report No.: FR4D1701AD Report Version: Rev. 01 Page: 1 of 51



# **Table of Contents**

| 1   | GENERAL DESCRIPTION                                    | 5  |
|-----|--|----|
| 1.1 | Information  | 5  |
| 1.2 | Local Support Equipment List                           | 8  |
| 1.3 | Test Setup Chart                                       | 8  |
| 1.4 | The Equipment List                                     | g  |
| 1.5 | Test Standards   | 10 |
| 1.6 | Measurement Uncertainty                                | 10 |
| 2   | TEST CONFIGURATION                                     | 11 |
| 2.1 | Testing Condition                                      | 11 |
| 2.2 | The Worst Test Modes and Channel Details               | 11 |
| 3   | TRANSMITTER TEST RESULTS                               | 12 |
| 3.1 | Conducted Emissions                                    | 12 |
| 3.2 | Unwanted Emissions into Restricted Frequency Bands     | 17 |
| 3.3 | Unwanted Emissions into Non-Restricted Frequency Bands | 35 |
| 3.4 | Conducted Output Power                                 | 40 |
| 3.5 | Number of Hopping Frequency                            | 42 |
| 3.6 | 20dB and Occupied Bandwidth                            | 44 |
| 3.7 | Channel Separation                                     | 46 |
| 3.8 | Number of Dwell Time                                   | 48 |
| 4   | TEST LABORATORY INFORMATION                            | 51 |



# **Release Record**

| Report No. | Version | Description   | Issued Date   |
|------------|---------|---------------|---------------|
| FR4D1701AD | Rev. 01 | Initial issue | Apr. 01, 2015 |

Report No.: FR4D1701AD Page: 3 of 51



# **Summary of Test Results**

| FCC Rules           | Test Items                 | Measured  | Result  |  |
|---------------------|----------------------------|---|---------|--|
| 15.207              | Conducted Emissions        | [dBuV]: 0.567MHz<br>40.31 (Margin -5.69dB) - AV | Pass    |  |
| 15.247(d)           | Radiated Emissions         | [dBuV/m at 3m]: 30.00MHz                        | Pass    |  |
| 15.209              | Radiated Effissions        | 34.49 (Margin -5.51dB) - PK                     | F a 5 5 |  |
| 15.247(d) Band Edge |                            | Meet the requirement of limit                   | Pass    |  |
| 15.247(b)(1)        | Conducted Output Power     | Power [dBm]: 8.62                               | Pass    |  |
| 15.247(a)(1)(iii)   | Number of Hopping Channels | Meet the requirement of limit                   | Pass    |  |
| 15.247(a)(1)        | Hopping Channel Separation | Meet the requirement of limit                   | Pass    |  |
| 15.247(a)(1)(iii)   | Dwell Time                 | Meet the requirement of limit                   | Pass    |  |
| 15.203              | Antenna Requirement        | Meet the requirement of limit                   | Pass    |  |

Report No.: FR4D1701AD Page: 4 of 51



# 1 General Description

### 1.1 Information

#### 1.1.1 Product Details

| Product Name       | Mobile Phone                      |
|--------------------|-----------------------------------|
| Brand Name FUJITSU |                                   |
| Model Name F-04G   |                                   |
| IMEI Code          | 357241060024329 / 357241060024287 |
| H/W Version v2.1.0 |                                   |
| S/W Version        | R21.5e                            |

### 1.1.2 Specification of the Equipment under Test (EUT)

| RF General Information |                   |                        |                |           |  |  |
|------------------------|-------------------|------------------------|----------------|-----------|--|--|
| Frequency Range (MHz)  | Bluetooth<br>Mode | Ch. Frequency<br>(MHz) | Channel Number | Data Rate |  |  |
| 2400-2483.5            | BR V4.1           | 2402-2480              | 0-78 [79]      | 1 Mbps    |  |  |
| 2400-2483.5            | BR V4.1           | 2402-2480              | 0-78 [79]      | 2 Mbps    |  |  |
| 2400-2483.5            | BR V4.1           | 2402-2480              | 0-78 [79]      | 3 Mbps    |  |  |

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.

Note 2: Bluetooth BR uses a GFSK.

Note 3: Bluetooth EDR uses a combination of  $\pi/4$ -DQPSK and 8DPSK.

#### 1.1.3 Antenna Details

| Туре         | Type Gain (dBi) |  | Remark |  |
|--------------|-----------------|--|--------|--|
| λ/4 Monopole | -6.48           |  |        |  |

### 1.1.4 Power Supply Type of Equipment under Test (EUT)

| Power Supply Type | AC adapter: (normal output rating) 5.0Vdc, 1.8A (quick charge output rating) 9.0Vdc, 1.8A Battery: 3.75Vdc |
|-------------------|--|
|-------------------|--|

Report No.: FR4D1701AD Page: 5 of 51



### 1.1.5 Accessories

| No.   | Equipment                | Description  |
|---|--------------------------|--|
| Brand Name: Fujitsu Limited  Model Name: F50 Input rating: (quick charge) 9.0Vdc, 1.5A Output rating: (quick charge) 9.0Vdc, 1.5A |                          | Model Name: F50 Input rating: (quick charge) 9.0Vdc, 1.5A                                  |
| 2   | Battery<br>(Unremovable) | Brand Name: NTT Docomo<br>Model Name: CA54310-0061<br>Power Rating: 3.75Vdc, 3120mAh, 12Wh |

### 1.1.6 Channel List

| Frequency band (MHz) |                    |         |                    | 2400~2483.5 |                    |         |                    |
|----------------------|--------------------|---------|--------------------|-------------|--------------------|---------|--------------------|
| Channel              | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) | Channel     | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) |
| 0                    | 2402               | 20      | 2422               | 40          | 2442               | 60      | 2462               |
| 1                    | 2403               | 21      | 2423               | 41          | 2443               | 61      | 2463               |
| 2                    | 2404               | 22      | 2424               | 42          | 2444               | 62      | 2464               |
| 3                    | 2405               | 23      | 2425               | 43          | 2445               | 63      | 2465               |
| 4                    | 2406               | 24      | 2426               | 44          | 2446               | 64      | 2466               |
| 5                    | 2407               | 25      | 2427               | 45          | 2447               | 65      | 2467               |
| 6                    | 2408               | 26      | 2428               | 46          | 2448               | 66      | 2468               |
| 7                    | 2409               | 27      | 2429               | 47          | 2449               | 67      | 2469               |
| 8                    | 2410               | 28      | 2430               | 48          | 2450               | 68      | 2470               |
| 9                    | 2411               | 29      | 2431               | 49          | 2451               | 69      | 2471               |
| 10                   | 2412               | 30      | 2432               | 50          | 2452               | 70      | 2472               |
| 11                   | 2413               | 31      | 2433               | 51          | 2453               | 71      | 2473               |
| 12                   | 2414               | 32      | 2434               | 52          | 2454               | 72      | 2474               |
| 13                   | 2415               | 33      | 2435               | 53          | 2455               | 73      | 2475               |
| 14                   | 2416               | 34      | 2436               | 54          | 2456               | 74      | 2476               |
| 15                   | 2417               | 35      | 2437               | 55          | 2457               | 75      | 2477               |
| 16                   | 2418               | 36      | 2438               | 56          | 2458               | 76      | 2478               |
| 17                   | 2419               | 37      | 2439               | 57          | 2459               | 77      | 2479               |
| 18                   | 2420               | 38      | 2440               | 58          | 2460               | 78      | 2480               |
| 19                   | 2421               | 39      | 2441               | 59          | 2461               |         |                    |

Report No.: FR4D1701AD Page: 6 of 51



# 1.1.7 Test Tool and Duty Cycle

| Test Tool | QRCT, version 3.0.54.0 |
|-----------|------------------------|
|           | 4. 10 1, 10 10 10 10   |

### 1.1.8 Power Setting

| Madulation Mada | Test Frequency (MHz) |      |      |  |
|-----------------|----------------------|------|------|--|
| Modulation Mode | 2402                 | 2441 | 2480 |  |
| GFSK/1Mbps      | 9                    | 9    | 9    |  |
| 8DPSK/3Mbps     | 9                    | 9    | 9    |  |

Report No.: FR4D1701AD Page: 7 of 51





## 1.2 Local Support Equipment List

|     | Support Equipment List |               |                  |     |        |                            |  |  |
|-----|------------------------|---------------|------------------|-----|--------|----------------------------|--|--|
| No. | Equipment              | Brand         | Model            | S/N | FCC ID | Signal cable / Length (m)  |  |  |
| 1   | Adapter                | NTT<br>docomo | AC Adaptor<br>05 |     |        |                            |  |  |
| 2   | Earphone               | APPLE         | MD827FE/A        | 6   |        | 1.2m non-shielded w/o core |  |  |

Note: Item 1 was provided by client.

### 1.3 Test Setup Chart





Report No.: FR4D1701AD Page: 8 of 51



# 1.4 The Equipment List

| Test Item   | RF Conducted |           |            |                  |                   |  |  |  |
|---|--------------|-----------|------------|------------------|-------------------|--|--|--|
| Test Site   | (TH01-WS)    |           |            |                  |                   |  |  |  |
| Instrument  | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Until |  |  |  |
| Spectrum Analyzer   | R&S          | FSV40     | 101063     | Feb. 03, 2015    | Feb. 02, 2016     |  |  |  |
| Power Meter   | Anritsu      | ML2495A   | 1241002    | Sep. 29, 2014    | Sep. 28, 2015     |  |  |  |
| Power Sensor  | Anritsu      | MA2411B   | 1207366    | Sep. 29, 2014    | Sep. 28, 2015     |  |  |  |
| Measurement<br>Software   | Sporton      | Sporton_1 | 1.3.30     | NA               | NA                |  |  |  |
| Note: Calibration Interval of instruments listed above is one year. |              |           |            |                  |                   |  |  |  |

| Test Item               | Radiated Emission           |                         |                     |                  |                   |  |  |  |  |  |  |
|-------------------------|-----------------------------|-------------------------|---------------------|------------------|-------------------|--|--|--|--|--|--|
| Test Site               | 966 chamber 3 / (03CH03-WS) |                         |                     |                  |                   |  |  |  |  |  |  |
| Instrument              | Manufacturer                | Model No.               | Serial No.          | Calibration Date | Calibration Until |  |  |  |  |  |  |
| Spectrum Analyzer       | Agilent                     | N9010A                  | MY53400091          | Sep. 16, 2014    | Sep. 15, 2015     |  |  |  |  |  |  |
| Receiver                | Agilent                     | N9038A                  | MY53290044          | Oct. 21, 2014    | Oct. 20, 2015     |  |  |  |  |  |  |
| Bilog Antenna           | SCHWARZBECK                 | VULB9168                | VULB9168-562        | Jan. 19, 2015    | Jan. 18, 2016     |  |  |  |  |  |  |
| Horn Antenna<br>1G-18G  | SCHWARZBECK                 | BBHA 9120 D             | BBHA 9120 D 1206    | Feb. 03, 2015    | Feb. 02, 2016     |  |  |  |  |  |  |
| Horn Antenna<br>18G-40G | SCHWARZBECK                 | BBHA 9170               | BBHA 9170517        | Nov. 10, 2014    | Nov. 09, 2015     |  |  |  |  |  |  |
| Loop Antenna            | R&S                         | HFH2-Z2                 | 11900               | Nov. 10, 2014    | Nov. 09, 2015     |  |  |  |  |  |  |
| Preamplifier            | EMC                         | EMC02325                | 980187              | Sep. 26, 2014    | Sep. 25, 2015     |  |  |  |  |  |  |
| Preamplifier            | Agilent                     | 83017A                  | MY53270014          | Sep. 17, 2014    | Sep. 16, 2015     |  |  |  |  |  |  |
| Preamplifier            | EMC                         | EMC184045B              | 980192              | Aug. 26, 2014    | Aug. 25, 2015     |  |  |  |  |  |  |
| RF cable-3M             | HUBER+SUHNER                | SUCOFLEX104             | MY22620/4           | Feb. 09, 2015    | Feb. 08, 2016     |  |  |  |  |  |  |
| RF cable-8M             | HUBER+SUHNER                | SUCOFLEX104             | MY22601/4           | Feb. 09, 2015    | Feb. 08, 2016     |  |  |  |  |  |  |
| RF cable-1M             | HUBER+SUHNER                | SUCOFLEX104             | MY22624/4           | Feb. 09, 2015    | Feb. 08, 2016     |  |  |  |  |  |  |
| LF cable-0.8M           | EMC                         | EMC8D-NM-NM-800         | EMC8D-NM-NM-800-001 | Feb. 09, 2015    | Feb. 08, 2016     |  |  |  |  |  |  |
| LF cable-3M             | EMC                         | EMC8D-NM-NM-3000        | 131103              | Feb. 09, 2015    | Feb. 08, 2016     |  |  |  |  |  |  |
| LF cable-13M            | EMC                         | EMC8D-NM-NM-13000       | 131104              | Feb. 09, 2015    | Feb. 08, 2016     |  |  |  |  |  |  |
| Measurement<br>Software | AUDIX                       | e3                      | 6.120210g           | NA               | NA                |  |  |  |  |  |  |
| Note: Calibration Int   | erval of instruments lis    | sted above is one year. |                     |                  |                   |  |  |  |  |  |  |

| Test Item   | Conducted Emission            |                  |               |                  |                   |  |  |  |  |
|---|-------------------------------|------------------|---------------|------------------|-------------------|--|--|--|--|
| Test Site   | Conduction room 1 / (CO01-WS) |                  |               |                  |                   |  |  |  |  |
| Instrument  | Manufacturer                  | Model No.        | Serial No.    | Calibration Date | Calibration Until |  |  |  |  |
| EMC Receiver  | R&S                           | ESCS 30          | 100169        | Oct. 17, 2014    | Oct. 16, 2015     |  |  |  |  |
| LISN  | SCHWARZBECK                   | Schwarzbeck 8127 | 8127-667      | Nov. 17, 2014    | Nov. 16, 2015     |  |  |  |  |
| RF Cable-CON  | Woken                         | CFD200-NL        | CFD200-NL-001 | Dec. 31, 2014    | Dec. 30, 2015     |  |  |  |  |
| Measurement<br>Software   | AUDIX                         | e3               | 6.120210k     | NA               | NA                |  |  |  |  |
| Note: Calibration Interval of instruments listed above is one year. |                               |                  |               |                  |                   |  |  |  |  |

Report No.: FR4D1701AD Page: 9 of 51



### 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 FCC Public notice DA 00-705 ANSI C63.10-2013

# 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

| Measurement Uncertainty  |             |  |  |  |  |  |
|--------------------------|-------------|--|--|--|--|--|
| Parameters               | Uncertainty |  |  |  |  |  |
| Bandwidth                | ±34.134 Hz  |  |  |  |  |  |
| Conducted power          | ±0.808 dB   |  |  |  |  |  |
| Power density            | ±0.463 dB   |  |  |  |  |  |
| Conducted emission       | ±2.670 dB   |  |  |  |  |  |
| AC conducted emission    | ±2.92 dB    |  |  |  |  |  |
| Radiated emission ≤ 1GHz | ±3.99 dB    |  |  |  |  |  |
| Radiated emission > 1GHz | ±5.52 dB    |  |  |  |  |  |

Report No.: FR4D1701AD Page: 10 of 51



# 2 Test Configuration

## 2.1 Testing Condition

| Test Item          | Test Site | Ambient Condition | Tested By  |
|--------------------|-----------|-------------------|------------|
| AC Conduction      | CO01-WS   | 18°C / 76%        | Peter Lin  |
| Radiated Emissions | 03CH03-WS | 20°C / 64-65%     | Aska Huang |
| RF Conducted       | TH01-WS   | 22°C / 65%        | Brad Wu    |

➤ FCC site registration No.: 390588➤ IC site registration No.: 10807C-1

## 2.2 The Worst Test Modes and Channel Details

| Test item                  | Mode                       | Test Frequency<br>(MHz)                                  | Data Rate (Mbps)        | Test Configuration |
|----------------------------|----------------------------|--|-------------------------|--------------------|
| Conducted Emissions        | GFSK                       | 2441   | 1Mbps                   | 1, 2               |
| Radiated Emissions ≤ 1GHz  | GFSK                       | 2441   | 1Mbps                   | 1, 2               |
| Radiated Emissions > 1GHz  | GFSK<br>8DPSK              | 2402, 2441, 2480<br>2402, 2441, 2480                     | 1Mbps<br>3Mbps          | 1                  |
| Conducted Output Power     | GFSK<br>л/4 QDPSK<br>8DPSK | 2402, 2441, 2480<br>2402, 2441, 2480<br>2402, 2441, 2480 | 1Mbps<br>2Mbps<br>3Mbps | 1                  |
| Number of Hopping Channels | GFSK<br>8DPSK              | 2402~2480<br>2402~2480                                   | 1Mbps<br>3Mbps          | 1                  |
| Hopping Channel Separation | GFSK<br>8DPSK              | 2402, 2441, 2480<br>2402, 2441, 2480                     | 1Mbps<br>3Mbps          | 1                  |
| Dwell Time                 | GFSK<br>8DPSK              | 2441<br>2441   | 1Mbps<br>3Mbps          | 1                  |

#### NOTE:

- 1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
- 2. The EUT had been tested by following test configurations for radiated emission below 1GHz.
  - 1) Configuration 1 : Adapter mode
  - 2) Configuration 2 : Cradle mode
- Adapter and cradle mode had been pretested for radiated emission above 1GHz and found that the adapter mode was the worst case and was selected for final test.

Report No.: FR4D1701AD Page: 11 of 51



### 3 Transmitter Test Results

#### 3.1 Conducted Emissions


#### 3.1.1 Limit of Conducted Emissions

| Conducted Emissions Limit                                |    |    |  |  |  |  |  |
|--|----|----|--|--|--|--|--|
| Frequency Emission (MHz) Quasi-Peak Average              |    |    |  |  |  |  |  |
| 0.15-0.5 66 - 56 * 56 - 46 *                             |    |    |  |  |  |  |  |
| 0.5-5  | 56 | 46 |  |  |  |  |  |
| 5-30   | 60 | 50 |  |  |  |  |  |
| Note 1: * Decreases with the logarithm of the frequency. |    |    |  |  |  |  |  |

#### 3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz

#### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR4D1701AD Page: 12 of 51



#### 3.1.4 Test Result of Conducted Emissions



Report No.: FR4D1701AD Page: 13 of 51




| Modulation                                | GFSK  |                              | Test Freq. (N                                    | IHz)   | 2441            |
|---|---|------------------------------|--|--|-----------------|
| Power Phase                               | Neutral   |                              | Test Configu                                     | 1  |                 |
| 80 Level (dBu                             | uV)   |                              |  |  |                 |
| 70  |   |                              |  | CIS  | SPR/CNS/VCCI-B  |
| 50  |   |                              |  | CISPF  | R/CNS/VCCI-B AV |
| 30  |   |                              |  | W 40 por service of the service of t | Philippy        |
| 10  |   |                              |  | 11   |                 |
| 0 <mark>    </mark><br>0.150.2            | 0.5   |                              |  | 5 10   | 20 30           |
| Freq                                      | n Level Limit                                   | Freque<br>Over Read          | ency (MHz)                                       |  |                 |
| MHz                                       | Line<br>z dBuV dBuV                             | Limit Level to               | factor loss<br>dB dB                             | Remark   |                 |
| 1 0.155<br>2 0.155<br>3* 0.567            | 42.50 65.52                                     | -16.55 38.16<br>-23.02 41.69 | 0.73 0.08<br>0.73 0.08                           | Average<br>QP  |                 |
| 4 0.567<br>5 0.779<br>6 0.779             | 7 43.40 56.00<br>9 29.03 46.00<br>9 33.22 56.00 |                              | 0.18 0.13<br>0.18 0.13<br>0.23 0.15<br>0.23 0.15 | Average<br>QP<br>Average<br>QP   |                 |
| 7 2.513<br>8 2.513<br>9 2.962<br>10 2.962 | 35.76 56.00<br>31.70 46.00                      | -14.30 30.90                 | 0.39 0.26<br>0.39 0.26<br>0.52 0.28<br>0.52 0.28 | Average<br>QP<br>Average<br>QP   |                 |
| 11 3.509<br>12 3.509                      |   |                              | 0.64 0.30<br>0.64 0.30                           | Average<br>QP  |                 |
|   |   |                              |  |  |                 |
|   |   |                              |  |  |                 |
|   |   |                              |  |  |                 |
|   |   |                              |  |  |                 |
|   |   |                              |  |  |                 |
|   |   |                              |  |  |                 |

Report No.: FR4D1701AD Page: 14 of 51



| Power PhaseLineTest Configuration2 | Modulation  | GFSK       | Test Freq. (MHz)   | 2441 |
|------------------------------------|-------------|------------|--------------------|------|
|                                    | Power Phase | Line       | Test Configuration | 2    |
|                                    |             |            |                    |      |
|                                    |             |            |                    |      |
| 80 Level (dBuV)                    | Level (dBu\ | <b>(</b> ) |                    |      |



|    | Freq  | Level | Limit | Over   | Read  | LISN   | cable |         |
|----|-------|-------|-------|--------|-------|--------|-------|---------|
|    |       |       | Line  | Limit  | Level | factor | loss  | Remark  |
|    | MHz   | dBu∀  | dBuV  | dB     | dBu∀  | dB     | dB    |         |
|    |       |       |       |        |       |        |       |         |
| 1  | 0.150 | 34.47 | 56.00 | -21.53 | 33.47 | 0.92   | 0.08  | Average |
| 2  | 0.150 | 46.95 | 66.00 | -19.05 | 45.95 | 0.92   | 0.08  | QP      |
| 3* | 0.552 | 39.52 | 46.00 | -6.48  | 39.24 | 0.15   | 0.13  | Average |
| 4  | 0.552 | 42.85 | 56.00 | -13.15 | 42.57 | 0.15   | 0.13  | QP      |
| 5  | 2.155 | 27.01 | 46.00 | -18.99 | 26.17 | 0.59   | 0.25  | Average |
| 6  | 2.155 | 33.27 | 56.00 | -22.73 | 32.43 | 0.59   | 0.25  | QP      |
| 7  | 2.993 | 29.12 | 46.00 | -16.88 | 28.43 | 0.41   | 0.28  | Average |
| 8  | 2.993 | 34.74 | 56.00 | -21.26 | 34.05 | 0.41   | 0.28  | QP      |
| 9  | 3.528 | 29.86 | 46.00 | -16.14 | 29.23 | 0.33   | 0.30  | Average |
| 10 | 3.528 | 36.64 | 56.00 | -19.36 | 36.01 | 0.33   | 0.30  | QP      |
| 11 | 4.224 | 26.24 | 46.00 | -19.76 | 25.65 | 0.28   | 0.31  | Average |
| 12 | 4.224 | 34.68 | 56.00 | -21.32 | 34.09 | 0.28   | 0.31  | QP      |
|    |       |       |       |        |       |        |       |         |

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB). 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV)

Report No.: FR4D1701AD Page: 15 of 51



| Modulation          | GFSK<br>Neutral         |                         |                       | Test Freq. (MHz) Test Configuration |                         |                      |                      | 2441   |             |   |
|---------------------|-------------------------|-------------------------|-----------------------|-------------------------------------|-------------------------|----------------------|----------------------|--|-------------|---|
| Power Phase         |                         |                         |                       |                                     |                         |                      |                      |  |             |   |
| 80 <mark>Lev</mark> | el (dBu                 | V)                      |                       |                                     |                         |                      |                      |  |             |   |
| 70                  |                         |                         |                       |                                     |                         |                      |                      |  | CISPR/      | CNS/VCCI-B  |
| 50                  |                         |                         | 4                     |                                     |                         |                      |                      | С  | ISPR/CN     | S/VCCI-B AV   |
| 30                  |                         |                         |                       |                                     |                         | 51                   |                      | My Water Manager and the Water Andrews and t | why produpp | [A <sub>thile</sub>   |
| 20<br>10            |                         |                         |                       |                                     |                         |                      |                      |  |             | "INPLANTATION OF THE PROPERTY |
| 0<br>0.15           | 50.2                    |                         | 0.5                   |                                     |                         | 2                    |                      | 5  | 10          | 20 30   |
|                     |                         |                         |                       |                                     | Frequ                   | ency (MH             |                      |  |             |   |
|                     | Freq<br>MHz             | Level<br>dBuV           | Limit<br>Line<br>dBuV | Over<br>Limit<br>dB                 | Read<br>Level<br>dBuV   | LISN<br>factor<br>dB | cable<br>loss<br>dB  | Remark   |             |   |
| 1<br>_ 2            | 0.153<br>0.153          | 37.23<br>41.99          | 55.82<br>65.82        | <br>-18.59<br>-23.83                | 36.33<br>41.09          | 0.82<br>0.82         | 0.08                 | <br>Average<br>QP  | _           |   |
| 3*<br>4             | 0.567                   | 40.31                   | 46.00<br>56.00        | -5.69<br>-11.07                     | 40.00                   | 0.18                 | 0.13                 | Average<br>QP  |             |   |
| 5<br>6<br>7         | 2.261<br>2.261<br>3.041 | 25.49<br>35.86<br>33.21 | 56.00                 | -20.51<br>-20.14<br>-12.79          | 24.93<br>35.30<br>32.40 | 0.31<br>0.31<br>0.53 | 0.25<br>0.25<br>0.28 | Average<br>QP<br>Average   |             |   |
| 8<br>9<br>10        | 3.041<br>3.364<br>3.364 | 29.58<br>41.54          | 56.00                 | -16.42<br>-14.46                    | 38.13<br>28.68<br>40.64 | 0.53<br>0.61<br>0.61 | 0.28<br>0.29<br>0.29 | QP<br>Average<br>QP  |             |   |
| 11<br>12            | 3.922<br>3.922          | 27.35<br>37.95          |                       | -18.65<br>-18.05                    | 26.32<br>36.92          | 0.72<br>0.72         | 0.31                 | _  |             |   |
|                     |                         |                         |                       |                                     |                         |                      |                      |  |             |   |
|                     |                         |                         |                       |                                     |                         |                      |                      |  |             |   |
|                     |                         |                         |                       |                                     |                         |                      |                      |  |             |   |
|                     |                         |                         |                       |                                     |                         |                      |                      |  |             |   |
|                     |                         |                         |                       |                                     |                         |                      |                      |  |             |   |
|                     |                         |                         |                       |                                     |                         |                      |                      |  |             |   |

Report No.: FR4D1701AD Page: 16 of 51



### 3.2 Unwanted Emissions into Restricted Frequency Bands

#### 3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

| Restricted Band Emissions Limit |                       |                         |                      |  |  |  |  |  |  |
|---------------------------------|-----------------------|-------------------------|----------------------|--|--|--|--|--|--|
| Frequency Range (MHz)           | Field Strength (uV/m) | Field Strength (dBuV/m) | Measure Distance (m) |  |  |  |  |  |  |
| 0.009~0.490                     | 2400/F(kHz)           | 48.5 - 13.8             | 300                  |  |  |  |  |  |  |
| 0.490~1.705                     | 24000/F(kHz)          | 33.8 - 23               | 30                   |  |  |  |  |  |  |
| 1.705~30.0                      | 30                    | 29                      | 30                   |  |  |  |  |  |  |
| 30~88                           | 100                   | 40                      | 3                    |  |  |  |  |  |  |
| 88~216                          | 150                   | 43.5                    | 3                    |  |  |  |  |  |  |
| 216~960                         | 200                   | 46                      | 3                    |  |  |  |  |  |  |
| Above 960                       | 500                   | 54                      | 3                    |  |  |  |  |  |  |

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:** 

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.2.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. Radiated emission above 1GHz / Peak value RBW=1MHz, VBW=3MHz and Peak detector

Radiated emission above 1GHz / Average value for harmonics

The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:


3. 
$$20\log \text{ (Duty cycle)} = 20\log \frac{1\text{s} / 1600 * 5}{100 \text{ ms}} = -30.1 \text{dB}$$

4. Radiated emission above 1GHz / Average value for other emissions RBW=1MHz, VBW=1/T and Peak detector

Report No.: FR4D1701AD Page: 17 of 51




### 3.2.3 Test Setup



Report No.: FR4D1701AD Page: 18 of 51



#### 3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR4D1701AD Page: 19 of 51



| Modulation   | GFSK     | Test Freq. (MHz)   | 2441 |
|--------------|----------|--------------------|------|
| Polarization | Vertical | Test Configuration | 1    |



|   | Freq.  | Emission<br>level | Limit  | Margin | SA<br>reading |        | Remark | ANT<br>High | Turn<br>Table |
|---|--------|-------------------|--------|--------|---------------|--------|--------|-------------|---------------|
|   | MHz    | dBuV/m            | dBuV/m | dB     | dBuV          | dB     |        | cm          | deg           |
| 1 | 45.52  | 34.13             | 40.00  | -5.87  | 46.96         | -12.83 | Peak   |             |               |
| 2 | 103.72 | 22.81             | 43.50  | -20.69 | 40.57         | -17.76 | Peak   |             |               |
| 3 | 286.08 | 27.22             | 46.00  | -18.78 | 40.42         | -13.20 | Peak   |             |               |
| 4 | 394.72 | 34.52             | 46.00  | -11.48 | 44.69         | -10.17 | Peak   |             |               |
| 5 | 655.65 | 25.77             | 46.00  | -20.23 | 30.65         | -4.88  | Peak   |             |               |
| 6 | 780.78 | 34.41             | 46.00  | -11.59 | 37.21         | -2.80  | Peak   |             |               |


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR4D1701AD Page: 20 of 51



| Modulation   | GFSK       | Test Freq. (MHz)   | 2441 |
|--------------|------------|--------------------|------|
| Polarization | Horizontal | Test Configuration | 2    |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Ū      | SA<br>reading<br>dBuV |        | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------|-----------------------|--------|--------|-------------------|----------------------|
|   |              |                             |                 |        |                       |        |        |                   |                      |
| 1 | 46.49        | 25.38                       | 40.00           | -14.62 | 38.23                 | -12.85 | Peak   |                   |                      |
| 2 | 102.75       | 23.41                       | 43.50           | -20.09 | 41.34                 | -17.93 | Peak   |                   |                      |
| 3 | 256.01       | 20.55                       | 46.00           | -25.45 | 35.07                 | -14.52 | Peak   |                   |                      |
| 4 | 586.78       | 25.05                       | 46.00           | -20.95 | 31.12                 | -6.07  | Peak   |                   |                      |
| 5 | 781.75       | 30.57                       | 46.00           | -15.43 | 33.37                 | -2.80  | Peak   |                   |                      |
| 6 | 956.35       | 31.51                       | 46.00           | -14.49 | 31.18                 | 0.33   | Peak   |                   |                      |

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR4D1701AD Page: 21 of 51



| Modulation   |    |       | G       | FSK     |       |        |        | Test  | Fre           | q. (MHz       | <u>z</u> ) |      | 2441 |      |       |
|--------------|----|-------|---------|---------|-------|--------|--------|-------|---------------|---------------|------------|------|------|------|-------|
| Polarization |    |       | Ve      | ertical |       |        |        | Test  | Cor           | figurat       | ion        |      | 2    |      |       |
|              |    |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              | 90 | Level | (dBuV/m | )       |       |        |        |       |               |               |            |      |      |      |       |
|              |    |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              | 80 |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              | 70 |       |         | -       |       |        |        |       | $\rightarrow$ |               |            | +    |      |      | _     |
|              | 60 |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              | •  |       |         |         |       |        |        |       |               |               |            |      | FCC  | CLAS | S-B   |
|              | 50 |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              | 40 |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              |    | 23    |         |         |       |        |        |       |               |               | 6<br>I     |      |      |      |       |
|              | 30 | ΗŤ    |         |         |       |        |        | !     | 5             |               |            |      |      |      |       |
|              | 20 |       | 4       |         |       |        |        |       |               |               |            |      |      |      |       |
|              |    |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              | 10 |       |         |         |       |        |        |       |               |               |            |      |      |      |       |
|              | 0  | 30 1  | 00.     | 200.    | 30    | 0. 40  | 00. 5  | 00.   | 600           | ). <b>7</b> 0 | 0.         | 800. | 90   | 00.  | 1000  |
|              |    |       |         |         | -     |        | Frequ  |       |               |               |            |      |      |      |       |
|              |    |       | Freq    | . Emi:  | ssion | Limit  | Margi  | s - S | А             | Factor        | Ren        | nark | Α    | NT   | Turn  |
|              |    |       |         |         | evel  |        |        |       | ding          |               |            |      | Н    | igh  | Table |
|              |    |       | MHz     | dB      | uV/m  | dBuV/r | n dB   | dB    | uV            | dB            |            |      | C    | m    | deg   |
| 1            |    |       | 30.     | 00 3    | 4.49  | 40.00  | -5.51  | 47    | .98           | -13.49        | Pea        | ale. |      |      |       |
| 2            |    |       | 45.     |         | 1.45  | 40.00  |        |       | . 28          | -12.83        |            |      |      |      |       |
| 3            |    |       | 61.     |         | 9.98  |        | -10.02 |       | .40           | -14.42        |            |      |      |      |       |
| 4            |    |       | 164.    |         |       |        | -24.10 |       |               | -13.85        |            |      |      |      |       |
| 5            |    |       | 559.    | 62 2    | 4.89  |        | -21.11 |       | .69           | -6.80         | ) Pea      | ak   |      |      |       |
| 6            |    |       | 779.    | 81 3    | 4.23  | 46.00  | -11.77 | 37    | .04           | -2.81         | l Pea      | ak   |      |      |       |

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR4D1701AD Page: 22 of 51



#### 3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 23 of 51



| odulation   | GFSK        |                      | Test Freq. (MHz)         | 24       | 2402        |  |  |
|-------------|-------------|----------------------|--------------------------|----------|-------------|--|--|
| olarization | Vertica     | al                   |                          | •        |             |  |  |
| on Leve     | el (dBuV/m) |                      |                          |          |             |  |  |
| 30          |             |                      |                          |          |             |  |  |
| 80          |             |                      |                          | F        | CC CLASS-B  |  |  |
| 70          |             |                      |                          |          |             |  |  |
| 60          |             |                      |                          | FCC CI   | ASS-B (AVG) |  |  |
| 50 2        | 4 6         |                      |                          | FCCCL    | A33-B (AVG) |  |  |
| 40          |             |                      |                          |          |             |  |  |
| 30          |             |                      |                          |          |             |  |  |
|             |             |                      |                          |          |             |  |  |
| 20          |             |                      |                          |          |             |  |  |
| 10          |             |                      |                          |          |             |  |  |
| 0 100       | 0 4000. 600 | 00. 8000. 10000. 120 | 00. 14000. 16000. 18000. | 20000 00 | 000. 250    |  |  |

|   | Freq. [ | mission<br>level | Limit  | Margin | SA<br>reading | Factor | Remark  | ANT<br>High | Turn<br>Table |
|---|---------|------------------|--------|--------|---------------|--------|---------|-------------|---------------|
|   | MHz     | dBuV/m           | dBuV/m | dB     | dBuV          | dB     |         | cm          | deg           |
| 1 | 1500.00 | 35.47            | 54.00  | -18.53 | 39.30         | -3.83  | Average |             |               |
| 2 | 1500.00 | 49.01            | 74.00  | -24.99 | 52.84         | -3.83  | Peak    |             |               |
| 3 | 2390.00 | 36.00            | 54.00  | -18.00 | 37.22         | -1.22  | Average |             |               |
| 4 | 2390.00 | 49.21            | 74.00  | -24.79 | 50.43         | -1.22  | Peak    |             |               |
| 5 | 4804.00 | 17.87            | 54.00  | -36.13 | 10.76         | 7.11   | Average |             |               |
| 6 | 4804.00 | 47.97            | 74.00  | -26.03 | 40.86         | 7.11   | Peak    |             |               |

Frequency (MHz)

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 24 of 51



| Modulation   |    |       | GI       | FSK   |                |      |      |     | Т                | est | Fred | q. (M  | Hz)           |        | 2           | 2441    |        |            |
|--------------|----|-------|----------|-------|----------------|------|------|-----|------------------|-----|------|--------|---------------|--------|-------------|---------|--------|------------|
| Polarization |    |       | Н        | orizo | ntal           |      |      |     | ,                |     |      |        |               |        |             |         |        |            |
|              |    |       |          |       |                |      |      |     |                  |     |      |        |               |        |             |         |        |            |
|              | 90 | Level | (dBuV/m) |       |                |      |      |     |                  |     |      |        |               |        |             |         |        | _          |
|              | 80 |       |          |       |                |      |      |     |                  |     |      |        |               |        |             |         |        | _          |
|              | 70 |       |          |       |                |      |      |     |                  |     |      |        |               |        |             | FCC CL  | ASS    | - <u>B</u> |
|              |    |       |          |       |                |      |      |     |                  |     |      |        |               |        |             |         |        |            |
|              | 60 |       |          |       | 6              |      |      |     |                  |     |      |        |               |        | FCC (       | CLASS-E | (AV    | <u>G)</u>  |
|              | 50 |       | 2        | 4     | Ť              |      |      |     |                  |     |      |        | $\rightarrow$ |        |             |         | +      |            |
|              | 40 |       |          |       |                |      |      |     |                  |     |      |        | _             |        |             |         | _      | _          |
|              | 30 |       |          |       |                |      |      |     |                  |     |      |        |               |        |             |         |        |            |
|              |    |       |          |       | 5              |      |      |     |                  |     |      |        |               |        |             |         |        |            |
|              | 20 |       |          |       |                |      |      |     |                  |     |      |        |               |        |             |         |        |            |
|              | 10 |       |          |       |                |      |      |     |                  |     |      |        |               |        |             |         | $\top$ |            |
|              | 0  | 1000  | 4000.    | 60    | 00. 8          | 000. | 100  |     | 12000.<br>requer |     |      | 16000. | 1800          | 00. 20 | 0000.       | 22000.  | 2      | 5000       |
|              |    |       | Freq.    | Emi   | issio          | n Li | mit  | Ma  | rgin             | 5   | Α .  | Fact   | tor           | Ren    | nark        | ANT     |        | Turn       |
|              |    |       |          | ]     | level          |      |      |     |                  | rea | ding |        |               |        |             | Hig     | h i    | Tabl       |
|              |    |       | MHz      | dE    | BuV/m          | dB   | uV/r | n d | В                | dB  | uV   | dE     | В             |        |             | cm      |        | deg        |
|              | 1  |       | 2483.5   | 0 3   | 36.42          | 54   | .00  | -17 | .58              | 37  | .31  | -0.    | .89           | Ave    | erage       |         | _      |            |
|              | 2  |       | 2483.5   | 0 4   | 19.65          | 74   | .00  | -24 | .35              |     | .54  |        | .89           | Pea    | ak          |         | -      |            |
|              | 3  |       | 4882.6   |       |                |      |      |     |                  |     | .66  |        | .77           |        | erage       |         | -      |            |
|              | 4  |       | 4882.6   |       |                |      |      |     |                  |     | .76  |        | .77           | Pea    |             |         | -      |            |
|              | 5  |       | 7323.6   |       | 21.17<br>51.27 |      |      |     |                  | 10  | .18  | 10.    | .99           | Αve    | erage<br>ak |         | -      |            |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 25 of 51

Report Version: Rev. 01



| Modulation    | GFSK     | Test I | Freq. (MHz) | 2441 |  |  |
|---------------|----------|--------|-------------|------|--|--|
| Polarization  | Vertical |        |             |      |  |  |
| 90 Level (dBu | //m)     |        |             |      |  |  |
| 90            |          |        |             |      |  |  |




|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Ū      | SA<br>reading<br>dBuV | Factor<br>dB | Remark  | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------|-----------------------|--------------|---------|-------------------|----------------------|
| 1 | 2483.50      | 36.37                       | 54.00           | -17.63 | 37.26                 | -0.89        | Average |                   |                      |
| 2 | 2483.50      | 49.69                       | 74.00           | -24.31 | 50.58                 | -0.89        | Peak    |                   |                      |
| 3 | 4882.00      | 17.86                       | 54.00           | -36.14 | 11.09                 | 6.77         | Average |                   |                      |
| 4 | 4882.00      | 47.96                       | 74.00           | -26.04 | 41.19                 | 6.77         | Peak    |                   |                      |
| 5 | 7323.00      | 21.41                       | 54.00           | -32.59 | 10.42                 | 10.99        | Average |                   |                      |
| 6 | 7323.00      | 51.51                       | 74.00           | -22.49 | 40.52                 | 10.99        | Peak    |                   |                      |

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Page: 26 of 51 Report No.: FR4D1701AD





\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 27 of 51



2

3

4

5

6

| Modulation   |          | GFS      | K                |            | 1      | est Fred                | լ. (MHz)   |            | 2480        |               |
|--------------|----------|----------|------------------|------------|--------|-------------------------|------------|------------|-------------|---------------|
| Polarization |          | Verti    | ical             |            | •      |                         |            |            |             |               |
|              | on Level | (dBuV/m) |                  |            |        |                         |            |            |             |               |
|              | 80       |          |                  |            |        |                         |            |            | FCC CLAS    | c D           |
|              | 70       |          |                  |            |        |                         |            |            | FCC CLAS    | 3-6           |
|              | 60       |          | 6                |            |        |                         |            | FCC        | CLASS-B (A  | VG)           |
|              | 50       | 2 4      | 1 1              |            |        |                         |            |            |             |               |
|              | 40       | 1        |                  |            |        |                         |            |            |             |               |
|              | 30       |          | 5                |            |        |                         |            |            |             |               |
|              | 20       | 3        |                  |            |        |                         |            |            |             |               |
|              | 10       |          |                  |            |        |                         |            |            |             |               |
|              | 1000     | 4000.    | 6000. 80         | 00. 10000. |        | . 14000. 1<br>ncy (MHz) | 6000. 1800 | 00. 20000. | 22000.      | 25000         |
|              |          | Freq. [  | mission<br>level | Limit M    | Margin | SA<br>reading           | Factor     | Remark     | ANT<br>High | Turn<br>Table |
|              |          | MHz      | dBuV/m           | dBuV/m     | dB     | dBuV                    | dB         |            | cm          | deg           |
| :            | 1        | 2483.50  | 36.01            | 54.00 -1   | 17.99  | 36.90                   | -0.89      | Average    |             |               |

50.23

10.84

40.94

10.54

-0.89

6.46

6.46

11.27

11.27

Peak

Peak

Peak

Average

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

2483.50 49.34 74.00 -24.66

4960.00 17.30 54.00 -36.70

4960.00 47.40 74.00 -26.60


7440.00 21.81 54.00 -32.19 10.54 7440.00 51.91 74.00 -22.09 40.64

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 28 of 51



#### 3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 29 of 51



| Modulation   |             |          | 8DPSk   | ( |  | Test | Freq. | (MHz) | 24 | 02     |     |
|--------------|-------------|----------|---------|---|--|------|-------|-------|----|--------|-----|
| Polarization |             |          | Vertica | I |  |      |       |       |    |        |     |
|              | Lev         | el (dBuV | //m)    |   |  |      |       |       |    |        |     |
|              | 90 Level (d |          |         |   |  |      |       |       |    |        |     |
|              | 00          |          |         |   |  |      |       |       | F/ | C CLAC | c n |



|   | Freq.   | Emission<br>level | Limit  | Margin | SA<br>reading | Factor | Remark  | ANT<br>High | Turn<br>Table |
|---|---------|-------------------|--------|--------|---------------|--------|---------|-------------|---------------|
|   | MHz     | dBuV/m            | dBuV/m | dB     | dBuV          | dB     |         | cm          | deg           |
| 1 | 1500.00 | 35.47             | 54.00  | -18.53 | 39.30         | -3.83  | Average |             |               |
| 2 | 1500.00 | 48.76             | 74.00  | -25.24 | 52.59         | -3.83  | Peak    |             |               |
| 3 | 2390.00 | 35.79             | 54.00  | -18.21 | 37.01         | -1.22  | Average |             |               |
| 4 | 2390.00 | 49.35             | 74.00  | -24.65 | 50.57         | -1.22  | Peak    |             |               |
| 5 | 4804.00 | 17.55             | 54.00  | -36.45 | 10.44         | 7.11   | Average |             |               |
| 6 | 4804.00 | 47.65             | 74.00  | -26.35 | 40.54         | 7.11   | Peak    |             |               |

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 30 of 51



| Modulation   |    |          | 8          | 8DPSK |               |     |         |       | Test Freq. (MHz) |                      |             | 244        | 2441 |             |       |
|--------------|----|----------|------------|-------|---------------|-----|---------|-------|------------------|----------------------|-------------|------------|------|-------------|-------|
| Polarization |    | F        | Horizontal |       |               |     |         |       |                  |                      |             |            |      |             |       |
|              | 00 | Level    | (dBuV/n    | n)    |               |     |         |       |                  |                      |             |            |      |             |       |
|              |    |          |            |       |               |     |         |       |                  |                      |             |            |      |             |       |
|              | 80 |          |            |       |               |     |         |       |                  |                      |             |            | FC   | C CLAS      | S-B   |
|              | 70 |          |            |       |               |     |         |       |                  |                      |             |            |      |             |       |
|              | 60 |          |            |       |               |     |         |       |                  |                      |             |            |      |             |       |
|              |    |          | 2          |       |               | 6   |         |       |                  |                      |             | FCC        | CLA  | SS-B (A     | VG)   |
|              | 50 | <u> </u> |            | 4     |               | П   |         |       |                  |                      |             |            |      |             |       |
|              | 40 |          |            | _     |               |     |         |       |                  |                      |             |            | _    |             |       |
|              | 30 |          |            |       |               |     |         |       |                  |                      |             |            |      |             |       |
|              | 20 |          |            |       |               | 5   |         |       |                  |                      |             |            |      |             |       |
|              | 20 |          |            | ľ     |               |     |         |       |                  |                      |             |            |      |             |       |
|              | 10 |          |            |       |               |     |         |       |                  |                      |             |            |      |             |       |
|              | 0  | 1000     | 400        | 0.    | 5000.         | 800 | 00. 100 |       |                  | 14000. 1<br>cy (MHz) | 16000. 1800 | 00. 20000. | 2200 | 00.         | 25000 |
|              |    |          | Г          |       |               |     | 122.    |       |                  |                      | F+          | Damanla    |      | ANT         | Turn  |
|              |    |          | Fre        | 4. E  | missi<br>leve |     | LIMIT   | Marg  |                  | SA<br>reading        | Factor      | Remark     |      | ANI<br>High | Table |
|              |    |          | MH         | Z     |               | _   | dBuV/ı  | m dB  |                  | dBuV                 | dB          |            |      | cm          | deg   |
| :            | 1  |          | 2483       | .50   | 36.3          | 8   | 54.00   | -17.6 | 2 -              | 37.27                | -0.89       | Averag     | e    |             |       |
|              | 2  |          |            |       | 49.8          |     |         | -24.1 |                  | 50.70                | -0.89       | Peak       |      |             |       |
|              | 3  |          | 4882       |       | 17.0          |     |         | -36.9 |                  | 10.32                | 6.77        | Averag     | e    |             |       |
|              | 4  |          | 4882       | .00   | 47.1          | 9   | /4.00   | -26.8 | 1                | 40.42                | 6.77        | Peak       |      |             |       |

10.99

10.99

Average

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


7323.00 21.05 54.00 -32.95 10.06 7323.00 51.15 74.00 -22.85 40.16

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 31 of 51



| Modulation    | 8DPSK    | Test Freq. (MHz) | 2441 |  |  |  |
|---------------|----------|------------------|------|--|--|--|
| Polarization  | Vertical |                  |      |  |  |  |
| 90 Level (dBi | ıV/m)    |                  |      |  |  |  |




|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Ū      | SA<br>reading<br>dBuV | Factor<br>dB | Remark  | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------|-----------------------|--------------|---------|-------------------|----------------------|
|   |              |                             |                 |        |                       |              |         |                   |                      |
| 1 | 2483.50      | 36.10                       | 54.00           | -17.90 | 36.99                 | -0.89        | Average |                   |                      |
| 2 | 2483.50      | 49.24                       | 74.00           | -24.76 | 50.13                 | -0.89        | Peak    |                   |                      |
| 3 | 4882.00      | 17.52                       | 54.00           | -36.48 | 10.75                 | 6.77         | Average |                   |                      |
| 4 | 4882.00      | 47.62                       | 74.00           | -26.38 | 40.85                 | 6.77         | Peak    |                   |                      |
| 5 | 7323.00      | 21.18                       | 54.00           | -32.82 | 10.19                 | 10.99        | Average |                   |                      |
| 6 | 7323.00      | 51.28                       | 74.00           | -22.72 | 40.29                 | 10.99        | Peak    |                   |                      |

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 32 of 51






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 33 of 51



| Modulation    | 8DPSK    | Test Freq. | (MHz) | 2480 |  |
|---------------|----------|------------|-------|------|--|
| Polarization  | Vertical |            |       |      |  |
| 90 Level (dBu | V/m)     |            |       |      |  |
| 30            |          |            |       |      |  |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Ū      | SA<br>reading<br>dBuV | Factor<br>dB | Remark  | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------|-----------------------|--------------|---------|-------------------|----------------------|
| 1 | 2483.50      | 35.84                       | 54.00           | -18.16 | 36.73                 | -0.89        | Average |                   |                      |
| 2 | 2483.50      | 49.20                       | 74.00           | -24.80 | 50.09                 | -0.89        | Peak    |                   |                      |
| 3 | 4960.00      | 17.15                       | 54.00           | -36.85 | 10.69                 | 6.46         | Average |                   |                      |
| 4 | 4960.00      | 47.25                       | 74.00           | -26.75 | 40.79                 | 6.46         | Peak    |                   |                      |
| 5 | 7440.00      | 21.69                       | 54.00           | -32.31 | 10.42                 | 11.27        | Average |                   |                      |
| 6 | 7440.00      | 51.79                       | 74.00           | -22.21 | 40.52                 | 11.27        | Peak    |                   |                      |

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4D1701AD Page: 34 of 51



# 3.3 Unwanted Emissions into Non-Restricted Frequency Bands

#### 3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

#### 3.3.2 Test Procedures


#### **Reference Level Measurement**

- Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

#### **Unwanted Emissions Level Measurement**

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- 4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

#### 3.3.3 Test Setup




Report No.: FR4D1701AD Page: 35 of 51




# 3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands

#### **GFSK**



Report No.: FR4D1701AD Page: 36 of 51






Report No.: FR4D1701AD Page: 37 of 51




#### 8DPSK



Report No.: FR4D1701AD Page: 38 of 51





Report No.: FR4D1701AD Page: 39 of 51



# 3.4 Conducted Output Power

## 3.4.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

| 1 Watt For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.         |
|---|
| 0.125 Watt For all other frequency hopping systems in the 2400–2483.5 MHz band.   |
| 0.125 Watt For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel. |

### 3.4.2 Test Procedures

- A wideband power meter is used for power measurement. Bandwidth of power senor and meter is 50MHz
- 2 If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

## 3.4.3 Test Setup



Report No.: FR4D1701AD Page: 40 of 51



# 3.4.4 Test Result of Conducted Output Power

| Modulation Mode | Freq. (MHz) | Output Power (mW) | Output Power<br>(dBm) | Limit (mW) |
|-----------------|-------------|-------------------|-----------------------|------------|
| GFSK            | 2402        | 4.40              | 6.43                  | 125        |
| GFSK            | 2441        | 7.28              | 8.62                  | 125        |
| GFSK            | 2480        | 6.40              | 8.06                  | 125        |
| л/4 DQPSK       | 2402        | 3.33              | 5.22                  | 125        |
| л/4 DQPSK       | 2441        | 5.53              | 7.43                  | 125        |
| л/4 DQPSK       | 2480        | 5.02              | 7.01                  | 125        |
| 8DPSK           | 2402        | 3.36              | 5.26                  | 125        |
| 8DPSK           | 2441        | 5.73              | 7.58                  | 125        |
| 8DPSK           | 2480        | 5.15              | 7.12                  | 125        |

| Modulation Mode | Freq. (MHz) | AV Output Power (mW) | AV Output Power (dBm) |
|-----------------|-------------|----------------------|-----------------------|
| GFSK            | 2402        | 4.03                 | 6.05                  |
| GFSK            | 2441        | 6.68                 | 8.25                  |
| GFSK            | 2480        | 5.94                 | 7.74                  |
| л/4 DQPSK       | 2402        | 2.01                 | 3.04                  |
| л/4 DQPSK       | 2441        | 3.44                 | 5.37                  |
| л/4 DQPSK       | 2480        | 3.10                 | 4.92                  |
| 8DPSK           | 2402        | 2.02                 | 3.06                  |
| 8DPSK           | 2441        | 3.47                 | 5.40                  |
| 8DPSK           | 2480        | 3.13                 | 4.95                  |

Note: Average power is for reference only.

Report No.: FR4D1701AD Page: 41 of 51



# 3.5 Number of Hopping Frequency


# 3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

### 3.5.2 Test Procedures

- 1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
- 2 Allow trace to stabilize.


## 3.5.3 Test Setup



Report No.: FR4D1701AD Page: 42 of 51



# 3.5.4 Test Result of Number of Hopping Frequency



Report No.: FR4D1701AD Page: 43 of 51




# 3.6 20dB and Occupied Bandwidth

### 3.6.1 Test Procedures

- Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.
- 4. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

### 3.6.2 Test Setup




Report No.: FR4D1701AD Page: 44 of 51



# 3.6.3 Test result of 20dB and Occupied Bandwidth

| Modulation Mode | Freq. (MHz) | 20dB Bandwidth (MHz) | Occupied Bandwidth (MHz) |
|-----------------|-------------|----------------------|--------------------------|
| GFSK            | 2402        | 0.952                | 0.912                    |
| GFSK            | 2441        | 0.952                | 0.912                    |
| GFSK            | 2480        | 0.957                | 0.907                    |
| 8DPSK           | 2402        | 1.296                | 1.181                    |
| 8DPSK           | 2441        | 1.291                | 1.185                    |
| 8DPSK           | 2480        | 1.291                | 1.190                    |



Report No.: FR4D1701AD Page: 45 of 51



# 3.7 Channel Separation


### 3.7.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

#### 3.7.2 Test Procedures

- 1. Set RBW=100kHz, VBW=300kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

### 3.7.3 Test Setup




Report No.: FR4D1701AD Page: 46 of 51



# 3.7.4 Test result of Channel Separation

| Modulation Mode | Freq. (MHz) | Channel<br>Separation (MHz) | 20dB Bandwidth<br>(MHz) | Minimum Limit<br>(MHz) |
|-----------------|-------------|-----------------------------|-------------------------|------------------------|
| GFSK            | 2402        | 1.003                       | 0.952                   | 0.635                  |
| GFSK            | 2441        | 1.003                       | 0.952                   | 0.635                  |
| GFSK            | 2480        | 1.003                       | 0.957                   | 0.638                  |
| 8DPSK           | 2402        | 1.003                       | 1.296                   | 0.864                  |
| 8DPSK           | 2441        | 1.003                       | 1.291                   | 0.861                  |
| 8DPSK           | 2480        | 1.003                       | 1.291                   | 0.861                  |



Report No.: FR4D1701AD Page: 47 of 51



#### 3.8 Number of Dwell Time


#### 3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 3.8.2 Test Procedures

- Set RBW=100kHz,VBW=300kHz,Sweep time = 500us(DH1),2ms(DH3),4ms(DH5), Detector=Peak, Span=0Hz,Trace max hold
- 2 Enable gating and trigger function of spectrum analyzer to measure burst on time.
- 3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds, or 0.625ms. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.
- 4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds, or 1.875ms. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
- The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds

### 3.8.3 Test Setup




Report No.: FR4D1701AD Page: 48 of 51




### 3.8.4 Test Result of Dwell Time

| Modulation<br>Mode | Freq. (MHz) | Length of<br>Transmission<br>Time (msec) | Number of<br>Transmission<br>in a 31.6 (79<br>Hopping*0.4) | Result<br>(s) | Limit (s) |
|--------------------|-------------|--|--|---------------|-----------|
| GFSK-DH1           | 2441        | 0.41978                                  | 320  | 0.134         | 0.4       |
| GFSK-DH3           | 2441        | 1.67457                                  | 160  | 0.268         | 0.4       |
| GFSK-DH5           | 2441        | 2.92783                                  | 106.6  | 0.312         | 0.4       |
| 8DPSK-DH1          | 2441        | 0.41529                                  | 320  | 0.133         | 0.4       |
| 8DPSK-DH3          | 2441        | 1.68630                                  | 160  | 0.270         | 0.4       |
| 8DPSK-DH5          | 2441        | 2.94000                                  | 106.6  | 0.313         | 0.4       |



Report No.: FR4D1701AD Page: 49 of 51





Report No.: FR4D1701AD Page: 50 of 51



# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C. Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FR4D1701AD Page: 51 of 51