

FCC CERTIFICATION TEST REPORT

REPORT NO.: FC140326C05A

MODEL NO.: F-06F

FCC ID: VQK-F06F2

RECEIVED: Mar. 26, 2014

TESTED: May 27 ~ Jun. 01, 2015

ISSUED: Jun. 01, 2015

APPLICANT: FUJITSU LIMITED

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,
Kawasaki 211-8588, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan
Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 SUMMARY OF TEST RESULTS	5
2.1 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 DESCRIPTION OF TEST MODES	7
3.3 DESCRIPTION OF SUPPORT UNITS	8
3.4 CONFIGURATION OF SYSTEM UNDER TEST	9
4 TEST TYPES AND RESULTS	10
4.1 CONDUCTED EMISSIONS MEASUREMENT	10
4.1.1 LIMITS OF CONDUCTED EMISSIONS MEASUREMENT	10
4.1.2 TEST INSTRUMENTS	10
4.1.3 TEST PROCEDURES	11
4.1.4 DEVIATION FROM TEST STANDARD	11
4.1.5 TEST SETUP	12
4.1.6 EUT OPERATING CONDITIONS	12
4.1.7 TEST RESULTS	13
4.2 RADIATED EMISSIONS MEASUREMENT	17
4.2.1 LIMITS OF RADIATED EMISSIONS MEASUREMENT	17
4.2.2 TEST INSTRUMENTS	19
4.2.3 TEST PROCEDURES	21
4.2.4 DEVIATION FROM TEST STANDARD	22
4.2.5 TEST SETUP	23
4.2.6 EUT OPERATING CONDITIONS	23
4.2.7 TEST RESULTS	24
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	30
6 INFORMATION ON THE TESTING LABORATORIES	31
7 APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	32



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FC140326C05A	Original release	Jun. 01, 2015

1 CERTIFICATION

PRODUCT: Smart Phone
MODEL: F-06F
BRAND: FUJITSU
APPLICANT: FUJITSU LIMITED
TEST SAMPLE: ENGINEERING SAMPLE
TESTED: May 27 ~ Jun. 01, 2015
STANDARD: FCC Part 15, Subpart B, Class B
ICES-003:2012 Issue 5, Class B
ANSI C63.4:2009

The above equipment (Model: F-06F) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Celine Chou , **DATE** : Jun. 01, 2015
Celine Chou / Specialist

APPROVED BY : Ken Liu , **DATE** : Jun. 01, 2015
Ken Liu / Senior Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications.

EMISSION			
Standard	Test Type	Result	Remarks
FCC Part 15, Subpart B, Class B	Conducted emissions test	PASS	Meet the requirement of limit. Minimum passing margin is -10.38dB at 2.73060MHz.
ICES-003:2012 Issue 5, Class B	Radiated emissions test (30MHz~40GHz)	PASS	Meet the requirement of limit. Minimum passing margin is -4.37dB at 168.62MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Frequency	Uncertainty
Conducted emissions	150kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 1GHz	4.70 dB
	Above 1GHz	2.26 dB

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Smart Phone
MODEL NO.	F-06F
POWER SUPPLY	3.8Vdc (Battery) 5.0Vdc (Adapter or cradle or host equipment)
I/O PORTS	Refer to users' manual
ACCESSORY DEVICES	Refer to Note as below

NOTE:

1. The EUT contains the following accessories.

No.	Product	Brand	Model	Description
1	Battery	NTT docomo	F30	3.8Vdc, 2100mA , 8.0Wh Type: Li-on
2	Cradle	NTT docomo	F46	Input : 5.0Vdc, 1.5A Output : 5.0Vdc, 1.5A

2. SW version is R06.2e.
3. HW version is V2.1.0.
4. IMEI Code: 352295064890205.
5. The EUT's highest operating frequency is 5GHz. Therefore the radiated emissions tests are tested up to 40GHz.
6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

The EUT consumes power from adapter, which is designed with AC power supply of 100-240Vac, 50-60Hz or from cradle with AC power supply of 100-240Vac.

For radiated emissions below 1GHz test, the EUT has been pre-tested under the following test modes, and **test mode 4** was found to be the worst case for final test.

Test Mode	Test Condition
1	GSM 850 Idle + WIFI Idle + BT Idle + GPS RX + MP4 (SD card) + Earphone + Adapter
2	GSM 1900 Idle + WIFI Idle + BT Idle + GPS RX + MP4 (SD card) + Adapter
3	WCDMA Band 5 Idle + WIFI Idle + BT Idle + GPS RX + Camera (Front) + Earphone + Adapter
4	GSM 1900 Idle + WIFI Idle + BT Idle + GPS RX + Camera (Back) + Earphone + RFID Idle + Adapter
5	GSM 1900 Idle + WIFI Idle + BT Idle + GPS RX + RFID Idle + Battery
6	EUT Charging + Adapter + Cradle

Test results are presented in the report as below.

Test Result	Test Condition
Conducted emissions test	
A	GSM 1900 Idle + WIFI Idle + BT Idle + GPS RX + Camera (Back) + Earphone + Adapter
B	EUT Charging + Adapter + Cradle
Radiated emissions test	
A	GSM 1900 Idle + WIFI Idle + BT Idle + GPS RX + Camera (Back) + Earphone + RFID Idle + Adapter

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID	Remark
A.	Universal Radio Communication Tester	R&S	CMU 200	101095	NA	-
B.	GPS simulator	PENDULUM	GSG-54	191121	NA	-
C.	Bluetooth Earphone	ELECOM	LBT-MPHS400	NA	NA	-
D.	Wireless N Dual band Router	D-LINK	DIR-815	PVK21B5000399	KA21R815A1	-
E.	Adapter	NTT docomo	AC Adapter 04	NA	NA	I/P: 100-240Vac, 0.22A, 50-60Hz O/P: 5.0Vdc, 1.8A
F.	Earphone / Mic	PHILIPS	HL145	NA	NA	-
G.	SIM Card	R&S	CMW-Z04	NA	NA	-
H.	Micro SD Card	Transcend	8GB	NA	NA	-

NOTE:


1. All power cords of the above support units are non-shielded (1.8 m).
2. Items A-D acted as communication partners to transfer data.
3. Item E was provided by the client.

No.	Cable	Qty.	Length (m)	Shielded (Yes/ No)	Cores (Number)	Remark
1.	Earphone cable	1	1.8	N	0	-
2.	Power cable	1	1.05	N	2	Attached on adapter


NOTE: The core(s) is(are) originally attached to the cable(s).

3.4 CONFIGURATION OF SYSTEM UNDER TEST

TEST MODE A



TEST MODE B



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSIONS MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.107)

ICES-003:2012 Issue 5 (section: 6.1)

Frequency (MHz)	Class A (dBUV)		Class B (dBUV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15-0.5	79	66	66-56	56-46
0.5-5	73	60	56	46
5-30	73	60	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 11, 2014	Nov. 10, 2015
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 26, 2014	Dec. 25, 2015
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 02, 2015	Mar. 01, 2016
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 21, 2014	Jul. 20, 2015
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under Limit - 20dB was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

TEST MODE A

- Placed the EUT on the test table.
- The EUT linked with the Universal Radio Communication Tester, Wireless Router, Bluetooth Earphone and GPS Simulator, which acted as communication partners, and then set the GSM, WIFI, RFID and Bluetooth functions in idle condition.
- The EUT played MP4 function and sent audio signals to the earphone.

TEST MODE B

- Placed the EUT on the cradle and located it on the test table, the EUT was powered by cradle at charging mode.


4.1.7 TEST RESULTS

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Pon Tsai	Test Date	2015/5/27
Test Mode	A		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	1.24871	0.08	41.65	32.61	41.73	32.69	56.00	46.00	-14.27	-13.31
2	1.44812	0.09	41.77	33.51	41.86	33.60	56.00	46.00	-14.14	-12.40
3	1.57324	0.10	42.52	33.96	42.62	34.06	56.00	46.00	-13.38	-11.94
4	1.72573	0.11	42.65	34.25	42.76	34.36	56.00	46.00	-13.24	-11.64
5	2.03462	0.13	43.07	33.82	43.20	33.95	56.00	46.00	-12.80	-12.05
6	2.32396	0.15	38.67	30.49	38.82	30.64	56.00	46.00	-17.18	-15.36
7	2.73060	0.18	45.32	35.44	45.50	35.62	56.00	46.00	-10.50	-10.38
8	3.02776	0.21	43.94	33.64	44.15	33.85	56.00	46.00	-11.85	-12.15
9	4.08737	0.28	43.07	29.46	43.35	29.74	56.00	46.00	-12.65	-16.26

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Pon Tsai	Test Date	2015/5/27
Test Mode	A		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.88899	0.17	33.12	26.32	33.29	26.49	56.00	46.00	-22.71	-19.51
2	1.46767	0.21	36.09	28.94	36.30	29.15	56.00	46.00	-19.70	-16.85
3	2.05808	0.24	38.42	30.06	38.66	30.30	56.00	46.00	-17.34	-15.70
4	2.32396	0.24	38.28	31.38	38.52	31.62	56.00	46.00	-17.48	-14.38
5	2.85181	0.25	39.61	30.11	39.86	30.36	56.00	46.00	-16.14	-15.64
6	4.27896	0.28	41.25	28.82	41.53	29.10	56.00	46.00	-14.47	-16.90

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Pon Tsai	Test Date	2015/5/27
Test Mode	B		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	1.30345	0.08	40.26	31.85	40.34	31.93	56.00	46.00	-15.66	-14.07
2	1.48331	0.09	41.02	32.84	41.11	32.93	56.00	46.00	-14.89	-13.07
3	1.65144	0.11	41.71	33.35	41.82	33.46	56.00	46.00	-14.18	-12.54
4	1.78829	0.12	42.29	33.47	42.41	33.59	56.00	46.00	-13.59	-12.41
5	2.04639	0.13	41.70	32.35	41.83	32.48	56.00	46.00	-14.17	-13.52
6	2.60548	0.18	44.65	34.90	44.83	35.08	56.00	46.00	-11.17	-10.92
7	2.87479	0.20	43.34	33.58	43.54	33.78	56.00	46.00	-12.46	-12.22
8	4.10288	0.28	42.54	28.68	42.82	28.96	56.00	46.00	-13.18	-17.04

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Pon Tsai	Test Date	2015/5/27
Test Mode	B		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	1.31909	0.20	34.48	25.21	34.68	25.41	56.00	46.00	-21.32	-20.59
2	1.51850	0.21	35.08	27.65	35.29	27.86	56.00	46.00	-20.71	-18.14
3	2.12846	0.24	36.27	27.78	36.51	28.02	56.00	46.00	-19.49	-17.98
4	2.67195	0.25	38.98	29.50	39.23	29.75	56.00	46.00	-16.77	-16.25
5	2.85963	0.25	37.96	28.03	38.21	28.28	56.00	46.00	-17.79	-17.72
6	4.04436	0.27	40.29	27.23	40.56	27.50	56.00	46.00	-15.44	-18.50
7	4.32197	0.28	39.63	27.25	39.91	27.53	56.00	46.00	-16.09	-18.47

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.2 RADIATED EMISSIONS MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSIONS MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.109)

ICES-003:2012 Issue 5 (section: 6.2)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5		
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined
Above 3000	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50.5	40.5
88-216	54	43.5		
216-230	56.9	46		
230-960				
960-1000	60	54	57.5	47.5
1000-3000	Avg: 60 Peak: 80	Avg: 54 Peak: 74	Avg: 56 Peak: 76	Avg: 50 Peak: 70
Above 3000			Avg: 60 Peak: 80	Avg: 54 Peak: 74

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 4. QP detector shall be applied if not specified.

Radiated Emissions Limits at 1.5 meter (dBμV/m)		
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B
18000-40000	Avg: 66 Peak: 86	Avg: 60 Peak: 80

Note: Limit@1.5m = Limit@3m + 20log(3/1.5)

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

4.2.2 TEST INSTRUMENTS

Frequency range 30MHz~1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ (V)	ESR-7	101240	Sep. 29, 2014	Sep. 28, 2015
Test Receiver ROHDE & SCHWARZ (H)	ESR-7	101264	Dec. 04, 2014	Dec. 03, 2015
BILOG Antenna SCHWARZBECK (V)	VULB9168	9168-149	Feb. 03, 2015	Feb. 02, 2016
BILOG Antenna SCHWARZBECK (H)	VULB9168	9168-154	Feb. 03, 2015	Feb. 02, 2016
Preamplifier Agilent (V)	8447D	2944A10636	Oct. 18, 2014	Oct. 17, 2015
Preamplifier Agilent (H)	8447D	2944A10637	Oct. 18, 2014	Oct. 17, 2015
Preamplifier Agilent	8449B	3008A01959	Oct. 18, 2014	Oct. 17, 2015
RF signal cable Woken (V)	8D-FB	Cable-CH(V)-01	Oct. 25, 2014	Oct. 24, 2015
RF signal cable Woken (H)	8D-FB	Cable-CH(H)-01	Oct. 25, 2014	Oct. 24, 2015
Software BV ADT	BV ADT_Radiated_ V 8.7.07	NA	NA	NA
Antenna Tower (V)	MFA-440	9707	NA	NA
Antenna Tower (H)	MFA-440	970705	NA	NA
Turn Table	DS430	50303	NA	NA
Controller (V)	MF7802	074	NA	NA
Controller (H)	MF7802	08093	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 1.
3. The FCC Site Registration No. is 477732.
4. The IC Site Registration No. is IC 7450F-1.
5. The VCCI Site Registration No. is R-1893.

Frequency range above 1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESR7	101471	Feb. 09, 2015	Feb. 08, 2016
Spectrum Analyzer Agilent	E4446A	MY51100039	Aug. 18, 2014	Aug. 17, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 03, 2015	Feb. 02, 2016
RF signal cable Woken	8D-FB	NA	Mar. 22, 2015	Mar. 21, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-405	Feb. 06, 2015	Feb. 05, 2016
Preamplifier Agilent (Above 1GHz)	8449B	3008A01961	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MWX322+MW X2211308S029 5	Nov. 06, 2014	Nov. 05, 2015
Software BV ADT	BV ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Controller BV ADT	SC100	SC93021702	NA	NA
HORN Antenna SCHWARZBECK	BBHA 9170	148	Feb. 02, 2015	Feb. 01, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 102	38218/2+3743 3/2	Oct. 25, 2014	Oct. 24, 2015
Fix tool for Boresight antenna tower	BAF-01	2	NA	NA
26GHz ~ 40GHz Amplifier	EMC26400	980175	Nov. 07 2014	Nov. 06, 2015

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 2.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 686814.
 5. The IC Site Registration No. is IC 7450F-2.
 6. The VCCI Site Registration No. is G-18.

4.2.3 TEST PROCEDURES

Frequency range 30MHz~1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE: The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-Peak (QP) detection at frequency below 1GHz.

Frequency range above 1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For frequency range 1GHz ~ 18GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For frequency range 18GHz ~ 40GHz, the EUT was set 1.5 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna can be varied from 1 meter to 4 meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.

NOTE:


1. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak (PK) detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz for Average (AV) detection at frequency above 1GHz.
2. For measurement of frequency above 1000MHz, the EUT was set 3 meters away from the receiver antenna.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

4.2.5 TEST SETUP

Frequency range 30MHz~1GHz



Frequency range above 1GHz



* : depends on the EUT height and the antenna 3dB beamwidth both.

For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.


4.2.7 TEST RESULTS

Frequency Range	30MHz ~ 1GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24°C, 72%RH
Tested by	Fox Chang	Test Date	2015/5/29

Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	38.92	13.79 QP	30.00	-16.21	3.50 H	337	28.73	-14.94
2	162.41	23.72 QP	30.00	-6.28	4.00 H	78	37.13	-13.41
3	168.38	25.16 QP	30.00	-4.84	4.00 H	89	38.90	-13.74
4	188.94	16.73 QP	30.00	-13.27	3.50 H	315	32.48	-15.75
5	245.40	19.75 QP	37.00	-17.25	3.00 H	75	33.59	-13.84
6	260.00	21.95 QP	37.00	-15.05	3.50 H	329	35.20	-13.25

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	30MHz ~ 1GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24°C, 72%RH
Tested by	Fox Chang	Test Date	2015/5/29

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	39.55	22.17 QP	30.00	-7.83	3.50 V	2	36.68	-14.51
2	168.62	25.63 QP	30.00	-4.37	1.00 V	16	38.72	-13.09
3	183.17	20.89 QP	30.00	-9.11	1.50 V	11	35.65	-14.76
4	263.15	16.92 QP	37.00	-20.08	3.00 V	306	29.44	-12.52
5	503.77	21.35 QP	37.00	-15.65	3.50 V	273	28.10	-6.75
6	604.37	24.26 QP	37.00	-12.74	3.50 V	230	28.09	-3.83

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	1GHz ~ 18GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	23°C, 59%RH
Tested by	Rolan Zheng	Test Date	2015/5/28

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1832.58	37.45 PK	74.00	-36.55	1.22 H	23	44.33	-6.88
2	1832.58	23.14 AV	54.00	-30.86	1.22 H	23	30.02	-6.88
3	2538.33	39.13 PK	74.00	-34.87	1.00 H	165	43.60	-4.47
4	2538.33	22.74 AV	54.00	-31.26	1.00 H	165	27.21	-4.47
5	3605.61	41.27 PK	74.00	-32.73	1.43 H	261	43.25	-1.98
6	3605.61	26.51 AV	54.00	-27.49	1.43 H	261	28.49	-1.98

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	1GHz ~ 18GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	23°C, 59%RH
Tested by	Rolan Zheng	Test Date	2015/5/28

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1856.23	38.56 PK	74.00	-35.44	1.00 V	256	45.39	-6.83
2	1856.23	22.36 AV	54.00	-31.64	1.00 V	256	29.19	-6.83
3	2793.37	39.71 PK	74.00	-34.29	1.33 V	251	43.55	-3.84
4	2793.37	23.57 AV	54.00	-30.43	1.33 V	251	27.41	-3.84
5	3815.56	40.42 PK	74.00	-33.58	1.68 V	154	41.67	-1.25
6	3815.56	25.87 AV	54.00	-28.13	1.68 V	154	27.12	-1.25

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	18GHz ~ 40GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	23°C, 66%RH
Tested by	Felix Chen	Test Date	2015/6/1

Antenna Polarity & Test Distance : Horizontal at 1.5 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	21243.55	52.03 PK	80.00	-27.97	1.00 H	258	57.14	-5.11
2	21243.55	41.97 AV	60.00	-18.03	1.00 H	258	47.08	-5.11

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	18GHz ~ 40GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	23°C, 66%RH
Tested by	Felix Chen	Test Date	2015/6/1

Antenna Polarity & Test Distance : Vertical at 1.5 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	20912.37	58.62 PK	80.00	-21.38	1.00 V	122	63.82	-5.20
2	20912.37	47.81 AV	60.00	-12.19	1.00 V	122	53.01	-5.20

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

7 APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

--- END ---