



REPORT No.: SZ18100065E01

TEST REPORT

APPLICANT : Shenzhen Sang Fei Consumer
Communications Co.,Ltd

PRODUCT NAME : Feature Phone

MODEL NAME : Philips E108

BRAND NAME : Philips

FCC ID : VQRCTE108

STANDARD(S) : 47 CFR Part 15 Subpart B

TEST DATE : 2018-10-15 to 2018-10-17

ISSUE DATE : 2018-10-29

Tested by:

Wang Dalong(Test Engineer)

Approved by:

Andy Yeh(Technical Director)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
2. Test Results	5
2.1. Applied Reference Documents	5
2.2. EUT Setup and Operating Conditions	6
3. 47 CFR Part 15B Requirements	7
3.1. Conducted Emission	7
3.2. Radiated Disturbance	11
Annex A Photographs of Test Setup	18
Annex B Test Uncertainty	20
Annex C Testing Laboratory Information	21

Change History		
Issue	Date	Reason for change
1.0	2018-10-29	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Shenzhen Sang Fei Consumer Communications Co.,Ltd
Applicant Address:	11 Science and Technology Road,Shenzhen Hi-tech Industrial Park Nanshan Distrct,Shenzhen city,GuangDong province, 518057,China
Manufacturer:	Shenzhen Sang Fei Consumer Communications Co.,Ltd
Manufacturer Address:	11 Science and Technology Road,Shenzhen Hi-tech Industrial Park Nanshan Distrct,Shenzhen city,GuangDong province, 518057,China

1.2. Equipment Under Test (EUT) Description

EUT Type:	Feature Phone	
Serial No:	(N/A, marked #1 by test site)	
Hardware Version:	6186_MB_V2.1	
Software Version:	E108_M6186Z_201834_V01_SA	
SIM Cards Description:	SIM 1 and SIM 2 is a chipset unit and tested as a single chipset. The SIM 1 is chosen for test	
Tx Frequency:	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz Bluetooth: 2402 MHz ~ 2480 MHz	
Rx Frequency:	GSM850: 869 MHz ~ 894 MHz GSM1900: 1930 MHz ~ 1990 MHz Bluetooth: 2402 MHz ~ 2480 MHz FM: 87.5 MHz ~ 108 MHz	
Ancillary Equipment:	Battery	
	Brand Name:	Philips
	Model No.:	AB1000EWMT
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	1000mAh
	Rated Voltage:	3.7V
	Charge Limit:	4.2V
	AC Adapter	



REPORT No.: SZ18100065E01

	Brand Name:	Philips
	Model No.:	TPA-97050050U03
	Serial No.:	(N/A, marked #1 by test site)
	Rated Input:	~ 100-240V, 50/60Hz, 0.15A
	Rated Output:	≡5V, 0.5A

Note:

1. The Feature Phone supports GSM850MHz, 1900MHz, Bluetooth and FM function.
2. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer



2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	15.107	Conducted Emission	2018.10.15	Wang Dalong	PASS
2	15.109	Radiated Emission	2018.10.17	Wang Dalong	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.



2.2. EUT Setup and Operating Conditions

Frequency range was investigated: Conducted emission test: from 150 KHz to 30 MHz; Radiated emission test: from 30 MHz to 6000 MHz.

Test Item	
Radiated Emission	
Mode 1 :	EUT + USB Cable + PC + Battery + Earphone + GSM Idle + WIFI Idle + Bluetooth Idle
Mode 2 :	EUT + USB Cable + Adapter + Battery + Earphone + GSM Idle + WIFI Idle + Bluetooth Idle + FM
Conducted Emission	
Mode 1 :	EUT + USB Cable + PC + Battery + Earphone + GSM Idle + WIFI Idle + Bluetooth Idle
Mode 2 :	EUT + USB Cable + Adapter + Battery + Earphone + GSM Idle + WIFI Idle + Bluetooth Idle + FM
Remark: The above test modes in boldface were the worst cases of conducted emission, radiated emission, flicker tests; only the test data of these modes was reported.	

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

3. 47 CFR Part 15B Requirements

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.






The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.


3.1.3. Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

A. Test Plot and Suspicious Points:



NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1952	57.04	41.68	63.81	53.81	Line	PASS
2	0.2579	48.69	34.06	61.50	51.50		PASS
3	0.3211	41.94	29.09	59.68	49.68		PASS
4	0.9148	36.12	26.00	56.00	46.00		PASS
5	1.3889	34.32	25.14	56.00	46.00		PASS
6	13.635	29.40	22.60	60.00	50.00		PASS



NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1503	46.63	27.99	65.99	55.99	Neutral	PASS
2	0.1997	58.34	41.47	63.62	53.62		PASS
3	0.2578	50.63	33.51	61.50	51.50		PASS
4	0.4333	31.11	22.89	57.19	47.19		PASS
5	2.4035	26.02	18.01	56.00	46.00		PASS
6	13.537	29.34	22.57	60.00	50.00		PASS

3.2. Radiated Disturbance

3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength Limitation at 3m Measurement Dist	
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dB $\mu\text{V/m}$ is calculated by 20log Emission Level($\mu\text{V/m}$).


3.2.2. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

3.2.3. Test Setup

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:


In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

3.2.4. Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions (6GHz-12.5GHz) which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.




No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	35.8258	35.35	N.A.	N.A.	N.A.	40.00	N.A.	V	PASS
2	107.9951	N.A.	39.57	N.A.	N.A.	43.50	N.A.	V	PASS
3	120.0011	N.A.	41.12	N.A.	N.A.	43.50	N.A.	V	PASS
4	137.7778	39.21	N.A.	N.A.	N.A.	43.50	N.A.	V	PASS
5	276.6266	41.16	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS
6	431.9820	36.88	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS



No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1231.0462	32.09	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
2	1933.1866	34.26	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
3	2677.3355	36.33	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
4	3629.5259	40.27	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
5	4769.7540	40.79	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
6	5288.8578	41.73	N.A.	N.A.	74.00	N.A.	54.00	V	PASS



No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	53.3033	29.86	N.A.	N.A.	N.A.	40.00	N.A.	H	PASS
2	126.1261	25.00	N.A.	N.A.	N.A.	43.50	N.A.	H	PASS
3	173.7037	38.05	N.A.	N.A.	N.A.	43.50	N.A.	H	PASS
4	210.4050	N.A.	31.82	N.A.	N.A.	43.50	N.A.	H	PASS
5	299.9299	43.24	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS
6	354.4550	N.A.	33.35	N.A.	N.A.	46.00	N.A.	H	PASS




No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1235.0470	33.18	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
2	2086.2172	35.08	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
3	2171.2342	38.43	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
4	2731.3463	36.35	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
5	3834.5669	41.21	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
6	4717.7435	40.42	N.A.	N.A.	74.00	N.A.	54.00	H	PASS

Annex A Photographs of Test Setup


1. Mains Terminal Disturbance Voltage Measurement




2. Conducted emission main's port side view



3. Radiated Field Strength Measurement(30MHz-1GHz)



4. Radiated Field Strength Measurement(above 1GHz)





Annex B Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	9kHz-150kHz	±4.1 dB
	150kHz-30MHz	±3.7dB

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	30MHz-200MHz	±5.06dB
	200MHz-1000MHz	±5.24dB
	1GHz-6GHz	±5.18dB
	6GHz-18GHz	±5.48dB



Annex C Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory:	The FCC designation number is CN1192. Test firm registration number is 226174. (Shenzhen Morlab Communications Technology Co., Ltd.)
---------------------------------------	--

4. Test Software Utilized

Model	Version Number	Producer
JS32-RE	Version 2.0.2.0	Tonscend
TS+ -[JS32-CE]	Version 2.5.0.0	Tonscend

**5. Test Equipments Utilized**

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
MXE EMI Receiver	Agilent	N9038A	MY54130016	2018.08.04	2019.08.03
Test Receiver	R&S	ESPI	101052	2018.08.04	2019.08.03
LISN	Schwarzbeck	NSLK 8127	812744	2018.10.15	2019.04.15
Pulse Limiter (20dB)	VTSD	9561D	9537	2018.10.15	2019.04.15
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-519	2018.05.08	2019.05.07
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	1774	2018.03.03	2019.03.02
Semi-Anechoic Chamber	CRT	9m*6m*6m	N/A	2017.01.12	2020.01.11

_____ END OF REPORT _____