


FCC Radio Test Report


FCC ID: VSFMS3A

This report concerns: Original Grant

Project No. : 1907H013
Equipment : Tablet
Brand Name : Juniper Systems
Test Model : MS3A
Series Model : N/A
Applicant : Juniper Systems
Address : 1132 W 1700 N Logan, UT 84321 USA
Manufacturer : Juniper Systems
Address : 1132 W 1700 N Logan, UT 84321 USA
Date of Receipt : Jul. 16, 2019
Date of Test : Jul. 16, 2019 ~ Nov. 03, 2019
Issued Date : Nov. 07, 2019
Report Version : R00
Test Sample : Engineering Sample No.: SH2019091645/SH2019091646/
SH2019091641-5 /SH2019091641-6
Standard(s) : 47 CFR FCC Part 90 Subpart R
47 CFR FCC Part 2 & ANSI/TIA-603-D-2010
FCC KDB 971168 D01 Power Meas License Digital Systems v03

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.


Prepared by : Krain Wu


Approved by : Young Chai



Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and is not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	5
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES AND TEST CONDITION	9
2.3 BLOCK DIGRAM SHOWING THECONFIGURATIONOFSYSTEMTESTED FOR RADIATED	10
3.4 DESCRIPTION OF SUPPORT UNITS	10
3 . TEST RESULT	11
3.1 OUTPUT POWER MEASUREMENT	11
3.1.1 LIMIT	11
3.1.2 TEST PROCEDURE	11
3.1.3 TESTSETUP LAYOUT	11
3.1.4 TEST DEVIATION	11
3.1.5 TEST RESULTS	11
3.2 OCCUPIED BANDWIDTH MEASUREMENT	12
3.2.1 TEST PROCEDURE	12
3.2.2 TEST SETUP LAYOUT	12
3.2.3 TEST DEVIATION	12
3.2.4 TEST RESULTS	12
3.3 CONDUCTED EMISSIONS MEASUREMENT	13
3.3.1 LIMIT	13
3.3.2 TEST PROCEDURES	13
3.3.3 TESTSETUP LAYOUT	13
3.3.4 TESTDEVIATION	13
3.3.5 TEST RESULTS	13
3.4 RADIATED EMISSIONS MEASUREMENT	14
3.4.1 LIMIT	14
3.4.2 TEST PROCEDURES	14
3.4.3 TESTSETUP LAYOUT	14
3.4.4 TESTDEVIATION	15
3.4.5 TEST RESULTS (9KHZ TO 30MHZ)	15
3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)	15
3.4.7 TEST RESULTS (ABOVE 1000MHZ)	15
3.5 BAND EDGE /EMISSION MASK MEASUREMENT	16
3.5.1 LIMIT	16

Table of Contents	Page
3.5.2 TEST PROCEDURES	16
3.5.3 TESTSETUP LAYOUT	16
3.5.4 TESTDEVIATION	16
3.5.5 TEST RESULTS	16
3.6 FREQUENCY STABILITY MEASUREMENT	17
3.6.1 LIMIT	17
3.6.2 TEST PROCEDURES	17
3.6.3 TESTSETUP LAYOUT	17
3.6.4 TESTDEVIATION	17
3.6.5 TEST RESULTS	17
3.7 PEAK TO AVERAGE RATIO MEASUREMENT	18
3.7.1 LIMIT	18
3.7.2 TEST PROCEDURES	18
3.7.3 TEST SETUP LAYOUT	18
3.7.4 TEST DEVIATION	18
3.7.5 TEST RESULTS	18
5. LIST OF MEASUREMENT EQUIPMENTS	19
APPENDIX A - OUTPUT POWER	21
APPENDIX B - OCCUPIED BANDWIDTH	24
APPENDIX C - CONDUCTED EMISSIONS	27
APPENDIX D - RADIATED EMISSION (9KHZ TO 30MHZ)	30
APPENDIX E - RADIATED EMISSION (30MHZ TO 1GHZ)	35
APPENDIX F - RADIATED EMISSION (ABOVE 1GHZ)	40
APPENDIX G - BAND EDGE	45
APPENDIX H - FREQUENCY STABILITY	47
APPENDIX I - PEAK TO AVERAGE RATIO	49

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Nov. 07, 2019

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part 90 Subpart R & Part 2			
Standard(s) Section	Test Item	Judgment	Tested By
2.1046 & 90.542	Radiated power	PASS	Summer Xu
2.1046 & 90.542	Conducted Output Power	PASS	Summer Xu
2.1049	Occupied Bandwidth	PASS	Summer Xu
2.1051 & 90.543	Conducted Spurious Emissions	PASS	Summer Xu
2.1053 & 90.543	Radiated Spurious Emissions	PASS	Summer Xu
2.1051 & 90.543	Band Edge Measurements	PASS	Summer Xu
2.1055 & 90.539	Frequency Stability	PASS	Summer Xu
-	Peak To Average Ratio	PASS	Summer Xu

Note:

For the verdict, the “N/A” denotes “not applicable”, the “N/T” denotes “not tested”.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China
 BTL's Test Firm Registration Number for FCC: 476765
 BTL's Designation Number for FCC: CN1241

1.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor) $k=1.96$ or $k=2$ (which provide confidence levels of respectively 90% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).
 Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$.

The BTL measurement uncertainty as below table:

A. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
SH-CB01	CISPR	9KHz ~ 30MHz	V	3.79
		9KHz ~ 30MHz	H	3.57
		30MHz ~ 200MHz	V	4.88
		30MHz ~ 200MHz	H	4.14
		200MHz ~ 1,000MHz	V	4.62
		200MHz ~ 1,000MHz	H	4.80

Test Site	Method	Measurement Frequency Range	U,(dB)
SH-CB01	CISPR	1GHz ~ 6GHz	4.40
		6GHz ~ 18GHz	4.86

Test Site	Method	Measurement Frequency Range	U,(dB)
SH-CB01	CISPR	18 ~ 26.5 GHz	3.64
		26.5 ~ 40 GHz	3.78

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Tablet		
Brand Name	Juniper Systems		
Test Model	MS3A		
Series Model	N/A		
Model Difference(s)	N/A		
Software Version	MS3A-userdebug 9.1.0.1-20190619 eng.mirror.20190619.093211 test-keys		
Hardware Version	DVT1		
Antenna Type	Internal Antenna		
Antenna Gain	PCS1900	0.5 dBi	
	WCDMA II		
	LTE Band 2		
	LTE Band 14	0.2 dBi	
Modulation Type	LTE	UL: QPSK,16QAM DL: QPSK,16QAM	
Operation Frequency	LTE Band 14 (Channel Bandwidth: 5MHz)		793MHz ~ 795.5MHz
	LTE Band 14 (Channel Bandwidth: 10MHz)		793.0MHz
Power Source	#1 DC voltage supplied from AC/DC adapter. Model: PSAA30R-120 #2 Supplied from Li-ion battery pack.		
Power Rating	#1 I/P: 100~240V 0.8A 50~60Hz O/P: 12V --- 2.5A #2 7.2V, 6.0A, 43.2W		
IMEI No.			

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2.2 DESCRIPTION OF TEST MODES AND TEST CONDITION

Following channel(s) was (were) selected for the final test as listed below:

LTE BAND 14 MODE					
Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Output Power & ERP	23330 to 23355	23330 to 23355	5MHz	QPSK, 16QAM	1RB/12RB/25RB
		23330	10MHz	QPSK, 16QAM	1RB/25RB/50RB
Occupied Bandwidth	23330 to 23355	23230	5MHz	QPSK, 16QAM	25RB
	23330 to 23355	23330	10MHz	QPSK, 16QAM	50RB
Conducted Spurious Emission	23330 to 23355	23230	5MHz	QPSK	1 RB
		23330	10MHz	QPSK	1 RB
Radiated Spurious Emission	23330 to 23355	23230	5MHz	QPSK	1 RB
	23330 to 23355	23330	10MHz	QPSK	1 RB
Band Edge	23330 to 23355	23330 to 23355	5MHz	QPSK	1RB/25RB
	23330 to 23355	23230	10MHz	QPSK	1RB/50RB
Peak To Average Ratio	23330 to 23355	23330 to 23355	5MHz	QPSK, 16QAM	1RB
	23330 to 23355	23330	10MHz	QPSK, 16QAM	1RB
Frequency Stability	23330 to 23355	23330	5MHz	QPSK	1RB
	23330 to 23355	23330	10MHz	QPSK	1RB


Note:

- 1) The mark "V" means that this configuration is chosen for testing.
- 2) The mark "-" means that this configuration is not testing.

EUT TEST CONDITIONS:

Test Item	Environmental Conditions	Test Voltage
EIRP	23°C, 59%RH	DC 7.2V
Output Power	23°C, 59%RH	DC 7.2V
Occupied Bandwidth	23°C, 59%RH	DC 7.2V
Conducted Emission	23°C, 59%RH	DC 7.2V
Radiated Emission	22°C, 58%RH	AC 120V/60Hz
Band Edge	23°C, 59%RH	DC 7.2V
Peak to Average Ratio	23°C, 59%RH	DC 7.2V
Frequency Stability	Normal and Extreme	Normal and Extreme

2.3 BLOCK DIGRAM SHOWING THECONFIGURATIONOFSYSTEMTESTED FOR RADIATED



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
A	CMW500	N/A	N/A	131463

Item	Cable Type	Shielded Type	Ferrite Core	Length
A	DC Cable	NO	NO	1.5m

3. TEST RESULT

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMIT

Portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.

3.1.2 TEST PROCEDURE

ERP:


$EIRP = \text{Output Power} + \text{Antenna gain}$

Conducted Power:

The EUT was set up for the maximum power with LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TESTSETUP LAYOUT

Conducted Power Measurement



3.1.4 TEST DEVIATION

No deviation

3.1.5 TEST RESULTS


Please refer to the Appendix A.

3.2 OCCUPIED BANDWIDTH MEASUREMENT

3.2.1 TEST PROCEDURE

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth and 26dB bandwidth.

3.2.2 TEST SETUP LAYOUT



3.2.3 TEST DEVIATION

No deviation

3.2.4 TEST RESULTS

Please refer to the Appendix B.

3.3 CONDUCTED EMISSIONS MEASUREMENT


3.3.1 LIMIT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13dBm.

3.3.2 TEST PROCEDURES

1. The testing follows FCC KDB 971168 v03 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured. Set $RBW \geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10 \log(P)](dB)$
 $= [30 + 10 \log(P)](dBm) - [43 + 10 \log(P)](dB)$
 $= -13dBm$

3.3.3 TESTSETUP LAYOUT



3.3.4 TESTDEVIATION

No deviation

3.3.5 TEST RESULTS

Please refer to the Appendix C.

3.4 RADIATED EMISSIONS MEASUREMENT

3.4.1 LIMIT


The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB. The limit of emission is equal to -13dBm.



3.4.2 TEST PROCEDURES

1. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
2. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
3. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
4. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.
5. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.4.3 TESTSETUP LAYOUT

Below 30MHz





3.4.4 TESTDEVIATION

No deviation

3.4.5 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix D.

3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Appendix E.

3.4.7 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix F.

3.5 BAND EDGE /EMISSION MASK MEASUREMENT

3.5.1 LIMIT

For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.


(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

3.5.2 TEST PROCEDURES

1. All measurements were done at low and high operational frequency range.
2. Set RBW=1% of 26dBc bandwidth, VBW=3 X RBW, detector=RMS, Sweep time = Auto.
3. Record the max trace plot into the test report.

3.5.3 TESTSETUP LAYOUT



3.5.4 TESTDEVIATION

No deviation

3.5.5 TEST RESULTS

Please refer to the Appendix G.

3.6 FREQUENCY STABILITY MEASUREMENT


3.6.1 LIMIT

1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

3.6.2 TEST PROCEDURES

1. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
2. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
3. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.
4. The frequency error was recorded frequency error from the communication simulator.

3.6.3 TESTSETUP LAYOUT



3.6.4 TESTDEVIATION

No deviation

3.6.5 TEST RESULTS

Please refer to the Appendix H.

3.7 PEAK TO AVERAGE RATIO MEASUREMENT


3.7.1 LIMIT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.7.2 TEST PROCEDURES

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.7.3 TEST SETUP LAYOUT



3.7.4 TEST DEVIATION

No deviation

3.7.5 TEST RESULTS

Please refer to the Appendix I.

5. LIST OF MEASUREMENT EQUIPMENTS

Radiated Emission Measurement(9K-30M)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Loop Antenna	EMCI	EMCI LPA600	275	Mar. 29, 2020
2	EMI Test Receiver	R&S	ESCI	100082	Mar. 29, 2020
3	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Measurement(30M-1G)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	719	Mar. 29, 2020
2	Pre-Amplifier	emci	EMC9135	980400	Mar. 29, 2020
3	MXE EMI Receiver	Keysight	N9038A	MY57150106	Mar. 29, 2020
4	Test Cable	emci	EMC104-SM-SM-7000	170330	Apr. 17, 2020
5	Test Cable	emci	EMC104-SM-SM-1000	170331	Apr. 17, 2020
6	Test Cable	emci	EMC104-SM-NM-3500	170621	Apr. 17, 2020
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Wideband Radio Communication Test	R&S	CMW500	131463	Nov. 20, 2019

Radiated Emission Measurement(1G-18G)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Pre-Amplifier	emci	EMC184045SE	980409	Mar. 29, 2020
2	Pre-Amplifier	emci	EMC012645SE	980421	Mar. 29, 2020
3	Pre-Amplifier	emci	EMC9135	980400	Mar. 29, 2020
4	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1787	Mar. 29, 2020
5	Double-Ridged Waveguide Horn Antenna	ETS-Lindgren	3116C	00203919	Mar. 29, 2020
6	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	719	Mar. 29, 2020
7	Cable	N/A	EMC102-SM-SM-6000	170336	Apr. 17, 2020
8	Wideband Radio Communication Test	R&S	CMW500	131463	Nov. 20, 2019

Conducted Emission & Band Edge & Occupied Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 29, 2020
2	Power Divider	JUK	PD-4SF-2060	N/A	N/A
3	Wideband Radio Communication Test	R&S	CMW500	131463	Nov. 20, 2019
4	Spectrum Analyzer	R&S	FSP40	100626	Mar. 29, 2020

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 29, 2020
2*	Power Divider	JUK	PD-4SF-2060	N/A	N/A
3	Wideband Radio Communication Test	R&S	CMW500	131463	Nov. 20, 2019
4	Spectrum Analyzer	R&S	FSP40	100626	Mar. 29, 2020
5	Temperature And Humidity Box	Blue pand	BPHS-120B	170616454	Nov. 20, 2019

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

*All calibration period of equipment list is three year

APPENDIX A - OUTPUT POWER

Output Power (dBm):

LTE Band / BW	Modulation	RB Size	RB Offset	Mid CH	High CH
				23330CH	23355CH
				793MHz	795.5MHz
14 / 5M	QPSK	1	0	23.57	23.62
		1	13	23.60	23.63
		1	24	23.53	23.51
		12	0	22.54	22.51
		12	6	22.54	22.52
		12	11	22.53	22.48
		25	0	22.52	22.49
	16QAM	1	0	22.57	22.68
		1	13	22.66	22.73
		1	24	22.63	22.64
		12	0	21.61	21.68
		12	6	21.65	21.68
		12	11	21.64	21.63
		25	0	21.55	21.59

LTE Band / BW	Modulation	RB Size	RB Offset	Mid CH
				23330CH
				793MHz
14 / 10M	QPSK	1	0	23.34
		1	25	23.69
		1	49	23.45
		25	0	22.52
		25	13	22.53
		25	25	22.51
		50	0	22.52
	16QAM	1	0	22.30
		1	25	22.39
		1	49	22.34
		25	0	21.62
		25	13	21.64
		25	25	21.59
		50	0	21.56

ERP Power (dBm):

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				23305CH	23330CH	23355CH
				790.5MHz	793MHz	795.5MHz
14 / 5M	QPSK	1	0	21.57	21.62	21.67
		1	13	21.63	21.65	21.68
		1	24	21.59	21.58	21.56
		12	0	20.55	20.59	20.56
		12	6	20.59	20.59	20.57
		12	11	20.58	20.58	20.53
		25	0	20.56	20.57	20.54
	16QAM	1	0	21.03	20.62	20.73
		1	13	20.68	20.71	20.78
		1	24	20.79	20.68	20.69
		12	0	19.72	19.66	19.73
		12	6	19.76	19.70	19.73
		12	11	19.76	19.69	19.68
		25	0	19.66	19.60	19.64


LTE Band / BW	Modulation	RB Size	RB Offset	Mid CH
				23330CH
				793MHz
14 / 10M	QPSK	1	0	21.39
		1	25	21.74
		1	49	21.50
		25	0	20.57
		25	13	20.58
		25	25	20.56
		50	0	20.57
	16QAM	1	0	20.35
		1	25	20.44
		1	49	20.39
		25	0	19.67
		25	13	19.69
		25	25	19.64
		50	0	19.61

APPENDIX B - OCCUPIED BANDWIDTH


LTE Band 14_5M					
QPSK			16QAM		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
23330	793.0	4.5154	23330	793.0	4.5146
23355	795.5	4.5136	23355	795.5	4.5029
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
23330	793.0	4.9480	23330	793.0	4.9550
23355	795.5	4.9390	23355	795.5	4.9330






LTE Band 14_10M					
QPSK			16QAM		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
23330	793.0	8.9924	23330	793.0	8.9999
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
23330	793.0	9.9190	23330	793.0	9.8000



APPENDIX C - CONDUCTED EMISSIONS




LTE Band 14_10M			
Channel	Frequency(MHz)	Channel	Frequency(MHz)
23330	793.0	23330	793.0
 <p>Date: 24.JUL.2019 20:38:16</p>		 <p>Date: 22.OCT.2019 11:57:54</p>	
Channel	Frequency(MHz)	-	-
23330	793.0	-	-
 <p>Date: 24.JUL.2019 20:41:37</p>		-	

APPENDIX D - RADIATED EMISSION (9KHZ TO 30MHZ)

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.0108	-12.70	77.91	65.21	126.94	-61.73	AVG	
2		0.0370	-16.67	67.60	50.93	116.24	-65.31	AVG	
3	*	0.1025	-7.56	57.85	50.29	107.39	-57.10	QP	

Test Mode: TX Mode


Ant 0°



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	0.2850	-3.90	49.21	45.31	98.51	-53.20	AVG	
2 *	2.7015	6.23	38.24	44.47	69.54	-25.07	QP	
3	14.2980	5.35	38.14	43.49	69.54	-26.05	QP	

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.0133	-14.30	76.39	62.09	125.13	-63.04	AVG	
2		0.0357	-16.40	67.99	51.59	116.55	-64.96	AVG	
3	*	0.1025	-7.90	57.85	49.95	107.39	-57.44	QP	

Test Mode: TX Mode


Ant 90°



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	0.3525	-3.80	47.55	43.75	96.66	-52.91	AVG	
2 *	1.7790	5.54	39.33	44.87	69.54	-24.67	QP	
3	14.7930	5.42	38.06	43.48	69.54	-26.06	QP	

APPENDIX E - RADIATED EMISSION (30MHZ TO 1GHZ)

Test Mode: LTE Band 14_TX Mode_5M



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	55.2200	-57.63	-17.30	-74.93	-13.00	-61.93	peak	
2		229.8200	-62.28	-17.36	-79.64	-13.00	-66.64	peak	
3		492.6900	-72.33	-12.70	-85.03	-13.00	-72.03	peak	
4		644.0100	-72.35	-8.53	-80.88	-13.00	-67.88	peak	
5		805.0300	-72.58	-6.42	-79.00	-13.00	-66.00	peak	
6		883.6000	-70.78	-5.62	-76.40	-13.00	-63.40	peak	

Test Mode: LTE Band 14_TX Mode_5M


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		82.3800	-63.46	-20.34	-83.80	-13.00	-70.80	peak	
2		210.4200	-65.30	-18.30	-83.60	-13.00	-70.60	peak	
3		261.8300	-61.04	-16.33	-77.37	-13.00	-64.37	peak	
4		655.6500	-70.32	-8.51	-78.83	-13.00	-65.83	peak	
5		833.1600	-70.00	-6.18	-76.18	-13.00	-63.18	peak	
6	*	914.6400	-70.10	-5.34	-75.44	-13.00	-62.44	peak	


Test Mode: LTE Band 14_TX Mode_10M

Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	56.1900	-56.35	-17.37	-73.72	-13.00	-60.72	peak	
2		139.6100	-62.67	-15.74	-78.41	-13.00	-65.41	peak	
3		212.3600	-65.71	-18.23	-83.94	-13.00	-70.94	peak	
4		612.9700	-72.63	-8.61	-81.24	-13.00	-68.24	peak	
5		792.4200	-72.25	-6.49	-78.74	-13.00	-65.74	peak	
6		881.6600	-72.24	-5.63	-77.87	-13.00	-64.87	peak	


Test Mode: LTE Band 14_TX Mode_10M



No. Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	79.4700	-59.76	-20.29	-80.05	-13.00	-67.05	peak	
2	139.6100	-64.89	-15.74	-80.63	-13.00	-67.63	peak	
3	421.8800	-70.74	-13.01	-83.75	-13.00	-70.75	peak	
4	673.1100	-72.34	-8.55	-80.89	-13.00	-67.89	peak	
5	829.2800	-72.18	-6.21	-78.39	-13.00	-65.39	peak	
6 *	947.6200	-72.52	-5.15	-77.67	-13.00	-64.67	peak	


APPENDIX F - RADIATED EMISSION (ABOVE 1GHZ)

Test Mode: LTE Band 14_TX CH23330_5M




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1588.130	-46.66	-19.06	-65.72	-13.00	-52.72	peak	

Test Mode: LTE Band 14_TX CH23330_5M




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1584.630	-45.13	-19.07	-64.20	-13.00	-51.20	peak	

Test Mode: LTE Band 14_TX CH23330_10M




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1589.440	-45.78	-19.05	-64.83	-13.00	-51.83	peak	

Test Mode: LTE Band 14_TX CH23330_10M



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1580.780	-42.70	-19.08	-61.78	-13.00	-48.78	peak	

APPENDIX G - BAND EDGE



APPENDIX H - FREQUENCY STABILITY

Test Mode: LTE Band 14_CH23330_5M

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	4.31	0.006157143	± 2.5
-10	-3.16	-0.004514286	
0	2.84	0.004057143	
10	4.45	0.006357143	
20	-4.72	-0.006742857	
30	-3.76	-0.005371429	
40	-2.33	-0.003328571	
50	2.15	0.003071429	
Max. Deviation (ppm)	-4.72	-0.006742857	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
6.6	6.10	-0.005171429	± 2.5
7.2	-3.62	0.004014286	
8.4	2.81	0.008714286	
Max. Deviation (ppm)	6.10	-0.005171429	

Test Mode: LTE Band 14_CH23330_10M

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	-2.49	-0.003557143	± 2.5
-10	2.37	0.003385714	
0	-3.54	-0.005057143	
10	3.78	0.0054	
20	6.22	0.008885714	
30	-1.98	-0.002828571	
40	2.81	0.004014286	
45	3.40	0.004857143	
Max. Deviation (ppm)	6.22	0.008885714	

Voltage vs. Frequency Stability


Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
6.6	2.40	0.003428571	± 2.5
7.2	4.72	0.006742857	
8.4	-3.43	-0.0049	
Max. Deviation (ppm)	4.72	0.006742857	

APPENDIX I - PEAK TO AVERAGE RATIO

LTE Band 14 Spectrum Plot_5M



LTE Band 14 Spectrum Plot_10M



End of Test Report