



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	PEGATRON CORPORATION
Applicant Address	5F No. 76, Ligong St., Beitou District, Taipei City 112, Taiwan
FCC ID	VUIDPC3929CA
Manufacturer's company	MAINTEK COMPUTER
Manufacturer Address	233 Jinfeng Rd., Suzhou, Jiangsu, PRC

Product Name	Wireless cable modem
Brand Name	CISCO
Model No.	DPC3929XXXX (X=0~1 and A~Z or blank)
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	May 07, 2014
Final Test Date	Jun. 03, 2014
Submission Type	Original Equipment

Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r01 and KDB 662911 D01 v02r01.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	8
3.7. Table for Explanation	8
3.8. Table for Supporting Units	8
3.9. Table for Parameters of Test Software Setting	9
3.10. EUT Operation during Test	9
3.11. Duty Cycle	10
3.12. Test Configurations	12
4. TEST RESULT	13
4.1. AC Power Line Conducted Emissions Measurement.....	13
4.2. Maximum Conducted Output Power Measurement.....	17
4.3. Power Spectral Density Measurement	20
4.4. 6dB Spectrum Bandwidth Measurement	28
4.5. Radiated Emissions Measurement	33
4.6. Emissions Measurement	50
4.7. Antenna Requirements	68
5. LIST OF MEASURING EQUIPMENTS	69
6. MEASUREMENT UNCERTAINTY.....	71
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. RADIATED EMISSION CO-LOCATION REPORT	B1 ~ B3


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR453003AA	Rev. 01	Initial issue of report	Jun. 16, 2014

1. CERTIFICATE OF COMPLIANCE

Product Name : Wireless cable modem
Brand Name : CISCO
Model No. : DPC3929XXXX (X=0~1 and A~Z or blank)
Applicant : PEGATRON CORPORATION
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on May 07, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	7.49 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	0.83 dB
4.3	15.247(e)	Power Spectral Density	Complies	4.74 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.30 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.08 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Internal Power Supply and Li-ion battery
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (HT20): 17.68 MHz ; MCS0 (HT40): 35.68 MHz
Maximum Conducted Output Power	MCS0 (HT20): 29.17 dBm ; MCS0 (HT40): 22.81 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Internal Power Supply and Li-ion battery
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 10.24 MHz ; 11g: 16.72 MHz
Maximum Conducted Output Power	11b: 24.22 dBm ; 11g: 23.88 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description	
Beamforming Function	<input type="checkbox"/> With beamforming	<input checked="" type="checkbox"/> Without beamforming

Antenna and Band width

Antenna	Single (TX)		Three (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11b	V	X	X	X
IEEE 802.11g	V	X	X	X
IEEE 802.11n	X	X	V	V

IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	3	MCS 0-23
802.11n (HT40)	3	MCS 0-23
<p>Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.</p> <p>Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n</p>		

3.2. Accessories

Power	Brand	Model	CISCO P/N	Rating
Li-ion Battery	PEG/ATRON	PB020	35-4043873-01	7.2V – 2600mAh, 18Wh
Others				
Power Cable: Non-Shielded, 1.45m				
RJ-45 Cable: Non-Shielded, 1.2m				

3.3. Table for Filed Antenna

Ant.	Brand Holder	Model Name	P/N	Antenna Type	Connector	Gain (dBi)	
						2.4GHz	5GHz
1	HL TECHNOLOGY GROUP LIMITED	DPC-3940CAD and DPC-3929CAD (Q Housing)	290-30035	PCB Antenna	I-PEX	1.94	-
2	HL TECHNOLOGY GROUP LIMITED	DPC-3940CAD and DPC-3929CAD (Q Housing)	290-30036	PCB Antenna	I-PEX	4.21	2.50
3	HL TECHNOLOGY GROUP LIMITED	DPC-3940CAD and DPC-3929CAD (Q Housing)	290-30037	PCB Antenna	I-PEX	4.21	2.55
4	HL TECHNOLOGY GROUP LIMITED	DPC-3940CAD and DPC-3929CAD (Q Housing)	290-30038	PCB Antenna	I-PEX	-	2.38

Note: The EUT has four Antennas.

<For 2.4GHz Function>:

For IEEE 802.11n mode (3TX/3RX)

Chain 1, Chain 2 and Chain 3 can be used as transmitting/receiving antenna.

Chain 1, Chain 2 and Chain 3 could transmit/receive simultaneously.

For IEEE 802.11b/g mode (1TX/1RX):

Only Chain 3 can be used as transmitting/receiving antenna.

<For 5GHz Function>:

For IEEE 802.11n/ac mode (3TX/3RX)


Chain 4, Chain 5 and Chain 6 can be used as transmitting/receiving antenna.

Chain 4, Chain 5 and Chain 6 could transmit/receive simultaneously.

For IEEE 802.11a mode (1TX/1RX):

Only Chain 6 can be used as transmitting/receiving antenna.

According to the above antennas, there are three antennas will transit simultaneously (one is Horizontal and the others are Vertical).



3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	802.11n HT20	MCS0	1/6/11	1+2+3
	802.11n HT40	MCS0	3/6/9	1+2+3
	11b/BPSK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3
Power Spectral Density	802.11n HT20	MCS0	1/6/11	1+2+3
	802.11n HT40	MCS0	3/6/9	1+2+3
	11b/BPSK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3
6dB Spectrum Bandwidth	802.11n HT20	MCS0	1/6/11	1+2+3
	802.11n HT40	MCS0	3/6/9	1+2+3
	11b/BPSK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3
Radiated Emissions 9kHz~1GHz	CTX	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	802.11n HT20	MCS0	1/6/11	1+2+3
	802.11n HT40	MCS0	3/6/9	1+2+3
	11b/BPSK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3
Band Edge Emissions	802.11n HT20	MCS0	1/6/11	1+2+3
	802.11n HT40	MCS0	3/6/9	1+2+3
	11b/BPSK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. EUT standing with 2.4GHz (CTX)

Mode 2. EUT standing with 5GHz (CTX)

Mode 2 is the worst case, so it was selected to record in this test report.

For Radiated Emission test <Below 1GHz>:

Mode 1. EUT standing with 2.4GHz (CTX)

Mode 2. EUT standing with 5GHz (CTX)

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emission test <Above 1GHz>:

Mode 1. EUT standing (CTX)

For Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Maximum Permissible Exposure (Please refer to Maximum Permissible Exposure Test Report: FA453003) and Co-location (please refer to Appendix B) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Explanation

The difference for each model is shown as below:

Model Name	Description
DPC3929XXXX	X=0~1 and A~Z or blank

DPC3929CAD was selected as representative model for the test and its data was recorded in this report.

3.8. Table for Supporting Units

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC

For Test Site No: 03CH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6220	DoC

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC

3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n

Test Software Version	Mtool 2.0.1.0		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 HT20	70	100	74
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 HT40	51	70	67

Power Parameters of IEEE 802.11b/g


Test Software Version	Mtool 2.0.1.0		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	100	100	100
IEEE 802.11g	76	100	78

3.10. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.11. Duty Cycle

IEEE 802.11n MCS0 HT20




Date: 22.MAY.2014 16:04:02

IEEE 802.11n MCS0 HT40




Date: 22.MAY.2014 16:02:47

IEEE 802.11b



Date: 22.MAY.2014 16:06:42


IEEE 802.11g



Date: 22.MAY.2014 16:05:43

3.12. Test Configurations

3.12.1. AC Power Line Conduction Emissions and Radiation Emissions Test Test Configuration



Item	Connection	Shielded	Length(m)
1	Power Cable	No	1.45m
2	RJ-45 Cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	51%
Test Engineer	Hank Huang	Phase	Line
Configuration	CTX	Test Mode	Mode 2



	Freq	Level	Over	Limit	LISN	Read	Cable		
	MHz	dBuV	Limit	Line	Factor	Level	Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.15000	58.32	-7.68	66.00	0.08	58.08	0.16	LINE	QP
2	0.15000	42.90	-13.10	56.00	0.08	42.66	0.16	LINE	AVERAGE
3	0.16327	49.02	-16.28	65.30	0.08	48.78	0.16	LINE	QP
4	0.16327	34.78	-20.52	55.30	0.08	34.54	0.16	LINE	AVERAGE
5	0.18152	52.17	-12.24	64.42	0.08	51.93	0.16	LINE	QP
6	0.18152	32.67	-21.74	54.42	0.08	32.43	0.16	LINE	AVERAGE
7	0.22676	44.14	-18.43	62.57	0.08	43.89	0.17	LINE	QP
8	0.22676	30.26	-22.31	52.57	0.08	30.01	0.17	LINE	AVERAGE
9	0.46367	37.03	-19.59	56.63	0.08	36.77	0.18	LINE	QP
10	0.46367	32.74	-13.88	46.63	0.08	32.48	0.18	LINE	AVERAGE
11	18.622	24.33	-25.67	50.00	0.35	23.49	0.49	LINE	AVERAGE
12	18.622	28.78	-31.22	60.00	0.35	27.94	0.49	LINE	QP

Temperature	24°C	Humidity	51%
Test Engineer	Hank Huang	Phase	Neutral
Configuration	CTX	Test Mode	Mode 2



	Freq	Level	Over	Limit	LISN	Read	Cable		
	MHz	dBuV	Limit	Line	Factor	Level	Loss	Pol/Phase	Remark
			dB	dBuV	dB	dBuV	dB		
1	0.15000	58.51	-7.49	66.00	0.08	58.27	0.16	NEUTRAL	QP
2	0.15000	41.97	-14.03	56.00	0.08	41.73	0.16	NEUTRAL	AVERAGE
3	0.15733	52.78	-12.82	65.60	0.08	52.54	0.16	NEUTRAL	QP
4	0.15733	30.09	-25.51	55.60	0.08	29.85	0.16	NEUTRAL	AVERAGE
5	0.18152	53.06	-11.35	64.42	0.08	52.82	0.16	NEUTRAL	QP
6	0.18152	36.01	-18.40	54.42	0.08	35.77	0.16	NEUTRAL	AVERAGE
7	0.30348	36.95	-23.20	60.15	0.09	36.69	0.17	NEUTRAL	QP
8	0.30348	26.65	-23.50	50.15	0.09	26.39	0.17	NEUTRAL	AVERAGE
9	0.47110	33.30	-13.19	46.49	0.09	33.03	0.18	NEUTRAL	AVERAGE
10	0.47110	37.16	-19.33	56.49	0.09	36.89	0.18	NEUTRAL	QP
11	19.532	28.23	-21.77	50.00	0.35	27.38	0.51	NEUTRAL	AVERAGE
12	19.532	32.93	-27.07	60.00	0.35	32.08	0.51	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11n
Test Date	May 22, 2014		

Configuration IEEE 802.11n MCS0 HT20 / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Total		
1	2412 MHz	17.26	18.15	16.71	22.19	30.00	Complies
6	2437 MHz	24.47	24.84	23.83	29.17	30.00	Complies
11	2462 MHz	18.88	19.29	17.62	23.42	30.00	Complies

Configuration IEEE 802.11n MCS0 HT40 / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Total		
3	2422 MHz	13.45	14.21	13.23	18.42	30.00	Complies
6	2437 MHz	17.62	18.92	17.42	22.81	30.00	Complies
9	2452 MHz	16.65	17.87	16.13	21.72	30.00	Complies

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11b/g
Test Date	May 22, 2014		

Configuration IEEE 802.11b / Chain 3

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	24.22	30.00	Complies
6	2437 MHz	23.41	30.00	Complies
11	2462 MHz	23.32	30.00	Complies

Configuration IEEE 802.11g / Chain 3

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.82	30.00	Complies
6	2437 MHz	23.88	30.00	Complies
11	2462 MHz	19.07	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT20 / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3	Total		
1	2412 MHz	-8.51	-7.12	-8.54	-3.23	8.00	Complies
6	2437 MHz	-1.98	-0.56	-2.17	3.26	8.00	Complies
11	2462 MHz	-7.28	-6.88	-8.28	-2.67	8.00	Complies

Configuration IEEE 802.11n MCS0 HT40 / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3	Total		
3	2422 MHz	-13.16	-14.05	-14.13	-8.99	8.00	Complies
6	2437 MHz	-9.81	-10.02	-9.85	-5.12	8.00	Complies
9	2452 MHz	-11.16	-10.08	-11.00	-5.95	8.00	Complies

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b / Chain 3

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	1.14	8.00	Complies
6	2437 MHz	1.23	8.00	Complies
11	2462 MHz	0.87	8.00	Complies


Configuration IEEE 802.11g / Chain 3

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-7.01	8.00	Complies
6	2437 MHz	-2.23	8.00	Complies
11	2462 MHz	-6.70	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1




Date: 22.MAY.2014 15:05:53

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 2




Date: 22.MAY.2014 15:20:52

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 3




Date: 22.MAY.2014 15:22:34

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 1




Date: 22.MAY.2014 15:33:38

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 2




Date: 22.MAY.2014 15:32:33

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 3




Date: 22.MAY.2014 15:31:29

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 3



Date: 22.MAY.2014 14:52:01

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 3



Date: 22.MAY.2014 14:58:39

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Deviation

There is no deviation with the original standard.

4.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.6. Test Result of 6dB Spectrum Bandwidth

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT20 / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.32	17.44	500	Complies
6	2437 MHz	15.12	17.68	500	Complies
11	2462 MHz	15.12	17.44	500	Complies

Configuration IEEE 802.11n MCS0 HT40 / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	31.36	35.68	500	Complies
6	2437 MHz	31.68	35.68	500	Complies
9	2452 MHz	32.64	35.68	500	Complies

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b / Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.00	10.24	500	Complies
6	2437 MHz	7.76	10.24	500	Complies
11	2462 MHz	8.00	10.16	500	Complies


Configuration IEEE 802.11g / Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.56	16.64	500	Complies
6	2437 MHz	16.32	16.72	500	Complies
11	2462 MHz	16.48	16.64	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1 + Chain 2 + Chain 3




Date: 22.MAY.2014 15:53:52

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2422 MHz / Chain 1 + Chain 2 + Chain 3




Date: 22.MAY.2014 15:55:26

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 3



Date: 22.MAY.2014 15:44:20

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 3



Date: 22.MAY.2014 15:46:41

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Deviation

There is no deviation with the original standard.

4.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.6. Results of Radiated Emissions (9kHz~30MHz)

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	CTX
Test Date	Jun. 03, 2014	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.7. Results of Radiated Emissions (30MHz~1GHz)


Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	CTX
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	deg	cm	
1	67.83	34.58	40.00	-5.42	54.46	1.25	6.82	27.95	Peak	0	100	HORIZONTAL
2	104.69	38.94	43.50	-4.56	53.18	1.53	12.00	27.77	Peak	0	100	HORIZONTAL
3	175.50	37.93	43.50	-5.57	53.27	1.98	10.08	27.40	Peak	0	100	HORIZONTAL
4	197.81	37.75	43.50	-5.75	52.65	2.08	10.28	27.26	Peak	0	100	HORIZONTAL
5	375.32	39.32	46.00	-6.68	47.78	2.89	15.91	27.26	Peak	0	100	HORIZONTAL
6	624.61	39.09	46.00	-6.91	43.41	3.81	19.45	27.58	Peak	0	100	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	deg	cm	
1	31.94	37.59	40.00	-2.41	46.00	0.87	18.70	27.98	Peak	2	100	VERTICAL
2	68.80	38.30	40.00	-1.70	58.17	1.26	6.81	27.94	QP	17	141	VERTICAL
3	97.90	40.40	43.50	-3.10	55.77	1.48	10.98	27.83	Peak	0	400	VERTICAL
4	147.37	37.14	43.50	-6.36	51.43	1.78	11.45	27.52	Peak	0	400	VERTICAL
5	375.32	40.71	46.00	-5.29	49.17	2.89	15.91	27.26	Peak	0	400	VERTICAL
6	812.79	38.82	46.00	-7.18	40.43	4.38	20.90	26.89	Peak	0	400	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.8. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4828.14	36.27	54.00	-17.73	32.21	5.87	33.39	35.20	Average	100	257	HORIZONTAL
2	4828.14	54.27	74.00	-19.73	50.21	5.87	33.39	35.20	Peak	100	257	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.14	36.78	54.00	-17.22	32.72	5.87	33.39	35.20	Average	100	193	VERTICAL
2	4826.36	47.34	74.00	-26.66	43.28	5.87	33.39	35.20	Peak	100	193	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss Factor	Factor	Remark	cm	deg	Pol/Phase
1	4871.66	54.28	74.00	-19.72	50.08	5.92	33.48	35.20 Peak	100	193	HORIZONTAL
2	4872.14	37.53	54.00	-16.47	33.33	5.92	33.48	35.20 Average	100	193	HORIZONTAL
3	7311.46	39.43	54.00	-14.57	31.22	7.13	36.51	35.43 Average	100	111	HORIZONTAL
4	7311.46	54.43	74.00	-19.57	46.22	7.13	36.51	35.43 Peak	100	111	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss Factor	Factor	Remark	cm	deg	Pol/Phase
1	4869.56	39.26	54.00	-14.74	35.09	5.92	33.45	35.20 Average	100	296	VERTICAL
2	4869.56	55.26	74.00	-18.74	51.09	5.92	33.45	35.20 Peak	100	296	VERTICAL
3	7311.46	56.43	74.00	-17.57	48.22	7.13	36.51	35.43 Peak	100	253	VERTICAL
4	7311.86	39.87	54.00	-14.13	31.66	7.13	36.51	35.43 Average	100	253	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4922.80	35.13	54.00	-18.87	30.78	5.97	33.58	35.20	Average	100	146	HORIZONTAL
2	4923.56	46.74	74.00	-27.26	42.39	5.97	33.58	35.20	Peak	100	146	HORIZONTAL
3	7381.68	37.11	54.00	-16.89	28.79	7.16	36.61	35.45	Average	100	275	HORIZONTAL
4	7390.78	49.78	74.00	-24.22	41.46	7.17	36.61	35.46	Peak	100	275	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4922.92	46.25	74.00	-27.75	41.90	5.97	33.58	35.20	Peak	100	35	VERTICAL
2	4928.76	37.88	54.00	-16.12	33.53	5.97	33.58	35.20	Average	100	35	VERTICAL
3	7384.78	37.22	54.00	-16.78	28.90	7.17	36.61	35.46	Average	100	125	VERTICAL
4	7389.02	50.34	74.00	-23.66	42.02	7.17	36.61	35.46	Peak	100	125	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT40 CH 3 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4839.28	46.25	74.00	-27.75	42.15	5.88	33.42	35.20	100	216	HORIZONTAL
2	4840.30	34.36	54.00	-19.64	30.26	5.88	33.42	35.20	100	216	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4848.10	33.19	54.00	-20.81	29.09	5.88	33.42	35.20	100	77	VERTICAL
2	4848.52	46.15	74.00	-27.85	42.05	5.88	33.42	35.20	100	77	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT40 CH 6 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.48	34.99	54.00	-19.01	30.79	5.92	33.48	35.20	Average	100	105 HORIZONTAL
2	4873.62	48.57	74.00	-25.43	44.37	5.92	33.48	35.20	Peak	100	105 HORIZONTAL
3	7309.22	36.93	54.00	-17.07	28.72	7.13	36.51	35.43	Average	100	236 HORIZONTAL
4	7315.46	49.44	74.00	-24.56	41.23	7.13	36.51	35.43	Peak	100	236 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4870.96	38.83	54.00	-15.17	34.63	5.92	33.48	35.20	Average	193	238 VERTICAL
2	4876.06	51.16	74.00	-22.84	46.96	5.92	33.48	35.20	Peak	193	238 VERTICAL
3	7306.10	48.98	74.00	-25.02	40.79	7.13	36.48	35.42	Peak	100	331 VERTICAL
4	7307.74	37.05	54.00	-16.95	28.84	7.13	36.51	35.43	Average	100	331 VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT40 CH 9 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss Factor	Factor	Remark	cm	deg	Pol/Phase
1	4903.03	38.43	54.00	-15.57	34.17	5.95	33.51	35.20 Average	156	330	HORIZONTAL
2	4903.12	51.31	74.00	-22.69	47.05	5.95	33.51	35.20 Peak	156	330	HORIZONTAL
3	7355.44	37.44	54.00	-16.56	29.16	7.16	36.56	35.44 Average	156	237	HORIZONTAL
4	7357.09	50.71	74.00	-23.29	42.43	7.16	36.56	35.44 Peak	100	237	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss Factor	Factor	Remark	cm	deg	Pol/Phase
1	4901.64	36.14	54.00	-17.86	31.88	5.95	33.51	35.20 Average	189	224	VERTICAL
2	4906.02	49.32	74.00	-24.68	45.03	5.95	33.54	35.20 Peak	189	224	VERTICAL
3	7353.69	50.33	74.00	-23.67	42.05	7.16	36.56	35.44 Peak	100	246	VERTICAL
4	7358.50	37.17	54.00	-16.83	28.90	7.16	36.56	35.45 Average	100	246	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 1 / Chain 3
Test Date	May 07, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.93	48.67	54.00	-5.33	44.61	5.87	33.39	35.20	Average	170	305	HORIZONTAL
2	4823.94	52.57	74.00	-21.43	48.51	5.87	33.39	35.20	Peak	170	305	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.92	56.07	74.00	-17.93	52.01	5.87	33.39	35.20	Peak	247	268	VERTICAL
2	4823.96	53.20	54.00	-0.80	49.14	5.87	33.39	35.20	Average	247	268	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 6 / Chain 3
Test Date	May 07, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4873.86	52.32	74.00	-21.68	48.12	5.92	33.48	35.20	Peak	153	235	HORIZONTAL
2	4873.97	48.47	54.00	-5.53	44.27	5.92	33.48	35.20	Average	153	235	HORIZONTAL
3	7309.90	52.14	74.00	-21.86	43.93	7.13	36.51	35.43	Peak	140	212	HORIZONTAL
4	7311.69	41.79	54.00	-12.21	33.58	7.13	36.51	35.43	Average	140	212	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4873.93	53.70	54.00	-0.30	49.50	5.92	33.48	35.20	Average	153	268	VERTICAL
2	4873.98	56.48	74.00	-17.52	52.28	5.92	33.48	35.20	Peak	153	268	VERTICAL
3	7309.44	51.48	74.00	-22.52	43.27	7.13	36.51	35.43	Peak	160	219	VERTICAL
4	7311.70	40.52	54.00	-13.48	32.31	7.13	36.51	35.43	Average	160	219	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 11 / Chain 3
Test Date	May 07, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4923.96	50.66	54.00	-3.34	46.31	5.97	33.58	35.20	Average	164	292	HORIZONTAL
2	4924.04	54.16	74.00	-19.84	49.81	5.97	33.58	35.20	Peak	164	292	HORIZONTAL
3	7384.74	51.66	74.00	-22.34	43.34	7.17	36.61	35.46	Peak	100	208	HORIZONTAL
4	7385.24	39.97	54.00	-14.03	31.65	7.17	36.61	35.46	Average	100	208	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4923.94	52.93	54.00	-1.07	48.58	5.97	33.58	35.20	Average	131	264	VERTICAL
2	4924.00	55.63	74.00	-18.37	51.28	5.97	33.58	35.20	Peak	131	264	VERTICAL
3	7384.37	51.42	74.00	-22.58	43.10	7.17	36.61	35.46	Peak	100	106	VERTICAL
4	7385.03	40.24	54.00	-13.76	31.92	7.17	36.61	35.46	Average	100	106	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 1 / Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4822.46	32.43	54.00	-21.57	28.37	5.87	33.39	35.20	Average	100	140	HORIZONTAL
2	4823.75	45.13	74.00	-28.87	41.07	5.87	33.39	35.20	Peak	100	140	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4821.50	32.39	54.00	-21.61	28.33	5.87	33.39	35.20	Average	100	65	VERTICAL
2	4823.98	44.82	74.00	-29.18	40.76	5.87	33.39	35.20	Peak	100	65	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 6 / Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4872.33	32.66	54.00	-21.34	28.46	5.92	33.48	35.20	Average	100	172	HORIZONTAL
2	4875.44	45.97	74.00	-28.03	41.77	5.92	33.48	35.20	Peak	100	172	HORIZONTAL
3	7308.52	49.05	74.00	-24.95	40.84	7.13	36.51	35.43	Peak	100	357	HORIZONTAL
4	7309.98	36.31	54.00	-17.69	28.10	7.13	36.51	35.43	Average	100	357	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4872.90	46.69	74.00	-27.31	42.49	5.92	33.48	35.20	Peak	100	241	VERTICAL
2	4873.39	33.43	54.00	-20.57	29.23	5.92	33.48	35.20	Average	100	241	VERTICAL
3	7309.57	49.25	74.00	-24.75	41.04	7.13	36.51	35.43	Peak	100	191	VERTICAL
4	7310.87	37.36	54.00	-16.64	29.15	7.13	36.51	35.43	Average	100	191	VERTICAL

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 11 / Chain 3
Test Date	May 12, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4925.38	46.24	74.00	-27.76	41.89	5.97	33.58	35.20	Peak	100	124	HORIZONTAL
2	4926.19	33.19	54.00	-20.81	28.84	5.97	33.58	35.20	Average	100	124	HORIZONTAL
3	7385.24	48.79	74.00	-25.21	40.47	7.17	36.61	35.46	Peak	100	207	HORIZONTAL
4	7385.28	36.49	54.00	-17.51	28.17	7.17	36.61	35.46	Average	100	207	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.17	46.30	74.00	-27.70	41.95	5.97	33.58	35.20	Peak	100	85	VERTICAL
2	4924.67	35.52	54.00	-18.48	31.17	5.97	33.58	35.20	Average	100	85	VERTICAL
3	7384.43	49.56	74.00	-24.44	41.24	7.17	36.61	35.46	Peak	100	13	VERTICAL
4	7385.67	36.53	54.00	-17.47	28.21	7.17	36.61	35.46	Average	100	13	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.
2. The radiated emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Deviation

There is no deviation with the original standard.

4.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.6. Test Result of Band Edge and Fundamental Emissions

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	53.53	54.00	-0.47	21.39	4.09	28.05	0.00	Average	196	72	VERTICAL
2	2390.00	69.45	74.00	-4.55	37.31	4.09	28.05	0.00	Peak	196	72	VERTICAL
3	2417.20	113.14	74.00			4.11	28.13	0.00	Peak	196	72	VERTICAL
4	2417.60	101.75	54.00			4.11	28.13	0.00	Average	196	72	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.60	66.91	74.00	-7.09	34.77	4.09	28.05	0.00	Peak	149	40	VERTICAL
2	2390.00	50.07	54.00	-3.93	17.93	4.09	28.05	0.00	Average	149	40	VERTICAL
3	2432.60	117.18	74.00			4.12	28.13	0.00	Peak	149	40	VERTICAL
4	2433.00	106.33	54.00			4.12	28.13	0.00	Average	149	40	VERTICAL
5	2483.50	50.93	54.00	-3.07	18.51	4.16	28.26	0.00	Average	149	40	VERTICAL
6	2488.30	70.71	74.00	-3.29	38.24	4.17	28.30	0.00	Peak	149	40	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2463.60	112.26	74.00			4.14	28.22	0.00	Peak	206	75	VERTICAL
2	2467.80	101.15	54.00			4.14	28.22	0.00	Average	206	75	VERTICAL
3	2483.50	53.75	54.00	-0.25	21.33	4.16	28.26	0.00	Average	206	75	VERTICAL
4	2483.70	71.91	74.00	-2.09	39.49	4.16	28.26	0.00	Peak	206	75	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT40 CH 3, 6, 9 / Chain 1 + Chain 2 + Chain 3
Test Date	May 12, 2014		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	53.76	54.00	-0.24	21.62	4.09	28.05	0.00	Average	206	55	VERTICAL
2	2390.00	70.03	74.00	-3.97	37.89	4.09	28.05	0.00	Peak	206	55	VERTICAL
3	2419.20	106.07	74.00			4.11	28.13	0.00	Peak	206	55	VERTICAL
4	2420.00	94.49	54.00			4.12	28.13	0.00	Average	206	55	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.80	68.82	74.00	-5.18	36.68	4.09	28.05	0.00	Peak	212	39	VERTICAL
2	2390.00	53.84	54.00	-0.16	21.70	4.09	28.05	0.00	Average	212	39	VERTICAL
3	2435.80	98.92	54.00			4.12	28.18	0.00	Average	212	39	VERTICAL
4	2435.80	111.04	74.00			4.12	28.18	0.00	Peak	212	39	VERTICAL
5	2483.50	50.42	54.00	-3.58	18.00	4.16	28.26	0.00	Average	212	39	VERTICAL
6	2484.30	61.63	74.00	-12.37	29.21	4.16	28.26	0.00	Peak	212	39	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2453.20	97.41	54.00			4.13	28.22	0.00	Average	204	73	VERTICAL
2	2453.20	110.17	74.00			4.13	28.22	0.00	Peak	204	73	VERTICAL
3	2487.10	71.25	74.00	-2.75	38.79	4.16	28.30	0.00	Peak	204	73	VERTICAL
4	2487.90	53.79	54.00	-0.21	21.32	4.17	28.30	0.00	Average	204	73	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 3
Test Date	May 12, 2014		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2388.80	53.73	54.00	-0.27	21.59	4.09	28.05	0.00	Average	203	57 VERTICAL
2	2389.20	65.24	74.00	-8.76	33.10	4.09	28.05	0.00	Peak	203	57 VERTICAL
3	2411.00	115.97	74.00			4.11	28.09	0.00	Peak	203	57 VERTICAL
4	2411.20	111.97	54.00			4.11	28.09	0.00	Average	203	57 VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2356.40	50.41	54.00	-3.59	18.37	4.07	27.97	0.00	Average	147	45 VERTICAL
2	2387.60	62.57	74.00	-11.43	30.43	4.09	28.05	0.00	Peak	147	45 VERTICAL
3	2436.20	111.92	54.00			4.12	28.18	0.00	Average	147	45 VERTICAL
4	2436.20	115.96	74.00			4.12	28.18	0.00	Peak	147	45 VERTICAL
5	2483.90	60.30	74.00	-13.70	27.88	4.16	28.26	0.00	Peak	147	45 VERTICAL
6	2499.90	49.12	54.00	-4.88	16.65	4.17	28.30	0.00	Average	147	45 VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2463.00	114.84	74.00			4.14	28.22	0.00	Peak	189	40 VERTICAL
2	2463.80	110.71	54.00			4.14	28.22	0.00	Average	189	40 VERTICAL
3	2483.50	63.28	74.00	-10.72	30.86	4.16	28.26	0.00	Peak	189	40 VERTICAL
4	2483.70	52.70	54.00	-1.30	20.28	4.16	28.26	0.00	Average	189	40 VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	23°C	Humidity	58%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 1, 6, 11 / Chain 3
Test Date	May 12, 2014		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2387.60	69.16	74.00	-4.84	37.02	4.09	28.05	0.00	Peak	178	52	VERTICAL
2	2390.00	53.73	54.00	-0.27	21.59	4.09	28.05	0.00	Average	178	52	VERTICAL
3	2415.40	101.47	54.00			4.11	28.09	0.00	Average	178	52	VERTICAL
4	2415.40	113.16	74.00			4.11	28.09	0.00	Peak	178	52	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2389.20	63.54	74.00	-10.46	31.40	4.09	28.05	0.00	Peak	185	46	VERTICAL
2	2390.00	50.82	54.00	-3.18	18.68	4.09	28.05	0.00	Average	185	46	VERTICAL
3	2429.80	106.70	54.00			4.12	28.13	0.00	Average	185	46	VERTICAL
4	2432.60	116.81	74.00			4.12	28.13	0.00	Peak	185	46	VERTICAL
5	2483.50	50.34	54.00	-3.66	17.92	4.16	28.26	0.00	Average	185	46	VERTICAL
6	2483.50	64.63	74.00	-9.37	32.21	4.16	28.26	0.00	Peak	185	46	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2465.40	100.78	54.00			4.14	28.22	0.00	Average	227	56	VERTICAL
2	2468.00	111.21	74.00			4.14	28.22	0.00	Peak	227	56	VERTICAL
3	2483.50	53.92	54.00	-0.08	21.50	4.16	28.26	0.00	Average	227	56	VERTICAL
4	2484.10	71.71	74.00	-2.29	39.29	4.16	28.26	0.00	Peak	227	56	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Date: 14.MAY.2014 06:15:01

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 14.MAY.2014 06:16:34

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 14.MAY.2014 06:17:15

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 14.MAY.2014 06:18:14

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 14.MAY.2014 06:18:49

Plot on Configuration IEEE 802.11n MCS0 HT40 / Reference Level




Date: 14.MAY.2014 06:22:15

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 14.MAY.2014 06:23:50

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 14.MAY.2014 06:24:31

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 30MHz~2400MHz (down 30dBc)




Date: 14.MAY.2014 06:25:59

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)




Date: 14.MAY.2014 06:27:08

Plot on Configuration IEEE 802.11b / Reference Level




Date: 14.MAY.2014 06:01:56

Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 14.MAY.2014 06:04:09

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 14.MAY.2014 06:04:55

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 14.MAY.2014 06:05:55

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 14.MAY.2014 06:06:29

Plot on Configuration IEEE 802.11g / Reference Level




Date: 14.MAY.2014 06:08:47

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 14.MAY.2014 06:10:02

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 14.MAY.2014 06:10:49

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 14.MAY.2014 06:11:52

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)



Date: 14.MAY.2014 06:12:24

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9 kHz ~ 2.75 GHz	Apr. 23, 2014	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150 kHz ~ 100 MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 11, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150 kHz ~ 30 MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Dec. 17, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch Receiver VSWR 1 = AMN/LISN VSWR 2 =	-0.080	dB	U-shaped	0.060
Combined standard uncertainty $U_c(y)$				1.2
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				2.4

Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	± 0.173	dB	k=1	0.086
Cable loss	± 0.174	dB	k=2	0.087
Antenna gain	± 0.169	dB	k=2	0.084
Site imperfection	± 0.433	dB	Triangular	0.214
Pre-amplifier gain	± 0.366	dB	k=2	0.183
Transmitter antenna	± 1.200	dB	Rectangular	0.600
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.778
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.555

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	± 0.191	dB	k=1	0.095
Cable loss	± 0.169	dB	k=2	0.084
Antenna gain	± 0.191	dB	k=2	0.096
Site imperfection	± 0.582	dB	Triangular	0.291
Pre-amplifier gain	± 0.304	dB	k=2	0.152
Transmitter antenna	± 1.200	dB	Rectangular	0.600
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.839
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.678

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	± 0.186	dB	k=1	0.093
Cable loss	± 0.167	dB	k=2	0.083
Antenna gain	± 0.190	dB	k=2	0.095
Site imperfection	± 0.488	dB	Triangular	0.244
Pre-amplifier gain	± 0.269	dB	k=2	0.134
Transmitter antenna	± 1.200	dB	Rectangular	0.600
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.771
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.541

Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	± 0.038	dB	k=2	0.019
Attenuator	± 0.047	dB	k=2	0.024
Power Meter specification	± 0.300	dB	Triangular	0.150
Power Sensor specification	± 0.300	dB	Rectangular	0.150
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				0.863
Measuring uncertainty for a level of confidence of 95% $U = 2U_c(y)$				1.726