


Label location:



NOTES:


- 1.Material:50u Top-coated Polyester Film,Thickness:0.052 ± 0.002mm
Glue Type:Embossed white glassine liner,Thickness:0.033 ± 0.003mm
材質：表面處理50番白色特多龍商標紙+格子膠
- 2.Dimension:64.4*74.4mm
- 3.Graphic color Pantone Black C
文字印刷黑色
- 4.The materials are compliant with the limits of
ROHS Directive 2002/95/EC and its subsequent amendments
- 5.In duplicate,Roll up
一式一份，整捲進料
- 6.Font : min 5.5pt Arial font
- 7.Barcode:must not be smaller than 1/8inch high



廠內列印示意圖
虛線部分為廠內列印區域


	Device Type: XB3V3 Model:DPC3941T DOCSIS 3.0 VOICE GATEWAY Rating:100-120 Vac, 50-60 Hz, 1.1A	FCC ID: VUIDPC3941
P/N	DPC3941-TMC14-K9	
S/N	267763034	
CM MAC	68EE96D70046	
Network Name (SSID 1):	HOME-0046-2.4	
Network Name (SSID 2):	HOME-0046-5	
Network Key(Password):	CCHWD7AATTAHH94R	
Encryption:	WPAWPA2-PSK(TKIP/AES)	
WPS Pin: 00702157	 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.	
RFPI:026BEABF58		
URL: http://10.0.0.1		
SW Ver.:dpc3941-P20-18-v303r204216-140109a-CMCST		
HW Ver.:1.0	Date of Mfg:01/14 Factory ID:F2 Made in China	

REV.	LTR	DATE	UPDATE DESCRIPTION	REMARK	SIGN	APPROVER
1		2014/03/25	增加UL/FCC &警語			




SCALE 1:1

Material Made



Roll Up



Example Of Factory Printing Location:

虛線部分為廠內列印區域

ITEM.	PART NAME	PART NO.	Q'TY /SET	MATERIAL (SPEC.)	REMARK
MATERIAL (SPEC.) 參照Notes標示		QUANTITY /SET 1/1	UNIHAN CORPORATION DESCRIPTION DEVICE LABEL DPC3941T		
FINISH		SCALE 1:1			
SELECT v		UNIT	SIZE	MODEL NO. DPC3941T	DRAWING NO. 1510-1HEW000
DIM.	TOL.	A	B	C	PARTS NO. 1510-1HEW000
~50	± 0.05	0.10	0.20	± 0.20	DESIGNED Anna
50~100	± 0.10	0.20	0.30	± 0.20	CHECKED Sujing Tsai
100~150	± 0.20	0.30	0.40	± 0.20	APPROVED Sujing Tsai
150~	± 0.20	0.40	0.50	± 0.20	