



Most Technology Service Co., Ltd.  
Tel: (86) 755-26825180 Fax: (86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

## Test Report

Product Name: GPS PORTABLE NAVIGATION DEVICE

FCC ID: VUP-G82C001

Model No.: 82C-1, 82C-2, 82C-3, 82C

Applicant:

YF INTERNATIONAL LIMITED  
7TH FL., CHINA ACADEMY OF SCIENCE&TECHNOLOGY DEV.,  
HIGH TECH SOUTH STREET 1, CHINA

**Date Received: 12/06/2008**

**Date Tested: 12/05-06/2008**



Most Technology Service Co., Ltd.  
Tel:(86) 755-26825180 Fax:(86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

## TABLE OF CONTENTS

**APPLICANT:** YF INTERNATIONAL LIMITED

**FCC ID:** VUP-G82C001

### TEST REPORT CONTAINING:

PAGE 1.....	TEST EQUIPMENT LIST
PAGE 2.....	TEST PROCEDURE
PAGE 3-5.....	POWER LINE CONDUCTED INTERFERENCE AND PLOTS
PAGE 6-8.....	RADIATION INTERFERENCE TEST DATA
PAGE 9-11.....	OCCUPIED BANDWIDTH AND PLOTS

### EXHIBIT INCLUDED:

PAGE 1.....	BLOCK DIAGRAM
PAGE 2.....	SCHEMATIC
PAGE 3.....	USERS MANUAL
PAGE 4.....	LABEL SAMPLE
PAGE 5.....	LABEL LOCATION
PAGE 6.....	EXTERNAL PHOTOGRAPHS
PAGE 7.....	INTERNAL PHOTOGRAPHS
PAGE 8.....	OPERATIONAL DESCRIPTION
PAGE 9.....	TEST SET UP PHOTOGRAPHS

APPLICANT: YF INTERNATIONAL LIMITED  
FCC ID: VUP-G82C001

TABLE OF CONTENTS



Most Technology Service Co., Ltd.

Tel: (86) 755-26825180 Fax: (86) 755-86170310

Http:// www. szmost.com Email: szmost@szmost.com

## EMC Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100492	Apr.05,2008	1 Year
LISN	ROHDE&SCHWARZ	ENV216	100093	Apr.05,2008	1 Year
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101202	Apr.05,2008	1 Year
Spectrum Analyzer	ANRITSU	MS2651B	6200238316	Apr.05,2008	1 Year
50 Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Apr.05,2008	1 Year
Bilog Antenna	Sunol	JB3	A121206	Apr.05,2008	1 Year
Horn Antenna	EMCO	3115	640201028-06	Apr.05,2008	1 Year
50 Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Apr.05,2008	1 Year
Cable	Resenberger	N/A	NO.1	Apr.05,2008	1 Year
Cable	SCHWARZBECK	N/A	NO.2	Apr.05,2008	1 Year
Cable	SCHWARZBECK	N/A	NO.3	Apr.05,2008	1 Year
Single Phase Power Line Filter	Kikusui	LIN40MA-PC R-L	LM002352	Apr.05,2008	1 Year
AC Power Source	Kikusui	AC40MA	LM003232	Apr.05,2008	1 Year
Test analyzer	Kikusui	KHA1000	LM003720	Apr.05,2008	1 Year
ESD Tester	Kikusui	KES4021	LM003537	Apr.07,2008	1 Year
Signal Generator	IFR	2032	203002/100	Apr.07,2008	1 Year
Amplifier	A&R	150W1000	301584	NCR	NCR
Dual Directional Coupler	A&R	DC6080	301508	Apr.05,2008	1 Year
Power Head	A&R	PH2000	301193	Apr.05,2008	1 Year
Power Meter	A&R	PM2002	302799	Apr.05,2008	1 Year
Field Monitor	A&R	FM5004	300329	Apr.05,2008	1 Year
Field Probe	A&R	FP5000	300221	Apr.05,2008	1 Year
EMC PRO System	EM Test	UCS-500-M4	V0648102026	Apr.05,2008	1 Year
EMC PRO System	EM Test	UCS-500-M4	V0648102026	Apr.05,2008	1 Year

Remark:

Test Firm Name: Most Technology Service Co., Ltd.

Test Firm Address:

No. 5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China

FCC Registered Test Site Number: 490827

APPLICANT: YF INTERNATIONAL LIMITED

FCC ID: VUP-G82C001



Most Technology Service Co., Ltd.  
Tel: (86) 755-26825180 Fax: (86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

## TEST PROCEDURE

**GENERAL:** This report shall NOT be reproduced except in full without the written approval of MOST TECHNOLOGY SERVICE CO., LTD. The EUT was transmitting a test signal during the testing.

**POWER LINE CONDUCTED INTERFERENCE:** The test procedure used was ANSI Standard C63.4-2003 using a 50 UH LISN. Both Lines were observed. The bandwidth of the receiver was 10kHz with an appropriate sweep speed. The ambient temperature of the EUT was 25 with a humidity of 58%.

**RADIATION INTERFERENCE:** The test procedure used was ANSI Standard C63.4-2003 using a ANRITSU spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. The ambient temperature of the EUT was 25 with a humidity of 58%.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer and cable loss. The antenna correction factors and cable loss are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF + CABLE = FS  
33 20 dBuV + 10.36 dB + 0.9 dB= 31.26 dBuV/m @ 3m

**ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES:** The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings were converted to average readings based on the duration of "ON" time.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI Standard C63.4-2003 10.1.7 with the EUT 40 cm from the vertical ground wall.



Most Technology Service Co., Ltd.  
Tel: (86) 755-26825180 Fax: (86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

**APPLICANT:** YF INTERNATIONAL LIMITED  
**FCC ID:** VUP-G82C001  
**NAME OF TEST:** POWER LINE CONDUCTED INTERFERENCE  
**RULES PART NUMBER:** 15.207

**REQUIREMENTS:**

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

**TEST PROCEDURE:** ANSI STANDARD C63.4-2003

THE HIGHEST EMISSION READ FOR LINE 1 WAS 55.42dBuV @ 0.254MHz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 53.68dBuV @ 0.243MHz.

THE PLOTS ON THE NEXT PAGE REPRESENT THE EMISSIONS READ FOR POWER LINE CONDUCTED FOR THIS DEVICE.

### Conducted Emission Measurement


File : 82C

Data : #11

Date: 2008-12-06

Time: 17:44:11

80.0 dBuV



Site site #1

Phase: **L1**

Temperature: 26

Limit: FCC Part 15C Conduction

Power: DC 5V Adaptor AC 120V/60Hz Humidity: 60 %

EUT: GPS Portable Navigation Device

M/N: 82C-1

Mode: ON(FM Mode)

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1660	47.55	9.96	57.51	65.16	-7.65	QP	
2		0.1660	34.45	9.96	44.41	55.16	-10.75	AVG	
3		0.2100	42.62	11.93	54.55	63.21	-8.66	QP	
4		0.2100	29.68	11.93	41.61	53.21	-11.60	AVG	
5	*	0.2540	43.78	11.64	55.42	61.63	-6.21	QP	
6		0.2540	33.72	11.64	45.36	51.63	-6.27	AVG	
7		0.2940	38.60	11.37	49.97	60.41	-10.44	QP	
8		0.2940	31.22	11.37	42.59	50.41	-7.82	AVG	
9		0.3380	36.80	11.08	47.88	59.25	-11.37	QP	
10		0.3380	29.22	11.08	40.30	49.25	-8.95	AVG	
11		0.6660	33.53	10.00	43.53	56.00	-12.47	QP	
12		0.6660	23.14	10.00	33.14	46.00	-12.86	AVG	

\*:Maximum data x:Over limit !:over margin

APPLICANT: YF INTERNATIONAL LIMITED  
FCC ID: VUP-G82C001

## Conducted Emission Measurement


File : 82C

Data : #12

Date: 2008-12-06

Time: 17:46:29

80.0 dBuV



Site site #1

Phase: **N**

Temperature: 26

Limit: FCC Part 15C Conduction

Power: DC 5V Adaptor AC 120V/60Hz Humidity: 60 %

EUT: GPS Portable Navigation Device

M/N: 82C-1

Mode: ON(FM Mode)

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1650	45.80	9.90	55.70	65.21	-9.51	QP	
2		0.1650	32.33	9.90	42.23	55.21	-12.98	AVG	
3		0.2040	41.34	11.97	53.31	63.45	-10.14	QP	
4		0.2040	30.10	11.97	42.07	53.45	-11.38	AVG	
5		0.2430	41.97	11.71	53.68	61.99	-8.31	QP	
6	*	0.2430	32.61	11.71	44.32	51.99	-7.67	AVG	
7		0.2908	39.14	11.39	50.53	60.50	-9.97	QP	
8		0.2908	28.49	11.39	39.88	50.50	-10.62	AVG	
9		0.3302	36.99	11.13	48.12	59.45	-11.33	QP	
10		0.3302	27.23	11.13	38.36	49.45	-11.09	AVG	
11		0.6304	32.69	10.00	42.69	56.00	-13.31	QP	
12		0.6304	23.65	10.00	33.65	46.00	-12.35	AVG	

\*:Maximum data x:Over limit !:over margin

APPLICANT: YF INTERNATIONAL LIMITED  
FCC ID: VUP-G82C001



Most Technology Service Co., Ltd.  
Tel:(86) 755-26825180 Fax:(86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

**APPLICANT:** YF INTERNATIONAL LIMITED

**FCC ID:** VUP-G82C001

**NAME OF TEST:** RADIATION INTERFERENCE

**RULES PART NUMBER:** 15.239, 15.209

**REQUIREMENTS:**

FIELD STRENGTH of S15.209  
Fundamental:

88-108 MHZ 30 -88 MHz 40 dBuV/m @3M  
88 - 216 MHz 43.5  
216 - 960 MHz 46  
47.96 dBuV/m @3m ABOVE 960 MHz 54dBuV/m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 dB BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

**REMARK: Emissions attenuated more than 20 dB below the permissible value are not reported.**

Fundamental Radiation Interference Data:

Frequency (MHz)	Antenna Polarization	Emission Level (dBuV/m)			FCC 15 Subpart C Limit (dBuV/m)
		Avg	QP	Peak	
88.1MHz					
88.100	Vertical	--	42.31	44.20	47.96
88.100	Horizontal	--	39.53	40.76	47.96
98.1MHz					
98.100	Vertical	--	41.03	43.69	47.96
98.100	Horizontal	--	39.82	40.01	47.96
107.9MHz					
107.900	Vertical	--	41.17	43.69	47.96
107.900	Horizontal	--	40.04	41.33	47.96

APPLICANT: YF INTERNATIONAL LIMITED  
FCC ID: VUP-G82C001





Most Technology Service Co., Ltd.  
Tel: (86) 755-26825180 Fax: (86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

**APPLICANT:** YF INTERNATIONAL LIMITED

**FCC ID:** VUP-G82C001

**NAME OF TEST:** RADIATION INTERFERENCE

**RULES PART NUMBER:** 15.239, 15.209

**REQUIREMENTS:**

FIELD STRENGTH of S15.209  
Fundamental:

88-108 MHZ 30 -88 MHz 40 dBuV/m @3M  
88 - 216 MHz 43.5  
216 - 960 MHz 46  
47.96 dBuV/m @3m ABOVE 960 MHz 54 dBuV/m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 dB BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

**Continued:**

General Radiation Interference Data:

Frequency (MHz)	Antenna Polarization	Emission Level (dBuV/m)			FCC 15 Subpart C Limit (dBuV/m)
		Avg	QP	Peak	
163.86	Horizontal	--	33.29	35.23	43.5
319.06	Horizontal	--	--	31.09	46.0
340.40	Horizontal	--	--	30.11	46.0
371.44	Horizontal	--	--	28.93	46.0
123.12	Vertical	--	--	33.15	43.5
163.86	Vertical	--	--	29.11	43.5
214.30	Vertical	--	33.09	35.16	43.5
371.44	Vertical	--	--	33.21	46.0

TEST PROCEDURE: ANSI Standard C63.4-2003 using a ANRITSU spectrum analyzer with a pre-selector and an appropriate antenna. The resolution bandwidth of spectrum analyzer was 100 kHz below 1 GHz and 1 MHz above 1 GHz. An appropriate sweep speed was used. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

APPLICANT: YF INTERNATIONAL LIMITED  
FCC ID: VUP-G82C001



Most Technology Service Co., Ltd.  
Tel:(86) 755-26825180 Fax:(86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

**APPLICANT:** YF INTERNATIONAL LIMITED

**FCC ID:** VUP-G82C001

**NAME OF TEST:** Occupied Bandwidth and Band Edge Compliance

**RULES PART NUMBER:** 15.239, 15.209

**REQUIREMENTS:** Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108 MHz.

Band edge emissions plots are included on the following pages

**METHOD OF MEASUREMENT:** A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to 10 dB per division.

**TEST RESULTS:** The unit DOES meet the FCC requirements.



Most Technology Service Co., Ltd.  
Tel: (86) 755-26825180 Fax: (86) 755-86170310  
Http:// www. szmost.com Email: szmost@szmost.com

When the EUT transmits the real MP3 file max volume level.

88.1MHz



98.1MHz



107.9MHz

