

No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663 Telephone: +86 (0) 20 8215 5555 Fax: +86 (0) 20 8207 5059

 $Email: sgs\_internet\_operations@sgs.com$ 

FEDERAL COMMUNICATIONS COMMISSION

Registration number: 556682

Report No.: SZEMO071203739RFF(I)

Page : 1 of 8

FCC ID : VVAAD232011

# TEST REPORT

**Application No.** : SZEMO071203739RF(SGS SZ NO.: SZTYR071203334/EL) **Applicant** : GUANGDONG ALPHA ANIMATION AND CULTURE CO., LTD.

(Former Name:GUANG DONG AULDEY TOY INDUSTRY CO., LTD.)

Manufacturer : AULDEY

FCC ID : VVAAD232011

Fundamental Frequency: 49MHz Equipment under Test (EUT):

EUT Name : HONDA CIVIC TYRE R, LEXUS IS 350, BNW 320SI WTCC

Item No. : LC232020, LC232030, LC232040.

Labelled Age Grading: AGE 3+ Country of Origin: China

Please refer to section 2 of this report which indicates which item was actually tested

and which were electrically identical.

Standards : FCC PART 15, SUBPART C : 2007 Section 15.235

Date of Receipt : 21 December 2007

Date of Test : 21 December 2007 to 13 January 2008

Date of Issue : 23 January 2008

Test Result : PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEMO070400629RFF(I)

Page : 2 of 8

# 2 Test Summary

Test	Test Requirement	Stanadard Paragraph	Result	
Radiated Emission (30MHz to 1000MHz)	FCC PART 15 :2007	Section 15.235	PASS *	
Occupied Bandwidth	FCC PART 15 :2007	Section 15.235	PASS	

Tx: In this whole report Tx (or tx) means Transmitter.Rx: In this whole report Rx (or rx) means Receiver.RF: In this whole report RF means Radiated Frequency.

Remark:

Item No.: LC232020, LC232030, LC232040

Only the Item in the picture 5.3 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above items.

\* The EUT passed the RE test after modification.



Report No.: SZEMO070400629RFF(I)

Page : 3 of 8

# 3 Contents

			Page
1	CO	VER PAGE	1
2	TES	ST SUMMARY	2
3	COI	NTENTS	3
4		NERAL INFORMATION	
	4.1 4.2 4.3 4.4 4.5	CLIENT INFORMATION  DETAILS OF E.U.T  DESCRIPTION OF SUPPORT UNITS  TEST LOCATION  OTHER INFORMATION REQUESTED BY THE CUSTOMER	4 4 4
5		ST RESULTS	
	5.1 5.2 5.3 <i>5.3.</i>	TEST INSTRUMENTS E.U.T. OPERATION TEST PROCEDURE & MEASUREMENT DATA	5 5 5-7



Report No.: SZEMO070400629RFF(I)

Page : 4 of 8

## 4 General Information

### 4.1 Client Information

Applicant: GUANGDONG ALPHA ANIMATION AND CULTURE CO., LTD.

(Former Name: GUANG DONG AULDEY TOY INDUSTRY CO., LTD.)

Address of Applicant: Auldey Ind Area, Wenguan Rd., (Central), Chenghai, Shantou, Guangdong,

China

### 4.2 Details of E.U.T.

Product Name: HONDA CIVIC TYRE R, LEXUS IS 350, BNW 320SI WTCC

Item No: LC232020, LC232030, LC232040.

Please refer to section 2 of this report which indicates which item was actually

tested and which were electrically identical.

Power Supply: 3.0V DC (2 \* 1.5V 'AA' Size Batteries) for Tx

Power Cord: N/A-

## 4.3 Description of Support Units

The EUT was tested as an independent unit: a 49MHz radio transmitter.

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Tel: +86 20 8215 5555 Fax: +86 20 8207 5059

### 4.5 Other Information Requested by the Customer

None.



Report No.: SZEMO070400629RFF(I)

Page : 5 of 8

## 5 Test Results

#### 5.1 Test Instruments

R8	R&TTE RE in Chamber									
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)				
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2007	15-06-2008				
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2007	11-12-2008				
3	3 EMI Test software AUDIX		E3	SEL0050	N/A	N/A				
4	Coaxial cable	SGS	N/A	SEL0028	01-06-2007	31-05-2008				
5	Coaxial cable	SGS	N/A	SEL0027	20-10-2007	19-10-2008				
6	6 BiConiLog Antenna (26-3000MHz) ETS-LINDGREN		3142C	SEL0014	12-08-2007	11-08-2008				
7	7 EMI Test Receiver Rohde & Schwarz		ESCI	SEL0022	27-06-2007	26-06-2008				
8	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	15-06-2007	14-06-2008				

### 5.2 E.U.T. Operation

Input voltage: 3.0V DC (2 \* 1.5V 'AA' Size Batteries) for the transmitter.

Operating Environment:

Temperature: 23.0 °C
Humidity: 52 % RH
Atmospheric Pressure: 1020 mbar

**EUT Operation:** 

Test the EUT in transmitting mode.

#### 5.3 Test Procedure & Measurement Data

### 5.3.1 Radiated Emissions

Test Requirement: FCC Part15 C Section 15.235

Test Method: ANSI C63.4:2003

Test Date: 26 December 2007(Initial Test)

13 January 2008(Test after Modification)

Measurement Distance: 3m (Semi-Anechoic Chamber)

Requirements: Carrier frequency will not exceed 80dBuV/m AT 3m.

Out of band emissions shall not exceed:  $40.0~dB\mu V/m$  between 30MHz~&~88MHz  $43.5~dB\mu V/m$  between 88MHz~&~216MHz  $46.0~dB\mu V/m$  between 216MHz~&~960MHz

 $54.0\; dB\mu V/m$  above 960MHz

Detector: Peak Scan (120kHz resolution bandwidth)

#### FCC ID.: VVAAD232011



Report No.: SZEMO070400629RFF(I)

Page : 6 of 8

#### Test Procedure:

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7 The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

Test the EUT in transmitting mode.

#### Intentional emission

Test Frequency	Peak (dBμV/m)		Limits	Margin (dB)	
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
49.860	83.74	55.25	100.0	16.25	44.75

Test Frequency	Average (dBμV/m)		Limits	Margin (dB)		
(MHz)	Vertical	Horizontal	(dBμV/m)	Vertical	Horizontal	
49.860	76.90	49.05	80.0	3.10	30.95	



SZEMO070400629RFF(I) Report No.:

Page 7 of 8

#### Other emissions

#### Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
97.90	1.18	9.02	27.89	52.02	34.33	43.50	-9.17
148.34	1.32	8.86	27.47	51.76	34.47	43.50	-9.03
198.78	1.40	10.19	27.16	51.31	35.74	43.50	-7.76
249.22	1.67	12.27	26.92	53.00	40.02	46.00	-5.98
347.19	2.05	15.34	27.07	46.66	36.98	46.00	-9.02
397.63	2.20	16.27	27.39	51.86	42.94	46.00	-3.06
447.10	2.40	16.84	27.56	45.89	37.57	46.00	-8.43
497.54	2.59	17.80	27.70	46.80	39.49	46.00	-6.51
547.98	2.65	18.87	27.67	46.57	40.42	46.00	-5.58

#### Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
249.22	1.67	12.27	26.92	37.96	24.98	46.00	-21.02
347.19	2.05	15.34	27.07	38.87	29.19	46.00	-16.81
397.63	2.20	16.27	27.39	40.54	31.62	46.00	-14.38
447.10	2.40	16.84	27.56	38.70	30.38	46.00	-15.62
497.54	2.59	17.80	27.70	40.19	32.88	46.00	-13.12
547.98	2.65	18.87	27.67	42.79	36.64	46.00	-9.36

#### Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a imit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

Test Results: The unit does meet the FCC Part 15 C Section 15.235 requirements.



Report No.: SZEMO070400629RFF(I)

Page : 8 of 8

# 5.3.2 Occupied Bandwidth

Test Requirement: FCC Part15 C Section 15.235

Test Method: ANSI C63.4:2003

Operation within the band 49.82 - 49.90 MHz

Test Date: 21 December 2007

Requirements: The field strength of any emissions appearing between the band edges

and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits in Section 15.209, whichever permits the higher emission levels. The field strength of any emissions removed by more than 10 kHz from the band edges shall not exceed the general radiated emission limits in


Section 15.209.

Method of measurement: The useful radiated emission from the EUT was detected by the spectrum

analyer with peak detector. The vertical Scale is set to −10dB per division.

The horizontal scale is set to 8KHz per division.

The graph as below, represents the emissions take for this device.



Date: 21.DEC.2007 13:15:55

The results: The unit does meet the FCC Part 15 C Section 15.235 requirements.

FCC ID.: VVAAD232011