




# RF EXPOSURE REPORT



Report No.: 15020952-FCC-H1

Supersede Report No.: N/A

Applicant	Beijing Jia An Electronic Technology Co., Ltd	
Product Name	BLE module	
Model No.	AN2640SA-B	
Test Standard	FCC 2.1091	
Test Date	November 17 to November 23, 2015	
Issue Date	November 24, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Deon Dai Test Engineer	Herve Idoko Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (Nanjing-China) Laboratories

2-1 Longcang Avenue Yuhua Economic and

Technology Development Park, Nanjing, China

Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: China@siemic.com.cn

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	15020952-FCC-H1
Page	3 of 8

---

This page has been left blank intentionally.

# CONTENTS

1	REPORT REVISION HISTORY.....	5
2	CUSTOMER INFORMATION .....	5
3	TEST SITE INFORMATION.....	5
4	EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5	FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	7

## 1 Report Revision History

Report No.	Report Version	Description	Issue Date
15020952-FCC-H1	NONE	Original	November 24,2015

## 2 Customer information

Applicant Name	Beijing Jia An Electronic Technology Co., Ltd
Applicant Add	No.19 GuCheng West Street, Shi Jing Shan District, Beijing 100043,CHINA
Manufacturer	Beijing Jia An Electronic Technology Co., Ltd
Manufacturer Add	No.19 GuCheng West Street, Shi Jing Shan District, Beijing 100043,CHINA

## 3 Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	Labview of SIEMIC version 1.0

## 4 Equipment under Test (EUT) Information

Description of EUT:	BLE module
Main Model:	AN2640SA-B
Serial Model:	N/A
Date EUT received:	November 05, 2015
Test Date(s):	November 17 to November 23, 2015
Output power	4.789 dBm (3.01mW)
Antenna Gain:	BLE: 0dBi
Type of Modulation:	BLE:GFSK
RF Operating Frequency (ies):	BLE: 2402-2480 MHz(TX/RX)
Number of Channels:	BLE: 40CH
Port:	N/A
Input Power:	DC 1.8V-3.8V
Trade Name :	N/A
FCC ID:	VVJ-AN2640SA-B

## 5 FCC §2.1091 - Maximum Permissible exposure (MPE)

### Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### Test Data

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)
Output power	BLE	Low	2402	4.789	4.0±1
		Mid	2440	3.824	
		High	2480	3.765	

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

#### BLE Mode:

The maximum peak output power (turn-up power) in low channel of BLE is 5.0 dBm

Maximum peak output power (turn-up power) at antenna input terminal: 3.16 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2402(MHz) lowest frequency

Antenna Gain (typical): 0 (dBi)

Antenna Gain (typical): 1 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.0006(mW/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm<sup>2</sup>)

$$0.0006(\text{mW}/\text{cm}^2) < 1(\text{mW}/\text{cm}^2)$$

The maximum peak output power (turn-up power) in Middle channel of BLE is 5.0 dBm

Maximum peak output power (turn-up power) at antenna input terminal: 3.16 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2440(MHz) lowest frequency

Antenna Gain (typical): 0(dBi)

Antenna Gain (typical):1(numeric)

The worst case is power density at predication frequency at 20 cm: 0.0006(mW/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm<sup>2</sup>)

$$0.0006 (\text{mW}/\text{cm}^2) < 1(\text{mW}/\text{cm}^2)$$

The maximum peak output power (turn-up power) in High channel of BLE is 5.0dBm

Maximum peak output power (turn-up power) at antenna input terminal: 3.16 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2480(MHz) lowest frequency

Antenna Gain (typical):0 (dBi)

Antenna Gain (typical):1(numeric)

The worst case is power density at predication frequency at 20 cm: 0.0006(mW/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm<sup>2</sup>)

$$0.0006 (\text{mW}/\text{cm}^2) < 1(\text{mW}/\text{cm}^2)$$

**Result: Pass**