

"High Frequency Ceramic Solutions"

2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013


Page 1 of 10

General Specifications

Part Number	2450AT45A100	Input Power	3W max. (CW)
Frequency Range	2400 - 2500 Mhz	Impedance	50 Ω
Operating Temp	-40°C to +125°C	Reel Quantity	1,000

Mechanical Specifications

	In	mm
L	0.374 \pm 0.008	9.50 \pm 0.20
W	0.079 \pm 0.008	2.00 \pm 0.20
T	0.047 \pm 0.004/-0.008	1.20 \pm 0.1/-0.2
a	0.020 \pm 0.012	0.50 \pm 0.30



Terminal Configuration

No.	Function
1	Feeding Point
2	NC


Typical Electrical Specs for "Vertical Orientation" (T=25°C)

Frequency Range	2400 - 2500 Mhz	Peak Gain	3.0 dBi typ. (XZ-V)
Return Loss	9.5 dB min.	Average Gain	1.0 dBi typ. (XZ-V)

Mounting Considerations 1: "Vertical Orientation"

Mount these devices with red mark facing up. Units: mm

* Line width should be designed to provide 50 Ω impedance matching characteristics.



a) Without Matching Circuit (moderate bandwidth)

b) With Matching Circuit* (wide bandwidth)
These matching circuit values only apply to Johanson's evaluation board, they will be different on the client's PCB, see pages 2 and 10 for details.

"C" Dimension will depend on the width of the trace required for it to have a 50ohm characteristic impedance (i.e. coplanar waveguide theory)

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.1

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100


Detail Specification: 9/4/2013

Page 2 of 10

Typical Electrical Characteristics for "Vertical Orientation" (T=25°C)


Test Board

Orderable Evaluation board:
p/n: 2450AT45A100-EB1SM/
"Vertical Orientation"



Note: It is recommended that the designer leave available slots for a "pi" (or shunt-series-shunt) network. The antenna matching network values above are used when antenna is mounted on Johanson's evaluation board. The matching values on client's PCB will be different, go to: <http://johansontechnology.com/tuning> and see how to obtain the new values. If you need further help, contact our RF Applications Eng Team at: <http://www.johansontechnology.com/en/ask-a-technical-question.html>

Return Loss



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"


2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013

Page 3 of 10

Typical Radiation Patterns for "Vertical Orientation" (@25C)



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013

Page 4 of 10

Typical Electrical Specs for "Horizontal Orientation_1" (T=25°C)


Frequency Range	2400 - 2500 Mhz	Peak Gain	1.5 dBi typ. (XZ-V)
Return Loss	9.5 dB min.	Average Gain	0.0 dBi typ. (XZ-V)

Mounting Considerations 2 - Horizontal Orientation_1

Mount these devices with brown mark facing up. Units: mm

*Line width should be designed to provide 50Ω impedance matching characteristics.

Units in mm



EVB p/n:
2450AT45A100-EB2SMA
Horizontal Orientation_1

"C" Dimension will depend on the width of the trace required for it to have a 50ohm characteristic impedance (i.e. coplanar waveguide theory)

*These matching circuit values only apply to Johanson's evaluation board, they will be different on the client's PCB, see pages 5 and 10 for

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100


Detail Specification: 9/4/2013

Page 5 of 10

Typical Electrical Characteristics "Horizontal Orientation_1" (T=25°C)

Test Board


Orderable Eval
p/n: 2450AT45A100-EB2SMA
"Horizontal Orientation_1"



Note: It is recommended that the designer leave available slots for a "pi" (or shunt-series-shunt) network. The antenna matching network values above are used when antenna is mounted on Johanson's evaluation board. The matching values on client's PCB will be different, go to: <http://johansontechnology.com/tuning> and see how to obtain the new values. If you need further help, contact our RF Applications Eng Team at: <http://www.johansontechnology.com/en/ask-a-technical-question.html>

Return Loss

a) With Matching Circuit



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"


2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013

Page 6 of 10

Typical Radiation Patterns for "Horizontal Orientation_1" (@25C)



Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013

Page 7 of 10

Typical Electrical Specs for "Horizontal Orientation_2" (T=25°C)


Frequency Range	2400 - 2500 Mhz	Average Gain	0.6 dBi typ. (XZ-V)
Return Loss	9.5 dB min.	Peak Gain	1.3 dBi typ. (XZ-V)

Mounting Considerations 3 - Horizontal Orientation_2

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50Ω impedance matching characteristics.

Units in mm



EVB p/n:
2450AT45A100-EB2SMA
Horizontal Orientation_2

Note: It is recommended that the designer leave available slots for a "pi" (or shunt-series-shunt) network. The antenna matching network values above are used when antenna is mounted on Johanson's evaluation board. The matching values on client's PCB will be different, go to: <http://johansontechnology.com/tuning> and see how to obtain the new values. If you need further help, contact our RF Applications Eng Team at: <http://www.johansontechnology.com/en/ask-a-technical-question.html>

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013

Page 8 of 10


Typical Electrical Characteristics Horizontal Orientation_2 (T=25°C)

Test Board

EVB p/n:



2450AT45A100-EB3SMA

Horizontal Orientation_2



Return Loss

a) With Matching Circuit (0ohm)



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"


2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013

Page 9 of 10

Typical Radiation Patterns for "Horizontal Orientation_2" (@25C)



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved

www.johansontechnology.com

"High Frequency Ceramic Solutions"

2.45 GHz High Gain SMD Chip Antenna

P/N 2450AT45A100

Detail Specification: 9/4/2013

Page 10 of 10

Part Number Explanation

P/N Suffix	Packaging Style*	Bulk (loose pieces)	Suffix = S	Eg. 2450AT45A100S
		T & R	Suffix = E	Eg. 2450AT45A100E
		T & R (Reverse)	Suffix = R	Eg. 2450AT45A100R (MOQ Applies)
		100% Tin	Suffix = None	Eg. 2450AT45A100(S, E, R)
	Termination style	Tin / Lead	Please consult Factory	
	Evaluation Boards (1-port SMA antenna test boards)	2450AT45A100-EB1SMA (Page 2)		
		2450AT45A100-EB2SMA (Page 5)		
		2450AT45A100-EB3SMA (Page 8)		

Storage Conditions and Shelf Life (On T&R or Bulk)

Temperature: +5C to +35°C	Shelf Life: 18 months max.
Relative Humidity: 45 to 75%	

Packaging information

www.johansontechnology.com/ipcpackaging.html

Soldering Information

www.johansontechnology.com/ipcsoldering-profile

Antenna layout and tuning techniques

www.johansontechnology.com/tuning

Antenna layout review, tuning, and characterization services

www.johansontechnology.com/ipcantennaservices

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.0

2013 Johanson Technology, Inc. All Rights Reserved