| Oty Designator 1 C18 2 C11, C12 2 C22, C23 2 C5, C6 2 C2, C8  | Description Ceramic capacitor, SMD 0402, NP0, 50V, +/-0.25pF Ceramic capacitor, SMD 0402, NP0, 50V, +/-5% Ceramic capacitor, SMD 0402, NP0, 50V, +/-5% Ceramic capacitor, SMD 0402, NP0, 50V, +/-5% Ceramic capacitor, SMD 0402, X7R, 25V, +/-10%                               | Manufacturer   | MPN                                | ShortName<br>1.5p<br>12p<br>18p<br>22p<br>10n |
|---|---|--|------------------------------------|---|
| 1 C4<br>12 C1, C10, C13, C16, C17, C21, C24, C25, C26, C3, C7, C9<br>2 R15, R16<br>2 R3, R8<br>5 R1, R10, R5, R6, R7<br>6 R12, R13, R14, R2, R4, R9 | Ceramic capacitor, SMD 0402, X7R, 16V, +/-10%<br>Ceramic capacitor, SMD 0402, X5R, 6.3V, +/-10%<br>Thick film resistor, SMD 0402, 1/16W, 1%<br>Thick film resistor, SMD 0402, 1/16W, 1%<br>Thick film resistor, SMD 0402, 1/16W, 1%<br>Thick film resistor, SMD 0402, 1/16W, 1% | Kemet<br>Kemet   | C0402C104K4RACTU<br>C0402C105K9PAC | 100n<br>1u<br>0R<br>22R<br>470R<br>10k        |
| 1 L1  | SMD RF inductor 0805. Z=1000Ohm (@100MHz), Max  | Murata Philips Texas Instruments ATMEL ATMEL ATMEL Texas Instruments   | BLM21AG102SN1D                     | BLM21AG102SN1D                                |
| 1 Q1  | General purpose SMD small signal BJT transistor.  |  | BC847W                             | BC847W  |
| 1 U5  | USB Port Transient Suppressor, SMD DSBGA  |  | SN65220YZBR                        | SN65220YZBT                                   |
| 1 U1  | AVR 8-bit RISC MCU with USB, QFN64 package  |  | AT90USB1287-16MU                   | AT90USB1287-16MU                              |
| 1 U2  | 2.4GHz ZigBee/802.15.4 tranceiver   |  | AT86RF230-ZU                       | AT86RF230-ZU                                  |
| 1 U3  | 2kbit Serial (TWI) EEPROM, AT24C02B, 1.8-5V   |  | AT24C02B-TSU-T                     | AT24C02B-TSU-T                                |
| 1 U4  | LDO 3.3V 150mA SOT23-5 (cer. cap)   |  | LP2985A-33DBV                      | LP2985A-33DBV                                 |
| 1 XC1   | 16MHz uXtal GSX-323, 2.0 x 2.5 mm SMD 10ppm   | Golledge Golledge ATMEL SAMTEC Everlight Everlight Everlight Everlight | GSX-323/111BF 16.0MHz              | 16MHz   |
| 1 XC2   | 8.0MHz Xtal GSX-752, 7 x 5 mm SMD 50ppm   |  | GSX-752B/551EF 8MHz                | 8MHz GSX-752                                  |
| 1 PCB1  | RZUSBStick PCB  |  | A08-0384                           | A08-0384                                      |
| 1 J2  | USB type A plug, SMD  |  | USB-AM-S-F-B-SM1-R                 | USB type A plug                               |
| 1 D2  | LED, Red, Wave length=639nm, SMD 0805, ±70°   |  | EL17-21USRC                        | EL17-21USRC                                   |
| 1 D3  | LED, Green, Wave length=575nm, SMD 0805, ±70°   |  | EL17-21SYGC                        | EL17-21SYGC                                   |
| 1 D4  | LED, Yellow, Wave length=591nm, SMD 0805, ±70°  |  | EL17-21UYC/A2                      | EL17-21UYC/A2                                 |
| 1 D1  | LED, Blue, Wave length=430nm, SMD 0805, ±70°  |  | EL17-21UBC                         | EL17-21UBC                                    |