Qty Designator 1 C105 2 C103, C104 1 R102 1 C111	Description Ceramic capacitor, SMD 0402, NP0, 50V, +/-0.25pF Ceramic capacitor, SMD 0402, NP0, 50V, +/-5% Ceramic capacitor, SMD 0402, NP0, 50V, +/-10% Ceramic capacitor, SMD 0402, X7R, 25V, +/-10%	MPN	Manufacturer	ShortName 1.5p 12p 100p 10n
1 C110 C101, C102, C106, C107, C108, C109, C112, C113,	Ceramic capacitor, SMD 0402, X7R, 16V, +/-10%	C0402C104K4RACTU	Kemet	100n
9 C114 3 R104, R105, R109 1 R106 1 R111	Ceramic capacitor, SMD 0402, X5R, 6.3V, +/-10% Thick film resistor, SMD 0402, 1/16W, 1% Thick film resistor, SMD 0402, 1/16W, 1% Thick film resistor, SMD 0402, 1/16W, 1% SMD RF inductor 0805. Z=1000Ohm (@100MHz), Max	C0402C105K9PAC	Kemet	1u 0R 470R 2.2k
1 L101	R(dc)=0.45Ohm, Max current=200mA	BLM21AG102SN1D	Murata	BLM21AG102SN1D
1 L102	867-915 MHZ FilterBalun, 2x1,25mm	0896FB15A0100E	Johanson Technology	867-915 MHZ FilterBalun
1 U101	7/8/900 MHz ZigBee/802.15.4 tranceiver	AT86RF212-ZU	ATMEL	AT86RF212-ZU
1 U103	1-wire Serial number chip	DS2411R/T&R	Maxim	DS2411R
1 U102	LDO 3.3V 150mA SOT23-5 SMT Crystal Resonator, 16.000 MHz,10 ppm,12 pF,	LP2985AIM5-3.3	National Semiconductor	LP2985 3.3V
1 XC101	2520(Q) Samtec SMH 2x5 Pin Socet Right-angle 2,54mm Pitch	SCQ18D48-16.000MHZ TR	SUNTSU FREQUENCY CONTROL	16MHz
1 J101	(Mirrored footprint)	SMH-105-02-T-D-TR	SAMTEC	SMH-105-02-T-D-TR
1 PCB101	RZ600 RF board PCB		NCAB	RZ600 RF board PCB
1 J102	SMA PCB mounted connector	LTI-SASF56GT	Lighthorse Technologies inc.	LTI-SASF56GT
1 Z102 1 PCBA101	Label for use on wireless PCBA that needs 64 bit MAC and FCC ID RZ600 RF board PCBA		2 ACT Logimark AS	Label PCBA with MAC64 and FCC ID RZ600 RF board PCBA