

# RF TEST REPORT



Report No.: FCC\_RF\_SL19042501-SEV-613-Co-Location

Supersede Report No.:

Applicant	:	ChargePoint, Inc.
Host Product Name	:	CPF50
WIFI Module Model No.	:	28010161
RFID Module Model No.	:	28010087
Test Standard	:	47 CFR 15.209
Test Method	:	ANSI C63.10: 2013
WIFI Module FCC ID	:	W38-28010161
RFID Module FCC ID	:	W38-28010087
Dates of test	:	05/31/2019
Issue Date	:	06/04/2019
Test Result	:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Equipment complied with the specification [X]		
Equipment did not comply with the specification [ ]		

This Test Report is Issued Under the Authority of:

<i>Gary Chou</i>	<i>Chen Ge</i>
<b>Gary Chou</b>	<b>Chen Ge</b>
Compliance Engineer	Engineer Reviewer

Issued By:  
SIEMIC Laboratories  
775 Montague Expressway, Milpitas, 95035 CA



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile (+1) 408 526 1088

Visit us at: [www.siemic.com](http://www.siemic.com); Follow us at:



## Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety
Israel	MOC, NIST	EMC, RF, Telecom, Safety

### Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & Radio Equipment Directive (RED)
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom

## CONTENTS

<b>1</b>	<b>REPORT REVISION HISTORY .....</b>	<b>4</b>
<b>2</b>	<b>EXECUTIVE SUMMARY .....</b>	<b>5</b>
<b>3</b>	<b>CUSTOMER INFORMATION .....</b>	<b>5</b>
<b>4</b>	<b>TEST SITE INFORMATION .....</b>	<b>5</b>
<b>5</b>	<b>MODIFICATION .....</b>	<b>5</b>
<b>6</b>	<b>EUT INFORMATION .....</b>	<b>6</b>
6.1	EUT Description .....	6
6.2	Radio Description .....	6
<b>7</b>	<b>SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION .....</b>	<b>8</b>
7.1	Supporting Equipment .....	8
7.2	Cabling Description .....	8
7.3	Test Software Description .....	8
<b>8</b>	<b>TEST SUMMARY .....</b>	<b>9</b>
<b>9</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>10</b>
<b>10</b>	<b>MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....</b>	<b>11</b>
10.1	Radiated Spurious Emissions below 1GHz .....	11
10.2	Radiated Spurious Emissions between 1GHz – 25GHz .....	13
<b>ANNEX A. TEST INSTRUMENT .....</b>		<b>15</b>
<b>ANNEX B. SIEMIC ACCREDITATION .....</b>		<b>16</b>

## 1 Report Revision History

Report No.	Report Version	Description	Issue Date
FCC_RF_SL19042501-SEV-613-Co-Location	None	Original	06/04/2019

## 2 Executive Summary

The purpose of this test program was to demonstrate compliance of following product

Company: ChargePoint, Inc.  
Host Model No.: CPF50

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1<sup>st</sup> page.

## 3 Customer information

Applicant Name	ChargePoint, Inc.
Applicant Address	254 E. Hacienda Ave Campbell, CA 95148
Manufacturer Name	ChargePoint, Inc.
Manufacturer Address	254 E. Hacienda Ave Campbell, CA 95148

## 4 Test site information

Lab performing tests	SIEMIC Laboratories
Lab Address	775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No.	540430
IC Test Site No.	4842D
VCCI Test Site No.	A0133

## 5 Modification

Index	Item	Description	Note
-	-	-	-

## 6 EUT Information

### 6.1 EUT Description

Host Model No.	CPF50
Trade Name	ChargePoint
Serial No.	N/A
Input Power	5Vdc
Wifi Radio Hardware version	27-010077
RFID Radio Hardware version	28-010087
Radio Software version	4.0.0.41
Date of EUT received	05/31/2019
Equipment Class/ Category	DTS, DXX
Port/Connectors	N/A
Remark	None

### 6.2 Radio Description

Radio Type	802.11b	802.11g	802.11n-20M
Operating Frequency	2412-2462MHz	2412-2462MHz	2412-2462MHz
Modulation	DSSS (CCK, DQPSK, DBPSK)	OFDM-CCK (BPSK, QPSK, 16QAM, 64QAM)	OFDM (BPSK, QPSK, 16QAM, 64QAM)
Channel Spacing	5MHz	5MHz	5MHz
Number of Channels	11	11	11
Antenna Type	PIFA		
Antenna Gain (Peak)	2.5 dBi		
Note	N/A		

Radio Type	RFID
Operating Frequency	13.56MHz
Modulation	ASK
Channel Spacing	None
Antenna Type	PCB loop antenna
Antenna Gain	0.5dBi
Antenna Connector Type	N/A

### EUT Power level setting

Mode	Frequency (MHz)	Power setting
802.11-b	2412	20
802.11-b	2437	20
802.11-b	2462	20
802.11-g	2412	20
802.11-g	2437	20
802.11-g	2462	20
802.11-n-20	2412	20
802.11-n-20	2437	20
802.11-n-20	2462	20

## 7 Supporting Equipment/Software and cabling Description

### 7.1 Supporting Equipment

Item	Supporting Equipment Description	Model	Serial Number	Manufacturer	Note
1	Laptop	Latitude E6510	N/A	Dell	-

### 7.2 Cabling Description

Name	Connection Start		Connection Stop		Length / shielding Info		Note
	From	I/O Port	To	I/O Port	Length (m)	Shielding	
Serial to USB	Serial	EUT	USB	Laptop	10	Unshielded	-

### 7.3 Test Software Description

Test Item	Software	Description
RF Testing	Putty	Set the EUT to transmit continuously in diferent test mode



## 8 Test Summary

### Requirement

Test Item	Test standard		Test Method/Procedure		Pass / Fail
Radiated Spurious Emissions	FCC	15.209	FCC	ANSI C63.10:2013	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Remark	<ol style="list-style-type: none"> <li>All measurement uncertainties do not take into consideration for all presented test results.</li> <li>The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual.</li> <li>Please refer to the original test reports for FCC ID: W38-28010161 (WIFI) and FCC ID: W38-28010087 (RFID) for other test items.</li> <li>2.4GHz is determined to be the worst case co-location.</li> </ol>				


## 9 Measurement Uncertainty

Emissions			
Test Item	Frequency Range	Description	Uncertainty
AC Conducted Emissions	150KHz – 30MHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2	±3.5dB
RF conducted measurement	150KHz – 40GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2	±0.95dB
Radiated Spurious Emissions	30MHz – 1GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	±6dB
Radiated Spurious Emissions	1GHz – 40GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	±6dB

## 10 Measurements, Examination and Derived Results

### 10.1 Radiated Spurious Emissions below 1GHz

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.209	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table><thead><tr><th>Frequency range (MHz)</th><th>Field Strength (uV/m)</th></tr></thead><tbody><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></tbody></table>	Frequency range (MHz)	Field Strength (uV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	<div><input checked="" type="checkbox"/></div>
Frequency range (MHz)	Field Strength (uV/m)												
30 – 88	100												
88 – 216	150												
216 960	200												
Above 960	500												
Test Setup	<div></div>												
Procedure	<div><div><div>1.</div><div>2.</div><div>3.</div><div>4.</div></div><div><p>The EUT was switched on and allowed to warm up to its normal operating condition.</p><p>The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:</p><div><div>a.</div><div>b.</div><div>c.</div></div><p>Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</p><p>The EUT was then rotated to the direction that gave the maximum emission.</p><p>Finally, the antenna height was adjusted to the height that gave the maximum emission.</p><p>A Quasi-peak measurement was then made for that frequency point.</p><p>Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p></div></div>												
Remark	<p>The EUT was scanned up to 1GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.</p>												
Result	<div><div><input checked="" type="checkbox"/> Pass</div><div><input type="checkbox"/> Fail</div></div>												


Test Data    ☒ Yes (See below)      ☐ N/A

Test Plot    ☒ Yes (See below)      ☐ N/A

Test was done by Gary Chou at 10m chamber.

## Radiated Emission Test Results (Below 1GHz)

Test specification	Below 1GHz			
Environmental Conditions:	Temp (°C):	23	Result	Pass
	Humidity (%)	46		
	Atmospheric (mbar):	1018		
Mains Power:	120VAC, 60Hz			
Tested by:	Gary Chou			
Test Date:	01/17/2019			
Remarks:	2.4GHz Wi-Fi and RFID co-location			




## Quasi Max Measurements

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol (V/H)	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
300.02	51.02	13.24	-21.85	42.41	Quasi Max	H	305	66	46	-3.59	Pass
314.24	39.13	13.31	-21.71	30.73	Quasi Max	H	339	48	46	-15.28	Pass
57.24	53.53	11.49	-27.12	37.9	Quasi Max	V	148	51	40	-2.11	Pass
850.01	42.9	15.53	-13.05	45.38	Quasi Max	H	103	124	46	-0.63	Pass
285.68	38.68	13.22	-22.05	29.84	Quasi Max	H	126	136	46	-16.16	Pass
297.13	46.31	13.24	-21.87	37.67	Quasi Max	H	117	188	46	-8.33	Pass

Note: Both horizontal and vertical polarities were investigated. The results above show only the worst case.

## 10.2 Radiated Spurious Emissions between 1GHz – 25GHz

### Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.209	a)	<div>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</div> <table><tr><th>Frequency range (MHz)</th><th>Field Strength (uV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>	Frequency range (MHz)	Field Strength (uV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	<div>☒</div>
Frequency range (MHz)	Field Strength (uV/m)												
30 – 88	100												
88 – 216	150												
216 960	200												
Above 960	500												
Test Setup	<div></div>												
Procedure	<div><div>1.</div><div>2.</div><div>3.</div><div>4.</div></div> <div><p>The EUT was switched on and allowed to warm up to its normal operating condition.</p><p>The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:</p><div><div>a.</div><div>b.</div><div>c.</div></div><p>Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</p><p>The EUT was then rotated to the direction that gave the maximum emission.</p><p>Finally, the antenna height was adjusted to the height that gave the maximum emission.</p><p>An average measurement was then made for that frequency point.</p><p>Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p></div>												
Remark	<div>The EUT was scanned up to 25GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.</div>												
Result	<div><div>☒ Pass</div><div>☐ Fail</div></div>												

**Test Data**    ☒ Yes (See below)      ☐ N/A

**Test Plot**    ☐ Yes (See below)      ☒ N/A

**Test was done by Gary Chou at 10m chamber.**

## Radiated Emission Test Results (Above 1GHz)

### Above 1GHz-25GHz – 2.4GHz Wi-Fi and RFID co-location

















Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol (V/H)	Height cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
17468.79	39.82	8.24	1.44	49.51	Peak Max	H	174	261	74	-24.49	Pass
6185.01	45.94	4.7	-8.68	41.96	Peak Max	H	186	298	74	-32.04	Pass
2934.70	51.98	3.24	-14.2	41.01	Peak Max	V	100	347	74	-32.99	Pass
11888.18	39.67	6.33	-2.27	43.74	Peak Max	V	147	99	74	-30.27	Pass
17468.79	25.91	8.24	1.44	35.59	Average Max	H	174	261	54	-18.41	Pass
6185.01	33.68	4.7	-8.68	29.7	Average Max	H	186	298	54	-24.3	Pass

Note: Both horizontal and vertical polarities were investigated. The results above show only the worst case.








## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Cycle	Cal Due	In use
<b>Radiated Emissions</b>						
50GHz Spectrum Analyzer	N9030B(PXA)	MY57140374	08/20/2018	1 Year	08/20/2019	<input checked="" type="checkbox"/>
Bi-Log antenna (30MHz~6GHz)	JB6	A111717	08/12/2018	1 Year	08/12/2019	<input checked="" type="checkbox"/>
Horn Antenna (1GHz~26GHz)	3115	100059	01/26/2019	1 Year	01/26/2020	<input checked="" type="checkbox"/>
Horn Antenna (26GHz~40GHz)	AH-840	101013	08/28/2018	1 Year	08/28/2019	<input checked="" type="checkbox"/>
Pre-Amplifier(0.3MHz-6.5GHz)	LPA-6-30	11170602	02/06/2019	1 Year	02/06/2020	<input checked="" type="checkbox"/>
Pre-Amplifier (1-26.5GHz)	8449B	3008A00715	08/16/2018	1 Year	08/16/2019	<input checked="" type="checkbox"/>
Pre-Amp (10MHz~50GHz)	RAMP00M50GA	17032300047	02/10/2019	1 Year	02/10/2020	<input checked="" type="checkbox"/>

## Annex B. SIEMIC Accreditation

Accreditations	Document	Scope / Remark
ISO 17025 (A2LA)		Please see the documents for the detailed scope
ISO Guide 65 (A2LA)		Please see the documents for the detailed scope
TCB Designation		<a href="#">A1</a> , <a href="#">A2</a> , <a href="#">A3</a> , <a href="#">A4</a> , <a href="#">B1</a> , <a href="#">B2</a> , <a href="#">B3</a> , <a href="#">B4</a> , C
FCC DoC Accreditation		FCC Declaration of Conformity Accreditation
FCC Site Registration		3 meter site
FCC Site Registration		10 meter site
IC Site Registration		3 meter site
IC Site Registration		10 meter site
EU NB		<b>Radio Equipment: EN45011:</b> EN ISO/IEC 17065
		<b>Electromagnetic Compatibility:</b> EN45011 – EN ISO/IEC 17065
Singapore iDA CB(Certification Body)	 	<a href="#">Phase I</a> , <a href="#">Phase II</a>
Vietnam MIC CAB Accreditation		Please see the document for the detailed scope
Hong Kong OFCA		<b>(Phase II)</b> OFCA Foreign Certification Body for Radio and Telecom
		<b>(Phase I)</b> Conformity Assessment Body for Radio and Telecom
Industry Canada CAB		<b>Radio:</b> Scope A – All Radio Standard Specification in Category I
		<b>Telecom:</b> CS-03 Part I, II, V, VI, VII, VIII



Japan Recognized Certification Body Designation		<p><b>Radio:</b> A1. Terminal equipment for purpose of calling</p> <p><b>Telecom:</b> B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law</p>
Korea CAB Accreditation		<p><b>EMI:</b> KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI</p> <p><b>EMS:</b> KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS</p> <p><b>Radio:</b> RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10, RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80, RRL Notice 2004-68</p> <p><b>Telecom:</b> President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4</p>
Taiwan NCC CAB Recognition		LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS14336, PLMN07, PLMN01, PLMN08
Taiwan BSMI CAB Recognition		CNS 13438
Japan VCCI		<p>R-3083: Radiation 3 meter site</p> <p>C-3421: Main Ports Conducted Interference Measurement</p> <p>T-1597: Telecommunication Ports Conducted Interference Measuremet</p>
Australia CAB Recognition		<p><b>EMC:</b> AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3, AS/NZS 61000.6.4</p> <p><b>Radiocommunications:</b> AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771</p> <p><b>Telecommunications:</b> AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06 AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1</p>
Australia NATA Recognition		AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2