



Date of Report: 7/9/09

Maximum Permissible Exposure Statement

Calculations prepared for:

Grid Net, Inc.
340 Brannan Street
Suite 501
San Francisco, CA 94107

Calculations prepared by:

Art Rice
CKC Laboratories, Inc.
4056 Sierra Pines Dr.
Mariposa, CA 95338

FCC ID Number:: W4J-WXI210G1
Model Number: WX-i210+c

Fundamental Operating Frequency: 2496-2690 MHz

Maximum Rated Output Power: 501.2 mW (+27 dBm)
Measured Output Power: 746mW

Maximum Antenna Gain: 2 dBi stated

Power Output and Operating Frequency Information used for these calculations were from:
CKC Laboratories, Test Report # FC09-048B

Device and Antenna Operating Configuration:

Maximum output was measured on low channel 2498.5 MHz at 16 QAM 3/4-5 MHz data rate.
Antenna is permanently installed internally in the EUT.

Test Procedure:

This equipment is evaluated in accordance with the guidelines set forth in OET Guide 65.

Other Considerations:

None.

4056 Sierra Pines Dr. * Mariposa, CA 95338 * PH (209) 966-5240 * Fax (209) 742-6133

WORLDWIDE EMC – COMMERCIAL * INDUSTRIAL * MEDICAL * MILITARY * AVIONICS
BREA, CA * FREMONT, CA * MARIPOSA, CA * REDMOND, WA

MPE Calculations:

MPE Limit in accordance with 1.1310:

Occupational / Controlled Exposure
X General Population / Uncontrolled Exposure

$$\begin{aligned} \text{MPE Limit} &= 1 \text{ (mW/cm}^2\text{)} \\ &= 1 \text{ (mW/cm}^2\text{)} \end{aligned}$$

Note: Limit is calculated based on the lowest frequency used in the operating frequency range.

$$\text{PowerDensity(mW / cm}^2\text{)} = \frac{\text{EIRP}}{4\pi d^2} \quad \text{Given: EIRP in mW and d in cm}$$

EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Result
1183.04	9.7	1.00	Pass

Statement of Compliance:

This device demonstrates compliance under the operating conditions specified in this document. Under normal operating conditions, the antenna is designed to be installed in accordance with the manufacturer's instructions in such a manor to maintain the minimum separation distance. The MPE calculations shown above demonstrate compliance to the provisions of 1.1310 in accordance with the guidelines of OET 65.

As can be seen from the MPE results, this device passes the limits specified in 1.1310 at a distance of 9.7 cm and at an output power of 746 mW under normal operating conditions.